



Workers for Platforms

Extend the capabilities of Cloudflare Workers to customers of your SaaS applications and deploy serverless functions on their behalf. [Workers for Platforms documentation](#)

Create a namespace with Wrangler CLI

In this guide you will configure a [dynamic dispatch namespace](#), a [user Worker](#) and a [dynamic dispatch Worker](#).

1: Create a dispatch namespace

The first step to working with Workers for Platforms is to create a dispatch namespace. A dispatch namespace is made up of a collection of [user Workers](#).

This command creates a new dispatch namespace called "staging".

```
$ npx wrangler dispatch-namespace create staging
```



If Wrangler is not already authenticated with your Cloudflare account, do that now by following [authentication instructions](#).

2: Upload a user Worker to the dispatch namespace

You will now create a Worker called customer-worker-1.

```
$ npm create cloudflare@latest customer-worker-1 -- --type=hello-world
```



The last step in the C3 flow is deploying the application. **When prompted, select No.**

Navigate to your project directory.

```
$ cd customer-worker-1
```



To deploy your application to the dispatch namespace run the following command:

```
$ wrangler deploy --dispatch-namespace staging
```





Navigate out of your user Worker directory.

```
$ cd ..
```



Create your dispatch Worker.

```
$ npm create cloudflare@latest my-dispatcher -- --type=hello-world
```



Navigate to your project directory.

```
$ cd my-dispatcher
```



Open the wrangler.toml file in your project directory and add the dispatch namespace binding.

```
[[dispatch_namespaces]]  
binding = "dispatcher"  
namespace = "<NAMESPACE_NAME>"
```



Add the following to your index.js file.

```
export default {  
  async fetch(req, env) {  
    const worker = env.dispatcher.get("customer-worker-1");  
    return worker.fetch(req);  
  }  
}
```



4: Deploy

Publish your dispatch Worker to the Cloudflare network.

```
$ npx wrangler deploy
```



5: Test a request

Send a request to the route your dispatch Worker is on. You should receive the response (Hello world) from your user Worker (customer-worker-1).

```
$ curl https://my-dispatcher.<YOUR_WORKERS_SUBDOMAIN>.workers.dev/
```





Kd8jc7v8cd@privaterelay.appleid.com's Account

Support ▼

+ Add ▼



To support you along your journey developing Workers for Platforms here are some resources.



Workers for Platforms docs

Learn more about how Workers for Platforms works, the features it offers and limits.



Workers for Platforms starter project

An example project to get started with Workers for Platforms.

Have questions? Need help? Want to show off what you're building? Join our Cloudflare Developer community on [Discord](#)

[Continue to dashboard](#)

[Support](#) | [System Status](#) | [Careers](#) | [Terms of Use](#) | [Report Security Issues](#)

| [Privacy Policy](#)



[Your Privacy Choices](#)

© 2025 Cloudflare, Inc.