



Design Specifications

ELECTRICAL RATINGS	Compressor clutch	Type	Dry, single plate, poly V-ribbed belt drive
		Electrical power consumption at 68 °F (20 °C)	35 W maximum at 12 V
	12 volt battery	Si (KA)	51R (55B24L): 12 V—47 Ah/20 HR (12 V—38 Ah/5 HF
		Except Si (KA)	EN LN2: 12 V—60 Ah/20 HR (12 V—48 Ah/5 HR)
	Fuses	Under-hood fuse/relay box	125 A, 70 A, 60 A, 50 A, 40 A, 30 A, 20 A, 15 A, 10 A,
		Under-dash fuse/relay box	20 A, 15 A, 10 A, 5 A
	Light bulbs	Headlights (low)	12 V—55 W
			LED
		Headlights (high)	12 V—60 W
			LED
		Front parking lights	LED
		Daytime Running Lights (DRL)	LED
		Front side marker lights	12 V—3 W
		Front turn signal lights	12 V—21 W
			LED
		Side turn signal lights (fender type)	12 V—5 W
		Side turn signal lights (door mirror type)	LED
		Fog lights	12 V—35 W
			LED
		Brake lights	12 V—21 W
		Taillights	LED
		Inner taillights	LED
		Rear side marker lights	LED
		Rear turn signal lights	12 V—21 W
		Back-up lights (except 2-door)	12 V—16 W
		Back-up lights (2-door)	12 V—6 W
		High mount brake light	LED
		License plate light	LED
		Ceiling light	12 V—8 W
		Trunk area light (2/4-door)	12 V—5 W
		Cargo area light (5-door)	12 V—5 W
		Vanity mirror lights	12 V—2 W
		Ambient light	LED
		Front individual map lights	12 V—8 W
		Tray light (upper/lower)	LED