

# Course Project Proposal - Rock Lyrics Generation

Junzhe Wang  
jwang169@stevens.edu  
Stevens Institution of Technology  
Hoboken, NJ

## ABSTRACT

In this project, I introduce a method and discuss results of text-based LSTM language model for automatic rock lyrics composition. The proposed model is designed to learn relationships within text documents, and creates lyrics with meaningful, interesting story and lyrical patterns for rock music. First, I perform analysis of different lyrics genre. Results show word frequency and the length of sentence vary from different music genre. Second, I implement web scraping to collect lyrics of selected artists as the training data set. Finally, I build the text generation model which can be used for producing rock lyrics, and evaluate the model by computing BLEU score.

## KEYWORDS

LSTM, lyrics, RNN, web scraping

## 1 INTRODUCTION

Rock music has embodied and served as the vehicle for cultural and social movements. My objective is to study the problem of computational creation of rock lyrics. Unlike many earlier styles of popular music, themes of rock lyrics are rather diverse in nature ranging from love, betrayal, sex, social and political themes such as rebelling against an establishment. Unlike rap lyrics, which often have a similar structure (similar word length per line and similar rhyming schemes), rock lyrics have less restrictions on the rhyming part, as Twenty one pilots says: "I wish I didn't have to rhyme every time I sang".

My interest in this problem is motivated by two different perspectives. First, I am interested in analyzing the formal topics of rock lyrics and in developing a model that can lead to generating artistic work. Second, in June 2016, Google published Dope Learning and released the DeepBeat program which uses machine learning techniques to generate rap lyrics by combining lines from existing rap songs. The rap lyrics generator has been deployed as an online tool called DeepBeat. Different from their approach, I approach the lyrics-generation problem by a word-by-word construction instead of line by line, so as to increase novelty rather than rhyming. This revolves around creating system that produce text that makes sense in content, grammar, lexical choice, and overall flow. The system also need to produce output that is non-repetitive, so it need to combine short sentences with the same subject. Assuming uses have a certain concept in their mind, formulated as a topic as a word, and their information need is to find the missing content, composing a song.

The project is organized as follows. In Section 2, I start with a brief discussion of lyrics genre analysis. Next, I introduce the data set that I have used, and describe the preparation of the training data set. I start in Section 3 by defining the framework of the proposed

neural language generator. I introduce the word-based RNN and semantically controlled LSTM cell in section 3.1, then discuss how to extend it to a deep structure in Section 3.2. Section 3.3 proposes the GANs framework to improve the generation model. Training details are described in Section 3.4. Section 4 presents a potential method for evaluation of the model.

## 2 RELATED WORK

The study of human-generated lyrics is relevant for various sub-fields of computers science. Relevant literature can be found under domains of computational creativity, information extraction and natural language processing. Additionally, methods can be found under the domain of machine learning, for instance, in the emerging field of deep learning. Recent advances in recurrent neural network-based language models(RNNLM)(Mikolov et al., 2010[2];Mikolov et al., 2011[3] have demonstrated the value of distributed representations and the ability to model arbitrarily long dependencies. Zhang and Lapata(2014)[4] also describes an interesting work using RNNs to generate Chinese poetry, while DopeLearning[1] recombines lines from rap songs.

## 3 LYRICS ANALYSIS

In this section, I first compare the difference of lyrics among different music genres. This information will be the basis for extracting useful features for generating lyrics.

I use 380,000 lyrics in different genre, analyze them by word frequencies and sentence length, and visualize the most frequent word by word cloud.

This information will explain the major features of generating the lyrics words and sentences. For further information, the data is available from <https://www.kaggle.com/gyani95/380000-lyrics-from-metrolyrics>.

### 3.1 Lyrics by genre

Since words like 'i', 'you', and 'the' are commonly used throughout all genres, all the consecutive statistics exclude them(together with some other common words). In order to see what are the differences between genres for each of these words, I plot the genre specific statistics with exact counts for each word.

'Love' is the most used of the uncommon words in most of the genres, while each genre has its own unique word, such as 'shit' and 'fuck' in Hip-pop, 'once' in R&B, and 'away' in Rock.

### 3.2 Rock Lyrics

This project will focus on the lyrics generation on Rock, and a typical rock song follows a pattern of alternating verses and choruses. The length of sentences and the word frequency also varies from




Figure 1: Most frequently used words in R&B.




Figure 2: Most frequently used words in Pop.

different topics. The training data only covers lyrics of rock music, and the length of output text will be restricted accordingly.

### 3.3 Data

I compiled a list of English-speaking rock artists based on my personal preference, and scraped all their songs available from a lyrics site <https://www.lyricsfreak.com/>. In total, I have around 300000 lines from 8500 songs. I then process a subset of those lyrics by removing the headers, removing unnecessary punctuation and white space, and lowercasing all the alphabet characters. Finally, I split the content of the lyrics into chorus verse sets.

## 4 THE NEURAL LANGUAGE GENERATOR

The generation model proposed in this project is based on a recurrent neural network architecture (Mikolov et al., 2012) in which a




Figure 3: Most frequently used words in Hip-Hop.




Figure 4: Most frequently used words in Rock.

1-hot encoding  $w_t$  of a token is input at each time step  $t$  conditioned on a recurrent hidden layer  $h_t$  and outputs the probability distribution of the next token.

### 4.1 Semantic Controlled LSTM cell

Long Short-term Memory is a recurrent neural network architecture which uses a vector of memory cell  $c_t \in \mathbb{R}^n$ , and a set of element-wise multiplication gates to control how information is stored, forgotten, and exploited inside the network. Of the various different connectivity designs for an LSTM cell (Graves, 2013; Zaremba et al., 2014), the architecture used in this paper is illustrated and defined by the following equations,

$$i_t = \sigma(W_{\omega i} w_t + W_{h i} h_{t-1}) \quad (1)$$

$$f_t = \sigma(W_{\omega f} w_t + W_{h f} h_{t-1}) \quad (2)$$

$$o_t = \sigma(W_{\omega o} w_t + W_{h o} h_{t-1}) \quad (3)$$

$$\hat{c}_t = \tanh(W_{\omega c} w_t + W_{h c} h_{t-1}) \quad (4)$$

