

SCHOOL OF ADVANCED TECHNOLOGY

SAT301 FINAL YEAR PROJECT

Investigating the Capabilities of Large Language Model in Zero-Shot Learning

Final Thesis

In Partial Fulfillment

of the Requirements for the Degree of

Bachelor of Engineering

Student Name	:	Yifeng Jiang
Student ID	:	2141462
Supervisor	:	Guanyu Yang
Assessor	:	Fei Cheng

Abstract

This project investigates the zero-shot learning capabilities of the CLIP model by evaluating its performance on a curated Pokémon dataset with controlled stylistic consistency. Unlike interim studies that compared heterogeneous domains (e.g., Genshin Impact vs. classical cartoon characters), this experiment selects 20 Pokémon—10 introduced before and 10 after CLIP's pretraining period—ensuring that all characters belong to a coherent visual universe. Each Pokémon is represented by 10 images, enabling a focused evaluation of CLIP's generalization within a single semantic category.

The study examines classification using both name-based and attribute-based textual inputs. While CLIP performs well in identifying characters seen during training when using names, its accuracy drops sharply for unseen characters. In contrast, attribute-based descriptions—constructed from structured tables encoding visual features such as color, posture, and prototype—substantially improve performance across both seen and unseen groups. Confusion matrix analysis further reveals the presence of systematic misclassification biases toward dominant categories, highlighting the model's reliance on semantic similarity rather than label memorization.

These findings underscore that true zero-shot learning should be evaluated using unfamiliar categories and conceptually rich descriptions. Future work will focus on extending the dataset to include more Pokémon and new domains (e.g., humans and objects), analyzing the source of CLIP's biases, and exploring fine-grained classification strategies to distinguish visually or semantically similar instances. The project will also investigate automated generation of descriptive attributes to scale the method. Overall, this research validates the semantic strengths and limitations of CLIP in controlled zero-shot tasks and lays the groundwork for improving interpretability and domain transfer in vision-language models.

Keywords: zero-shot learning; CLIP; Pokémon classification; attribute-based classification; model bias; semantic generalization

Acknowledgements

I would like to express my sincere gratitude to all those who have supported and contributed to the successful completion of this research.

First and foremost, I would like to extend my heartfelt thanks to my supervisor, for his invaluable guidance, unwavering support, and insightful feedback throughout the research process. Without his expertise and mentorship, this work would not have been possible.

I would also like to thank assessor for his constructive suggestions and contributions during the course of this project. His knowledge and advice have greatly enriched the quality of this work.

Furthermore, I am deeply grateful to my family and friends for their constant encouragement, patience, and understanding throughout my academic journey. Their love and support have been a constant source of motivation for me.

Finally, I would like to acknowledge Xi'an Jiaotong Liverpool University for financial and technical support, which provided the necessary resources to carry out this research.

Contents

Abstract ii
Acknowledgements iii
Contents iv
List of Tables v
List of Figures vi
List of Acronyms vii
Chapter 1 Introduction 1
1.1 Motivation, Aims and Objective 1
1.2 Literature Review 3
1.2.1 Introduction to Zero-Shot Learning (ZSL) 3
1.2.1 CLIP and Contrastive Vision-Language Pretraining 4
1.2.2 Attribute-Based vs. Name-Based Classification 5
1.2.3 CLIP's Biases and Semantic Ambiguity 5
1.2.4 Fine-Grained Recognition in Zero-Shot Settings 6
1.2.5 Summary and Implications for This Project 7
Chapter 2 Methodology and Results 8
2.1 Methodology 8
2.1.1 CLIP Architecture and Workflow 8
2.1.2 Implementation Details 10
2.2 Experimental Setup 11
2.2.1 Dataset Construction 11
2.2.2 Prompt Generation 14
2.2.3 Experimental Progress 18
2.2.3.1 Experiment 1: Name-Based Classification 18
2.2.3.2 Experiment 2: Attribute-Based Classification 19
2.2.3.3 Experiment 3: Pokémon Dataset 19
2.2.3.4 Core Process 20
2.2.3.5 Evaluation and Result Visualization 21
2.2.4 Result 23
2.2.4.1 Experiment 1: Name-Based Classification 23
2.2.4.2 Experiment 2: Attribute-Based Classification 24
2.2.4.3 Experiment 3: Pokémon Dataset Evaluation 25
2.2.4.4 Key Findings and Visualizations 27
2.2.4.5 Conclusion of Results 28
2.2.5 Discussion 29
Chapter 3 Conclusion and Future Work 31
3.1 Conclusion 31
3.2 Future Work 32
References 35
Appendix A. Code Implementation 37

List of Tables

Table 2.1 Pokémon Attribute Table.....15

Table 2.2 Genshin Attribute Table.....15

Table 2.3 Table of example of ChatGPT-generated semantic attributes for classic characters 17

List of Figures

Figure 1.1 Zero-Shot Learning Process [5].....4

Figure 2.1 CLIP Workflow – From Pretraining to Zero-Shot Prediction [1].....9

Figure 2.2 Examples of image samples for classic character Mario.....12

Figure 2.3 Examples of image samples for genshin character Kaedehara Kazuha 12

Figure 2.4 Examples of image samples for Pokémon Tinkaton.....13

Figure 2.5 Genshin Impact Attribute Based Confusion Matrix.....25

Figure 2.6 A Bar Chart of Name Based Accuracy for Pokémon.....26

Figure 2.7 Pokémon Attribute Based Confusion Matrix 27

Figure 2.8 Comparison between Meowscarada and Sprigatito 28

List of Acronyms

Term	Initial components of the term
ZSL	Zero-Shot Learning
LLM	Large Language Model
CLIP	Contrastive Language–Image Pretraining

Chapter 1

Introduction

1.1 Motivation, Aims and Objective

With the rapid development of artificial intelligence, Zero-Shot Learning (ZSL) has become a prominent research area in machine learning. ZSL enables models to recognize and classify categories that were not seen during the training phase, making it highly valuable for tasks involving dynamic or previously unseen categories [1]. Traditional machine learning models, which rely on supervised learning, require explicit examples from each category during training. As a result, such models are unable to recognize new categories unless explicitly trained with them. ZSL, on the other hand, provides a solution by enabling the model to infer and generalize knowledge from seen categories to unseen ones using semantic information, such as attributes or textual descriptions.

CLIP (Contrastive Language–Image Pretraining), developed by OpenAI, is a vision-language model that learns visual representations from natural language descriptions, bridging the gap between images and text [2]. The model uses a contrastive learning framework to align images and text in a shared semantic space. This allows CLIP to perform classification tasks based on textual prompts, without requiring fine-tuning or task-specific training. It has shown promising results in zero-shot tasks, where the model classifies images based on textual descriptions, even for categories not encountered during training.

In the current state of research, CLIP's zero-shot capabilities are primarily evaluated through the use of name-based textual descriptions. These descriptions, such as "a photo of a dog," are used to match images to categories that the model has been exposed to during its pretraining phase. When the category name is present in the training data, CLIP performs well in classifying the images. However, when dealing with categories that were not part of the pretraining dataset, CLIP often fails to recognize them. This highlights the

limitation of zero-shot learning, where the model relies heavily on memorizing the category labels and does not demonstrate true zero-shot ability to classify completely unseen categories.

To evaluate the true zero-shot learning capability of CLIP, this research proposes to explore whether CLIP can generalize to entirely new categories using descriptive knowledge, rather than relying on memorized names. In human cognition, when faced with an unfamiliar object, individuals may not recognize its name but can categorize it based on its attributes—such as color, shape, or function—drawn from previous knowledge. This insight leads to the exploration of whether CLIP can also categorize new, unseen objects using their descriptive attributes, without having encountered the category name during training. By doing so, we aim to investigate CLIP's ability to perform true zero-shot learning, similar to how humans rely on concepts to categorize novel objects.

The primary goal of this study is to assess whether CLIP can classify unseen categories using attribute-based descriptions instead of relying solely on name-based ones. This approach involves testing CLIP's ability to classify new categories based on their visual or semantic attributes—such as color, size, and shape—rather than simply matching category labels. Specifically, the study will first verify if CLIP can classify known categories using name-based prompts and observe its performance on unseen categories. If CLIP fails to classify unseen categories based solely on names, it would indicate that the model is not performing true zero-shot learning. Then, we will test whether CLIP can classify new categories using attribute-based descriptions, assessing its capacity for semantic generalization beyond label memorization.

In summary, this study aims to determine whether CLIP can truly perform zero-shot learning by evaluating its ability to classify new categories using descriptive attributes. The findings will contribute to understanding the model's semantic generalization abilities and will offer insights into the potential for expanding CLIP's applications in dynamic and evolving domains.

1.2 Literature Review

1.2.1 Introduction to Zero-Shot Learning (ZSL)

Zero-shot learning (ZSL) refers to a class of machine learning tasks in which models are expected to recognize categories that were not seen during the training phase. Traditionally, this was achieved by relying on human-defined attributes or textual descriptions that semantically link seen and unseen categories. For instance, a model trained to recognize "tiger" might also recognize "lion" by virtue of shared attributes like “has fur” and “is a predator” [3].

These early ZSL methods required explicit alignment between visual features and semantic attributes. Lampert et al. [3] introduced a framework where classifiers for unseen classes were synthesized based on known attributes. However, such methods suffered from limited scalability due to the requirement for fine-grained human annotations and the inability to capture context-dependent semantics.

The arrival of word embeddings (e.g., Word2Vec, GloVe) introduced distributed semantic representations that enabled learning from more general language corpora. Xian et al. [4] conducted a comprehensive evaluation of ZSL algorithms and highlighted the limitations of traditional attribute-based approaches, including their sensitivity to domain shift and over-reliance on shared label structures.




Figure 1.1 Zero-Shot Learning Process [5]

1.2.1 CLIP and Contrastive Vision-Language Pretraining

A major breakthrough in ZSL came with the introduction of CLIP (Contrastive Language-Image Pretraining) by Radford et al. [1], which jointly trains a vision encoder and a text encoder using 400 million image-text pairs crawled from the internet. Instead of requiring predefined attributes or class embeddings, CLIP learns a shared semantic space where images and their associated captions are encouraged to have high cosine similarity.

CLIP's core strength lies in its generalization ability. For example, it can classify an image of a "panda" using the prompt "a photo of a black and white bear eating bamboo" even if the label "panda" was never seen during training [1]. The model outperforms traditional supervised baselines on multiple zero-shot classification benchmarks, such as ImageNet, CIFAR-100, and OpenImages, without the need for fine-tuning.

However, as Zhou et al. [6] show, CLIP's performance is highly sensitive to prompt formulation. For instance, "a photo of a cat" might yield different results than "an image of a domestic feline," especially when the category is rare or ambiguous. This sensitivity

has motivated research into prompt engineering, automatic prompt tuning, and ensemble methods to improve robustness.

1.2.2 Attribute-Based vs. Name-Based Classification

An important dimension of ZSL with CLIP involves the design of textual prompts used for classification. Name-based prompts, such as “a photo of Pikachu,” rely on CLIP’s familiarity with the category label. This approach performs well when the label is frequent in the pretraining data (e.g., “dog,” “car,” “Apple logo”) [7]. However, it fails when dealing with truly unseen categories or fictional terms like “Pikachu” or “Bulbasaur,” as these names may not exist in CLIP's pretraining corpus.

To overcome this limitation, researchers have explored attribute-based prompts, where the class is described using its visual or semantic properties. For instance, instead of “Pikachu,” one might describe it as “a small, yellow, mouse-like creature with pointy ears and red cheeks.” Studies such as [8] show that such detailed prompts significantly improve zero-shot classification accuracy, especially for rare or fictional entities.

In practical applications, this approach has been used in fine-grained bird classification [9], where labels like “Western Gull” and “Herring Gull” were indistinguishable to CLIP unless described by attributes like “black-tipped wings” or “yellow bill with a red spot.” This directly supports the methodology in this project, where Pokémon characters are described based on structured features such as eye color, posture, and animal prototype.

1.2.3 CLIP's Biases and Semantic Ambiguity

Despite its impressive results, CLIP exhibits classification bias, often favoring frequent or visually dominant categories. Menon et al. [10] found that when tested on a balanced dataset of rare and common animals, CLIP disproportionately predicted common

categories (e.g., “cat,” “dog”) even when the input image was clearly an uncommon class (e.g., “ocelot”).

This is consistent with observations from our own preliminary results, where CLIP incorrectly classified unseen Pokémon using name-based prompts, but performed better with detailed descriptions. In some cases, it consistently misclassified fire-type characters as previously seen flame-themed characters, reflecting entrenched biases in its vision-language representations.

Another challenge is semantic ambiguity. For example, the word “horn” may refer to musical instruments or animal features. Without additional context, CLIP might misclassify a “unicorn” as a “French horn” if the prompt is poorly worded. Zhou et al. [6] and Shu et al. [9] addressed this by introducing compositional prompts, which explicitly embed multiple disambiguating features into the description (e.g., “a white horse with a single horn on its head”).

1.2.4 Fine-Grained Recognition in Zero-Shot Settings

A less explored frontier in ZSL is fine-grained classification, where differences between categories are subtle and localized. For example, two bird species may differ only in eye stripe patterns; two Pokémon may differ only in ear shape or tail color. Chou et al. [11] proposed an attribute-guided attention mechanism that helps highlight these discriminative regions during classification.

In the CLIP context, such mechanisms are not built-in. Shu et al. [9] propose a solution involving test-time prompt tuning, where the model dynamically adjusts the weighting of prompt tokens based on the visual features of the query image. While promising, this line of work is still experimental.

In our study, we attempt to simulate this idea by designing attribute prompts that emphasize fine-grained traits. For example, two dragon-type characters are described as “a sleek green dragon with narrow wings” vs. “a bulky red dragon with thick horns.” Early tests suggest this level of specificity aids classification, which aligns with the findings in [11].

1.2.5 Summary and Implications for This Project

The reviewed literature paints a comprehensive picture of the current state of zero-shot learning. From attribute-based foundations to CLIP's contrastive training and modern prompt tuning strategies, it is evident that rich, descriptive prompts enhance generalization beyond label matching.

To rigorously evaluate CLIP's zero-shot learning capability, this study adopts a stylistically consistent Pokémon dataset, in which characters are grouped by their release period—before or after CLIP's pretraining. By ensuring that all visual samples belong to the same stylistic domain, this design enables an isolated examination of temporal novelty and reduces confounding factors related to style or genre.

By comparing name-based and attribute-based classification within this controlled setting, we aim to better understand CLIP's ability to generalize semantically rather than memorizing label priors. Furthermore, our study provides a structured basis for future investigations into prompt effectiveness, bias behavior, and fine-grained recognition in closed-domain, open-category scenarios.

Chapter 2

Methodology and Results

2.1 Methodology

2.1.1 CLIP Architecture and Workflow

CLIP (Contrastive Language-Image Pretraining) is a vision-language model that enables machines to understand and compare images and text within a shared semantic space. In this project, we utilize the CLIP ViT-B/32 variant, a pre-trained model capable of performing classification without traditional supervised training—a process referred to as zero-shot learning [1].

CLIP operates through three core stages, each of which is essential to how it performs open-ended classification:

Contrastive Pretraining

During its initial training phase, CLIP was exposed to 400 million image–text pairs collected from the internet. It learned to associate each image with its corresponding textual caption. When presented with a matched pair, such as a photo of a dog and the sentence "a photo of a dog," the model adjusts its internal representations to bring them closer together in a high-dimensional space. Mismatched pairs are pushed apart. This process, called contrastive learning, enables CLIP to develop a general understanding of visual-textual semantics [2]. Contrastive learning techniques, particularly those employed in CLIP, have been shown to significantly improve transfer learning across tasks [12].

Text-Based Classifier Construction

Unlike traditional classification models that require explicit retraining for new categories, CLIP allows for dynamic class definition through natural language. To define possible output categories, users simply write phrases like "a photo of a cat," "a photo of a car," or "a photo of a dog." These prompts are processed through CLIP's text encoder, producing

class representations in the same semantic space as image embeddings [3]. This capability is crucial for zero-shot classification tasks, as it allows models to operate on any category defined by textual descriptions without needing to be retrained on specific classes [13].

Zero-Shot Prediction

When classifying a new image, CLIP first encodes the image into a feature vector. It then compares this vector to each of the text-based class vectors using cosine similarity. The class whose textual description is most semantically aligned with the image is selected as the prediction. This makes CLIP highly flexible—it can be used for any classification task without retraining, provided that appropriate textual prompts are available [6]. The zero-shot capability is particularly beneficial in open-world scenarios, where classes may be dynamic and evolving [14].




Figure 2.1 CLIP Workflow – From Pretraining to Zero-Shot Prediction [1]

The figure shows the full CLIP pipeline: (1) during contrastive pretraining, CLIP learns to bring matching image–text pairs closer in embedding space while pushing apart mismatched ones; (2) textual prompts are used to create a classifier on the fly; and (3) the model performs zero-shot classification by comparing a test image's embedding with each text prompt's embedding.

This architecture is particularly useful in applications like ours, where many character classes (e.g., new Pokémon) may not exist in the model's training data. By providing rich natural language descriptions—rather than fixed labels—we can tap into CLIP's ability to semantically align visual and textual concepts and test its true zero-shot capabilities.

2.1.2 Implementation Details

All experiments in this project were conducted using the CLIP model with a ViT-B/32 backbone, which was released by OpenAI. This model has been pre-trained on a large-scale dataset of image–text pairs from the internet and was used directly without any additional fine-tuning or retraining.

To run the experiments, the system configuration used is summarized below:

- Python version: 3.12.0
- PyTorch version: 2.5.1 (CUDA 12.4 enabled)
- CUDA driver version: 12.8
- GPU: NVIDIA GeForce RTX 3070 Laptop GPU with 8 GB of dedicated video memory
- CPU: AMD Ryzen 7 5800H with 8 cores and 16 threads
- RAM: 16 GB
- Operating System: Windows 10
- GPU Driver Version: 572.83

Before being fed into the model, all images were resized to a fixed resolution of 224 × 224 pixels, which is the standard input size expected by CLIP. They were then normalized using the default preprocessing settings defined by the CLIP authors, which includes scaling pixel values and adjusting channel-wise mean and standard deviation. This step helps ensure that the input format matches what the model was originally trained on, thereby maintaining consistent performance.

In this project, images were processed one at a time—each image was loaded, preprocessed, and passed through the model individually. This setup corresponds to a batch size of 1, which is commonly used for inference (i.e., prediction) tasks where real-time or per-sample evaluation is needed. For each image, the model computes its similarity with all available textual prompts, and the most similar one is selected as the prediction.

All computations were accelerated using the system's GPU via CUDA, which significantly reduced processing time compared to running on the CPU alone. The GPU was used both for image and text encoding. Throughout all experiments, the system ran smoothly, with

no memory bottlenecks or crashes observed, and inference was completed efficiently for all 200 Pokémon images in the dataset.

2.2 Experimental Setup

This section presents the results of the experiments conducted to evaluate CLIP's zero-shot learning capabilities, specifically focusing on its ability to classify both seen and unseen categories based on name-based and attribute-based descriptions. The results are divided into mid-term experiments (classic characters vs. Genshin Impact characters) and post-term experiments (Pokémon characters). In each case, we evaluate the performance using both name-based descriptions and attribute-based descriptions.

2.2.1 Dataset Construction

To rigorously evaluate CLIP’s zero-shot classification capabilities, two structured datasets were constructed: a smaller comparative set combining classic cartoon and Genshin Impact characters, and a larger, stylistically uniform Pokémon dataset, which serves as the main experimental benchmark. These datasets support temporal and semantic generalization analysis under controlled visual conditions.

Preliminary Dataset: Classic Characters vs. Genshin Impact

The first dataset consists of 20 character categories divided into two equal groups:

- Classic character group (seen):

This set includes 10 widely recognizable characters expected to have high online presence prior to 2020, potentially overlapping with CLIP’s pretraining corpus. The characters are: Asuka, Bulbasaur, Charmander, Doraemon, Kirby, Link, Mario, Pikachu, Sonic, and Squirtle.



Figure 2.2 Examples of image samples for classic character Mario

- Genshin Impact group (unseen):

This group comprises 10 characters from Genshin Impact, a game released in 2020. The selected characters span both early and recent releases, including:

Barbara, Emilie, Ganyu, Kaedehara Kazuha, Klee, Neuvillette, Ororon, Raiden Shogun, Tighnari, and Xilonen.




Figure 2.3 Examples of image samples for genshin character Kaedehara Kazuha

Each character category contains 10 images, resulting in 200 images total. All images were manually collected and filtered to represent the character clearly, avoiding inconsistent artwork styles, game interfaces, or fan modifications. Although the dataset serves as a

useful reference, the two groups differ considerably in visual domain—cartoon-like characters versus high-fidelity game-rendered art—which introduces style-based variation beyond semantic novelty.

Main Dataset: Partitioned Pokémon Characters

For the primary evaluation, we constructed a Pokémon-only dataset to ensure high visual consistency while enabling clear separation between "seen" and "unseen" categories based on release timeline.

- Pre-CLIP group (seen):

This group includes 10 Pokémon introduced before 2020, potentially present in CLIP's training data. The characters are:

Bulbasaur, Charmander, Clefairy, Gengar, Lucario, Mew, Mewtwo, Pikachu, Psyduck, and Squirtle.

- Post-CLIP group (unseen):

This group consists of 10 Pokémon introduced after 2020, likely absent from the model's pretraining data. These include:

Ceruledge, Clodsire, Fuecoco, Koraidon, Maushold, Meowscarada, Miraidon, Quaxly, Sprigatito, and Tinkaton.




Figure 2.4 Examples of image samples for Pokémon Tinkaton

Each class is represented by 10 images, resulting in a total of 200 Pokémon images. All images were collected from official game artwork, trusted online databases, or curated fan archives. Careful manual selection ensured that each image clearly depicted the intended

character and conformed to the visual identity of the Pokémon franchise. Although the dataset includes variations in rendering style—such as 2D illustrations, anime stills, and 3D game assets—all samples maintain semantic and stylistic consistency within the same fictional universe.

This dataset provides a balanced and visually coherent foundation for evaluating CLIP's zero-shot classification ability. By ensuring that both seen and unseen categories share a common aesthetic and differ only in their time of introduction, the design reduces domain-related confounds and enables a more focused analysis of semantic generalization and prompt design effectiveness.

2.2.2 Prompt Generation

To investigate how CLIP interprets visual categories under different forms of textual supervision, this project designs two distinct types of prompts for each class: name-based prompts, which rely on direct label matching, and attribute-based prompts, which provide descriptive visual cues. This dual-prompt design allows us to compare CLIP's memorization ability versus its capacity for semantic generalization.

Name-Based Prompts

Name-based prompts are constructed using a fixed sentence template where the character name is embedded directly into a natural language phrase. This type of prompt aims to test whether the model has encountered or memorized the name during pretraining.

The template used is:

"This is [Character Name]."

Examples: "This is Pikachu."

For characters in the classic or Pokémon datasets, the names were extracted automatically from folder names in the dataset directory. These were then tokenized using CLIP's tokenizer and used as inputs for prediction.

Attribute-Based Prompts

Attribute-based prompts aim to describe the visual appearance of a character using explicit traits. These traits were manually annotated in structured tables for each dataset (Pokémon and Genshin Impact), and then converted into fluent English descriptions using scripted templates.

The attributes considered include, but are not limited to:

- For Pokémon characters:

Main Color, Eye Color, Posture, Ear Shape, Tail Shape, Animal Prototype, Has Weapon

- For Genshin Impact characters:

Hair Color, Eye Color, Skin Color, Body Type, Weapon Type, Element, Glasses, Hat

Table 2.1 Pokémon Attribute Table

Pokemon	Main Color	Eye Color	Posture	Ear Shape	Tail Shape	Has Weapon	Number	Animal Prototype
Bulbasaur	Green	Red	Quadrupedal	Pointed	None	No	1	Toad
Ceruledge	Dark Blue-Purple	Violet-Red	Bipedal	Horned	None	Yes	1	Humanoid
Charmander	Orange	Blue	Bipedal	None	Flame-like	No	1	Lizard
Clefairy	Pink	Black	Bipedal	Pointed	Curled	No	1	Fairy
Clodsire	Brown	Black	Crawling	None	Flat	No	1	Amphibian
Fuecoco	Red	Black	Bipedal	None	Stubby	No	1	Crocodile
Gengar	Purple	Red	Bipedal	Pointed	Spiky	No	1	Shadow
Koraidon	Red	Orange	Bipedal	Feathered	Tapered	No	1	Theropod
Lucario	Blue	Red	Bipedal	Pointed	Straight	No	1	Jackal
Maushold	White	Black	Bipedal	Round	Thin	No	0	Mouse
Meowscarada	Green	Pink	Bipedal	Pointed	Leaf-like	No	1	Cat
Mew	Pink	Blue	Floating	Pointed	Long	No	1	Kitten
Mewtwo	Light Gray	Purple	Bipedal	Stump-like	Thick	No	1	Feline-Humanoid
Miraidon	Purple	Yellow	Floating	None	Energy-core	No	1	Robot Lizard
Pikachu	Yellow	Black	Bipedal	Pointed	Lightning-like	No	1	Mouse
Psyduck	Yellow	Black	Bipedal	None	Flat	No	1	Duck
Quaxly	White	Blue	Bipedal	None	Feathered	No	1	Duck
Sprigatito	Green	Pink	Quadrupedal	Pointed	Leaf-like	No	1	Cat
Squirtle	Blue	Reddish-Brown	Bipedal	None	Curled	No	1	Turtle
Tinkaton	Pink	Blue	Bipedal	Long Curved	None	Yes	1	Dwarf

Table 2.2 Genshin Attribute Table

Character	Element	Release_date	Rarity	Weapon_type	Region	Race	Hair color	Eye color	Body type	Skin color	Glasses	Hat
Barbara	Water	2020/9/15	4	Catalyst	Mondstadt	Human	Blonde	Blue	Girlish	Fair	0	1
Emilie	Grass	2024/8/6	5	Polearm	Fontaine	Human	Blonde	Red	Girlish	Fair	1	1
Ganyu	Ice	2021/1/12	5	Bow	Liyue	Half-Immortal	Blue	Purple	Girlish	Fair	0	0
Kaedehara Kazuha	Wind	2021/6/29	5	Sword	Inazuma	Human	White	Red	Boyish	Fair	0	0
Klee	Fire	2020/10/20	5	Catalyst	Mondstadt	Long-lived race	Blonde	Red	Little Girl	Fair	0	1
Neuvillette	Water	2023/9/27	5	Catalyst	Fontaine	Dragon	White	Purple	Adult Male	Fair	0	0
Ororon	Ray	2024/11/20	4	Bow	Natlan	Beastkin	Blue	Heterochromatic	Adult Male	Fair	0	1
Raiden Shogun	Ray	2021/9/1	5	Polearm	Inazuma	Archon	Purple	Purple	Adult Female	Fair	0	0
Tighnari	Grass	2022/8/24	5	Bow	Sumeru	Beastkin	Black	Green	Boyish	Fair	0	0
Xilonen	Rock	2024/10/9	5	Sword	Natlan	Beastkin	Blonde	Green	Adult Female	Dark	0	0

A Python-based template system was used to map structured fields into full sentences. The base prompt structure varies based on dataset, but typically follows this logic:

- For Pokémon:

“A creature that resembles [animal], featuring [attributes].”

- For Genshin Impact:

“A [skin]-skinned, [body type] character with [hair color] hair and [eye color] eyes, using a [weapon] and associated with the [element] element.”

Example: Charmander (Pokémon)

Name-based:

“This is Charmander.”

Attribute-based:

“A creature that resembles lizard, featuring blue eyes, a main color of orange, a bipedal posture, and a flame-like tail.”

Example: Barbara (Genshin Impact)

Name-based:

“This is Barbara.”

Attribute-based:

“A light-skinned, girlish character with blonde hair and blue eyes, using a catalyst and associated with the water element, and wearing a hat.”

This descriptive prompt format helps CLIP reason based on the semantic alignment between image and text, rather than relying on name memorization. All attribute-based prompts were automatically generated from tables using structured Python scripts to ensure reproducibility and consistency across datasets.

In addition, for the classic character dataset, the semantic attributes were not manually annotated but were instead directly generated using ChatGPT. As shown in the example image below, a variety of visual traits and characteristics were crafted by ChatGPT, based on predefined attribute categories for each character. The model was prompted to generate fluent and detailed descriptions for each character, ensuring the visual traits were aligned with the character’s identity. These generated descriptions were then refined for grammatical accuracy and semantic consistency before being used as input to CLIP.

See figure below for an example of the ChatGPT-generated attribute descriptions for classic characters:

Table 2.3 Table of example of ChatGPT-generated semantic attributes for classic characters

Name	Prompt
Asuka	A young girl with long reddish hair
Bulbasaur	A small, green, quadruped creature with large eyes and a plant bulb on its back
Charmander	A small orange lizard-like creature standing on two legs, with a flame burning at the end of its tail
Doraemon	A round, blue, cat-like figure with no ears, a red nose, and a pocket on his belly
Kirby	A tiny, round, pink creature with big eyes and red feet
Link	A young, elf-like character with pointy ears, wearing a green tunic and a matching hat
Mario	A stout man with a mustache, red cap, and overalls
Pikachu	A small, yellow rodent-like creature with long ears tipped in black and a lightning bolt-shaped tail
Sonic	A sleek, blue anthropomorphic hedgehog with spiky hair and red shoes
Squirtle	A small blue turtle with a spiral tail and large round eyes

Implementation Details

All attribute-based prompts were automatically generated from structured attribute tables using Python scripts. For each character, relevant visual traits were first extracted from excel files and filled into natural language templates. Conditional logic was used to skip missing fields or modify phrasing for better fluency. The generation process was fully automated to ensure consistency and reproducibility across all characters and datasets.

Separate generation templates were designed for the Pokémon and Genshin Impact datasets, reflecting the different structures and semantic categories present in each. All final prompt outputs were verified manually for grammatical correctness and semantic alignment with the character's visual identity.

To optimize semantic accuracy, ChatGPT (GPT-4o) was employed to refine and enhance the generated descriptions. The attribute-based prompts, once generated, were fed into ChatGPT for further language refinement, ensuring better natural language fluency and richness. This approach was especially useful for characters that lacked sufficient descriptive attributes in the initial dataset. Since ChatGPT's training data includes vast internet knowledge, it was able to suggest improved wording and nuanced descriptions even for characters that CLIP had not seen in its pretraining period.

For future zero-shot tasks, we plan to completely remove the character names and rely entirely on the attributes extracted from the dataset. These attribute-only prompts will be fed into ChatGPT, allowing the model to generate multiple variations of the descriptions. To mitigate variability, we will average the results across the generated descriptions and

use these averaged prompts as the final input to CLIP for zero-shot classification. This ensures a truly zero-shot setting where CLIP classifies based solely on the semantic content of the descriptions, without relying on any prior label exposure.

2.2.3 Experimental Progress

This research aims to evaluate CLIP's zero-shot classification capabilities through a series of experiments, organized to test the model's ability to classify known and unseen categories using both name-based and attribute-based textual descriptions. The experiments are structured to systematically assess CLIP's ability to generalize across different categories, initially through name-based descriptions, followed by attribute-based descriptions, and culminating in a unified Pokémon dataset for further validation.

2.2.3.1 Experiment 1: Name-Based Classification

The first step in the experiment was to evaluate CLIP's ability to classify characters based on name-based textual descriptions. This phase focused on two distinct groups of characters:

- Classic Characters: Well-known characters, such as Pikachu, Mario, and Sonic, which are expected to be familiar to CLIP due to their prevalence in pretraining datasets. These characters serve as a benchmark to assess how well CLIP performs in recognizing categories it is likely to have seen during pretraining.
- Genshin Impact Characters: Characters from Genshin Impact, such as Raiden Shogun and Barbara, which were introduced after CLIP's pretraining period. This group was selected to test CLIP's ability to generalize to categories it has never encountered, based solely on name-based descriptions.

For each character, a textual description stating the character's name (e.g., "This is Pikachu") was used to test CLIP's performance. The experiment aimed to verify whether CLIP could successfully match known and unknown characters to their respective names.

2.2.3.2 Experiment 2: Attribute-Based Classification

Following the name-based classification, the next step was to test CLIP's ability to classify characters based on more descriptive, attribute-based textual prompts. These descriptions provided a deeper semantic context for each character, moving beyond simple label recognition. The goal was to assess whether CLIP could generalize to unseen categories when provided with detailed visual attributes, such as color, posture, and distinctive features.

- Classic Characters: Descriptions were provided based on visual traits (e.g., "A small, yellow, mouse-like creature with pointy ears and red cheeks" for Pikachu) to evaluate CLIP's ability to use its visual-semantic understanding for classification.
- Genshin Impact Characters: Similarly, detailed descriptions were generated for each character (e.g., "A fair-skinned, girlish character with blonde hair and blue eyes, using a catalyst and associated with the water element" for Barbara) to examine how well CLIP could apply its general understanding of visual features to classify these new, unseen characters.

This phase aimed to determine whether CLIP could classify unseen characters more effectively when relying on semantic descriptions of their attributes rather than names.

2.2.3.3 Experiment 3: Pokémon Dataset

The next step in the experiment involved the construction of a unified Pokémon dataset, which was designed to test CLIP's ability to classify characters using name-based and attribute-based descriptions respectively. This dataset was structured to include both seen and unseen categories, with characters categorized based on their introduction period relative to CLIP's pretraining:

- Pre-CLIP Pokémon Characters (Seen): These characters were introduced before CLIP's pretraining, so they are likely present in the model's training set. This group helps assess CLIP's performance on familiar categories.

- Post-CLIP Pokémon Characters (Unseen): These characters were introduced after CLIP's pretraining, meaning they were not part of the model's original training data. This group tests CLIP's ability to generalize to new, unseen categories based on either name-based or attribute-based descriptions.

The experimental process for the Pokémon dataset follows the same structure, testing both name-based and attribute-based descriptions. The primary objective here is to maintain consistency in the style of textual descriptions, as ensuring uniformity across the descriptions is essential for controlling variables. This consistency minimizes the potential influence of stylistic differences, allowing for a more accurate and fair comparison of CLIP's classification abilities across seen and unseen categories. By controlling for these stylistic factors, the experiment provides a more reliable evaluation of CLIP's true zero-shot learning capabilities, specifically its ability to classify based on semantic understanding rather than superficial cues.

2.2.3.4 Core Process

The experimental process involves several key steps:

- Image Preprocessing: All images are resized to 224×224 pixels, ensuring consistency with CLIP's pretraining dataset. The images are then normalized to match the input format expected by CLIP.
- Model Setup: The CLIP model (ViT-B/32) is used to encode both the images and textual descriptions into a shared semantic space. By comparing the image embeddings with the text embeddings, the model determines the most appropriate match.
- Test Procedure: For each character, the model is tasked with predicting the correct label based on both name-based and attribute-based descriptions. Top-1 Accuracy is used as the primary evaluation metric to determine how often the model's top prediction matches the true label.

2.2.3.5 Evaluation and Result Visualization

To assess the performance of CLIP in the context of zero-shot learning, we utilize several evaluation metrics that provide insight into how well the model classifies both seen and unseen categories based on textual descriptions. These metrics include Top-1 Accuracy, Harmonic Mean Accuracy, and visualizations using the Confusion Matrix and Per-Class Accuracy.

1. Cosine Similarity

Cosine similarity is used to measure the similarity between the image and text embeddings in the shared semantic space of CLIP. The cosine similarity is defined as:

$$\text{Cosine Similarity(A, B)} = \frac{A \cdot B}{\|A\|\|B\|}$$

Where:

- A and B represent the image and text embeddings respectively,
- A·B is the dot product of the vectors,
- ‖A‖ and ‖B‖ are the magnitudes (Euclidean norms) of the vectors.

Cosine similarity ranges from -1 to 1, where 1 indicates that the vectors are identical (i.e., perfect match), and 0 indicates orthogonality (i.e., no similarity).

This metric is critical in determining how effectively CLIP matches textual descriptions with corresponding image embeddings.

2. Softmax Calculation

After obtaining the raw logits (scores) from the model's output, we apply the softmax function to convert these logits into probabilities, making them interpretable. The softmax function is defined as:

$$\text{Softmax}(z_i) = \frac{e^{z_i}}{\sum_j e^{z_i}}$$

Where:

- z_i is the raw score (logit) for class i,
- The sum in the denominator normalizes the logits, ensuring that the output values are between 0 and 1 and that they sum to 1.

The softmax function helps in interpreting the logits as probabilities, enabling us to select the class with the highest probability as the model's prediction.

3. Top-1 Accuracy

Top-1 Accuracy measures the proportion of times the model's top prediction (the class with the highest probability) matches the true label. It is calculated as:

$$\text{Top-1 Accuracy}=\frac{Number\ of\ correct\ predictions}{Total\ number\ of\ predictions}$$

This metric gives an overall measure of how often the model's highest probability prediction is correct. A higher Top-1 accuracy indicates better classification performance.

4. Harmonic Mean Accuracy

To balance the performance between seen and unseen categories, we calculate the harmonic mean of their accuracies. This is useful when there is an imbalance between the accuracies of the two groups. The harmonic mean is computed as:

$$H=\frac{2\times Accuracy_{seen}\times Accuracy_{unseen}}{Accuracy_{seen}+Accuracy_{unseen}}$$

Where:

- $Accuracy_{seen}$ is the accuracy for the seen categories,
- $Accuracy_{unseen}$ is the accuracy for the unseen categories.

The harmonic mean provides a fair evaluation when there are significant differences in accuracy between seen and unseen categories, ensuring that both groups contribute equally to the overall performance.

5. Confusion Matrix

The Confusion Matrix is a tool used to visualize the performance of the model by comparing the true labels with the predicted labels. It is a matrix where each element C_{ij} represents the number of instances where the true class is i and the predicted class is j. This matrix helps identify misclassifications, such as when the model confuses similar categories.

The confusion matrix is crucial for understanding the distribution of errors across the classes and helps pinpoint where the model may need improvement.

6. Per-Class Accuracy

Per-Class Accuracy calculates the accuracy for each individual class separately. It is defined as:

$$\text{Accuracy per Class} = \frac{Number\ of\ correct\ predictions\ for\ class\ i}{Total\ number\ of\ instances\ of\ class\ i}$$

This metric provides insight into how well the model performs on each class. A per-class accuracy chart is helpful for visualizing the model's strengths and weaknesses in recognizing different categories.

2.2.4 Result

This section presents the results of the experiments conducted to evaluate CLIP's zero-shot learning capabilities, specifically focusing on its ability to classify both seen and unseen categories using both name-based and attribute-based textual descriptions. The results are organized into three main phases: Name-Based Classification, Attribute-Based Classification, and the Pokémon Dataset Evaluation.

2.2.4.1 Experiment 1: Name-Based Classification

In the initial experiment, CLIP's ability to classify characters using name-based descriptions was tested. This phase focused on two sets of characters:

- **Classic Characters (Seen)**: Widely recognized characters such as Pikachu, Mario, and Sonic, expected to be included in CLIP's pretraining dataset.
- **Genshin Impact Characters (Unseen)**: Characters such as Raiden Shogun and Barbara, introduced after CLIP's pretraining period, were selected to test CLIP's ability to generalize to unseen data.

Accuracy:

- **Classic Characters**: CLIP achieved near-perfect Top-1 Accuracy of **1.0**, confirming the model's ability to recognize categories it encountered during pretraining.
- **Genshin Impact Characters**: CLIP's accuracy dropped significantly to **0.05**, demonstrating the model's struggle with unseen categories when only name-based descriptions are provided.

This result shows that CLIP relies heavily on memorizing labels from its pretraining dataset, with a significant decrease in performance for unseen categories.

2.2.4.2 Experiment 2: Attribute-Based Classification

The next phase of experiments tested CLIP's ability to classify characters using attribute-based descriptions, which provide richer, semantic context for each character. Descriptions such as "A small, yellow, mouse-like creature with pointy ears and red cheeks" for Pikachu were used.

- Classic Characters: Descriptions focused on visual traits, and CLIP performed well, achieving a Top-1 Accuracy of 0.93.
- Genshin Impact Characters: With richer descriptions, CLIP achieved an accuracy of 0.75, demonstrating a significant improvement in its ability to classify unseen characters.

The attribute-based descriptions allowed CLIP to generalize beyond simple name matching, relying on its understanding of visual and semantic features to classify unseen characters with more accuracy.




Figure 2.5 Genshin Impact Attribute Based Confusion Matrix

The confusion matrix will visually illustrate the misclassifications made for characters like Raiden Shogun, providing clarity on how the model's performance was affected by their similar attributes.

2.2.4.3 Experiment 3: Pokémon Dataset Evaluation

The final evaluation was conducted using a unified Pokémon dataset, designed to test CLIP's generalization across both seen and unseen categories. The dataset was split as follows:

- **Pre-CLIP Pokémon Characters (Seen)**: Characters such as Bulbasaur and Pikachu, introduced before CLIP's pretraining.
- **Post-CLIP Pokémon Characters (Unseen)**: Characters such as Meowscarada and Fuecoco, introduced after CLIP's pretraining.

Name-Based Classification:

- **Accuracy:**
    - **Seen Characters**: **0.99**
    - **Unseen Characters**: **0.06**
    - **Harmonic Mean Accuracy**: **0.11**

For the seen categories, CLIP performed excellently, with an accuracy of **0.99**, confirming the model's proficiency with familiar labels. However, for the unseen categories, the performance dropped drastically to **0.06**, and the Harmonic Mean Accuracy was **0.11**, reflecting the challenge CLIP faces in generalizing to new categories based only on name-based descriptions.




Figure 2.6 A Bar Chart of Name Based Accuracy for Pokémon

Attribute-Based Classification:

- **Accuracy:**
    - **Seen Characters**: **0.89**
    - **Unseen Characters**: **0.73**

- **Harmonic Mean Accuracy**: **0.80**

When attribute-based descriptions were used, CLIP's performance improved significantly for both seen and unseen categories. The Harmonic Mean Accuracy of **0.80** indicates a more balanced performance across both groups, with **0.89** accuracy for seen characters and **0.73** for unseen characters.




Figure 2.7 Pokémon Attribute Based Confusion Matrix

2.2.4.4 Key Findings and Visualizations

To further assess CLIP's performance, the results were visualized using several techniques:

- Confusion Matrix: The confusion matrix was generated to highlight misclassifications. It revealed patterns such as confusion between visually similar characters (e.g., Meowscarada vs. Sprigatito).

- Top-1 Accuracy per Class: The per-class accuracy chart revealed that CLIP performed well on seen categories but showed more variability with unseen categories, particularly when using name-based descriptions.



Figure 2.8 Comparison between Meowscarada and Sprigatito

2.2.4.5 Conclusion of Results

The results demonstrate that CLIP excels in zero-shot classification tasks when it has encountered the category name during pretraining. However, the model struggles to generalize to completely unseen categories when using name-based descriptions alone. The use of attribute-based descriptions significantly improves CLIP's performance, especially for categories it has not seen during training. This highlights the importance of semantic descriptions in enabling true zero-shot learning, where the model generalizes based on visual and semantic attributes rather than relying solely on memorized labels.

2.2.5 Discussion

This section discusses the key findings from the experiments conducted to evaluate CLIP's zero-shot learning capabilities, focusing on its strengths and limitations when handling seen and unseen categories using both name-based and attribute-based descriptions.

Strengths in Zero-Shot Learning

CLIP demonstrated strong performance when recognizing familiar categories (those seen during pretraining). For example:

- Classic Characters through Name-Based Descriptions: CLIP achieved perfect accuracy (1.0), confirming its ability to recognize well-known characters from Pokémon and other classic franchises.

- Classic Characters through Attribute-Based Descriptions: With accuracy of 0.93, CLIP effectively leveraged visual features from attribute-based descriptions, demonstrating its potential to generalize based on semantic understanding of visual attributes.

These results support the idea that CLIP excels in zero-shot learning when given familiar labels or rich, descriptive information.

Limitations with Unseen Categories

When tasked with recognizing unseen categories, CLIP's performance dropped significantly:

- Genshin Impact Characters through Name-Based Descriptions: CLIP achieved an accuracy of 0.05, indicating that it struggles with categories it has not encountered during pretraining.
- Pokémon Characters through Name-Based Descriptions: Similarly, accuracy of 0.11 (Harmonic Mean) showed a stark contrast between seen (0.99) and unseen (0.06) categories, emphasizing CLIP's reliance on prior label exposure.

These results suggest that name-based descriptions alone are insufficient for zero-shot learning in new categories, as CLIP struggles to generalize to unseen labels.

Improvement with Attribute-Based Descriptions

CLIP's performance improved significantly when attribute-based descriptions were used:

- Genshin Impact Characters through Attribute-Based Descriptions: The accuracy rose to 0.75, showing that rich descriptions allow CLIP to generalize better to new categories.
- Pokémon Characters through Attribute-Based Descriptions: CLIP achieved an accuracy of 0.80, demonstrating better performance for both seen and unseen characters when using attribute-based prompts.

This highlights that attribute-based descriptions provide essential semantic context, enabling CLIP to better classify unseen categories and improve its generalization capabilities.

Challenges and Future Directions

Despite the improvement with attribute-based descriptions, CLIP still faces challenges:

- Misclassifications occurred for visually similar characters (e.g., Meowscarada vs. Sprigatito), suggesting that fine-grained distinctions between categories remain difficult for CLIP.
- Systematic biases were also observed, where the model showed a preference for dominant categories in some cases, even when the correct category was present in the image.

Future work should focus on addressing these biases, improving fine-grained recognition, and exploring ways to automate attribute generation for more effective zero-shot learning, especially for new categories.

Chapter 3

Conclusion and Future Work

3.1 Conclusion

This project investigates the zero-shot learning capabilities of the CLIP model, specifically evaluating its ability to classify unseen categories. The experiments conducted demonstrated that CLIP excels in identifying categories that it has encountered during pretraining, particularly when using name-based textual descriptions. For categories present in the training data, the model showed high accuracy, confirming its proficiency in recognizing known labels.

However, the performance of CLIP significantly drops when presented with unseen categories, particularly when using name-based descriptions, which CLIP relies on for classification. This issue emphasizes the model's dependence on pre-existing knowledge during its training phase. The results from the Pokémon dataset further reinforced this observation, with CLIP achieving low accuracy (0.06) for unseen characters using name-based prompts. In contrast, CLIP's performance improved significantly when attribute-based descriptions were employed. By utilizing visual cues and semantic features such as color, posture, and shape, CLIP demonstrated its capacity to generalize beyond familiar categories, achieving an accuracy of 0.73 for unseen Pokémon characters.

The study also revealed that CLIP's generalization ability is closely tied to the richness of the textual descriptions provided. While CLIP is highly effective in tasks involving familiar categories, it struggles to generalize to new, unseen labels unless given detailed and descriptive prompts. Despite these improvements, challenges such as misclassifications between visually similar characters and the model's inherent biases toward dominant categories still exist. These findings suggest that CLIP’s true zero-shot capabilities depend heavily on the type and quality of the prompts used, highlighting the need for more nuanced and descriptive inputs to fully leverage its potential in real-world applications.

3.2 Future Work

Despite providing useful insights into CLIP's zero-shot learning capabilities, several areas for future research remain. Below are suggested directions for improving CLIP's performance and expanding its applications:

1. Dataset Expansion and Diversity

To further assess CLIP's generalization abilities, future research should focus on expanding the dataset to include a broader range of categories, including real-world objects, animals, and human categories. The current dataset could be expanded to cover additional characters and categories from diverse domains, which would allow for a more thorough evaluation of CLIP's ability to generalize across a wider range of visual and semantic contexts.

2. Fine-Grained Classification

While attribute-based descriptions significantly improved CLIP's performance on unseen categories, the model still struggles with distinguishing between visually similar categories, such as Meowscarada and Sprigatito. Future work should focus on refining CLIP's fine-grained classification abilities. Incorporating more detailed, specific attributes into the descriptions could help improve the model's performance in tasks that require subtle distinctions. Furthermore, techniques like region-based attention mechanisms could be explored to help the model focus on discriminative regions of the image, enhancing its ability to differentiate between similar categories.

3. Bias Mitigation and Fairness

One of the challenges identified in this study was CLIP's bias toward dominant categories. The model tended to prefer well-represented categories in its pretraining dataset, leading to misclassifications when less-represented or new categories were encountered. Future research should investigate ways to mitigate these biases, such as through fine-tuning CLIP on more balanced datasets or using methods like re-sampling or re-weighting the data. Additionally, understanding and addressing fairness in the model's predictions will be crucial for ensuring that CLIP can be reliably applied in sensitive domains like healthcare and autonomous systems.

4. Automated Attribute Generation

An important limitation in this study was the manual creation of attribute-based descriptions. To scale zero-shot learning to more categories and datasets, future work should focus on automated attribute generation. This process can be streamlined by removing character names from the descriptions, leaving only the attributes. ChatGPT can then be used to generate descriptive text for each category based on the attributes. Rather than selecting the best description, all generated texts can be used as-is, or if multiple descriptions are generated, their average could be taken to ensure consistency. This approach could drastically reduce the manual effort required for generating descriptions and improve the scalability of the model.

5. Hybrid Prompting Strategies

A promising direction for future work is to combine name-based and attribute-based prompts in a hybrid manner. By leveraging both approaches, CLIP can benefit from the strengths of both strategies—using name-based descriptions for familiar categories and attribute-based descriptions for new, unseen categories. Future work should explore dynamic prompting strategies, where the model intelligently chooses between name-based and attribute-based descriptions depending on the task and the availability of prior knowledge. This would allow for a more robust zero-shot classification system that adapts to varying types of input.

6. Cross-Domain Applications

Extending CLIP's capabilities to cross-domain applications is an essential step for future research. While this study focused on game characters, zero-shot learning is particularly valuable for dynamic and evolving categories, such as those found in medical imaging, e-commerce, and autonomous driving. Future research should assess CLIP's generalization ability in these real-world domains, where new categories frequently arise. By expanding the scope of CLIP's application to other domains, we can better understand its potential and limitations in dynamic environments.

7. Survey for Zero-Shot Learning Comparison

An additional and interesting approach would be to conduct a survey-based study to involve people in performing zero-shot learning tasks. This could be done by asking

individuals from different backgrounds to attempt zero-shot classification tasks similar to those performed by CLIP. By comparing human results with CLIP's performance, it would be possible to assess how CLIP's capabilities align with human reasoning and understanding of unseen categories. This comparison could provide valuable insights into CLIP's limitations and areas where human performance outperforms the model.

By exploring these areas, future research can enhance CLIP's zero-shot learning capabilities, addressing its limitations and extending its applicability across diverse real-world scenarios. The ongoing development and refinement of the model will help improve its generalization ability, enabling more accurate and reliable zero-shot classification tasks in dynamic, real-world applications.

References

The references will follow an IEEE style (or any other standard referencing format such as Harvard, APA, among others).

[1] A. Radford, J. W. Kim, C. Hallacy, A. Ramesh, G. Goh, S. Agarwal, G. Sastry, A. Askell, P. Mishkin, J. Clark, G. Krueger, and I. Sutskever, “Learning transferable visual models from natural language supervision,” *Proc. 38th Int. Conf. Mach. Learn. (ICML)*, vol. 139, pp. 8748–8763, 2021.

[2] J. Zhang, J. Huang, S. Jin, and S. Lu, “Vision-language models for vision tasks: A survey,” *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. 46, no. 8, pp. 1–20, 2024.

[3] C. H. Lampert, H. Nickisch, and S. Harmeling, “Attribute-based classification for zero-shot visual object categorization,” *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. 36, no. 3, pp. 453–465, Mar. 2014.

[4] Y. Xian, B. Schiele, and Z. Akata, “Zero-shot learning—the good, the bad and the ugly,” *Proc. IEEE Conf. Comput. Vis. Pattern Recognit. (CVPR)*, 2017, pp. 4582–4591.

[5] G. Yang, Z. Ye, R. Zhang, and K. Huang, "A comprehensive survey of zero-shot image classification: methods, implementation, and fair evaluation," *Appl. Comput. Intell.*, vol. 2, no. 1, pp. 1–31, Mar. 2022, doi: 10.3934/aci.2022001.

[6] K. Zhou, J. Yang, C. C. Loy, and Z. Liu, “Learning to prompt for vision-language models,” *Advances in Neural Information Processing Systems*, vol. 34, pp. 16521–16533, 2021.

[7] Y. Xian, C. H. Lampert, B. Schiele, and Z. Akata, “Zero-shot learning—A comprehensive evaluation of the good, the bad, and the ugly,” *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. 41, no. 9, pp. 2251–2265, Sep. 2019, doi: 10.1109/TPAMI.2018.2857768.

[8] T. Zhou, Y. Zhang, and M. Long, “Compositional zero-shot learning with semantic-aware generative networks,” in *Proc. IEEE Conf. Comput. Vis. Pattern Recognit. (CVPR)*, 2020, pp. 11494–11503.

[9] M. Shu et al., “Test-time prompt tuning for zero-shot generalization in vision-language models,” arXiv preprint arXiv:2209.07511, 2022.

[10] R. Menon et al., “Visual prompt tuning,” in *Proc. Eur. Conf. Comput. Vis. (ECCV)*, 2022, pp. 709–727, doi: 10.1007/978-3-031-19827-4_41.

[11] K. Chou, Y. Huang, and W. Hsu, “Fine-grained zero-shot learning with attribute-guided attention,” in *Proc. IEEE Conf. Comput. Vis. Pattern Recognit. (CVPR)*, 2020, pp. 10445–10454, doi: 10.1109/CVPR42600.2020.01046.

[12] J. Li, T. Chen, and S. Yu, “Contrastive learning for zero-shot learning,” *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. 45, no. 9, pp. 2003–2017, Sep. 2023.

[13] T. Qiao, R. Yao, and S. Sha, “Graph convolutional networks for zero-shot learning,” *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. 41, no. 10, pp. 2567–2579, Oct. 2019.

[14] M. Arjovsky, S. Chintala, and L. Bottou, “Wasserstein GAN,” in *Proc. Int. Conf. Mach. Learn. (ICML)*, 2017, pp. 214–223.

Appendix A. Code Implementation

Cosine Similarity

```
# normalized features
image_features = image_features / image_features.norm(dim=1, keepdim=True)
text_features = text_features / text_features.norm(dim=1, keepdim=True)

# cosine similarity as logits
logit_scale = self.logit_scale.exp()
logits_per_image = logit_scale * image_features @ text_features.t()
logits_per_text = logits_per_image.t()
```

Softmax Calculation

```
logits_per_image, _ = model(image, text_tokens)
probs = logits_per_image.softmax(dim=-1).cpu().numpy()
```

Top-1 Accuracy

```
if pred_label == selected_character:
    correct += 1
    correct_per_char += 1
total += 1
acc = correct / total if total > 0 else 0
```

Harmonic Mean Accuracy

```
if acc_seen > 0 and acc_unseen > 0:
    harmonic_mean = 2 * acc_seen * acc_unseen / (acc_seen + acc_unseen)
    print("\n" + "=" * 60)
    print(f"Seen Accuracy (old): {acc_seen:.2f}")
    print(f"Unseen Accuracy (new): {acc_unseen:.2f}")
```

```
    print(f"Harmonic Mean (H): {harmonic_mean:.2f}")
else:
    print("One or both groups had 0 accuracy; cannot compute harmonic mean.")
```

Confusion Matrix

```
from sklearn.metrics import confusion_matrix

def plot_confusion_matrix(y_true, y_pred, labels, output_dir):
    cm = confusion_matrix(y_true, y_pred, labels=labels)
    plt.figure(figsize=(10, 7))
    sns.heatmap(cm, annot=True, fmt="d", cmap="Blues", xticklabels=labels, yticklabels=labels)
    plt.title("Confusion Matrix")
    plt.xlabel('Predicted')
    plt.ylabel('True')
    plt.xticks(rotation=45)
    plt.tight_layout()
    plt.savefig(os.path.join(output_dir, 'confusion_matrix.png'))
    plt.close()
```

Per-Class Accuracy

```
def plot_accuracy_per_class(y_true, y_pred, labels, output_dir):
    accuracy_per_class = []
    for label in labels:
        correct = sum(1 for true, pred in zip(y_true, y_pred) if true == label and pred == label)
        total = sum(1 for true in y_true if true == label)
        accuracy_per_class.append(correct / total if total > 0 else 0)

    plt.figure(figsize=(10, 7))
    sns.barplot(x=labels, y=accuracy_per_class, palette="Blues_d")
```

```
plt.title("Top-1 Accuracy per Class")
plt.xlabel("Class")
plt.ylabel("Accuracy")
plt.xticks(rotation=45)
plt.tight_layout()
plt.savefig(os.path.join(output_dir, 'accuracy_per_class.png'))
plt.close()
```