

Replicated Redis List: An Operational **Transformation Approach**

Anonymous Author(s)

$$\text{OT}\left(\text{Ins}(i_{1},e_{1},p_{1}),\text{Ins}(i_{2},e_{2},p_{2})\right) = \begin{cases} i_{1} < i_{2} \\ i_{1} > i_{2} \\ i_{1} = i_{2} \wedge e_{1} = e_{2} \\ i_{1} = i_{2} \wedge e_{1} \neq e_{2} \wedge p_{1} > p_{2} \\ i_{1} = i_{2} \wedge e_{1} \neq e_{2} \wedge p_{1} \leq p_{2} \end{cases}$$

$$\text{OT}\left(\text{Trim}(i,j),\text{Trim}(m,n)\right) = \begin{cases} \text{Trim}(0,-1) & (i,j) \cap (m,n) = \emptyset \\ & \cdots \end{cases}$$

$$(2)$$

$$\text{OT}\left(\text{Trim}(i,j),\text{Del}(k)\right) = \begin{cases} \text{Trim}(i-1,j-1) & k < i \leq j \\ \text{Trim}(i,j-1) & k = i < j \\ \text{Trim}(i,j-1) & i < k < j \\ \text{Trim}(i,j-1) & i < k < j \\ \text{Trim}(i,j-1) & i < k < j \\ \text{Del}(k) & k = i < j \\ \text{Del}(k-i) & i < k = j \\ \cdots \end{cases}$$

$$(4)$$

Figure 1. Operational Transformations for the Redis List.

Operational Transformations for the Redis List

According to the official document, a Redis list supports 17 operations [1]. Among the 14 non-blocking operations, we study the following ones: LPUSH, RPUSH, LPUSHX, RPUSHX, LPOP, RPOP, INSERT, SET, TRIM, and REM. We also consider DEL and INS, deletions and insertions by indices. Table 1 presents the (informal) sequential specification of these 16 Redis list operations.

Table 1. Redis list operations.

221	References	276
222	[1] [n. d.]. ([n. d.]).	277
223		278
224		279
225		280
226		281
227		282
228		283
229		284
230		285
231		286
232		287
233		288
234		289
235 236		290 291
237		291
238		293
239		294
240		295
241		296
242		297
243		298
244		299
245		300
246		301
247		302
248		303
249		304
250		305
251		306
252		307
253		308
254		309
255		310
256 257		311 312
258 259		313 314
260		315
261		316
262		317
263		318
264		319
265		320
266		321
267		322
268		323
269		324
270		325
271		326
272		327
273		328
274		329
275	3	330