

```

|----- MODULE OpCorrectness -----|
| EXTENDS Correctness |
|-----|
| VARIABLES buset  buset[r]: the buffer of local updates generated by r ∈ Replica since the last broadcast |
|-----|
| OpCInit  ≜ |
|   ∧ CInit |
|   ∧ buset = [r ∈ Replica ↦ {}] |
| |
| OpCDo(r)  ≜ |
|   ∧ CDo(r) |
|   ∧ buset' = [buset EXCEPT ![r] = @ ∪ {[r ↦ r, seq ↦ seq[r]]}]  collect a new update |
| |
| OpCSend(r)  ≜ |
|   ∧   CSend(r) |
|   ∧   uincoming' = [x ∈ Replica ↦ |
|       IF x = r THEN uincoming[x]  broadcast buset[r] |
|       ELSE uincoming[x] ∪ {[aid ↦ [r ↦ r, seq ↦ seq[r]], update ↦ buset[r]]}] |
|   ∧   buset' = [buset EXCEPT ![r] = {}]  clear buset[r] |
| |
| OpCDeliver(r, aid)  ≜ |
|   ∧ CDeliver(r, aid) |
|   ∧ UNCHANGED ⟨buset⟩ |
|-----|
| \ * Modification History |
| \ * Last modified Thu Aug 29 10:46:30 CST 2019 by xhdn |
| \ * Created Wed Aug 28 19:24:11 CST 2019 by xhdn |

```