From Data to Action: Designing Human-Centered, Impact-Driven Decision Systems

Assignment 2

Due Date	Submission
September 18, 2026 11:59PM	Gradescope

This assignment is worth *100 points*, accounting for **15%** of the total course grade. It consists of **3 problems** aligned with techniques/tools covered in **lectures in Weeks 3-4**. Each problem may have one or two components: **written** and **programming**. You are expected to first work through the written questions to build context and conceptual understanding, and then, if applicable, complete the programming part.

Please strictly adhere to the Academic Integrity policies stated in the course syllabus and DO NOT CHEAT. We will run plagiarism checks on Gradescope.

In general, the following is required:

- Follow Submission Instruction *(2 points)*
- Problem #1: Shortest Path via Backward Induction *(35 points)*
- Problem #2: Hospital Surge Staffing via Q-Learning *(35 points)*
- Problem #3: Ride-hailing Pricing via Decision-Dependent Predict-then-Optimize *(28 points)*

Submission Instruction

Gradescope will have **two submission entries**: one for the programming and the other for the written. Failing to follow the submission instructions will result in a 2-point deduction as well as a delay in the grading process.

Programming Submission

One programming submission attempt should include **all Jupyter Notebooks and, if required, CSV files**. Submission attempts are unlimited. The Autograder relies on file names to run and assign grades. Therefore, please do **NOT rename** the provided start notebooks. If the handout specifies a required name for an output file, you must **use that exact same name** so the Autograder can successfully access it.

Written Submission

The written submission should be **1 single PDF file** containing your answers to all written questions. It must strictly follow this handout template without altering its layout or page structure. In other words, your PDF submission should have the same number of pages and the same alignment as this provided PDF template. Misalignment will cause Gradescope to incorrectly detect answer positions, which you can notice right after submission; as a result, your submission may not be graded correctly by the AI-assisted Autograder.

To ensure page consistency and alignment, you may complete the written questions in one of the following ways:

- type in LaTeX using the provided `.tex` file (we recommend using Overleaf)
- write on an electronic handout directly
- print the handout, write by hand, and scan it at Letter size

Each written question is either a multiple-choice question (MCQ) or a short-answer question (SAQ). You may receive partial credit on "Select all that apply" MCQs. Specific answer instructions are as follows:

For "Select one" questions, please fill in the appropriate circle completely:

1. (1 pt) **Select one:** Who teaches this course?

   ● Peter Zhang

   ○ Michael Johnson

   ○ Jennifer Smith

- If you work in LaTeX, simply replace `\choice` with `\CorrectChoice` as your answers. Our pre-defined environment will render PDF correctly.
- If you write on an electronic copy, use **black** color to fill the circle. An overfilled circle is acceptable.
- If you write on a print copy and need to change your answer, you may cross out the previous answer and circle in the new answer:

  (1 pt) **Select one:** Who teaches this course?

  ● Peter Zhang

  ○ Michael Johnson

  ⊗ Jennifer Smith

For "Select all that apply" questions, please fill in all appropriate squares completely:

2. (2 pts) **Select all that apply:** Which ones are the correct course number?

   ■ 94-867

   ■ 19-867

   ■ 12-768

   □ 12-867

   □ None of the above

- If you work in LaTeX, please do **NOT modify** the following line, which ensures square option symbol:
  `\checkboxchar{$\Box$} \checkedchar{$\blacksquare$}`
- To change answers on a print copy, you may cross out the previous answer(s) and fill in the new answer(s), the same as "Select one".

For "Short answer" and "Show your plot" questions, please complete inside the corresponding answer boxes. Two sample answers are shown below: one is acceptable, while the other is NOT.

3. (5 pts) **Short answer:** Use the `lipsum` package to generate a paragraph of Lorem Ipsum text

> Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

↑ This answer is **acceptable**.

(5 pts) **Short answer:** Use the `lipsum` package to generate the first paragraph of Lorem Ipsum text.

> Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

↑ This answer is **NOT acceptable**.

For "Show your code" questions, the general requirements stay the same as "Short answer" and "Show your plot". When asked to show code for a function, your response must include the complete function definition with all lines of code (an example below for your reference). Note that pseudocode will NOT receive any credits.

4. (5 pts) **Show your code:** Complete the `show_all_entry()` function.

```
def show_all_entry(array):
    for r in range(array.shape[0]):
        for c in range(array.shape[1]):
            print(array[r, c])
```

You can use one of the following ways to show code:

- Type code in LaTeX. The given answer box is already pre-formatted for coding.
- Insert a screenshot of your code inside the answer box
- Write by hand with clear indents

1 Shortest Path via Backward Induction

The shortest path problem is a classic example in dynamic programming. It involves finding the most efficient route through a network where each step has an associated cost. Rather than solving the entire problem at once, dynamic programming breaks it into smaller stages, solving each subproblem and building up to the overall solution. This approach is especially useful when decisions at one stage affect future outcomes.

In this problem, you are asked to plan a trip from your home to one of the downtown parking lots. Nodes constitute the traffic network (Figure 1). The number in the **upper-left corner** of each node denotes its node ID and the number **inside the node** specifies the travel time required to pass through that node. **Your home is located at Node `A3`, while the parking lots are represented by any node in the rightmost column** (Nodes `F1-F6`). Each intermediate node corresponds to a neighborhood. The edges represent neighborhood boundaries, and crossing a boundary does not add any additional time.

The objective is to determine the **shortest path from your home to a parking lot** (any one of `F1-F6`). Although one could use forward calculation by enumerating all possible paths from the home node to a parking lot, it is computationally expensive. A more efficient method is to apply Backward Induction (BI) to the network.




Figure 1: Path Network

The problem can be formulated as a dynamic decision process with multiple stages, where the six columns of neighborhoods represent the six stages, with the following notations:

- **Stage** $t \in \{1, 2, \ldots, 6\}$ represents the column in the network, where $T = 6$ is the terminal stage
- **State** s_t, with s_T as the terminal state and
- **Action** $a(s_t)$, e.g. $a(s_t = \texttt{A3}) = \texttt{B3}$
- **Transition Set** $N(s_t)$ is a set of all feasible next states that can be reached from the current state s_t
- **Cost Function** $g(s_t)$, e.g. $g(s_t = \texttt{B3}) = 7$
- **Cost-to-go Value** $J_t(s_t)$, with $J_T(s_T)$ for the terminal stage

1.1 Written

(a) *(5 points)* **Select all that apply:** Which of the following statements are correct?

- ■ States refer to the specific node in the network at stages.
- ■ Actions refer to the decision of which neighboring node to move to next.
- □ The number of states depends on the path chosen.
- ■ The cost function measures the travel time.
- □ The cost-to-go value is the minimal travel time spent from home to the current state.

(b) *(5 points)* **Select all that apply:** Which of the following statements are correct?

- □ The first step of BI is to assign cost-to-go values to the home node.
- □ The first step of BI is to choose the parking lot with the lowest cost.
- □ BI computes the cost of all possible paths in this network.
- ■ If two different paths have the same minimum total cost, BI considers either path as optimal.
- ■ An optimal path must contain optimal sub-paths.

(c) *(5 points)* **Select all that apply:** Which of the following would affect the optimal path in this network?

- ■ Close one of the parking lots
- ■ Change travel time inside a single neighborhood
- □ Increase travel time in every node by the same constant
- ■ Adding extra edges between neighborhoods
- □ Rename the node IDs

(d) *(5 points)* **Short answer:** Write the cost-to-go function *(Tip: formualte $J_t(s_t)$ and $J_T(s_T)$ separately).*

At the terminal stage $t = T = 6$ nothing remains to be decided, so the cost-to-go of a parking lot is just its own travel time.

$$J_T(s_T) = g(s_T), \qquad s_T \in \{\texttt{F1}, \ldots, \texttt{F6}\}$$

Every earlier stage is then computed backward for $t = T - 1$ down to $t = 1$.

$$J_t(s_t) = \min_{s_{t+1} \in N(s_t)} \{\, g(s_t) + J_{t+1}(s_{t+1}) \,\} = g(s_t) + \min_{s_{t+1} \in N(s_t)} J_{t+1}(s_{t+1})$$

Cost sits on the nodes and not on the edges, so $g(s_t)$ is paid whichever neighbor we pick and it factors out of the min. The stored action is $a(s_t) = \arg\min_{s_{t+1} \in N(s_t)} J_{t+1}(s_{t+1})$.

(e) *(10 points)* **Show your calculation:** Compute the cost-to-go value for node D4, $J_4(s_4 = \texttt{D4})$. Include the calculation steps from the terminal stage to stage 4. What is the action $a(s_4 = \texttt{D4})$?

Stage 6. Nothing remains to be decided once we reach a parking lot, so every terminal value is just that node's own travel time.

$$J_6(\texttt{F1}) = 8, \quad J_6(\texttt{F2}) = 2, \quad J_6(\texttt{F3}) = 6, \quad J_6(\texttt{F4}) = 5, \quad J_6(\texttt{F5}) = 5, \quad J_6(\texttt{F6}) = 3$$

Stage 5. From D4 the only feasible next states are $N(\texttt{D4}) = \{\texttt{E3}, \texttt{E4}\}$, so those are the two values we actually need.

$$J_5(\texttt{E3}) = g(\texttt{E3}) + \min\{J_6(\texttt{F3}),\, J_6(\texttt{F4})\} = 7 + \min\{6,\, 5\} = 7 + 5 = 12$$
$$J_5(\texttt{E4}) = g(\texttt{E4}) + \min\{J_6(\texttt{F4}),\, J_6(\texttt{F5})\} = 9 + \min\{5,\, 5\} = 9 + 5 = 14$$

The two continuations from E4 are tied at 5, so either one is optimal there.
Stage 4.

$$J_4(s_4 = \texttt{D4}) = g(\texttt{D4}) + \min_{s_5 \in N(\texttt{D4})} J_5(s_5) = 3 + \min\{\, J_5(\texttt{E3}),\, J_5(\texttt{E4}) \,\}$$
$$= 3 + \min\{12,\, 14\} \;=\; 3 + 12 \;=\; \mathbf{15}$$

The minimum is attained at E3, so $J_4(s_4 = \texttt{D4}) = 15$ and $a(s_4 = \texttt{D4}) = \texttt{E3}$. Only five of the 36 nodes were needed to answer this, which is the whole point of working backward instead of enumerating paths.

(f) *(5 points)* **Short answer:** What is the optimal path of actions? Use the node ID.

Carrying the same recursion left to stage 1 gives $J_1(s_1 = \texttt{A3}) = 23$. Reading the stored actions forward from home then produces the path.

$$\texttt{A3} \;\to\; \texttt{B4} \;\to\; \texttt{C4} \;\to\; \texttt{D5} \;\to\; \texttt{E5} \;\to\; \texttt{F6}$$

The travel times add to $7 + 3 + 6 + 3 + 1 + 3 = 23$, which matches $J_1(\texttt{A3})$ as it should. Note that F2 is the cheapest lot at 2 and we still do not end there, since reaching it costs more than the single unit it saves. D4 is not on this path either, even though part (e) valued it, because backward induction values every state and not only the ones we end up visiting.

2 Hospital Surge Staffing via Q-Learning

In this assignment, we will revisit the Hospital Surge Staffing problem discussed in the recitation.

As the following questions are based on the solution notebook, please study the notebook carefully before answering. You can find all `function()` and `class` mentioned in the questions from the notebook.

For your convenience, the solution notebook, named as `D2A_A2_HospitalStaffing.ipynb`, is included in the handout package. It is the recitation solution notebook posted on Canvas, with an added SARSA section at the end.

2.1 Written

(a) *(5 points)* **Select all that apply:** Which of the following statements about the Q-learning update rule (Equation 1) are correct?

$$Q_t(x_t, u_t) \leftarrow (1-\alpha)Q_t(x_t, u_t) + \alpha\Big(r_t + \gamma \min_{u_{t+1}} Q_{t+1}(x_{t+1}, u_{t+1})\Big) \tag{1}$$

- ■ It blends old and new estimates using the learning rate α.
- ■ It uses the immediate cost plus the discounted best estimate of future cost.
- □ It requires the full transition model of the environment to run.
- ■ It is a sample-based approximation of the Bellman optimality equation.
- □ It ignores rewards or costs when updating.

(b) *(5 points)* **Select all that apply:** Which of the following statements correctly describe the role of ϵ-greedy exploration in Q-learning, i.e., the `choose_action()` function of `QLearningAgent`?

- ■ It prevents the agent from prematurely converging to a suboptimal policy.
- □ It guarantees the agent always finds the globally optimal solution.
- ■ It encourages trying actions with uncertain or unexplored values.
- ■ It balances the trade-off between learning new information and exploiting known information.
- □ The agent will still explore sufficiently after removing ϵ-greedy, because the learning rate α provides randomness.

(c) *(5 points)* **Select all that apply:** Which of the following statements distinguish Backward Induction from Q-learning?

- ■ Backward induction requires full knowledge of the transition probabilities and costs.
- ■ Backward induction computes the exact cost-to-go function, while Q-learning estimates it iteratively.
- □ Backward induction always converges faster than Q-learning, regardless of problem size.
- ■ Q-learning learns optimal policies through simulated or real experience.
- □ Q-learning cannot achieve the optimal policy even with infinite training.

(d) *(2 points)* **Short answer:** When calling the `step()` function of `HospitalEnvQL`, one of the results is variable of next state. What does this next state variable include? Explain in words what it/they means/mean in the context of hospital surge staffing.

It is a tuple of two integers, $(t_{\text{next}}, x_{\text{next}})$, which are the next hour of the day and the number of patients still waiting at the start of that hour.
Inside `step()` the queue updates as `x_next = np.clip(x + d - cap, 0, X_MAX)`, with `d = rng.poisson(lam)` and `cap = 2*(10 + u)`. In simpler terms we take who is already waiting, add the patients who walked in this hour, subtract everyone the 10 base plus u surge doctors can treat at 2 patients per hour, and do not go below zero.
The clock has to be part of the state and not just the queue. Twenty patients waiting at 9am and twenty at 7pm call for completely different decisions, since at 9am there are hours of capacity left to work the queue down while at 7pm every remaining patient triggers the terminal penalty $W = \$300$. That is why the notebook calls (t, x) the augmented state. When $t + 1 > T$ the variable becomes $(13, x_{\text{next}})$, which flags the end of the day so the terminal cost is charged.

Q-table is one of the keys in tabular Q-learning. In the notebook, `QLearningAgent` initializes the Q-table using the code below, which is a 3-dimensional table.

```
self.Q = np.zeros((T+2, X_MAX+1, U_MAX+1), dtype=float)
```

(e) *(2 points)* **Short answer:** What does each dimension represent in the context of hospital surge staffing?

The table is indexed `Q[t, x, u]`, so the three dimensions are the stage, the state and the action.

- Size `T+2` is the stage t, meaning the hour of the day for $t = 1, \ldots, T = 12$, plus an unused index 0 so the hours stay 1-indexed, plus the terminal stage $t = T + 1 = 13$.
- Size `X_MAX+1` is the state x_t, the number of patients waiting at the start of hour t, running from 0 to `X_MAX`.
- Size `U_MAX+1` is the action u_t, the number of on-demand doctors staffed in hour t, running from 0 to `U_MAX`.

Each entry is then the expected cumulative cost of staffing u surge doctors when x patients are waiting in hour t and behaving optimally afterward.

(f) *(2 points)* **Short answer:** Why is it `X_MAX+1` instead of `X_MAX` directly?

The queue length is used directly as a zero-based array index, and it can take any integer value from 0 to `X_MAX` inclusive. That is `X_MAX` + 1 distinct states rather than `X_MAX`.
Both endpoints are real states that have to be stored. An empty waiting room sits at index 0, and a full waiting room needs index `X_MAX` to exist. Sizing the axis at `X_MAX` would make `X_MAX` − 1 the largest valid index and raise an `IndexError` the first time `np.clip` pushes the queue up to its cap.
The same counting gives `U_MAX+1`, since staffing no extra doctors is itself a valid action and it occupies index 0.

Learning rates decay over the course of learning in the notebook implementation. Therefore, we should formally write the update rule as Equation 2 where a_t varies over time.

$$Q_t(x_t, u_t) \leftarrow (1 - \alpha_t) Q_t(x_t, u_t) + \alpha_t \Big(r_t + \gamma \min_{u_{t+1}} Q_{t+1}(x_{t+1}, u_{t+1}) \Big) \tag{2}$$

(g) *(2 points)* **Show your code:** Which line of the `learn()` function of `QLearningAgent` in the notebook controls the learning rate decaying?

```
self.lr = max(self.lr_min, self.lr - self.lr_dec)
```

(h) *(5 points)* **Select all that apply:** Which of the following statements are correct?

- ☐ A high learning rate α always guarantees faster and more stable convergence.
- ■ Decaying the learning rate α over time helps stabilize learning once Q-values are close to convergence.
- ■ The discount factor γ controls how much future costs are taken into account relative to immediate ones.
- ■ If $\gamma = 1$, future costs are considered equally important as immediate costs.
- ☐ If both γ and α are set to zero, Q-learning still converges to the optimal policy.

(i) *(2 points)* **Short answer:** The current a_t follows a time-dependent linear decay until it reaches a minimum threshold. How would you modify this schedule to use a non-linear decay instead? **Express your answer as a formula of the form** $a_t = \ldots$. Your proposed schedule could be either time-dependent or time-independent.

I would replace the subtractive step with a multiplicative one, which gives geometric decay down to the same floor.

$$\alpha_t \;=\; \max\{\, \alpha_{\min},\;\; \alpha_0 \cdot \rho^{\,t} \,\}, \qquad 0 < \rho < 1$$

This is the same as $\alpha_t = \max\{\alpha_{\min}, \alpha_0 e^{-\lambda t}\}$ with $\lambda = -\ln \rho$, and $\alpha_0 = 0.3$, $\rho = 0.9995$, $\alpha_{\min} = 0.05$ would be reasonable here. In code it is one character of change, since `self.lr - self.lr_dec` becomes `self.lr * self.lr_dec`. Removing a constant fraction each step rather than a constant amount means the rate drops quickly while the Q-values are still crude and then flattens into a long tail of fine tuning.
A time-independent alternative would decay each state and action pair by its own visit count $N_t(x_t, u_t)$.

$$\alpha_t \;=\; \frac{\alpha_0}{1 + \kappa\, N_t(x_t, u_t)}$$

I would prefer this one for the hospital problem, since visits are very uneven and a global clock shrinks α for rarely seen queue lengths before they have learned anything. It also satisfies the Robbins-Monro conditions $\sum_t \alpha_t = \infty$ and $\sum_t \alpha_t^2 < \infty$ that the convergence proof needs.

SARSA (State-Action-Reward-State-Action) is a simpler reinforcement learning algorithm than Q-learning. The agent works similarly to Q-learning that takes actions, receives feedback, and continuously updates its behavior to maximize long-term rewards.

SARSA updates the Q-value using Equation 3.

$$Q_t(x_t, u_t) \leftarrow (1 - \alpha_t)Q_t(x_t, u_t) + \alpha_t\Big(r_t + \gamma Q_{t+1}(x_{t+1}, u_{t+1})\Big) \tag{3}$$

As you can see, the key difference is that SARSA does not include min operation. Therefore, SARSA is an **on-policy** algorithm learning the value of the policy it is actually following, while Q-learning is **off-policy** that learns the value of the optimal policy while possibly following a different exploratory policy when taking actions.

(j) *(3 points)* **Select all that apply:** Which of the algorithms eventually converge to the same Q-values, despite differences in the number of steps required for convergence?

- ■ Q-learning with ϵ-greedy, where $\epsilon = 0.1$
- □ SARSA with the same ϵ-greedy, $\epsilon = 0.1$
- ■ SARSA with dynamic ϵ-greedy, where ϵ is gradually reduced from 0.1 to 0
- □ All three algorithms above lead to different Q-values

(k) *(2 points)* **Short answer:** Reason your answer to the above question.

The three differ in which policy the update target is evaluating, not in how fast they learn.
Q-learning with a fixed ϵ converges to Q^*. Its target bootstraps from $\min_{u_{t+1}} Q_{t+1}(x_{t+1}, u_{t+1})$, which is the value of the best next action rather than the action actually taken. That makes it off-policy and a sample-based version of the Bellman optimality equation, so behaving randomly 10% of the time changes which cells get visited but not the fixed point they settle on.
SARSA with the same fixed ϵ does not. Its target bootstraps from $Q_{t+1}(x_{t+1}, u_{t+1})$ where u_{t+1} is the action the ϵ-greedy policy will really take, so it is on-policy and converges to Q^π for that exploratory policy instead. Since the policy takes a random and often expensive action 10% of the time, SARSA is correctly pricing in the cost of its own exploration, and its values stay pessimistic relative to Q^*. This is not a bug, it is a different question being answered.
SARSA with ϵ decayed to zero converges to Q^* again. The policy being evaluated becomes the greedy policy in the limit, so $Q^\pi \to Q^*$ and the on-policy target lines up with the off-policy one.
So options 1 and 3 share the same limit while option 2 does not. The notebook shows this on the 1-D driving example, where the exact $Q^*(1, \mathrm{R})$ is 6.20, Q-learning reaches 6.20, SARSA with a decaying ϵ reaches 6.18, and SARSA with a fixed ϵ only reaches about 5.75.

3 Ride-hailing Pricing via Decision-Dependent Predict-then-Optimize

3.1 Programming

Complete the provided start Jupyter notebook, `D2A_A2_SurgePricing.ipynb`.

Export the following spreadsheets of your model results as guided in the notebook.

(a) *(10 points)* `prediction_test.csv`

(b) *(15 points)* `optimization_decisions.csv`

3.2 Written




Figure 2: Sample Plot of the Last Cell of the Notebook

(a) *(3 points)* **Short answer:** If your notebook is implemented correctly, the last cell should output a figure similar to Figure 2. The figure includes the supply and demand curves. The black dashed vertical line indicates where the optimized surge multiplier is.
Carefully read the code and understand the plot. How do you interpret this plot?
(Answer box is on the next page)

Both curves are what the two random forests predict for one fixed scenario as the surge multiplier is swept across its whole feasible range from 1 to 3. The time of day, day of week and weather score are held constant, so the only thing moving along the horizontal axis is the decision itself.

The supply curve rises. A larger multiplier pays drivers more, so more of them make themselves available, and predicted supply climbs from roughly 131 at $s = 1$ to roughly 188 at $s = 3$. The demand curve falls, since the same multiplier is a higher fare to riders, and predicted demand drops from roughly 141 down to roughly 72 over that range. Neither curve is smooth, because both are tree ensembles and they move in flat steps rather than as continuous functions.

Matches are $\min\{y_S, y_D\}$, so the objective is the lower envelope of the two curves and not either curve on its own. Left of the crossing point supply is the short side, so raising the multiplier recruits drivers and adds matches. Right of the crossing demand is the short side, so raising it further only prices riders out and destroys matches. The peak of the lower envelope therefore sits at the crossing, and that is where the black dashed line lands. In my run the optimum came out just below $s = 1.2$ with about 135 matches, a little to the left of where the curves meet near $s = 1.22$, and supply was still the binding side there.

Two things stand out to me. For one, the optimal multiplier is modest. Across all ten scenarios it only ranges from about 1.12 to 1.34 and never approaches the cap of 3, so aggressive surge is counterproductive when the goal is matching rather than revenue. The other point is that this plot is a picture of why the problem is decision dependent. The multiplier is both the decision variable and an input feature to both predictors, so the forecast moves as the decision moves. We cannot predict once and then optimize against a fixed number, which is exactly why the fitted forests are embedded inside the Gurobi model rather than being called before it.

Deliverables

Congratulations! All of the work is complete. The last step is to submit your deliverables to Gradescope:

- 1 single PDF file to "**Assignment 2 Written**"
- the follwoing files to "**Assignment 2 Programming**"
  - `D2A_A2_SurgePricing.ipynb`
  - `prediction_test.csv`
  - `optimization_decisions.csv`