Developer Documentation

Decision Records / Use # as indicator for BibTeX string constants

Use # as indicator for BibTeX string constants

Bibtex supports string constants. The entry editor should support that, too. Affected code is (at least) org.jabref.logic.importer.fileformat.BibtexParser#parseFieldContent and org.jabref.logic.bibtex.FieldWriter#formatAndResolveStrings

Decision Drivers

- Full BibTeX compatibility
- Intuitive for the user
- UI backwards compatible

Considered Options

- Wrap string constants in #
- Replace the internal # in JabRef by the non-used character §
- Replace the internal # in JabRef by the non-used character %
- Replace the internal # in JabRef by the non-used character &
- Replace the internal # in JabRef by a single &
- Change the data type of a field value
- Wrap plan # in curly braces: {#}

Decision Outcome

Chosen option: "Wrap string constants in #", because already existing behavior.

Pros and Cons of the Options

Wrap string constants in

When BibTeX on the disk contains <code>field = value</code>, it is rendered as <code>field = #value#</code> in the entry editor. The user then knows that <code>value</code> is a BibTeX string.

Example:

left: BibTeX; right: Entry Editor

```
@String{ value = "example" }
field1 = value    -> #value#
field2 = {value}    -> value
field1 = value # value --> #value#
```

- Good, because In place in JabRef since more than 10 years
- Bad, because # is used in BibTeX for string concatenation
- Bad, because # is used in Markdown to indicate headings. When using Markdown in fields such as comments, this causes writing errors
- Bad, because # could appear in URLs

Replace the internal # in JabRef by the non-used character §

When BibTeX on the disk contains <code>field = value</code>, it is rendered as <code>field = §value§</code> in the entry editor. The user then knows that <code>value</code> is a BibTeX string.

Example:

left: BibTeX; right: Entry Editor

```
field1 = value -> §value§
field2 = {value} -> value

field1 = value # value --> §value§ # §value§
```

- Good, because easy to implement
- Good, because no conflict with BibTeX's # sign
- Bad, because documentation needs to be updated
- Bad, because s is not available on a US keyboard

Replace the internal # in JabRef by the non-used character %

Similar to "Replace the internal # in JabRef by the non-used character §"

Example:

left: BibTeX; right: Entry Editor

- Good, because a user does not write LaTeX comments inside a string
- Bad, because 🛭 could be used in Markdown, too
- Bad, because & is used for comments in LaTeX and thus might cause confusion
- Bad, because & could appear in URLs: There is url percent encoding

Replace the internal # in JabRef by the non-used character &

Similar to "Replace the internal # in JabRef by the non-used character §"

Example:

left: BibTeX; right: Entry Editor

- Good, because Users do not write LaTeX tables
- Bad, because & is a LaTeX command for tables

Replace the internal # in JabRef by a single &

Prefix strings with &

Example:

left: BibTeX; right: Entry Editor

- Good, because near to C syntax
- Bad, because & is a LaTeX command for tables
- Bad, because & could appear in URLs

Change the data type of a field value

```
org.jabref.model.entry.BibEntry#setField(org.jabref.model.entry.field.Field, java.lang.String) changes
to org.jabref.model.entry.BibEntry#setField(org.jabref.model.entry.field.Field,
org.jabref.model.entry.field.Value)

(org.jabref.model.entry.field.Value)
```

(org.jabref.model.entry.BibEntry#setField(org.jabref.model.entry.field.Field, java.lang.String)). This would bring JabRef's internal data model even more close to BibTeX

Good, because more object-orientated design of BibTeX field storage

- Good, because eases implementation of an advanced field editor
- Bad, because high effort to implement