

Documentation Home

Learn LaTeX in 30 minutes

ShareLaTeX guides

- Creating a document in ShareLaTeX
- Uploading a project
- Copying a project
- Creating a project from a template
- Including images in ShareLaTeX
- Exporting your work from ShareLaTeX
- Using bibliographies in ShareLaTeX
- Sharing your work with others
- Debugging Compilation timeout errors
- Knowledge Base

LaTeX Basics

- Creating your first LaTeX document
- Choosing a LaTeX Compiler
- Paragraphs and new lines
- Bold, italics and underlining
- Lists
- Errors

Mathematics

- Mathematical expressions
- Subscripts and superscripts
- Brackets and Parentheses
- Fractions and Binomials
- Aligning Equations
- Operators
- Spacing in math mode
- Integrals, sums and limits
- Display style in math mode
- List of Greek letters and math symbols
- Mathematical fonts

Figures and tables

- Inserting Images
- Tables
- Positioning Images and Tables
- Lists of Tables and Figures
- Drawing Diagrams Directly in LaTeX
- TikZ package

References and Citations

- Bibliography management in LaTeX
- Bibliography management with biblatex
- Biblatex bibliography styles
- Biblatex citation styles
- Bibliography management with natbib
- Natbib bibliography styles
- Natbib citation styles
- Bibliography management with bibtex
- Bibtex bibliography styles

Languages

- International language support
- Quotations and quotation marks
- Arabic
- Chinese
- French
- German
- Greek
- Italian
- Japanese
- Korean
- Portuguese
- Russian
- Spanish

Document structure

- Sections and chapters
- Table of contents
- Cross referencing sections and equations
- Indices
- Glossaries
- Nomenclatures
- Management in a large project
- Multi-file LaTeX projects
- Hyperlinks

Formatting

- Lengths in LaTeX
- Headers and footers
- Page numbering
- Paragraph formatting
- Line breaks and blank spaces
- Text alignment
- Page size and margins
- Single sided and double sided documents
- Multiple columns
- Counters
- Code listing
- Code Highlighting with minted
- Using colours in LaTeX
- Footnotes
- Margin notes

Fonts

- Font sizes, families, and styles
- Font typefaces
- Supporting modern fonts with XeLaTeX

Presentations

- Beamer
- Powerdot
- Posters

Commands

- Commands
- Environments

Field specific

- Theorems and proofs
- Chemistry formulae
- Feynman diagrams
- Molecular orbital diagrams
- Chess notation
- Knitting patterns
- Circuitikz package
- Pgfplots package
- Typing exams in LaTeX
- Knitr
- Attribute Value Matrices

Class files

- Understanding packages and class files
- List of packages and class files
- Writing your own package
- Writing your own class
- Tips

 Search help library....

Operators

Characters in mathematical mode are usually shown in italics, but sometimes especial function names require different formatting, this is accomplished by using operators defined in LaTeX.

Contents

- 1 Introduction
- 2 Operators in different contexts
- 3 Defining your own operators
- 4 Reference guide
- 5 Further reading

Introduction

Trigonometrical functions, logarithms, and some others can be written in a document by means of some special commands.

Examples of mathematical operators

```
\[
\sin(a + b) = \sin(a)\cos(b) + \cos(a)\sin(b)
\]
```

$$\sin(a + b) = \sin(a) \cos(b) + \cos(a) \sin(b)$$

The commands will print the name of the function in Roman characters instead of italics.

[Open an example in ShareLaTeX](#)

Operators in different contexts

Some operators can take parameters that are handled in a special way, for instance, limits.

Testing notation for limits

```
\[
\lim_{h \rightarrow 0} \frac{f(x+h)-f(x)}{h}
\]
```

This operator changes when used alongside text `\(\lim_{x \rightarrow h} (x-h) \)`.

Testing notation for limits

$$\lim_{h \rightarrow 0} \frac{f(x + h) - f(x)}{h}$$

This operator changes when used alongside text `\lim_{x \rightarrow h} (x - h)`.

Notice how the limit declaration can include a subscript. See the [reference guide](#) for a complete list of available operators.

Some languages may add or change some commands, check the [main page](#) for language-specific articles.

[Open an example in ShareLaTeX](#)

Defining your own operators

If you need to add a personalized operator to be displayed in Roman font instead of italics use `\DeclareMathOperator`

```
\documentclass{article}

\usepackage{amssymb}
\usepackage{amsmath}

\DeclareMathOperator{\Mr}{M_{\mathbb{R}}}

\begin{document}

User-defined operator for matrices with Real entries

\[
x \in \Mr
\]
```

User-defined operator for matrices with Real entries

$$x \in M_{\mathbb{R}}$$

The command `\DeclareMathOperator` takes two parameters, the first one is the name of the new operator and the second one is the text to be displayed. For this command to work you have to import the package **amsmath** in the preamble with

```
\usepackage{amsmath}
```

The command can be slightly modified if you need that your defined operator uses subscripts, as the `\lim` operator, in such case use `\DeclareMathOperator*`.

[Open an example in ShareLaTeX](#)

Reference guide

Complete list of mathematical operators

Operator	Renders as
<code>\cos</code>	cos
<code>\csc</code>	csc
<code>\exp</code>	exp
<code>\ker</code>	ker
<code>\limsup</code>	lim sup
<code>\min</code>	min
<code>\sinh</code>	sinh
<code>\arcsin</code>	arcsin
<code>\cosh</code>	cosh
<code>\deg</code>	deg
<code>\gcd</code>	gcd
<code>\lg</code>	lg
<code>\ln</code>	ln
<code>\Pr</code>	Pr
<code>\sup</code>	sup
<code>\arctan</code>	arctan
<code>\cot</code>	cot
<code>\det</code>	det
<code>\hom</code>	hom
<code>\lim</code>	lim
<code>\log</code>	log
<code>\sec</code>	sec
<code>\tan</code>	tan
<code>\arg</code>	arg
<code>\coth</code>	coth
<code>\dim</code>	dim
<code>\liminf</code>	lim inf
<code>\max</code>	max
<code>\sin</code>	sin
<code>\tanh</code>	tanh

Further reading

For more information see

- Mathematical expressions
- Subscripts and superscripts
- Fractions and Binomials
- Spacing in math mode
- Integrals, sums and limits
- Display style in math mode
- The not so short introduction to LaTeX 2_ε