

Documentation Home

Learn LaTeX in 30 minutes

ShareLaTeX guides

Creating a document in ShareLaTeX

Uploading a project

Copying a project

Creating a project from a template

Including images in ShareLaTeX

Exporting your work from ShareLaTeX

Using bibliographies in ShareLaTeX

Sharing your work with others

Debugging Compilation timeout errors

Knowledge Base

LaTeX Basics

Creating your first LaTeX document

Choosing a LaTeX Compiler

Paragraphs and new lines

Bold, italics and underlining

Lists

Errors

Mathematics

Mathematical expressions

Subscripts and superscripts

Brackets and Parentheses

Fractions and Binomials

Aligning Equations

Operators

Spacing in math mode

Integrals, sums and limits

Display style in math mode

List of Greek letters and math symbols

Mathematical fonts

Figures and tables

Inserting Images

Tables

Positioning Images and Tables

Lists of Tables and Figures

Drawing Diagrams Directly in LaTeX

TikZ package

References and Citations

Bibliography management in LaTeX

Bibliography management with biblatex

Biblatex bibliography styles

Biblatex citation styles

Bibliography management with natbib

Natbib bibliography styles

Natbib citation styles

Bibliography management with bibtex

Bibtex bibliography styles

Languages

International language support

Quotations and quotation marks

Arabic

Chinese

French

German

Greek

Italian

Japanese

Korean

Portuguese

Russian

Spanish

Document structure

Sections and chapters

Table of contents

Cross referencing sections and equations

Indices

Glossaries

Nomenclatures

Management in a large project

Multi-file LaTeX projects

Hyperlinks

Formatting

Lengths in L^AT_EX

Headers and footers

Page numbering

Paragraph formatting

Line breaks and blank spaces

Text alignment

Page size and margins

Single sided and double sided documents

Multiple columns

Counters

Code listing

Code Highlighting with minted

Using colours in LaTeX

Footnotes

Margin notes

Fonts

Font sizes, families, and styles

Font typefaces

Supporting modern fonts with X_YL^AT_EX

Presentations

Beamer

Powerdot

Posters

Commands

Commands

Environments

Field specific

Theorems and proofs

Chemistry formulae

Feynman diagrams

Molecular orbital diagrams

Chess notation

Knitting patterns

CircuiTikz package

Pgfplots package

Typing exams in LaTeX

Knitr

Attribute Value Matrices

Class files

Understanding packages and class files

List of packages and class files

Writing your own package

Writing your own class

Tips

Q

Search help library....

Aligning equations with amsmath

The *amsmath* package provides a handful of options for displaying equations. You can choose the layout that better suits your document, even if the equations are really long, or if you have to include several equations in the same line.

Contents

- 1 Introduction
- 2 Including the amsmath package
- 3 Writing a single equation
- 4 Displaying long equations
- 5 Splitting and aligning an equation
- 6 Aligning several equations
- 7 Grouping and centering equations
- 8 Further reading

Introduction

The standard LaTeX tools for equations may lack some flexibility, causing overlapping or even trimming part of the equation when it's too long. We can surpass this difficulties with *amsmath*. Let's check an example:

```
\begin{equation} \label{eq1}
\begin{split}
A \&= \frac{\pi r^2}{2} \\
&= \frac{1}{2} \pi r^2
\end{split}
\end{equation}
```

$$\begin{aligned} A &= \frac{\pi r^2}{2} \\ &= \frac{1}{2} \pi r^2 \end{aligned} \tag{1}$$

You have to wrap you equation in the *equation* environment if you want it to be numbered, use *equation** (with an asterisk) otherwise. Inside the *equation* environment use the *split* environment to split the equations into smaller pieces, these smaller pieces will be aligned accordingly. The double backslash works as a newline character. Use the ampersand character *&*, to set the points where the equations are vertically aligned.

[Open an example of the amsmath package in ShareLaTeX](#)

Including the amsmath package

This is a simple step, if you use LaTeX frequently sure you already know this. In the preamble of the document include the code:

```
\usepackage{amsmath}
```

[Open an example of the amsmath package in ShareLaTeX](#)

Writing a single equation

To display a single equation, as mentioned in the introduction, you have to use the *equation** or *equation* environment, depending on whether you want the equation to be numbered or not. Additionally you might add a label for future reference within the document.

```
\begin{equation} \label{eu_eqn}
e^{\pi i} + 1 = 0
\end{equation}
```

The beautiful equation \ref{eu_eqn} is known as the Euler equation

$$e^{\pi i} + 1 = 0$$

The beautiful equation 1 is known as the Euler equation

[Open an example of the amsmath package in ShareLaTeX](#)

Displaying long equations

For equations longer than a line use the *multline* environment. Insert a double backslash to set a point for the equation to be broken. The first part will be aligned to the left and the second part will be displayed in the next line and aligned to the right.

Again, the use of an asterisk *** in the environment name determines whether the equation is numbered or not.

```
\begin{multline*}
p(x) = 3x^6 + 14x^5y + 590x^4y^2 + 19x^3y^3 \\
- 12x^2y^4 - 12xy^5 + 2y^6 - a^3b^3
\end{multline*}
```

$$\begin{aligned} p(x) &= 3x^6 + 14x^5y + 590x^4y^2 + 19x^3y^3 \\ &\quad - 12x^2y^4 - 12xy^5 + 2y^6 - a^3b^3 \end{aligned}$$

[Open an example of the amsmath package in ShareLaTeX](#)

Splitting and aligning an equation

Split is very similar to *multline*. Use the *split* environment to break an equation and to align it in columns, just as if the parts of the equation were in a table. This environment must be used inside an *equation* environment. For an example check the introduction of this document.

Aligning several equations

If there are several equations that you need to align vertically, the *align* environment will do it:

```
\begin{align*}
2x - 5y \&= 8 \\
3x + 9y \&= -12
\end{align*}
```

$$\begin{aligned} 2x - 5y &= 8 \\ 3x + 9y &= -12 \end{aligned}$$

Usually the binary operators (*>*, *<* and *=*) are the ones aligned for a nice-looking document.

As mentioned before, the ampersand character *&* determines where the equations align. Let's check a more complex example:

```
\begin{align*}
x&=y & w \&=z & & a\&=b+c \\
2x\&=-y & 3w\&=\frac{1}{2}z & & a\&=b \\
-4 + 5x\&=2+y & w+2\&=-1+w & & ab\&=cb
\end{align*}
```

$$\begin{array}{ccc} x = y & w = z & a = b + c \\ 2x = -y & 3w = \frac{1}{2}z & a = b \\ -4 + 5x = 2 + y & w + 2 = -1 + w & ab = cb \end{array}$$

Here we arrange the equations in three columns. LaTeX assumes that each equation consists of two parts separated by a *&*; also that each equation is separated from the one before by an *&*.

Again, use *** to toggle the equation numbering. When numbering is allowed, you can label each row individually.

[Open an example of the amsmath package in ShareLaTeX](#)

Grouping and centering equations

If you just need to display a set of consecutive equations, centered and with no alignment whatsoever, use the *gather* environment. The asterisk trick to set/unset the numbering of equations also works here.

```
\begin{gather*}
2x - 5y = 8 \\
3x^2 + 9y = 3a + c
\end{gather*}
```

$$\begin{aligned} 2x - 5y &= 8 \\ 3x^2 + 9y &= 3a + c \end{aligned}$$

[Open an example of the amsmath package in ShareLaTeX](#)

Further reading

For more information see

- Mathematical expressions
- Brackets and Parentheses
- Subscripts and superscripts
- Spacing in math mode
- Display style in math mode
- Mathematical fonts
- List of Greek letters and math symbols
- Operators
- Fractions and Binomials
- amsmath package documentation