

Arch Install and Setup Documentation

To begin with I read the Arch Wiki and installed/downloaded the archlinux-2025.11.01-x86_64.iso file, uploaded it, and created my virtual machine. I ran into a problem right from the start. I didn't set enough memory, so I had to restart my VM right away. I changed the settings, and after getting the internet connection, I started installation. I got to disk formatting and setup; I partitioned and formatted the disk and mounted it—the installation process allowed for the package installation for the new system. I configured my timezone with `timedatectl set-timezone America/New_York` and created an administrator user with my name `passwd useradd -m -G wheel josue passwd josue`. Then I did the same for Codi's username. From there, I could start installing the GUI packages. I encountered some issues where some of the packages didn't install completely, but I was able to reinstall them and finish the installation. After that I added in color coding. Green meaning a correct bash script was written and red for an incorrect script

```
archvm% sl
zsh: command not found: sl
archvm% ls
Desktop Documents Downloads Music Pictures Public Templates uptime-Kuma Videos
```

I began to install the ssh then but I ran into a bit of trouble because it wouldn't install. After some trial and error I figured it out.

```
Windows PowerShell
Copyright (C) Microsoft Corporation. All rights reserved.

Install the latest PowerShell for new features and improvements! https://aka.ms/PSWindows

PS C:\Users\josue> ssh josue@localhost -p 2222
>>
The authenticity of host '[localhost]:2222 ([127.0.0.1]:2222)' can't be established.
ED25519 key fingerprint is SHA256:CdlcCN+NgUnH9E6DvFtaqN6c00vhzwVvp/zRV/r0cWU.
This key is not known by any other names.
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added '[localhost]:2222' (ED25519) to the list of known hosts.
josue@localhost's password:
```

I also created six custom aliases in my shell configuration to make command-line navigation easier. Two of these aliases were `alias ll='ls -lh'` and `alias la='ls -A'`. The `ll` alias displays files in a long, human-readable format, while `la` lists all files, including hidden ones. I also included an alias for my linux to always stay updated when I bash in “update”

```
archvm% update
:: Synchronizing package databases...
core is up to date
extra is up to date
:: Starting full system upgrade...
there is nothing to do
```

All in all I did not run into many problems. My biggest problem I had was setting the amount of storage when running the VM because if I didn't set enough I would have to start all over again.