



Nonsmooth Nonlinear Conjugate Gradient Method for Interactive Contact Force Computation


Morten Silcowitz Sarah Niebe Kenny Erleben

Department of Computer Science
University of Copenhagen
Denmark

June 2010



What is it all about?



An Interactive Goal Oriented Task



The Interactive Requirements


Must

- Be responsive
- Be interactive
- Have high fidelity



Why is it a Hard Problem?

- Computational very heavy
- Limited time to compute result
- End user is unpredictable
- End user has divine power \approx very unphysical
- “Traditionally” proof of existence of multiple solutions



Solution: Iterative methods!



The State-of-the-Art Iterative Method

Projected Gauss-Seidel (PGS) from ODE, Bullet etc..

- Linear Convergence Rate
- Inaccurate Friction Forces
- Incredible Robust



Consequences: Great for blow them up physics but simulation is an art form!



Facts of Life and Hypotheses

- Better accuracy improves fidelity
- With better convergence rate one gets better accuracy in fewer iterations
- A Newton method is great but
 - Lack robustness!
 - Iteration cost is high!
 - Performance is unpredictable!



Desire: Something that behaves like PGS but with better convergence!



The Contact Force Problem

Deriving it. . .

- Start with classical mechanics
- Add some approximations
- Do a whole bunch of mathematical tricks

then our final problem is to find λ where

$$\mathbf{y} = \mathbf{A}\lambda + \mathbf{b}$$

and for each i we have

$$y_i < 0 \Rightarrow \lambda_i = \mathbf{u}_i(\lambda),$$

$$y_i > 0 \Rightarrow \lambda_i = \mathbf{l}_i(\lambda),$$

$$y_i = 0 \Rightarrow \mathbf{l}_i(\lambda) \leq \lambda_i \leq \mathbf{u}_i(\lambda).$$

where \mathbf{l}_i and \mathbf{u}_i are affine functions modeling friction bounds and non-negative normal forces.



An Quick Observation

The Contact Force Problem is a Nonlinear Complementarity Problem (NCP)

Oh no! If only we had a mixed Linear Complementary Problem then

We could use a Projected Conjugate Gradient method on a Quadratic Programming Problem reformulation

That would give us

- Same iteration cost as PGS
- But quadratic convergence rate instead of linear



Projected Gauss-Seidel Method (PGS)

Using a splitting of $\mathbf{A} = \mathbf{L} + \mathbf{D} + \mathbf{U}$

and a whole lot of math later ...

we have the Projected Gauss-Seidel Method

$$\lambda^{k+1} \leftarrow \min(\mathbf{u}(\lambda^k), \max(\mathbf{l}(\lambda^k), (\mathbf{D} + \mathbf{L})^{-1} (\mathbf{U}\lambda^k - \mathbf{b})))$$

One iteration of PGS can be implemented nicely as a forward loop
we write it as

$$\lambda^{k+1} = \mathbf{PGS}(\lambda^k)$$



The Idea Part One

Assuming convergence $\lambda^k \rightarrow \lambda^*$ for $k \rightarrow \infty$

$$\lambda^* = \underbrace{\min(\mathbf{u}(\lambda^*), \max(\mathbf{l}(\lambda^*), (\mathbf{D} + \mathbf{L})^{-1} (\mathbf{U}\lambda^* - \mathbf{b})))}_{\simeq \mathbf{H}\lambda^* + \mathbf{h}},$$

Conceptually evaluation of an affine function

$$0 = (\mathbf{H} - \mathbf{I})\lambda^* + \mathbf{h}$$

Residual is given by

$$\mathbf{r}^k = (\mathbf{H} - \mathbf{I})\lambda^k + \mathbf{h} = \mathbf{PGS}(\lambda^k) - \lambda^k$$



The Idea Part Two

Define a non-smooth nonlinear quasi-quadratic function

$$f(\lambda^k) \equiv \frac{1}{2} \| \mathbf{r}^k \|^2$$

Gradient is given by

$$\nabla f(\lambda^k) = -\mathbf{r}^k$$

Oh! Gradient Descent method is equivalent to the PGS method



Nonlinear Nonsmooth Conjugate Gradients (NNCG)

Use a Fletcher–Reeves nonlinear conjugate gradient method on f . Update step,

$$\lambda^{k+1} = \lambda^k + \tau^k \mathbf{p}^k$$

\mathbf{p}^k is the search direction and τ^k is the line step. Initially $\mathbf{p}^1 = -\nabla f^1$,



$$\beta^{k+1} = \frac{\|\nabla f^{k+1}\|^2}{\|\nabla f^k\|^2}$$
$$\mathbf{p}^{k+1} = \beta^{k+1} \mathbf{p}^k - \nabla f^{k+1}$$

Restart if $\|\nabla f^{k+1}\|^2 > \|\nabla f^k\|^2$.




Interactive Results

- Fast convergence for small sized stacks




Interactive Results


- Better convergence for large mass ratios



Heavy Box Resting on Light Boxes



NNCG Method in Action





Interactive Comparisons with PGS



Non-Interactive Results

- Quadratic convergence rates was observed
- Notice restart spikes



Conclusion and Future Work

Findings

- Roughly same iteration cost as PGS
- Lower error level than PGS
- Super linear and even quadratic convergence rate
- Best for small problems with obvious structure

Speculation

- Over-determinacy causes inability to improve convergence on larger and more complex problems

Future work

- Preconditioning or multigrid techniques



Thank you for attending this talk!

