601.433/633 Introduction to Algorithms **Fall 2026**
Homework #4 **Due:** October 15, 2026, 11:59pm

Remember: you may work in groups, but must write up your solution entirely on your own. Solutions must by typeset (LaTeX preferred but not required). Collaboration is limited to discussing the problems – you may not look at, compare, reuse, etc. any text from anyone else in the class. You may use the internet to look up formulas, definitions, etc., but may not simply look up the answers online.

Please include proofs with all of your answers, unless stated otherwise.

1 Hashing (50 points)

We say that H is a 2-*universal hash family* if $\mathbf{Pr}_{h\sim H}[h(x) = a \wedge h(y) = b] \leq 1/M^2$ for all $x, y \in U$ with $x \neq y$ and $a, b \in \{0, 1, \ldots, M-1\}$.

(a) (25 points) Prove that any 2-universal hash family is also a universal hash family.

To prove that H is a universal hash family, we must prove that $\mathbf{Pr}_{h\sim H}[h(x) = h(y)] \leq \frac{1}{M}$ for all $x, y \in U$ with $x \neq y$. To find when $h(x) = h(y)$, we can set both to an arbitrary value $a \in \{0, 1, \ldots, M-1\}$. The definition never states that $a \neq b$, so we can write this as:

$\mathbf{Pr}_{h\sim H}[h(x) = h(y)] = \mathbf{Pr}_{h\sim H}[h(x) = a \wedge h(y) = a] \leq 1/M^2$

However, this just gives the probability that $h(x)$ and $h(y)$ to a, when we want to find when x and y map to any value in $\{0, 1, \ldots, M-1\}$. Thus, we can write the above as a summation over every possible value of a:

$\mathbf{Pr}_{h\sim H}[h(x) = h(y)] = \sum_{a=0}^{M-1}(\mathbf{Pr}_{h\sim H}[h(x) = a \wedge h(y) = a])$

For any a within the bounds, $\mathbf{Pr}_{h\sim H}[h(x) = a \wedge h(y) = a] \leq \frac{1}{M^2}$. Thus, we can set up the lower bound for each individual value inside the summation:

$\mathbf{Pr}_{h\sim H}[h(x) = h(y)] = \sum_{a=0}^{M-1}(\mathbf{Pr}_{h\sim H}[h(x) = a \wedge h(y) = a]) \leq \sum_{a=0}^{M-1}(\frac{1}{M^2})$

$\mathbf{Pr}_{h\sim H}[h(x) = h(y)] \leq \sum_{a=0}^{M-1}(\frac{1}{M^2})$

Simplifying by summing over the M terms of the summation:

$\mathbf{Pr}_{h\sim H}[h(x) = h(y)] \leq \frac{M}{M^2}$

$\mathbf{Pr}_{h\sim H}[h(x) = h(y)] \leq \frac{1}{M}$

We have proven that the definition of a universal hash family applies to any 2-universal hash family. Thus, any 2-universal hash family is a universal hash family

(b) (25 points) Prove that for every u and b with $u > b \geq 1$ there is some universal hash family from U to $\{0, 1, \ldots, M-1\}$ (with $|U| = 2^u$ and $M = 2^b$) which is *not* a 2-universal hash family. Hint: think about the constructions from class and the textbook.

To prove that any given construction leads to a universal hash family, we must prove:

$\mathbf{Pr}_{h\sim H}[h(x) = h(y)] \leq \frac{1}{2^b}$ for all $x, y \in U$ with $x \neq y$.

To prove that it is not a 2-universal hash family, we must prove that:

$\mathbf{Pr}_{h\sim H}[h(x) = i \wedge h(y) = j] > \frac{1}{M^2}$ for some distinct $x, y \in U$.

We first consider the construction in **Theorem 10.3.5** in the lexture notes, which states:

$\mathbf{Pr}_{h\sim H}[h(x) = h(y)] \leq \frac{1}{M}$ for all $x \neq y \in \{0,1\}^u$

In this theorem, $M = 2^b$ and $|\{0,1\}^u| = 2^u$, so we can see that this represents a universal hash family for every u and b, as per the specs in the question.

However, we must now examine its 2 universality before concluding the construction in class fits this proof. Any hash function in this family is defined as $h(x) = Gx \mod 2$, where G is a uniformly chose $b \times u$ matrix. Thus, there are 2^{bu} possible matrices (and therefore 2^{bu} functions in the hash family). By the definition of the hash function, any output $h(x)$ is a b-row, 1 column matrix. We consider 2 distinct inputs, x and y, and two output possibilities i and j.

We consider $\mathbf{Pr}_G[Gx = i \wedge Gy = j] = \frac{\#\text{ of matrices where } Gx=i \wedge Gy=j}{2^{bu}}$. Beginning with a simpler constraint, we consider $\mathbf{Pr}_G[Gx = i]$. For this, we choose a nonzero x. We can break this down by digit, and determine that $Gx = i$ means $g_1 \cdot x = i_1 \mod 2$, $g_2 \cdot x = i_2 \mod 2$, $g_3 \cdot x = i_3 \mod 2$, ... , $g_b \cdot x = i_b \mod 2$. We consider a single row g_k, with u entries, so there are 2^u possible rows. Since $x \neq 0$, the number of rows g_k satisfying $g_k \cdot x = i_k$ is 2^{u-1}. Each of the b rows of i has 2^{u-1} possible matrices satisfying it, so by multiplication, there are $2^{b(u-1)}$. Therefore:

$\mathbf{Pr}_G[Gx = i] = \frac{2^{b(u-1)}}{2^{bu}} = \frac{1}{2^b} = \frac{1}{M}$

Now, we consider a y equal to 0. Since we consider $x \neq 0$, this satisfies $x \neq y$. Since $y = 0$, we know that $Gy = j = 0$ regardless of what matrix G is chosen. Therefore, $\mathbf{Pr}_G[Gy = j] = 1$.

Since $Gy = j$ is always true, the logic value $(Gx = i \wedge Gy = j) = (Gx = i \wedge \text{TRUE}) = (Gx = i)$. Therefore, we can compute the probability of $\mathbf{Pr}_G[Gx = i \wedge Gy = j]$ as follows:

$\mathbf{Pr}_G[Gx = i \wedge Gy = j] = \mathbf{Pr}_G[Gx = i] = \frac{1}{M} > \frac{1}{M^2}$ for all $M > 1$.

Since M is at minimum 2, we have found an x and y within this universal hash family for which:

$\mathbf{Pr}_{h\sim H}[h(x) = i \wedge h(y) = j] > \frac{1}{M^2}$.

Therefore, we have proven the existence of some hash family for all u, b where $u > b \geq 1$ which is universal but not 2-universal.

2 Union-Find (50 points)

In class we proved that if we use trees to represent disjoint sets and use both union-by-rank and path compression, then the amortized cost of any operation (Make-Set, Find, or Union) is only $O(\log^* n)$. In this question we'll analyze what happens if we change our data structure in two ways: we do not use path compression, and we do union-by-cardinality rather than union-by-rank.

Slightly more formally, we change our data structure as follows. As before, every node has three values: an element, a parent pointer, and a value. But the value isn't a rank, but is rather the number of nodes in the subtree rooted at it, i.e., the *cardinality* of the subtree. So the root of any tree stores the cardinality of the set represented by the tree. The basic operations work as follows:

- Make-Set(x) simply returns a single node with the element x, where the parent pointer points to itself and the initial cardinality is 1.

- Find(x) follows the parent pointer from x recursively until it ends up at the root (which it knows since only the root will have its parent pointer point to itself), and then it returns the element at this root.
- Union(x, y) first does Find(x) to find the root r_x of the tree containing x and Find(y) to find the root r_y of the tree containing y. If $(r_x \to \mathit{cardinality}) \geq (r_y \to \mathit{cardinality})$, then we set the parent of r_y to be r_x and set $(r_x \to \mathit{cardinality}) = (r_x \to \mathit{cardinality}) + (r_y \to \mathit{cardinality})$. Similarly, if $(r_y \to \mathit{cardinality}) > (r_x \to \mathit{cardinality})$, then we set the parent of r_x to be r_y and set $(r_y \to \mathit{cardinality}) = (r_x \to \mathit{cardinality}) + (r_y \to \mathit{cardinality})$.

(a) (25 points) Prove that the worst-case running time of any operation is $O(\log n)$, where n is the number of Make-Set operations (i.e., the number of elements). Hint: can you bound the depth/height of a tree by its cardinality?

(b) (25 points) We now want to provide a matching lower bound not just on the worst-case running time, but even on the amortized running time. So suppose that we first do n Make-Set operations (so there are n elements). Give a sequence of $O(n)$ Union operations which cumulatively take $\Omega(n \log n)$ time (implying that the amortized cost of an operation is $\Omega(\log n)$). Each union operation should be a union of two distinct sets, i.e., you should never call Union(x,y) on elements x and y that are in the same set.