

Package ‘PriceIndices’

November 16, 2021

Title Calculating Bilateral and Multilateral Price Indexes

Version 0.0.6

Description Preparing a scanner data set for price dynamics calculations (data selecting, data classification, data matching, data filtering). Computing bilateral and multilateral indexes. For details on these methods see: de Haan and Krsinich (2017) <[doi:10.1111/roiw.12304](https://doi.org/10.1111/roiw.12304)> and Diewert and Fox (2020) <[doi:10.1080/07350015.2020.1816176](https://doi.org/10.1080/07350015.2020.1816176)>.

Depends R (>= 3.5.0)

Imports lubridate (>= 1.7.4), dplyr (>= 0.8.3), ggplot2 (>= 3.2.0),
reshape, reclin, stringr, xgboost, caret, strex

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

Suggests testthat, knitr, rmarkdown

VignetteBuilder knitr

NeedsCompilation no

Author Jacek Białek [aut, cre] (<<https://orcid.org/0000-0002-0952-5327>>)

Maintainer Jacek Białek <jacek.bialek@uni.lodz.pl>

Repository CRAN

Date/Publication 2021-11-16 07:50:20 UTC

R topics documented:

agmean	5
available	6
banajree	7
bialek	8
bmw	9
carli	10
ccdi	11

ccdi_fbew	12
ccdi_fbmw	13
ccdi_splice	14
chagmean	16
chbanajree	17
chbialek	18
chbmw	19
chcarli	20
chcswd	21
chdavies	22
chdrobisch	23
chdutot	24
chfisher	25
chgeary_khamis	26
chgeohybrid	27
chgeolaspeyres	28
chgeolowe	29
chgeopaasche	30
chgeoyoung	31
chharmonic	32
chhybrid	33
chjevons	34
chlaspeyres	35
chlehr	36
chlloyd_moulton	37
chlowe	38
chmarshall_edgeworth	39
chpaasche	40
chpalgrave	41
chsato_vartia	42
chstuvel	43
chtornqvist	44
chvartia	45
chwalsh	46
chyoung	47
coffee	48
compare_distances	49
compare_final_indices	50
compare_indices	51
cswd	53
dataAGGR	54
dataCOICOP	55
dataMATCH	55
dataU	56
data_aggregating	57
data_check	57
data_classifying	58
data_filtering	59

data_matching	60
data_norm	62
data_preparing	63
data_selecting	65
data_unit	66
davies	67
dissimilarity	68
dissimilarity_fig	69
drobisch	70
dutot	71
final_index	72
final_index2	74
fisher	76
geary_khamis	77
geks	78
geksaqi	79
geksaqi_fbew	80
geksaqi_fbmw	81
geksaqi_splice	82
geksaqu	84
geksaqu_fbew	85
geksaqu_fbmw	86
geksaqu_splice	87
geksgaqi	89
geksgaqi_fbew	90
geksgaqi_fbmw	91
geksgaqi_splice	92
geksgl	94
geksgl_fbew	95
geksgl_fbmw	96
geksgl_splice	97
geksj	99
geksj_fbew	100
geksj_fbmw	101
geksj_splice	102
geksl	104
geksl_fbew	105
geksl_fbmw	106
geksl_splice	107
geksw	109
geksw_fbew	110
geksw_fbmw	111
geksw_splice	112
geks_fbew	114
geks_fbmw	115
geks_splice	116
generate	117
geohybrid	119

geolaspeyres	120
geolowe	121
geopaasche	122
geoyoung	123
gk	124
gk_fbew	125
gk_fbmw	126
gk_splice	127
harmonic	128
hybrid	129
jevons	130
laspeyres	131
lehr	132
lloyd_moulton	133
load_model	134
lowe	135
marshall_edgeworth	136
matched	137
matched_fig	138
matched_index	139
milk	140
model_classification	141
paasche	143
palgrave	144
pqcor	145
pqcor_fig	145
PriceIndices	146
prices	152
price_index	153
price_indices	154
QU	156
quantities	157
sales	158
sales_groups	159
sales_groups2	160
sato_vartia	161
save_model	162
SPQ	163
stuvcl	164
sugar	165
tindex	166
tornqvist	167
tpd	168
tpd_fbew	169
tpd_fbmw	170
tpd_splice	171
vartia	172
walsh	173

wgeks	174
wgeksaqi	175
wgeksaqi_fbew	177
wgeksaqi_fbmw	178
wgeksaqi_splice	179
wgeksaqu	180
wgeksaqu_fbew	181
wgeksaqu_fbmw	183
wgeksaqu_splice	184
wgeksgaqi	185
wgeksgaqi_fbew	186
wgeksgaqi_fbmw	188
wgeksgaqi_splice	189
wgeksgl	190
wgeksgl_fbew	191
wgeksgl_fbmw	193
wgeksgl_splice	194
wgekssl	195
wgekssl_fbew	196
wgekssl_fbmw	197
wgekssl_splice	198
wgeks_fbew	200
wgeks_fbmw	201
wgeks_splice	202
young	204

Index	206
--------------	------------

agmean	<i>Calculating the bilateral AG Mean price index</i>
--------	--

Description

This function returns a value (or vector of values) of the bilateral AG Mean price index.

Usage

```
agmean(data, start, end, sigma = 0.7, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".

sigma	The elasticity of substitution parameter (as numeric)
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start,end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the bilateral AG Mean price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Lent J., & Dorfman, A. H. (2009). *Using a Weighted Average of Base Period Price Indexes to Approximate a Superlative Index*. Journal of Official Statistics, 25(1), 139-149.

Examples

```
agmean(sugar, start="2019-01", end="2020-01", sigma=0.5)
agmean(milk, start="2018-12", end="2020-01", interval=TRUE)
```

available	<i>Providing values from the indicated column that occur at least once in one of the compared periods or in a given time interval</i>
-----------	---

Description

The function returns all values from the indicated column (defined by the type parameter) which occur at least once in one of the compared periods or in a given time interval.

Usage

```
available(data, period1, period2, type = "prodID", interval = FALSE)
```

Arguments

data	The user's data frame. It must contain a column time (as Date in format: year-month-day, e.g. '2020-12-01') and also a column indicated by the type parameter.
period1	The first period (as character) limited to the year and month, e.g. "2019-03".
period2	The second period (as character) limited to the year and month, e.g. "2019-04".

type	This parameters defines the column which is used in the procedure. Possible values of the type parameter are: retID, prodID, codeIN, codeOUT or description.
interval	A logical parameter indicating whether the procedure is to work for the whole time period between period1 and period2 (then it is TRUE).

Value

The function returns all values from the indicated column (defined by the type parameter) which occur at least once in one of the compared periods or in a given time interval. Possible values of the type parameter are: retID, prodID, codeIN, codeOUT or description. If the interval parameter is set to FALSE, then the function compares only periods defined by period1 and period2. Otherwise the whole time period between period1 and period2 is considered.

Examples

```
available(milk, period1="2018-12", period2="2019-12", interval=TRUE)
available(milk, period1="2018-12", period2="2019-12", type="description")
```

banajree

Calculating the bilateral Banajree price index

Description

This function returns a value (or vector of values) of the bilateral Banajree price index.

Usage

```
banajree(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the bilateral Banajree price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function)..

References

- Banajree, K. S. (1977). *On the factorial approach providing the true index of cost of living*. Göttingen : Vandenhoeck und Ruprecht.
- (2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.
- Von der Lippe, P. (2007). *Index Theory and Price Statistics*. Peter Lang: Berlin, Germany.

Examples

```
banajree(sugar, start="2018-12", end="2019-12")
banajree(milk, start="2018-12", end="2020-01", interval=TRUE)
```

bialek

Calculating the bilateral Bialek price index

Description

This function returns a value (or vector of values) of the bilateral Bialek price index.

Usage

```
bialek(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start,end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the bilateral Bialek price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Von der Lippe, P. (2012). *Some short notes on the price index of Jacek Bialek*. *Econometrics (Ekonometria)*, 1(35), 76-83.
- Bialek, J. (2013). *Some Remarks on the Original Price Index Inspired by the Notes of Peter von der Lippe*. *Econometrics (Ekonometria)*, 3(41), 40-54.
- Bialek, J. (2014). *Simulation Study of an Original Price Index Formula*. *Communications in Statistics - Simulation and Computation*, 43(2), 285-297

Examples

```
bialek(sugar, start="2018-12", end="2019-12")
bialek(milk, start="2018-12", end="2020-01", interval=TRUE)
```

bmw

Calculating the unweighted BMW price index

Description

This function returns a value (or vector of values) of the unweighted Balk-Mehrhoff-Walsh (BMW) price index.

Usage

```
bmw(data, start, end, interval = FALSE)
```

Arguments

data	User's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric) and prodID (as numeric, factor or character). A column quantities (as positive numeric) is also needed because this function uses unit values as monthly prices.
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the unweighted bilateral BMW price index depending on the `interval` parameter. If the `interval` parameter is set to `TRUE`, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Mehrhoff, J.(2007). *A linear approximation to the Jevons index*. In: Von der Lippe (2007): Index Theory and Price Statistics, Peter Lang: Berlin, Germany.

(2018). *Harmonised Index of Consumer Prices (HICP). Methodological Manual*. Publication Office of the European union, Luxembourg.

Examples

```
bmw(sugar, start="2018-12", end="2019-12")
bmw(milk, start="2018-12", end="2020-01", interval=TRUE)
```

carli

Calculating the unweighted Carli price index

Description

This function returns a value (or vector of values) of the unweighted bilateral Carli price index.

Usage

```
carli(data, start, end, interval = FALSE)
```

Arguments

<code>data</code>	The user's data frame with information about sold products. It must contain columns: <code>time</code> (as Date in format: year-month-day, e.g. '2020-12-01'), <code>prices</code> (as positive numeric) and <code>prodID</code> (as numeric, factor or character). A column <code>quantities</code> (as positive numeric) is also needed because this function uses unit values as monthly prices.
<code>start</code>	The base period (as character) limited to the year and month, e.g. "2020-03".
<code>end</code>	The research period (as character) limited to the year and month, e.g. "2020-04".
<code>interval</code>	A logical value indicating whether the function is to compare the research period defined by <code>end</code> to the base period defined by <code>start</code> (then <code>interval</code> is set to <code>FALSE</code>) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <code><start,end></code> are considered and <code>start</code> defines the base period (<code>interval</code> is set to <code>TRUE</code>).

Value

The function returns a value (or vector of values) of the unweighted bilateral Carli price index depending on the `interval` parameter. If the `interval` parameter is set to `TRUE`, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Carli, G. (1804). *Del valore e della proporzione de' metalli monetati*. Scrittori Classici Italiani di Economia Politica, 13, 297-336.

(2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Examples

```
carli(sugar, start="2018-12", end="2019-12")
carli(milk, start="2018-12", end="2020-01", interval=TRUE)
```

ccdi	<i>Calculating the multilateral GEKS price index based on the Tornqvist formula (typical notation: GEKS-T or CCDI)</i>
------	--

Description

This function returns a value of the multilateral CCDI price index, i.e. the GEKS price index based on the superlative Tornqvist index formula.

Usage

```
ccdi(data, start, end, wstart = start, window = 13)
```

Arguments

<code>data</code>	The user's data frame with information about sold products. It must contain columns: <code>time</code> (as Date in format: year-month-day, e.g. '2020-12-01'), <code>prices</code> (as positive numeric), <code>quantities</code> (as positive numeric) and <code>prodID</code> (as numeric, factor or character).
<code>start</code>	The base period (as character) limited to the year and month, e.g. "2020-03".
<code>end</code>	The research period (as character) limited to the year and month, e.g. "2020-04".
<code>wstart</code>	The beginning of the time interval (which is used by multilateral methods) limited to the year and month, e.g. "2020-01".
<code>window</code>	The length of the time window (as positive integer: typically multilateral methods are based on the 13-month time window).

Value

This function returns a value of the multilateral CCDI price index (to be more precise: the GEKS index based on the Tornqvist formula) which considers the time window defined by `wstart` and window parameters. It measures the price dynamics by comparing period end to period start (both start and end must be inside the considered time window). To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product sub-groups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.
- Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.
- Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.
- Caves, D.W., Christensen, L.R. and Diewert, W.E. (1982). *Multilateral comparisons of output, input, and productivity using superlative index numbers*. Economic Journal 92, 73-86.

Examples

```
ccdi(milk, start="2019-01", end="2019-08", window=10)
ccdi(milk, start="2018-12", end="2019-12")
```

ccdi_fbew	<i>Extending the multilateral CCDI price index by using the FBEW method.</i>
-----------	--

Description

This function returns a value of the multilateral CCDI price index (GEKS based on the Tornqvist formula) extended by using the FBEW (Fixed Base Monthly Expanding Window) method.

Usage

```
ccdi_fbew(data, start, end)
```

Arguments

<code>data</code>	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
<code>start</code>	The base period (as character) limited to the year and month, e.g. "2019-12".
<code>end</code>	The research period (as character) limited to the year and month, e.g. "2020-04".

Value

This function returns a value of the multilateral CCDI price index extended by using the FBEW (Fixed Base Monthly Expanding Window) method. The FBEW method uses a time window with a fixed base month every year (December). The window is enlarged every month with one month in order to include information from a new month. The full window length (13 months) is reached in December of each year. The function measures the price dynamics between periods end and start. The month of the start parameter must be December. If the distance between end and start exceeds 13 months, then internal Decembers play a role of chain-linking months. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Caves, D.W., Christensen, L.R. and Diewert, W.E. (1982). *Multilateral comparisons of output, input, and productivity using superlative index numbers*. Economic Journal 92, 73-86.

Chessa, A.G. (2016). *A New Methodology for Processing Scanner Data in the Dutch CPI*. Eurona 1/2016, 49-69.

Examples

```
ccdi_fbmw(milk, start="2018-12", end="2019-08")
```

ccdi_fbmw	<i>Extending the multilateral CCDI price index by using the FBMW method.</i>
-----------	--

Description

This function returns a value of the multilateral CCDI price index (GEKS based on the Tornqvist formula) extended by using the FBMW (Fixed Base Moving Window) method.

Usage

```
ccdi_fbmw(data, start, end)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".

Value

This function returns a value of the multilateral CCDI price index extended by using the FBMW (Fixed Base Moving Window) method. It measures the price dynamics between periods end and start and it uses a 13-month time window with a fixed base month taken as year(end)-1. If the distance between end and start exceeds 13 months, then internal Decembers play a role of chain-linking months. The month of the start parameter must be December. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Caves, D.W., Christensen, L.R. and Diewert, W.E. (1982). *Multilateral comparisons of output, input, and productivity using superlative index numbers*. Economic Journal 92, 73-86.

Lamboray, C.(2017). *The Geary Khamis index and the Lehr index: how much do they differ?* Paper presented at the 15th Ottawa Group meeting, 10-12 May 2017, Elville am Rhein, Germany.

Examples

```
ccdi_fbmw(milk, start="2019-12", end="2020-04")
```

ccdi_splice	<i>Extending the multilateral CCDI price index by using window splicing methods.</i>
-------------	--

Description

This function returns a value (or values) of the multilateral CCDI price index (GEKS based on the Tornqvist formula) extended by using window splicing methods. Available splicing methods are: movement splice, window splice, half splice, mean splice and their additional variants: window splice on published indices (WISP), half splice on published indices (HASP) and mean splice on published indices (see References).

Usage

```
ccdi_splice(
  data,
  start,
  end,
  window = 13,
  splice = "movement",
  interval = FALSE
)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
window	The length of the time window (as positive integer: typically multilateral methods are based on the 13-month time window).
splice	A character string indicating the splicing method. Available options are: "movement", "window", "half", "mean", "window_published", "half_published", "mean_published".
interval	A logical value indicating whether the function is to provide the price index comparing the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base multilateral indices are to be presented (the fixed base month is defined by start).

Value

This function returns a value or values (depending on interval parameter) of the multilateral CCDI price index extended by using window splicing methods. Available splicing methods are: movement splice, window splice, half splice, mean splice and their additional variants: window splice on published indices (WISP), half splice on published indices (HASP) and mean splice on published indices (see References). The time window starts in start and should consist of at least two months. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Caves, D.W., Christensen, L.R. and Diewert, W.E. (1982). *Multilateral comparisons of output, input, and productivity using superlative index numbers*. Economic Journal 92, 73-86.
- de Haan, J., van der Grient, H.A. (2011). *Eliminating chain drift in price indexes based on scanner data*. Journal of Econometrics, 161, 36-46.
- Krsinich, F. (2014). *The FEWS Index: Fixed Effects with a Window Splice? Non-Revisable Quality-Adjusted Price Indices with No Characteristic Information*. Paper presented at the UNECE-ILO Meeting of the Group of Experts on Consumer Price Indices, 2-4 May 2016, Geneva, Switzerland.
- de Haan, J.(2015). *A Framework for Large Scale Use of Scanner Data in the Dutch CPI*. Paper presented at the 14th Ottawa Group meeting, Tokyo, Japan.
- Diewert, W.E., and Fox, K.J. (2017). *Substitution Bias in Multilateral Methods for CPI Construction using Scanner Data*. Discussion paper 17-02, Vancouver School of Economics, The University of British Columbia, Vancouver, Canada.

Examples

```
ccdi_splice(milk, start="2018-12", end="2020-02",splice="half")
ccdi_splice(milk, start="2018-12", end="2020-02",window=10,interval=TRUE)
```

chagmean

Calculating the monthly chained AG Mean price index

Description

This function returns a value (or vector of values) of the monthly chained AG Mean price index.

Usage

```
chagmean(data, start, end, sigma = 0.7, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
sigma	The elasticity of substitution parameter (as numeric).
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start,end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the monthly chained AG Mean price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Lent J., & Dorfman,A. H. (2009). *Using a Weighted Average of Base Period Price Indexes to Approximate a Superlative Index*. Journal of Official Statistics, 25(1), 139-149.

Examples

```
chagmean(sugar, start="2019-01", end="2019-04",sigma=0.5)
chagmean(milk, start="2018-12", end="2020-01", interval=TRUE)
```

chbanajree	<i>Calculating the monthly chained Banajree price index</i>
------------	---

Description

This function returns a value (or vector of values) of the monthly chained Banajree price index.

Usage

```
chbanajree(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the monthly chained Banajree price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Banajree, K. S. (1977). *On the factorial approach providing the true index of cost of living*. Göttingen : Vandenhoeck und Ruprecht.

(2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Von der Lippe, P. (2007). *Index Theory and Price Statistics*. Peter Lang: Berlin, Germany.

Examples

```
chbanajree(sugar, start="2018-12", end="2019-04")
chbanajree(milk, start="2018-12", end="2020-01", interval=TRUE)
```

chbialek

*Calculating the monthly chained Bialek price index***Description**

This function returns a value (or vector of values) of the monthly chained Bialek price index.

Usage

```
chbialek(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the monthly chained Bialek price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Von der Lippe, P. (2012). *Some short notes on the price index of Jacek Bialek*. *Econometrics (Ekonometria)*, 1(35), 76-83.

Bialek, J. (2013). *Some Remarks on the Original Price Index Inspired by the Notes of Peter von der Lippe*. *Econometrics (Ekonometria)*, 3(41), 40-54.

Bialek, J. (2014). *Simulation Study of an Original Price Index Formula*. *Communications in Statistics - Simulation and Computation*, 43(2), 285-297

Examples

```
chbialek(sugar, start="2018-12", end="2019-04")
chbialek(milk, start="2018-12", end="2020-01", interval=TRUE)
```

chbmw

*Calculating the monthly chained BMW price index***Description**

This function returns a value (or vector of values) of the monthly chained Balk-Mehrhoff-Walsh (BMW) price index.

Usage

```
chbmw(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric) and prodID (as numeric, factor or character). A column quantities (as positive numeric) is also needed because this function uses unit values as monthly prices.
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start,end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the monthly chained BMW price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Mehrhoff, J.(2007). *A linear approximation to the Jevons index*. In: Von der Lippe (2007): Index Theory and Price Statistics, Peter Lang: Berlin, Germany.

(2018). *Harmonised Index of Consumer Prices (HICP). Methodological Manual*. Publication Office of the European union, Luxembourg.

Examples

```
chbmw(sugar, start="2018-12", end="2019-04")
chbmw(milk, start="2018-12", end="2020-01", interval=TRUE)
```

chcarli

*Calculating the monthly chained Carli price index***Description**

This function returns a value (or vector of values) of the monthly chained Carli price index.

Usage

```
chcarli(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric) and prodID (as numeric, factor or character). A column quantities (as positive numeric) is also needed because this function uses unit values as monthly prices.
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the monthly chained Carli price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Carli, G. (1804). *Del valore e della proporzione de'metalli monetati*. Scrittori Classici Italiani di Economia Politica, 13, 297-336.

(2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Examples

```
chcarli(sugar, start="2018-12", end="2019-04")
chcarli(milk, start="2018-12", end="2020-01", interval=TRUE)
```

chcswd

*Calculating the monthly chained CSWD price index***Description**

This function returns a value (or vector of values) of the monthly chained Carruthers-Sellwood-Ward-Dalen (CSWD) price index.

Usage

```
chcswd(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric) and prodID (as numeric, factor or character). A column quantities (as positive numeric) is also needed because this function uses unit values as monthly prices.
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the monthly chained CSWD price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Carruthers, A.G., Sellwood, D. J, Ward, P. W. (1980). *Recent developments in the retail price index*. Journal of the Royal Statistical Society. Series D (The Statistician), 29(1), 1-32.

Dalen, J. (1992). *Recent developments in the retail price index*. The Statistician, 29(1), 1-32.

(2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Examples

```
chcswd(sugar, start="2018-12", end="2019-04")
chcswd(milk, start="2018-12", end="2020-01", interval=TRUE)
```

chdavies

Calculating the monthly chained Davies price index

Description

This function returns a value (or vector of values) of the monthly chained Davies price index.

Usage

```
chdavies(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the monthly chained Davies price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Davies, G. R. (1924). *The Problem of a Standard Index Number Formula*. Journal of the American Statistical Association, 19 (146), 180-188.

(2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Von der Lippe, P. (2007). *Index Theory and Price Statistics*. Peter Lang: Berlin, Germany.

Examples

```
chd Davies(sugar, start="2018-12", end="2019-04")
chd Davies(milk, start="2018-12", end="2020-01", interval=TRUE)
```

chdrobisch

Calculating the monthly chained Drobisch price index

Description

This function returns a value (or vector of values) of the monthly chained Drobisch price index.

Usage

```
chdrobisch(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the monthly chained Drobisch price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Drobisch, M. W. (1871). *Ueber einige Einwurfe gegen die in diesen Jahrbuchern veröffentlichte neue Methode, die Veränderungen der Waarenpreise und des Geldwerths zu berechnen*. Jahrbucher für Nationalökonomie und Statistik, Vol. 16, s. 416-427.

(2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Von der Lippe, P. (2007). *Index Theory and Price Statistics*. Peter Lang: Berlin, Germany.

Examples

```
chdrobisch(sugar, start="2018-12", end="2019-04")
chdrobisch(milk, start="2018-12", end="2020-01", interval=TRUE)
```

chdutot

Calculating the monthly chained Dutot price index

Description

This function returns a value (or vector of values) of the monthly chained Dutot price index.

Usage

```
chdutot(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric) and prodID (as numeric, factor or character). A column quantities (as positive numeric) is also needed because this function uses unit values as monthly prices.
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the monthly chained Dutot price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Dutot, C. F., (1738). *Reflexions Politiques sur les Finances et le Commerce*. The Hague: Les Freres Vaillant et Nicolas Prevost, Vol. 1.

(2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Examples

```
chdutot(sugar, start="2018-12", end="2019-04")
chdutot(milk, start="2018-12", end="2020-01", interval=TRUE)
```

chfisher	<i>Calculating the monthly chained Fisher price index</i>
----------	---

Description

This function returns a value (or vector of values) of the monthly chained Fisher price index.

Usage

```
chfisher(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the monthly chained Fisher price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Fisher, I. (1922). *The Making of Index Numbers*. Boston: Houghton Mifflin.
 (2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Examples

```
chfisher(sugar, start="2018-12", end="2019-04")
chfisher(milk, start="2018-12", end="2020-01", interval=TRUE)
```

chgeary_khamis

*Calculating the monthly chained Geary-Khamis price index***Description**

This function returns a value (or vector of values) of the monthly chained Geary-Khamis price index.

Usage

```
chgeary_khamis(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the monthly chained Geary-Khamis price index depending on the interval parameter (please use [gk](#) function to calculate the multilateral Geary-Khamis price index). If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Geary, R. G. (1958). *A Note on Comparisons of Exchange Rates and Purchasing Power between Countries*. Journal of the Royal Statistical Society, Series A, 121, 97-99.
- Khamis, S. H. (1970). *Properties and Conditions for the Existence of a new Type of Index Number*. Sankhya Series B32, 81-98.
- (2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.
- Von der Lippe, P. (2007). *Index Theory and Price Statistics*. Peter Lang: Berlin, Germany.

Examples

```
chgeary_khamis(sugar, start="2018-12", end="2019-04")
chgeary_khamis(milk, start="2018-12", end="2020-01", interval=TRUE)
```

chgeohybrid

Calculating the the monthly chained geohybrid price index

Description

This function returns a value (or vector of values) of the monthly chained geohybrid price index. The geohybrid index was proposed by Bialek (2020) and it uses correlation coefficients between prices and quantities.

Usage

```
chgeohybrid(data, start, end, base = start, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
base	The prior period used in the geohybrid price index formula (as character) limited to the year and month, e.g. "2020-01"
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the monthly chained geohybrid price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Bialek, J. (2020). *Proposition of a Hybrid Price Index Formula for the Consumer Price Index Measurement*. Equilibrium. Quarterly Journal of Economics and Economic Policy, 15(4), 697-716.

Examples

```
chgeohybrid(sugar, start="2019-12", end="2020-05", base="2018-12")
chgeohybrid(milk, start="2019-12", end="2020-08", base="2018-12", interval=TRUE)
```

chgeolaspeyres	<i>Calculating the monthly chained geo-logarithmic Laspeyres price index</i>
----------------	--

Description

This function returns a value (or vector of values) of the monthly chained geo-logarithmic Laspeyres price index.

Usage

```
chgeolaspeyres(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the monthly chained geo-logarithmic Laspeyres price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product sub-groups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Von der Lippe, P. (2007). *Index Theory and Price Statistics*. Peter Lang: Berlin, Germany.
 (2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Examples

```
chgeolaspeyres(sugar, start="2018-12", end="2019-04")
chgeolaspeyres(milk, start="2018-12", end="2020-01", interval=TRUE)
```

chgeolowe

Calculating the monthly chained geometric Lowe price index

Description

This function returns a value (or vector of values) of the monthly chained geometric Lowe price index.

Usage

```
chgeolowe(data, start, end, base = start, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
base	The prior period used in the geometric Lowe price index formula (as character) limited to the year and month, e.g. "2020-01"
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start,end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the monthly chained geometric Lowe price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

(2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Examples

```
chgeolowe(sugar, start="2019-01", end="2019-04", base="2018-12")
chgeolowe(milk, start="2018-12", end="2020-01", interval=TRUE)
```

chgeopaasche	<i>Calculating the monthly chained geo-logarithmic Paasche price index</i>
--------------	--

Description

This function returns a value (or vector of values) of the monthly chained geo-logarithmic Paasche price index.

Usage

```
chgeopaasche(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the monthly chained geo-logarithmic Paasche price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product sub-groups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Von der Lippe, P. (2007). *Index Theory and Price Statistics*. Peter Lang: Berlin, Germany.
 (2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Examples

```
chgeopaasche(sugar, start="2018-12", end="2019-04")
chgeopaasche(milk, start="2018-12", end="2020-01", interval=TRUE)
```

chgeoyoung

Calculating the monthly chained geometric Young price index

Description

This function returns a value (or vector of values) of the monthly chained geometric Young price index.

Usage

```
chgeoyoung(data, start, end, base = start, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
base	The prior period used in the geometric Young price index formula (as character) limited to the year and month, e.g. "2020-01".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start,end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the monthly chained geometric Young price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Young, A. H. (1992). *Alternative Measures of Change in Real Output and Prices*. Survey of Current Business, 72, 32-48.

(2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Examples

```
chgeoyoung(sugar, start="2019-01", end="2019-04", base="2018-12")
chgeoyoung(milk, start="2018-12", end="2020-01", interval=TRUE)
```

chharmonic	<i>Calculating the monthly chained harmonic price index</i>
------------	---

Description

This function returns a value (or vector of values) of the monthly chained "unnamed" harmonic price index.

Usage

```
chharmonic(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric) and prodID (as numeric, factor or character). A column quantities (as positive numeric) is also needed because this function uses unit values as monthly prices.
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the monthly chained harmonic price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Von der Lippe, P. (2007). *Index Theory and Price Statistics*. Peter Lang: Berlin, Germany.
 (2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Examples

```
chharmonic(sugar, start="2018-12", end="2019-04")
chharmonic(milk, start="2018-12", end="2020-01", interval=TRUE)
```

chhybrid

Calculating the the monthly chained hybrid price index

Description

This function returns a value (or vector of values) of the monthly chained hybrid price index. The hybrid index was proposed by Bialek (2020) and it uses correlation coefficients between prices and quantities.

Usage

```
chhybrid(data, start, end, base = start, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
base	The prior period used in the hybrid price index formula (as character) limited to the year and month, e.g. "2020-01"
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the monthly chained hybrid price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Bialek, J. (2020). *Proposition of a Hybrid Price Index Formula for the Consumer Price Index Measurement*. *Equilibrium. Quarterly Journal of Economics and Economic Policy*, 15(4), 697-716.

Examples

```
chhybrid(sugar, start="2019-12", end="2020-05", base="2018-12")
chhybrid(milk, start="2019-12", end="2020-08", base="2018-12", interval=TRUE)
```

chjevons

Calculating the monthly chained Jevons price index

Description

This function returns a value (or vector of values) of the monthly chained Jevons price index

Usage

```
chjevons(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric) and prodID (as numeric, factor or character). A column quantities (as positive numeric) is also needed because this function uses unit values as monthly prices.
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the monthly chained Jevons price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Jevons, W. S., (1865). *The variation of prices and the value of the currency since 1782*. J. Statist. Soc. Lond., 28, 294-320.

(2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Examples

```
chjevons(sugar, start="2018-12", end="2019-04")
chjevons(milk, start="2018-12", end="2020-01", interval=TRUE)
```

chlaspeyres

Calculating the monthly chained Laspeyres price index

Description

This function returns a value (or vector of values) of the monthly chained Laspeyres price index.

Usage

```
chlaspeyres(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the monthly chained Laspeyres price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Laspeyres, E. (1871). *Die Berechnung einer mittleren Waarenpreissteigerung*. Jahrbucher fur Nationalokonomie und Statistik 16, 296-314.

(2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Examples

```
chlaspeyres(sugar, start="2018-12", end="2019-04")
chlaspeyres(milk, start="2018-12", end="2020-01", interval=TRUE)
```

chlehr

Calculating the monthly chained Lehr price index

Description

This function returns a value (or vector of values) of the monthly chained Lehr price index.

Usage

```
chlehr(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the monthly chained Lehr price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Lehr, J. (1885). *Beitrage zur Statistik der Preise, insbesondere des Geldes und des Holzes*. J. D. Sauerlander, Frankfurt am Main.

(2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Examples

```
chlehr(sugar, start="2018-12", end="2019-04")
chlehr(milk, start="2018-12", end="2020-01", TRUE)
```

chlloyd_moulton

Calculating the monthly chained Lloyd-Moulton price index

Description

This function returns a value (or vector of values) of the monthly chained Lloyd-Moulton price index.

Usage

```
chlloyd_moulton(data, start, end, sigma = 0.7, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
sigma	The elasticity of substitution parameter (as numeric).
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the monthly chained Lloyd-Moulton price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Lloyd, P. J. (1975). *Substitution Effects and Biases in Nontrue Price Indices*. The American Economic Review, 65, 301-313.
- Moulton, B. R. (1996). *Constant Elasticity Cost-of-Living Index in Share-Relative Form*. Washington DC: U. S. Bureau of Labor Statistics, mimeograph
- (2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.
- Von der Lippe, P. (2007). *Index Theory and Price Statistics*. Peter Lang: Berlin, Germany.

Examples

```
chlloyd_moulton(sugar, start="2018-12", end="2019-04", sigma=0.9)
chlloyd_moulton(milk, start="2018-12", end="2020-01", interval=TRUE)
```

chlowe

Calculating the monthly chained Lowe price index

Description

This function returns a value (or vector of values) of the monthly chained Lowe price index.

Usage

```
chlowe(data, start, end, base = start, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
base	The prior period used in the Lowe price index formula (as character) limited to the year and month, e.g. "2020-01".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the monthly chained Lowe price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

(2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Examples

```
chlowe(sugar, start="2019-01", end="2019-04",base="2018-12")
chlowe(milk, start="2018-12", end="2020-01", interval=TRUE)
```

chmarshall_edgeworth *Calculating the monthly chained Marshall-Edgeworth price index*

Description

This function returns a value (or vector of values) of the monthly chained Marshall-Edgeworth price index.

Usage

```
chmarshall_edgeworth(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start,end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the monthly chained Marshall-Edgeworth price index depending on the `interval` parameter. If the `interval` parameter is set to `TRUE`, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product sub-groups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Marshall, A. (1887). *Remedies for Fluctuations of General Prices*. Contemporary Review, 51, 355-375.
- Edgeworth, F. Y. (1887). *Measurement of Change in Value of Money I*. The first Memorandum presented to the British Association for the Advancement of Science; reprinted in Papers Relating to Political Economy, Vol. 1, New York, Burt Franklin, s. 1925.
- (2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.
- Von der Lippe, P. (2007). *Index Theory and Price Statistics*. Peter Lang: Berlin, Germany.

Examples

```
chmarshall_edgeworth(sugar, start="2018-12", end="2019-04")
chmarshall_edgeworth(milk, start="2018-12", end="2020-01", interval=TRUE)
```

chpaasche

Calculating the monthly chained Paasche price index

Description

This function returns a value (or vector of values) of the monthly chained Paasche price index.

Usage

```
chpaasche(data, start, end, interval = FALSE)
```

Arguments

- | | |
|--------------------|--|
| <code>data</code> | The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character). |
| <code>start</code> | The base period (as character) limited to the year and month, e.g. "2020-03". |
| <code>end</code> | The research period (as character) limited to the year and month, e.g. "2020-04". |

interval A logical value indicating whether the function is to compare the research period defined by `end` to the base period defined by `start` (then `interval` is set to `FALSE`) or all fixed base indices are to be calculated. In this latter case, all months from the time interval `<start,end>` are considered and `start` defines the base period (`interval` is set to `TRUE`).

Value

The function returns a value (or vector of values) of the monthly chained Paasche price index depending on the `interval` parameter. If the `interval` parameter is set to `TRUE`, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Paasche, H. (1874). *Über die Preisentwicklung der letzten Jahre nach den Hamburger Borsennotirungen*. Jahrbucher für Nationalökonomie und Statistik, 12, 168-178.

(2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Examples

```
chpaasche(sugar, start="2018-12", end="2019-04")
chpaasche(milk, start="2018-12", end="2020-01", interval=TRUE)
```

chpalgrave

Calculating the monthly chained Palgrave price index

Description

This function returns a value (or vector of values) of the monthly chained Palgrave price index.

Usage

```
chpalgrave(data, start, end, interval = FALSE)
```

Arguments

data The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).

start The base period (as character) limited to the year and month, e.g. "2020-03".

end The research period (as character) limited to the year and month, e.g. "2020-04".

interval A logical value indicating whether the function is to compare the research period defined by `end` to the base period defined by `start` (then `interval` is set to `FALSE`) or all fixed base indices are to be calculated. In this latter case, all months from the time interval `<start,end>` are considered and `start` defines the base period (`interval` is set to `TRUE`).

Value

The function returns a value (or vector of values) of the monthly chained Palgrave price index depending on the `interval` parameter. If the `interval` parameter is set to `TRUE`, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Palgrave, R. H. I. (1886). *Currency and Standard of Value in England, France and India and the Rates of Exchange Between these Countries*. Memorandum submitted to the Royal Commission on Depression of trade and Industry, Third Report, Appendix B, 312-390.

(2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Von der Lippe, P. (2007). *Index Theory and Price Statistics*. Peter Lang: Berlin, Germany.

Examples

```
chpalgrave(sugar, start="2018-12", end="2019-04")
chpalgrave(milk, start="2018-12", end="2020-01", interval=TRUE)
```

chsato_vartia	<i>Calculating the monthly chained Vartia-II (Sato-Vartia) price index</i>
---------------	--

Description

This function returns a value (or vector of values) of the monthly chained Vartia-II (Sato-Vartia) price index.

Usage

```
chsato_vartia(data, start, end, interval = FALSE)
```

Arguments

data The user's data frame with information about sold products. It must contain columns: `time` (as Date in format: year-month-day,e.g. '2020-12-01'), `prices` (as positive numeric), `quantities` (as positive numeric) and `prodID` (as numeric, factor or character).

start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start,end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the monthly chained Vartia-II (Sato-Vartia) price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product sub-groups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Sato, K. (1976). *The Ideal Log-Change Index Number*. The Review of Economics and Statistics, 58(2), 223-228.
- Vartia, Y. O. (1976). *Ideal Log-Change Index Numbers*. Scandinavian Journal of Statistics 3(3), 121-126.
- (2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.
- Von der Lippe, P. (2007). *Index Theory and Price Statistics*. Peter Lang: Berlin, Germany.

Examples

```
chsato_vartia(sugar, start="2018-12", end="2019-04")
chsato_vartia(milk, start="2018-12", end="2020-01", interval=TRUE)
```

chstuvel

Calculating the monthly chained Stuvcl price index

Description

This function returns a value (or vector of values) of the monthly chained Stuvcl price index.

Usage

```
chstuvel(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start,end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the monthly chained Stuvcl price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Stuvcl, G. (1957). *A New Index Number Formula*. *Econometrica*, 25, 123-131.
- (2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.
- Von der Lippe, P. (2007). *Index Theory and Price Statistics*. Peter Lang: Berlin, Germany.

Examples

```
chstuvcl(sugar, start="2018-12", end="2019-04")
chstuvcl(milk, start="2018-12", end="2020-01", interval=TRUE)
```

chtornqvist

Calculating the monthly chained Tornqvist price index

Description

This function returns a value (or vector of values) of the monthly chained Tornqvist price index.

Usage

```
chtornqvist(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the monthly chained Tornqvist price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Tornqvist, L. (1936). *The Bank of Finland's Consumption Price Index*. Bank of Finland Monthly Bulletin 10, 1-8.

(2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Examples

```
chtornqvist(sugar, start="2018-12", end="2019-04")
chtornqvist(milk, start="2018-12", end="2020-01", interval=TRUE)
```

chvartia

Calculating the monthly chained Vartia-I price index

Description

This function returns a value (or vector of values) of the monthly chained Vartia-I price index.

Usage

```
chvartia(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the monthly chained Vartia-I price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Vartia, Y. O. (1976). *Ideal Log-Change Index Numbers*. Scandinavian Journal of Statistics 3(3), 121-126.
- (2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.
- Von der Lippe, P. (2007). *Index Theory and Price Statistics*. Peter Lang: Berlin, Germany.

Examples

```
chvartia(sugar, start="2018-12", end="2019-04")
chvartia(milk, start="2018-12", end="2020-01", interval=TRUE)
```

chwalsh

Calculating the monthly chained Walsh price index

Description

This function returns a value (or vector of values) of the monthly chained Walsh price index.

Usage

```
chwalsh(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start,end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the monthly chained Walsh price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Walsh, C. M. (1901). *The Measurement of General Exchange Value*. The MacMillan Company, New York.
- (2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.
- Von der Lippe, P. (2007). *Index Theory and Price Statistics*. Peter Lang: Berlin, Germany.

Examples

```
chwalsh(sugar, start="2018-12", end="2019-04")
chwalsh(milk, start="2018-12", end="2020-01", interval=TRUE)
```

chyoung

Calculating the monthly chained Young price index

Description

This function returns a value (or vector of values) of the monthly chained Young price index.

Usage

```
chyoung(data, start, end, base = start, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
base	The prior period used in the Young price index formula (as character) limited to the year and month, e.g. "2020-01".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the monthly chained Young price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Young, A. H. (1992). *Alternative Measures of Change in Real Output and Prices*. Survey of Current Business, 72, 32-48.

(2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Examples

```
chyoung(sugar, start="2019-01", end="2019-04", base="2018-12")
chyoung(milk, start="2018-12", end="2020-01", interval=TRUE)
```

 coffee

A real data set on sold coffee

Description

A collection of scanner data on the sale of coffee in one of Polish supermarkets in the period from December 2017 to October 2020

Usage

```
coffee
```

Format

A data frame with 6 columns and 42561 rows. The used variables are as follows:

time - Dates of transactions (Year-Month-Day)

prices - Prices of sold products [PLN]

quantities - Quantities of sold products [kg]

prodID - Unique product codes (data set contains 79 different prodIDs)

retID - Unique codes identifying outlets/retailer sale points (data set contains 20 different retIDs)

description Descriptions of sold coffee products (data set contains 3 different product descriptions)

compare_distances	<i>Calculating distances between price indices</i>
-------------------	--

Description

The function calculates distances between price indices

Usage

```
compare_distances(
  data = data.frame(),
  measure = "MAD",
  pp = TRUE,
  first = TRUE,
  prec = 3
)
```

Arguments

data	The data frame containing values of indices which are to be compared
measure	A parameter specifying what measure should be used to compare the indexes. Possible parameter values are: "MAD" (Mean Absolute Distance) or "RMSD" (Root Mean Square Distance).
pp	Logical parameter indicating whether the results are to be presented in percentage points (then pp = TRUE).
first	A logical parameter that determines whether the first row of the data frame is to be taken into account when calculating the distance between the indices (then first = TRUE). Usually, the first row concerns the index values for the base period - all indexes are then set to one.
prec	Parameter that determines how many decimal places are to be used in the presentation of results.

Value

The function calculates average distances between price indices and it returns a data frame with these values for each pair of price indices.

Examples

```
#Creating a data frame with unweighted bilateral index values
df<-price_indices(milk,
bilateral=c("jevons","dutot","carli"),
start="2018-12",end="2019-12",interval=TRUE)
#Calculating average distances between indices (in p.p)
compare_distances(df)
```

compare_final_indices *A general function for graphical comparison of price indices*

Description

This function returns a figure with plots of previously calculated price indices.

Usage

```
compare_final_indices(finalindices = list(), names = c())
```

Arguments

finalindices	A list of data frames with previously calculated price indices. Each data frame must consist of two columns, i.e. the first column must include dates limited to the year and month (e.g.: "2020-04") and the second column must indicate price index values for corresponding dates. The above-mentioned single data frame may be created manually in the previous step or it may be a result of functions: price_index or final_index. All considered data frames must have an identical number of rows.
names	A vector of character strings describing names of presented indices.

Value

This function returns a figure with plots of previously calculated price indices. It allows for graphical comparison of price index values which were previously calculated and now are provided as data frames (see finalindices parameter).

Examples

```
## Calculating two indices by using two different package functions:
index1<-final_index(datasets=list(milk), start="2018-12",
end="2019-12",formula="walsh",interval=TRUE)
index2<-price_index(milk,start="2018-12", end="2019-12",
formula="geks",interval=TRUE)
## Graphical comparison of these two indices
compare_final_indices(finalindices=list(index1,index2),
names=c("Walsh index", "GEKS index"))
```

compare_indices	<i>A function for graphical comparison of price indices</i>
-----------------	---

Description

This function returns a figure with plots of selected price indices.

Usage

```
compare_indices(
  data,
  start,
  end,
  bilateral = c(),
  bindex = c(),
  base = c(),
  cesindex = c(),
  sigma = c(),
  simindex = c(),
  fbmulti = c(),
  fbwindow = c(),
  splicemulti = c(),
  splicewindow = c(),
  splice = c(),
  namebilateral = bilateral,
  namebindex = bindex,
  namecesindex = cesindex,
  namesimindex = simindex,
  namefbmulti = fbmulti,
  namesplicemulti = splicemulti
)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric) and prodID (as numeric, factor or character). A column
------	--

	quantities is also essential (as positive numeric) because unit values are calculated.
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
bilateral	A vector of character strings indicating bilateral price index formulas that are to be calculated. To see available options please use the link: PriceIndices .
bindex	A vector of character strings indicating Lowe- or Young-type price index formulas that are to be calculated. Available options are: young, geoyoung, lowe and geolowe.
base	The vector of prior periods used in the Young- or Lowe-type price indices. Each element of the vector (as character) must be limited to the year and month, e.g. "2020-01".
cesindex	A vector of character strings indicating CES price index formulas that are to be calculated. To see available options, please use the link: PriceIndices .
sigma	The vector of elasticity of substitution parameters used in the Lloyed-Moulton and AG Mean indices.
simindex	A vector of character strings indicating multilateral price index formulas based on relative price and quantity similarity that are to be calculated. To see available options, please use the link: PriceIndices .
fbmulti	A vector of character strings indicating multilateral price index formulas that are to be calculated. The available set of indices includes full-window multilateral indices or their FBEW and FBMW extensions. To see available options, please use the link: PriceIndices .
fbwindow	A vector of integers. Each element of the vector defines the length of the time window of the corresponding multilateral index (if it is selected by fbmulti).
splicemulti	The vector of character strings indicating multilateral price index formulas are to be extended by using splicing methods. To see available options please use the link: PriceIndices .
splicewindow	A vector of integers. Each element of the vector defines the length of the time window of the corresponding multilateral index (if it is selected by splicemulti).
splice	A vector of character strings. Each element of the vector indicates the splicing method is to be used for the corresponding multilateral index (if it is selected by splicemulti). Available values of vector elements are: "movement", "window", "half", "mean".
namebilateral	A vector of character strings describing names of bilateral price indices that are to be displayed. If this vector is empty, then default names are used.
namebindex	A vector of character strings describing names of Young- and/or Lowe-type price indices are to be displayed. If this vector is empty then default names are used.
namecesindex	A vector of character strings describing names of CES price indices that are to be displayed. If this vector is empty, then default names are used.
namesimindex	A vector of character strings describing names of multilateral price index formulas based on relative price and quantity similarity that are to be displayed. If this vector is empty, then default names are used.

- `namefbmulti` A vector of character strings describing names of full-window multilateral indices or their FBEW and FBMW extensions that are to be displayed. If this vector is empty, then default names are used.
- `namesplicemulti` A vector of character strings describing names of multilateral splice indices that are to be displayed. If this vector is empty, then default names are used.

Value

This function calculates selected bilateral or/and multilateral price indices and returns a figure with plots of these indices (together with dates on X-axis and a corresponding legend). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use functions: [final_index](#) and [compare_final_indices](#)).

Examples

```
compare_indices(milk, start="2018-12", end="2019-04",
bilateral=c("jevons"),fbmulti=c("tpd"),fbwindow=c(6))
compare_indices(milk, start="2018-12", end="2019-05",
fbmulti=c("tpd","geks"),fbwindow=c(10,12))
```

cswd

Calculating the unweighted CSWD price index

Description

This function returns a value (or vector of values) of the unweighted Carruthers-Sellwood-Ward-Dalen (CSWD) price index.

Usage

```
cswd(data, start, end, interval = FALSE)
```

Arguments

- `data` The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric) and prodID (as numeric, factor or character). A column quantities (as positive numeric) is also needed because this function uses unit values as monthly prices.
- `start` The base period (as character) limited to the year and month, e.g. "2020-03".
- `end` The research period (as character) limited to the year and month, e.g. "2020-04".
- `interval` A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start,end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the unweighted bilateral CSWD price index depending on the `interval` parameter. If the `interval` parameter is set to `TRUE`, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Carruthers, A.G., Sellwood, D. J, Ward, P. W. (1980). *Recent developments in the retail price index*. Journal of the Royal Statistical Society. Series D (The Statistician), 29(1), 1-32.

Dalen, J. (1992). *Recent developments in the retail price index*. The Statistician, 29(1), 1-32.

(2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Examples

```
cswd(sugar, start="2018-12", end="2019-12")
cswd(milk, start="2018-12", end="2020-01", interval=TRUE)
```

dataAGGR	<i>A small artificial scanner data set for a demonstration of data aggregation</i>
----------	--

Description

A collection of artificial scanner data on milk products sold in three different months

Usage

```
dataAGGR
```

Format

A data frame with 6 columns and 9 rows. The used variables are as follows:

`time` - Dates of transactions (Year-Month-Day: 4 different dates)

`prices` - Prices of sold products [PLN]

`quantities` - Quantities of sold products [l]

`prodID` - Retailer product codes (3 prodIDs)

`retID` - Unique codes identifying outlets/retailer sale points (4 retIDs)

`description` Descriptions of sold products (two subgroups: goat milk, powdered milk)

dataCOICOP

An artificial scanner data set for the product classification

Description

A collection of artificial scanner data on the sale of tomatoes, fruit juices, low fat milk, full fat milk, sugar, chocolate, yoghurt, coffee, eggs and salt in the period from December 2018 to October 2020

Usage

dataCOICOP

Format

A data frame with 8 columns and 96600 rows (some rows are not complete). The used variables are as follows:

time - Dates of transactions (Year-Month-Day)

prices - Prices of sold products [EUR]

quantities - Quantities of sold products [unit defined in the 'unit' column]

prodID - Retailer product codes

retID - Unique codes identifying outlets/retailer sale points (10 retIDs)

description Descriptions of sold products

unit Sales units, e.g.: kg, ml, etc.

coicop Identifiers of COICOP groups (10 groups)

dataMATCH

An artificial scanner data set for product matching

Description

A collection of scanner data on the sale of sample artificial products.

Usage

dataMATCH

Format

A data frame with 7 columns and 30 rows. The used variables are as follows:

time - Dates of transactions (Year-Month-Day)

prices - Prices of sold products [PLN]

quantities - Quantities of sold products [liters]

codeIN - Unique internal (retailer) product codes (data set contains 5 different codeINs)

codeOUT - Unique external product codes (data set contains 5 different codeOUTs)

retID - Unique codes identifying outlets/retailer sale points (data set contains 2 different retIDs)

description Descriptions of sold products (data set contains 3 different product descriptions)

dataU

An artificial, small scanner data set

Description

A collection of artificial scanner data on 6 products sold in Dec, 2018. Product descriptions contain the information about their grammage and unit.

Usage

dataU

Format

A data frame with 5 columns and 6 rows. The used variables are as follows:

time - Dates of transactions (Year-Month-Day)

prices - Prices of sold products [PLN]

quantities - Quantities of sold products [item]

prodID - Unique product codes

description Descriptions of sold products (data set contains 6 different product descriptions)

data_aggregating	<i>Aggregating the user's data frame</i>
------------------	--

Description

The function aggregates the user's data frame over time and optionally over outlets.

Usage

```
data_aggregating(data, join_outlets = TRUE)
```

Arguments

data	The user's data frame.
join_outlets	A logical value indicating whether the data aggregation over outlets should be also done.

Value

The function aggregates the user's data frame over time and/or over outlets. Consequently, we obtain monthly data, where the unit value is calculated instead of a price for each prodID observed in each month (the time column gets the Date format: "Year-Month-01"). If the parameter join_outlets is TRUE, then the function also performs aggregation over outlets (retIDs) and the retID column is removed from the data frame. The main advantage of using this function is the ability to reduce the size of the data frame and the time needed to calculate the price index.

Examples

```
#Example 1
data_aggregating(dataAGGR, join_outlets = FALSE)
data_aggregating(dataAGGR, join_outlets = FALSE)
#Example 2 (data frame reduction)
nrow(milk)
nrow(data_aggregating(milk))
```

data_check	<i>Checking the user's data frame</i>
------------	---------------------------------------

Description

The function checks if the argument data points to a data frame which is suitable for further price index calculation. In particular, the function checks whether the indicated data frame contains the required columns and whether they are of the appropriate type (if not, the function returns FALSE and an appropriate comment).

Usage

```
data_check(data)
```

Arguments

`data` Any R object but ultimately it is a data frame.

Value

The function returns TRUE if the data frame indicated by the `data` parameter is suitable for the calculation of price indices and returns FALSE otherwise.

Examples

```
data_check(milk)
data_check(iris)
```

`data_classifying`*Predicting product COICOP levels via the machine learning model*

Description

This function predicts product COICOP levels via the selected machine learning model.

Usage

```
data_classifying(model = list(), data)
```

Arguments

`model` A list of 8 elements which identify the previously built machine learning model (the list is obtained via the `model_classification` function).

`data` A data set for the model (products with their characteristics). This data set must contain all the columns which were used in the built model.

Value

This function provides the indicated data set with an additional column, i.e. `coicop_predicted`, which is obtained by using the selected machine learning model.

Examples

```
#Building the model
my.grid=list(eta=c(0.01,0.02,0.05),subsample=c(0.5))
data_train<-dplyr::filter(dataCOICOP,dataCOICOP$time<=as.Date("2020-08-01"))
data_test<-dplyr::filter(dataCOICOP,dataCOICOP$time>as.Date("2020-08-01"))
ML<-model_classification(data_train,data_test,grid=my.grid,
  indicators=c("prodID","unit","description"),key_words=c("milk"),rounds=50)
#Data classification
data_classifying(ML, data_test)
```

data_filtering

Filtering a data set for further price index calculations

Description

This function returns a filtered data set, i.e. a reduced user's data frame with the same columns and rows limited by a criterion defined by filters.

Usage

```
data_filtering(
  data,
  start,
  end,
  filters = c(),
  plimits = c(),
  pquantiles = c(),
  dplimits = c(),
  lambda = 1.25,
  interval = FALSE,
  retailers = FALSE
)
```

Arguments

data	The user's data frame with information about products to be filtered. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric) and quantities (as positive numeric).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
filters	A vector of filter names (options are: extremeprices, dumpprices and/or lowsales).
plimits	A two-dimensional vector of thresholds for minimum and maximum price change (it works if one of the chosen filters is extremeprices filter).
pquantiles	A two-dimensional vector of quantile levels for minimum and maximum price change (it works if one of the chosen filters is extremeprices filter).

dplimits	A two-dimensional vector of thresholds for maximum price drop and maximum expenditure drop (it works if one of the chosen filters is dumpprices filter).
lambda	The lambda parameter for lowsales filter (see References below).
interval	A logical value indicating whether the filtering process concerns only two periods defined by start and end parameters (then the interval is set to FALSE) or whether that function is to filter products sold during the whole time interval <start, end>, i.e. any subsequent months are compared.
retailers	A logical parameter indicating whether filtering should be done for each outlet (retID) separately. If it is set to FALSE, then there is no need to consider the retID column.

Value

This function returns a filtered data set (a reduced user's data frame). If the set of filters is empty, then the function returns the original data frame (defined by the data parameter) limited to considered months. On the other hand, if all filters are chosen, i.e. `filters=c(extremeprices, dumpprices, lowsales)`, then these filters work independently and a summary result is returned. Please note that both variants of extremeprices filter can be chosen at the same time, i.e. `plimits` and `pquantiles`, and they work also independently.

References

Van Loon, K., Roels, D. (2018) *Integrating big data in Belgian CPI*. Meeting of the Group of Experts on Consumer Price Indices, Geneva.

Examples

```
data_filtering(milk, start="2018-12", end="2019-03",
  filters=c("extremeprices"), pquantiles=c(0.01, 0.99), interval=TRUE)
data_filtering(milk, start="2018-12", end="2019-03",
  filters=c("extremeprices", "lowsales"), plimits=c(0.25, 2))
```

data_matching

Matching products

Description

This function returns a data set defined in the first parameter (data) with an additional column (prodID). Two products are treated as being matched if they have the same prodID value.

Usage

```
data_matching(
  data,
  start,
  end,
  interval = FALSE,
```

```

variables = c(),
codeIN = TRUE,
codeOUT = TRUE,
description = TRUE,
onlydescription = FALSE,
precision = 0.95
)

```

Arguments

data	The user's data frame with information about products to be matched. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01') and at least one of the following columns: codeIN (as numeric, factor or character), codeOUT (as numeric, factor or character) and description (as character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the matching process concerns only two periods defined by start and end parameters (then the interval is set to FALSE) or whether that function is to match products sold during the whole time interval <start, end>.
variables	The optional parameter describing the vector of additional column names. Values of these additional columns must be identical for matched products.
codeIN	A logical value, e.g. if there are retailer (internal) product codes (as numeric or character) written in codeIN column and there is a need to use that column while data matching, then that parameter should be set to TRUE. Otherwise it is set to FALSE.
codeOUT	A logical value, e.g. if there are external product codes, such as GTIN or SKU (as numeric or character) written in codeOUT column and there is a need to use that column while data preparing then, that parameter should be set to TRUE. Otherwise it is set to FALSE.
description	A logical value, e.g. if there are product labels (as character) written in description column and there is a need to use that column while data preparing, then that parameter should be set to TRUE. Otherwise it is set to FALSE.
onlydescription	A logical value indicating whether products with identical labels (described in the description) are to be matched.
precision	A threshold value for the Jaro-Winkler distance measure when comparing labels (its value must belong to the interval [0,1]). Two labels are treated as similar enough if their Jaro-Winkler distance exceeds the precision value.

Value

This function returns a data set defined in the first parameter (data) with an additional column (prodID). Two products are treated as being matched if they have the same prodID value. The procedure of generating the above-mentioned additional column depends on the set of chosen columns for matching. In most extreme case, when the onlydescription parameter value is TRUE, two

products are also matched if they have identical descriptions. Other cases are as follows: Case 1: Parameters codeIN, codeOUT and description are set to TRUE. Products with two identical codes or one of the codes identical and an identical description are automatically matched. Products are also matched if they have identical one of codes and the Jaro-Winkler distance of their descriptions is bigger than the precision value. Case 2: Only one of the parameters: codeIN or codeOUT are set to TRUE and also the description parameter is set to TRUE. Products with an identical chosen code and an identical description are automatically matched. In the second stage, products are also matched if they have an identical chosen code and the Jaro-Winkler distance of their descriptions is bigger than the precision value. Case 3: Parameters codeIN and codeOUT are set to TRUE and the parameter description is set to FALSE. In this case, products are matched if they have both codes identical. Case 4: Only the parameter description is set to TRUE. This case requires the onlydescription parameter to be TRUE and then the matching process is based only on product labels (two products are matched if they have identical descriptions). Case 5: Only one of the parameters: codeIN or codeOUT are set to TRUE and the description parameter is set to FALSE. In this case, the only reasonable option is to return the prodID column which is identical with the chosen code column. Please note that if the set of column names defined in the variables parameter is not empty, then the values of these additional columns must be identical while product matching.

Examples

```
data_matching(dataMATCH, start="2018-12",end="2019-02",onlydescription=TRUE,interval=TRUE)
data_matching(dataMATCH, start="2018-12",end="2019-02",precision=0.98, interval=TRUE)
```

data_norm	<i>Normalization of grammage units and recalculation of prices and quantities with respect to these units</i>
-----------	---

Description

The function normalizes grammage units of products and recalculates product prices and quantities with respect to these normalized grammage units.

Usage

```
data_norm(
  data = data.frame(),
  rules = list(c("ml", "l", 1000), c("g", "kg", 1000)),
  all = TRUE
)
```

Arguments

data	The user's data frame. The data frame must contain the following columns: prices (as positive numeric), quantities (as positive numeric), grammage (as numeric or character) and unit (as character).
------	---

rules	User rules for transforming grammage, unit, prices and quantities of products. For instance, a rule ("ml", "l", 1000) changes the 'old' grammage unit: ml into the new one: l on the basis of the provided relation: 1000ml=1l. As a consequence, for each product which is sold in liters l , the unit price and quantity are calculated.
all	A logical value indicating whether the resulting data frame is to be limited to products with detected grammage. Its default value is TRUE which means that not transformed rows (products) are also returned.

Value

The function returns the user's data frame with two transformed columns: grammage and unit, and two rescaled columns: prices and quantities. The above-mentioned transformation and rescaling take into consideration the user rules. Recalculated prices and quantities concern grammage units defined as the second parameter in the given rule.

Examples

```
# Preparing a data set
data<-data_unit(dataU,units=c("g","ml","kg","l"),multiplication="x")
# Normalization of grammage units
data_norm(data, rules=list(c("ml","l",1000),c("g","kg",1000)))
```

data_preparing	<i>Preparing a data set for further data processing or price index calculations</i>
----------------	---

Description

This function returns a prepared data frame based on the user's data set. The resulting data frame is ready for further data processing (such as data selecting, matching or filtering) and it is also ready for price index calculations (if only it contains required columns).

Usage

```
data_preparing(
  data,
  time = NULL,
  prices = NULL,
  quantities = NULL,
  prodID = NULL,
  retID = NULL,
  description = NULL,
  codeIN = NULL,
  codeOUT = NULL,
  grammage = NULL,
  unit = NULL,
  additional = c()
)
```

Arguments

data	The user's data frame to be prepared. The user must indicate columns: time (as Date or character type, allowed formats are, eg.: '2020-03' or '2020-12-28'), prices and quantities (as numeric). Optionally, the user may also indicate columns: prodID, codeIN, codeOUT, retID (as numeric, factor or character), description (as character), grammage (as numeric or character), unit (as character) and other columns specified by the additional parameter.
time	A character name of the column which provides transaction dates.
prices	A character name of the column which provides product prices.
quantities	A character name of the column which provides product quantities.
prodID	A character name of the column which provides product IDs. The prodID column should include unique product IDs used for product matching (as numeric or character). It is not obligatory to consider this column while data preparing but it is required while price index calculating (to obtain it, please see data_matching).
retID	A character name of the column which provides outlet IDs (retailer sale points). The retID column should include unique outlet IDs used for aggregating subindices over outlets. It is not obligatory to consider this column while data preparing but it is required while final price index calculating (to obtain it, please see the final_index or final_index2 function).
description	A character name of the column which provides product descriptions. It is not obligatory to consider this column while data preparing but it is required while product selecting (please see the data_selecting function).
codeIN	A character name of the column which provides internal product codes (from the retailer). It is not obligatory to consider this column while data preparing but it may be required while product matching (please see the data_matching function).
codeOUT	A character name of the column which provides external product codes (e.g. GTIN or SKU). It is not obligatory to consider this column while data preparing but it may be required while product matching (please see the data_matching function).
grammage	A character name of the numeric column which provides the grammage of products
unit	A character name of the column which provides the unit of the grammage of products
additional	A character vector of names of additional columns to be considered while data preparing (records with missing values are deleted).

Value

The resulting data frame is free from missing values, zero or negative prices and quantities. As a result, column time is set to be Date type (in format: 'Year-Month-01'), columns prices and quantities are set to be numeric. If the column description is selected, then it is set to be character type. If columns: prodID, retID, codeIN or codeOUT are selected, then they are set to be factor type.

Examples

```
data_preparing(milk, time="time",prices="prices",quantities="quantities")
data_preparing(dataCOICOP, time="time",
prices="prices",quantities="quantities",additional="coicop")
```

data_selecting	<i>Selecting products from the user's data set for further price index calculations</i>
----------------	---

Description

The function returns a subset of the user's data set obtained by selection based on keywords and phrases.

Usage

```
data_selecting(
  data,
  include = c(),
  must = c(),
  exclude = c(),
  sensitivity = FALSE,
  coicop = NULL
)
```

Arguments

data	The user's data frame. It must contain a column description (as character).
include	A vector consisting of words and phrases. The function reduces the data set to one in which the description column contains any of these values.
must	A vector consisting of words and phrases. The function reduces the data set to one in which the description column contains each of these values.
exclude	A vector consisting of words and phrases. The function reduces the data set to one in which the description column does not contain any of these values.
sensitivity	A logical parameter indicating whether sensitivity to lowercase and uppercase letters is taken into consideration (if yes, its value is TRUE).
coicop	An optional parameter indicating a value for an additional column coicop which is added to the resulting data frame

Value

The function returns a subset of the user's data set obtained by selection based on keywords and phrases defined by parameters: include, must and exclude (an additional column coicop is optional). Providing values of these parameters, please remember that the procedure distinguishes between uppercase and lowercase letters only when sensitivity is set to TRUE.

Examples

```
data_selecting(milk, include=c("milk"), must=c("UHT"))
data_selecting(milk, must=c("milk"), exclude=c("paust"))
```

data_unit

*Providing information about the grammage and unit of products***Description**

The function returns the grammage and unit of products as two additional columns.

Usage

```
data_unit(
  data = data.frame(),
  units = c("g", "ml", "kg", "l"),
  multiplication = "x",
  space = 1
)
```

Arguments

data	The user's data frame. The data frame must contain the description column (as character).
units	Units of products which are to be detected
multiplication	A sign of the multiplication used in product descriptions
space	A maximum space between the product grammage and its unit

Value

The function returns the user's data frame with two additional columns: grammage and unit (both are character type). The values of these columns are extracted from product descriptions on the basis of provided units. Please note, that the function takes into consideration a sign of the multiplication, e.g. if the product description contains: '2x50 g', we obtain: grammage: 100 and unit: g for that product (for multiplication set to 'x').

Examples

```
data_unit(dataU,units=c("g","ml","kg","l"),multiplication="x")
```

davies	<i>Calculating the bilateral Davies price index</i>
--------	---

Description

This function returns a value (or vector of values) of the bilateral Davies price index.

Usage

```
davies(data, start, end, interval = FALSE)
```

Arguments

<code>data</code>	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
<code>start</code>	The base period (as character) limited to the year and month, e.g. "2020-03".
<code>end</code>	The research period (as character) limited to the year and month, e.g. "2020-04".
<code>interval</code>	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the bilateral Davies price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Davies, G. R. (1924). *The Problem of a Standard Index Number Formula*. Journal of the American Statistical Association, 19 (146), 180-188.

(2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Von der Lippe, P. (2007). *Index Theory and Price Statistics*. Peter Lang: Berlin, Germany.

Examples

```
davies(sugar, start="2018-12", end="2019-12")
davies(milk, start="2018-12", end="2020-01", interval=TRUE)
```

dissimilarity	<i>Calculating the relative price and/or quantity dissimilarity measure between periods</i>
---------------	---

Description

This function returns a value of the relative price and/or quantity dissimilarity measure.

Usage

```
dissimilarity(data, period1, period2, type = "p")
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
period1	The first period (as character) limited to the year and month, e.g. '2019-03'.
period2	The second period (as character) limited to the year and month, e.g. '2019-04'.
type	The parameter indicates what type of dissimilarity measure is to be calculated. Possible values of the type parameter are: p (for the price dissimilarity measure calculation), q (for the quantity dissimilarity measure calculation) or pq (for the dSPQ measure calculation, i.e. the measure of relative price and quantity dissimilarity - see References).

Value

This function returns a value of the relative price (dSP) and/or quantity (dSQ) dissimilarity measure. In a special case, when the type parameter is set to pq, the function provides the value of dSPQ measure (the relative price and quantity dissimilarity measure calculated as $\min(\text{dSP}, \text{dSQ})$).

References

Diewert, E. (2020). *The Chain Drift Problem and Multilateral Indexes*. Chapter 6 in: Consumer Price Index Theory (draft)

Examples

```
dissimilarity(milk, period1="2018-12", period2="2019-12", type="q")
dissimilarity(milk, period1="2018-12", period2="2019-12", type="pq")
```

dissimilarity_fig	<i>Presenting the relative price and/or quantity dissimilarity measure over time</i>
-------------------	--

Description

This function presents values of the relative price and/or quantity dissimilarity measure over time.

Usage

```
dissimilarity_fig(
  data,
  start,
  end,
  type = "p",
  benchmark = "end",
  figure = TRUE
)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. '2019-03'.
end	The research period (as character) limited to the year and month, e.g. '2019-07'.
type	The parameter indicates what type of dissimilarity measure is to be calculated. Possible values of the type parameter are: p (for the price dissimilarity measure calculation), q (for the quantity dissimilarity measure calculation) or pq (for the dSPQ measure calculation, i.e. the measure of relative price and quantity dissimilarity - see References).
benchmark	The benchmark period (as character) limited to the year and month, e.g. '2019-07'.
figure	A logical parameter indicating the resulting object. If it is TRUE, the function presents the above-mentioned dissimilarities over time via a figure. Otherwise, the function returns a dataframe.

Value

This function presents values of the relative price and/or quantity dissimilarity measure over time. The user can choose a benchmark period (defined by benchmark) and the type of dissimilarity measure is to be calculated (defined by type). The obtained results of dissimilarities over time can be presented in a dataframe form or via a figure (the default value of figure is TRUE, which results in a figure).

References

Diewert, E. (2020). *The Chain Drift Problem and Multilateral Indexes*. Chapter 6 in: Consumer Price Index Theory (draft)

Examples

```
dissimilarity_fig(milk, start="2018-12",end="2019-12",type="q",figure=FALSE)
dissimilarity_fig(milk, start="2018-12",end="2019-12",type="pq",benchmark="start")
```

drobisch

Calculating the bilateral Drobisch price index

Description

This function returns a value (or vector of values) of the bilateral Drobisch price index.

Usage

```
drobisch(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start,end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the bilateral Drobisch price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Drobisch, M. W. (1871). *Ueber einige Einwurfe gegen die in diesen Jahrbuchern veröffentlichte neue Methode, die Veränderungen der Waarenpreise und des Geldwerths zu berechnen*. Jahrbucher für Nationalökonomie und Statistik, Vol. 16, s. 416-427.

(2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Von der Lippe, P. (2007). *Index Theory and Price Statistics*. Peter Lang: Berlin, Germany.

Examples

```
drobisch(sugar, start="2018-12", end="2019-12")
drobisch(milk, start="2018-12", end="2020-01", interval=TRUE)
```

dutot	<i>Calculating the unweighted Dutot price index</i>
-------	---

Description

This function returns a value (or vector of values) of the unweighted bilateral Dutot price index.

Usage

```
dutot(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric) and prodID (as numeric, factor or character). A column quantities (as positive numeric) is also needed because this function uses unit values as monthly prices.
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start,end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the unweighted bilateral Dutot price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Dutot, C. F., (1738). *Reflexions Politiques sur les Finances et le Commerce*. The Hague: Les Freres Vaillant et Nicolas Prevost, Vol. 1.

(2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Examples

```
dutot(sugar, start="2018-12", end="2019-12")
dutot(milk, start="2018-12", end="2020-01", interval=TRUE)
```

final_index

The most general package function to compute the price dynamics

Description

This function returns a value or values of the selected (final) price index taking into consideration aggregation over product subgroups and/or over outlets.

Usage

```
final_index(
  datasets = list(),
  start,
  end,
  formula = "fisher",
  window = 13,
  splice = "movement",
  base = start,
  sigma = 0.7,
  aggrret = "tornqvist",
  aggrsets = "tornqvist",
  interval = FALSE
)
```

Arguments

datasets	The user's list of data frames with subgroups of sold products. Each data frame must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric), prodID (as numeric, factor or character) and retID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
formula	The character string indicating the (final or main) price index formula is to be calculated. To see available options please use the link: PriceIndices .

window	The length of the time window if the multilateral index is selected (as positive integer: typically multilateral methods are based on the 13-month time window and thus the default value is 13).
splice	A character string indicating the splicing method (if the multilateral splicing index is selected). Available options are: "movement", "window", "half", "mean" and also "window_published", "half_published" and "mean_published".
base	The prior period used in the Young- or Lowe-type price indices (as character) limited to the year and month, e.g. "2020-01".
sigma	The elasticity of substitution parameter used in the Lloyd-Moulton and AG Mean indices (as numeric).
aggrret	A character string indicating the formula for aggregation over outlets (retailer sale points). Available options are: "none", "laspeyres", "paasche", "geolaspeyres", "geopaasche", "fisher", "tornqvist", "arithmetic" and "geometric". The first option means that there is no aggregating over outlets. The last two options mean unweighted methods of aggregating, i.e. the arithmetic or geometric mean is used.
aggrsets	A character string indicating the formula for aggregation over product subgroups. Available options are: "none", "laspeyres", "paasche", "geolaspeyres", "geopaasche", "fisher", "tornqvist", "arithmetic" and "geometric". The first option means that there is no aggregating over product subgroups. The last two options mean unweighted methods of aggregating, i.e. the arithmetic or geometric mean is used.
interval	A logical value indicating whether the function is to provide the price index comparing the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be presented (the fixed base month is defined by start).

Value

This function returns a value or values of the selected (final) price index taking into consideration aggregation over product subgroups and/or over outlets (retailer sale points defined in `retID` column). To be more precise: if both types of aggregation are selected, then for each subgroup of products and for each outlet (point of sale) price indices are calculated separately and then aggregated (according to the aggregation methods indicated) to the form of the final price index. If the `interval` parameter is set to `TRUE` then it returns a data frame with two columns: dates and final index values (after optional aggregating). Please note that different index formulas may use different time intervals (or time periods) for calculations and each time, aggregation over outlets is done for the set of `retIDs` being available during the whole considered time interval.

Examples

```
final_index(datasets=list(milk),start="2018-12",end="2020-02",
formula="walsh",aggrret="paasche",aggrsets="none")
## defining two subgroups of milk
g1<-dplyr::filter(milk, milk$description=="full-fat milk UHT")
g2<-dplyr::filter(milk, milk$description=="low-fat milk UHT")
## Final price index calculations (for the whole time interval)
## with aggregating over subgroups g1 and g2 and over outlets
```

```
## Please note that the default value (formula) for aggregating over outlets is "tornqvist"
final_index(datasets=list(g1,g2), start="2018-12",
end="2019-12",formula="fisher",aggrsets="geometric",interval=TRUE)
```

final_index2

The most general package function to compute the price dynamics

Description

This function returns a value or values of the selected (final) price index taking into consideration aggregation over product subgroups and/or over outlets. Optionally, the function returns a data frame or a figure presenting calculated indices, i.e. the price index for the whole data set and price indices for product subgroups.

Usage

```
final_index2(
  data = data.frame(),
  by,
  all = FALSE,
  start,
  end,
  formula = "fisher",
  window = 13,
  splice = "movement",
  base = start,
  sigma = 0.7,
  aggrret = "tornqvist",
  aggrsets = "tornqvist",
  interval = FALSE,
  figure = FALSE
)
```

Arguments

data	The user's data frame with subgroups of sold products (see by parameter). Each data frame must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric), prodID (as numeric, factor or character) and retID (as numeric, factor or character). An additional column indicated via by parameter is also needed.
by	The column name indicating grouping variable, i.e. this column is used for creating subgroups of products.
all	A logical value indicating whether the the selected price index is to be calculated only for the whole set of products or also for created subgroups of products (then all is set to TRUE).
start	The base period (as character) limited to the year and month, e.g. "2019-12".

end	The research period (as character) limited to the year and month, e.g. "2020-04".
formula	The character string indicating the (final or main) price index formula is to be calculated. To see available options please use the link: PriceIndices .
window	The length of the time window if the multilateral index is selected (as positive integer: typically multilateral methods are based on the 13-month time window and thus the default value is 13).
splice	A character string indicating the splicing method (if the multilateral splicing index is selected). Available options are: "movement", "window", "half", "mean" and also "window_published", "half_published" and "mean_published".
base	The prior period used in the Young- or Lowe-type price indices (as character) limited to the year and month, e.g. "2020-01".
sigma	The elasticity of substitution parameter used in the Lloyed-Moulton and AG Mean indices (as numeric).
aggrret	A character string indicating the formula for aggregation over outlets (retailer sale points). Available options are: "none", "laspeyres", "paasche", "geolaspeyres", "geopaasche", "fisher", "tornqvist", "arithmetic" and "geometric". The first option means that there is no aggregating over outlets. The last two options mean unweighted methods of aggregating, i.e. the arithmetic or geometric mean is used.
aggrsets	A character string indicating the formula for aggregation over product subgroups. Available options are: "none", "laspeyres", "paasche", "geolaspeyres", "geopaasche", "fisher", "tornqvist", "arithmetic" and "geometric". The first option means that there is no aggregating over product subgroups. The last two options mean unweighted methods of aggregating, i.e. the arithmetic or geometric mean is used.
interval	A logical value indicating whether the function is to provide the price index comparing the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be presented (the fixed base month is defined by start).
figure	A logical value indicating whether the function returns a figure presenting all calculated indices (it works if all and interval are set to TRUE)

Value

This function returns a value or values of the selected (final) price index taking into consideration aggregation over product subgroups and/or over outlets (retailer sale points defined in retID column). Optionally, the function returns a data frame or a figure presenting calculated indices, i.e. the price index for the whole data set and price indices for product subgroups. To be more precise: if both types of aggregation are selected, then for each subgroup of products and for each outlet (point of sale) price indices are calculated separately and then aggregated (according to the aggregation methods indicated) to the form of the final price index. If the interval parameter is set to TRUE then it returns a data frame (or a figure) with dates and final index values (after optional aggregating). Please note that different index formulas may use different time intervals (or time periods) for calculations and each time, aggregation over outlets is done for the set of retIDs being available during the whole considered time interval.

Examples

```
final_index2(data=coffee, by="description",all=TRUE,start="2018-12",end="2019-12",
formula="fisher",interval=TRUE,aggrsets="laspeyres",aggrret="none",figure=FALSE)
final_index2(data=coffee, by="retID",all=TRUE,start="2018-12",end="2019-12",
formula="fisher",interval=TRUE,aggrsets="none",aggrret="none",figure=TRUE)
```

fisher

Calculating the bilateral Fisher price index

Description

This function returns a value (or vector of values) of the bilateral Fisher price index.

Usage

```
fisher(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start,end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the bilateral Fisher price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Fisher, I. (1922). *The Making of Index Numbers*. Boston: Houghton Mifflin.
 (2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Examples

```
fisher(sugar, start="2018-12", end="2019-12")
fisher(milk, start="2018-12", end="2020-01", interval=TRUE)
```

geary_khamis

Calculating the bilateral Geary-Khamis price index

Description

This function returns a value (or vector of values) of the bilateral Geary-Khamis price index.

Usage

```
geary_khamis(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the bilateral Geary-Khamis price index depending on the interval parameter (please use [gk](#) function to calculate the multilateral Geary-Khamis price index). If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Geary, R. G. (1958). *A Note on Comparisons of Exchange Rates and Purchasing Power between Countries*. Journal of the Royal Statistical Society, Series A, 121, 97-99.

Khamis, S. H. (1970). *Properties and Conditions for the Existence of a new Type of Index Number*. Sankhya Series B32, 81-98.

(2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Von der Lippe, P. (2007). *Index Theory and Price Statistics*. Peter Lang: Berlin, Germany.

Examples

```
geary_khamis(sugar, start="2018-12", end="2019-12")
geary_khamis(milk, start="2018-12", end="2020-01", interval=TRUE)
```

geks

Calculating the multilateral GEKS price index

Description

This function returns a value of the multilateral GEKS price index (to be more precise: the GEKS index based on the Fisher formula).

Usage

```
geks(data, start, end, wstart = start, window = 13)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
wstart	The beginning of the time interval (which is used by multilateral methods) limited to the year and month, e.g. "2020-01".
window	The length of the time window (as positive integer: typically multilateral methods are based on the 13-month time window).

Value

This function returns a value of the multilateral GEKS price index (to be more precise: the GEKS index based on the Fisher formula) which considers the time window defined by `wstart` and `window` parameters. It measures the price dynamics by comparing period end to period start (both `start` and `end` must be inside the considered time window). To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Gini, C. (1931). *On the Circular Test of Index Numbers*. *Metron* 9:9, 3-24.
- Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. *Statisztikai Szemle* 42, 507-518.
- Szulc, B. (1983). *Linking Price Index Numbers*. In: *Price Level Measurement*, W. E. Diewert and C. Montmarquette (eds.), 537-566.

Examples

```
geks(milk, start="2019-01", end="2019-08", window=10)
geks(milk, start="2018-12", end="2019-12")
```

geksaqi

Calculating the multilateral GEKS-AQI price index

Description

This function returns a value of the multilateral GEKS-AQI price index (to be more precise: the GEKS index based on the asynchronous quality adjusted price index formula).

Usage

```
geksaqi(data, start, end, wstart = start, window = 13)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
wstart	The beginning of the time interval (which is used by multilateral methods) limited to the year and month, e.g. "2020-01".
window	The length of the time window (as positive integer: typically multilateral methods are based on the 13-month time window).

Value

This function returns a value of the multilateral GEKS-AQI price index (to be more precise: the GEKS index based on the asynchronous quality adjusted price index formula) which considers the time window defined by wstart and window parameters. It measures the price dynamics by comparing period end to period start (both start and end must be inside the considered time window). To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.

Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.

Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.

Examples

```
geksaqi(milk, start="2019-01", end="2019-08", window=10)
geksaqi(milk, start="2018-12", end="2019-12")
```

geksaqi_fbew	<i>Extending the multilateral GEKS-AQI price index by using the FBEW method.</i>
--------------	--

Description

This function returns a value of the multilateral GEKS-AQI price index extended by using the FBEW (Fixed Base Monthly Expanding Window) method.

Usage

```
geksaqi_fbew(data, start, end)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".

Value

This function returns a value of the multilateral GEKS-AQI price index (the GEKS index based on the asynchronous quality adjusted price index formula) extended by using the FBEW (Fixed Base Monthly Expanding Window) method. The FBEW method uses a time window with a fixed base month every year (December). The window is enlarged every month with one month in order to include information from a new month. The full window length (13 months) is reached in December of each year. The function measures the price dynamics between periods end and start. The month of the start parameter must be December. If the distance between end and start exceeds 13 months, then internal Decembers play a role of chain-linking months. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Gini, C. (1931). *On the Circular Test of Index Numbers*. *Metron* 9:9, 3-24.
- Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. *Statisztikai Szemle* 42, 507-518.
- Szulc, B. (1983). *Linking Price Index Numbers*. In: *Price Level Measurement*, W. E. Diewert and C. Montmarquette (eds.), 537-566.
- Chessa, A.G. (2016). *A New Methodology for Processing Scanner Data in the Dutch CPI*. *Eurona* 1/2016, 49-69.

Examples

```
geksaqi_fbew(milk, start="2018-12", end="2019-08")
```

geksaqi_fbmw	<i>Extending the multilateral GEKS-AQI price index by using the FBMW method.</i>
--------------	--

Description

This function returns a value of the multilateral GEKS-AQI price index extended by using the FBMW (Fixed Base Moving Window) method.

Usage

```
geksaqi_fbmw(data, start, end)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".

Value

This function returns a value of the multilateral GEKS-AQI price index (the GEKS index based on the asynchronous quality adjusted price index formula) extended by using the FBMW (Fixed Base Moving Window) method. It measures the price dynamics between periods end and start and it uses a 13-month time window with a fixed base month taken as year(end)-1. If the distance between end and start exceeds 13 months, then internal Decembers play a role of chain-linking months. The month of the start parameter must be December. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product sub-groups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.
- Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.
- Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.
- Lamboray, C.(2017). *The Geary Khamis index and the Lehr index: how much do they differ?* Paper presented at the 15th Ottawa Group meeting, 10-12 May 2017, Elville am Rhein, Germany.

Examples

```
geksaqi_fbmw(milk, start="2019-12", end="2020-04")
```

geksaqi_splice	<i>Extending the multilateral GEKS-AQI price index by using window splicing methods.</i>
----------------	--

Description

This function returns a value (or values) of the multilateral GEKS-AQI price index extended by using window splicing methods. Available splicing methods are: movement splice, window splice, half splice, mean splice and their additional variants: window splice on published indices (WISP), half splice on published indices (HASP) and mean splice on published indices (see References).

Usage

```
geksaqi_splice(
  data,
  start,
  end,
  window = 13,
  splice = "movement",
  interval = FALSE
)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
window	The length of the time window (as positive integer: typically multilateral methods are based on the 13-month time window).

splice	A character string indicating the splicing method. Available options are: "movement", "window", "half", "mean", "window_published", "half_published", "mean_published".
interval	A logical value indicating whether the function is to provide the price index comparing the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base multilateral indices are to be presented (the fixed base month is defined by start).

Value

This function returns a value or values (depending on interval parameter) of the multilateral GEKS-AQI price index (the GEKS index based on the asynchronous quality adjusted price index formula) extended by using window splicing methods. Available splicing methods are: movement splice, window splice, half splice, mean splice and their additional variants: window splice on published indices (WISP), half splice on published indices (HASP) and mean splice on published indices (see References). The time window starts in start and should consist of at least two months. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Chessa, A. G. (2019). *A Comparison of Index Extension Methods for Multilateral Methods*. Paper presented at the 16th Meeting of the Ottawa Group on Price Indices, 8-10 May 2019, Rio de Janeiro, Brazil.
- de Haan, J., van der Grient, H.A. (2011). *Eliminating chain drift in price indexes based on scanner data*. Journal of Econometrics, 161, 36-46.
- Krsinich, F. (2014). *The FEWS Index: Fixed Effects with a Window Splice? Non-Revisable Quality-Adjusted Price Indices with No Characteristic Information*. Paper presented at the UNECE-ILO Meeting of the Group of Experts on Consumer Price Indices, 2-4 May 2016, Geneva, Switzerland.
- de Haan, J.(2015). *A Framework for Large Scale Use of Scanner Data in the Dutch CPI*. Paper presented at the 14th Ottawa Group meeting, Tokyo, Japan.
- Diewert, W.E., and Fox, K.J. (2017). *Substitution Bias in Multilateral Methods for CPI Construction using Scanner Data*. Discussion paper 17-02, Vancouver School of Economics, The University of British Columbia, Vancouver, Canada.

Examples

```
geksaqi_splice(milk, start="2018-12", end="2020-02",splice="half")
geksaqi_splice(milk, start="2018-12", end="2020-02",window=10,interval=TRUE)
```

geksaqu

*Calculating the multilateral GEKS-AQU price index***Description**

This function returns a value of the multilateral GEKS-AQU price index (to be more precise: the GEKS index based on the asynchronous quality adjusted unit value formula).

Usage

```
geksaqu(data, start, end, wstart = start, window = 13)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
wstart	The beginning of the time interval (which is used by multilateral methods) limited to the year and month, e.g. "2020-01".
window	The length of the time window (as positive integer: typically multilateral methods are based on the 13-month time window).

Value

This function returns a value of the multilateral GEKS-AQU price index (to be more precise: the GEKS index based on the asynchronous quality adjusted unit value formula) which considers the time window defined by wstart and window parameters. It measures the price dynamics by comparing period end to period start (both start and end must be inside the considered time window). To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.
- Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.
- Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.

Examples

```
geksaqu(milk, start="2019-01", end="2019-08", window=10)
geksaqu(milk, start="2018-12", end="2019-12")
```

geksaqu_fbew	<i>Extending the multilateral GEKS-AQU price index by using the FBEW method.</i>
--------------	--

Description

This function returns a value of the multilateral GEKS-AQU price index extended by using the FBEW (Fixed Base Monthly Expanding Window) method.

Usage

```
geksaqu_fbew(data, start, end)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".

Value

This function returns a value of the multilateral GEKS-AQU price index (the GEKS index based on the asynchronous quality adjusted unit value formula) extended by using the FBEW (Fixed Base Monthly Expanding Window) method. The FBEW method uses a time window with a fixed base month every year (December). The window is enlarged every month with one month in order to include information from a new month. The full window length (13 months) is reached in December of each year. The function measures the price dynamics between periods end and start. The month of the start parameter must be December. If the distance between end and start exceeds 13 months, then internal Decembers play a role of chain-linking months. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.

Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.

Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.

Chessa, A.G. (2016). *A New Methodology for Processing Scanner Data in the Dutch CPI*. Eurona 1/2016, 49-69.

Examples

```
geksaqu_fbew(milk, start="2018-12", end="2019-08")
```

geksaqu_fbmw	<i>Extending the multilateral GEKS-AQU price index by using the FBMW method.</i>
--------------	--

Description

This function returns a value of the multilateral GEKS-AQU price index extended by using the FBMW (Fixed Base Moving Window) method.

Usage

```
geksaqu_fbmw(data, start, end)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".

Value

This function returns a value of the multilateral GEKS-AQU price index (the GEKS index based on the asynchronous quality adjusted unit value formula) extended by using the FBMW (Fixed Base Moving Window) method. It measures the price dynamics between periods end and start and it uses a 13-month time window with a fixed base month taken as year(end)-1. If the distance between end and start exceeds 13 months, then internal Decembers play a role of chain-linking months. The month of the start parameter must be December. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product sub-groups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.
- Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.
- Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.
- Lamboray, C.(2017). *The Geary Khamis index and the Lehr index: how much do they differ?* Paper presented at the 15th Ottawa Group meeting, 10-12 May 2017, Elville am Rhein, Germany.

Examples

```
geksaqu_fbmw(milk, start="2019-12", end="2020-04")
```

geksaqu_splice	<i>Extending the multilateral GEKS-AQU price index by using window splicing methods.</i>
----------------	--

Description

This function returns a value (or values) of the multilateral GEKS-AQU price index extended by using window splicing methods. Available splicing methods are: movement splice, window splice, half splice, mean splice and their additional variants: window splice on published indices (WISP), half splice on published indices (HASP) and mean splice on published indices (see References).

Usage

```
geksaqu_splice(
  data,
  start,
  end,
  window = 13,
  splice = "movement",
  interval = FALSE
)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
window	The length of the time window (as positive integer: typically multilateral methods are based on the 13-month time window).

splice	A character string indicating the splicing method. Available options are: "movement", "window", "half", "mean", "window_published", "half_published", "mean_published".
interval	A logical value indicating whether the function is to provide the price index comparing the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base multilateral indices are to be presented (the fixed base month is defined by start).

Value

This function returns a value or values (depending on interval parameter) of the multilateral GEKS-AQU price index (the GEKS index based on the asynchronous quality adjusted unit value formula) extended by using window splicing methods. Available splicing methods are: movement splice, window splice, half splice, mean splice and their additional variants: window splice on published indices (WISP), half splice on published indices (HASP) and mean splice on published indices (see References). The time window starts in start and should consist of at least two months. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Chessa, A. G. (2019). *A Comparison of Index Extension Methods for Multilateral Methods*. Paper presented at the 16th Meeting of the Ottawa Group on Price Indices, 8-10 May 2019, Rio de Janeiro, Brazil.
- de Haan, J., van der Grient, H.A. (2011). *Eliminating chain drift in price indexes based on scanner data*. Journal of Econometrics, 161, 36-46.
- Krsinich, F. (2014). *The FEWS Index: Fixed Effects with a Window Splice? Non-Revisable Quality-Adjusted Price Indices with No Characteristic Information*. Paper presented at the UNECE-ILO Meeting of the Group of Experts on Consumer Price Indices, 2-4 May 2016, Geneva, Switzerland.
- de Haan, J.(2015). *A Framework for Large Scale Use of Scanner Data in the Dutch CPI*. Paper presented at the 14th Ottawa Group meeting, Tokyo, Japan.
- Diewert, W.E., and Fox, K.J. (2017). *Substitution Bias in Multilateral Methods for CPI Construction using Scanner Data*. Discussion paper 17-02, Vancouver School of Economics, The University of British Columbia, Vancouver, Canada.

Examples

```
geksaqu_splice(milk, start="2018-12", end="2020-02",splice="half")
geksaqu_splice(milk, start="2018-12", end="2020-02",window=10,interval=TRUE)
```


geksgaqi

*Calculating the multilateral GEKS-GAQI price index***Description**

This function returns a value of the multilateral GEKS-GAQI price index (to be more precise: the GEKS index based on the geometric asynchronous quality adjusted price index formula).

Usage

```
geksgaqi(data, start, end, wstart = start, window = 13)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
wstart	The beginning of the time interval (which is used by multilateral methods) limited to the year and month, e.g. "2020-01".
window	The length of the time window (as positive integer: typically multilateral methods are based on the 13-month time window).

Value

This function returns a value of the multilateral GEKS-GAQI price index (to be more precise: the GEKS index based on the geometric asynchronous quality adjusted price index formula) which considers the time window defined by wstart and window parameters. It measures the price dynamics by comparing period end to period start (both start and end must be inside the considered time window). To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.
- Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.
- Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.

Examples

```
geksgaqi(milk, start="2019-01", end="2019-08", window=10)
geksgaqi(milk, start="2018-12", end="2019-12")
```

geksgaqi_fbew	<i>Extending the multilateral GEKS-GAQI price index by using the FBEW method.</i>
---------------	---

Description

This function returns a value of the multilateral GEKS-GAQI price index extended by using the FBEW (Fixed Base Monthly Expanding Window) method.

Usage

```
geksgaqi_fbew(data, start, end)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".

Value

This function returns a value of the multilateral GEKS-GAQI price index (the GEKS index based on the geometric asynchronous quality adjusted price index formula) extended by using the FBEW (Fixed Base Monthly Expanding Window) method. The FBEW method uses a time window with a fixed base month every year (December). The window is enlarged every month with one month in order to include information from a new month. The full window length (13 months) is reached in December of each year. The function measures the price dynamics between periods end and start. The month of the start parameter must be December. If the distance between end and start exceeds 13 months, then internal Decembers play a role of chain-linking months. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.
- Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.
- Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.
- Chessa, A.G. (2016). *A New Methodology for Processing Scanner Data in the Dutch CPI*. Eurona 1/2016, 49-69.

Examples

```
geksgaqi_fbew(milk, start="2018-12", end="2019-08")
```

geksgaqi_fbmw	<i>Extending the multilateral GEKS-GAQI price index by using the FBMW method.</i>
---------------	---

Description

This function returns a value of the multilateral GEKS-GAQI price index extended by using the FBMW (Fixed Base Moving Window) method.

Usage

```
geksgaqi_fbmw(data, start, end)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".

Value

This function returns a value of the multilateral GEKS-GAQI price index (the GEKS index based on the geometric asynchronous quality adjusted price index formula) extended by using the FBMW (Fixed Base Moving Window) method. It measures the price dynamics between periods end and start and it uses a 13-month time window with a fixed base month taken as year(end)-1. If the distance between end and start exceeds 13 months, then internal Decembers play a role of chain-linking months. The month of the start parameter must be December. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.
- Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.
- Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.
- Lamboray, C.(2017). *The Geary Khamis index and the Lehr index: how much do they differ?* Paper presented at the 15th Ottawa Group meeting, 10-12 May 2017, Elville am Rhein, Germany.

Examples

```
geksgaqi_fbmw(milk, start="2019-12", end="2020-04")
```

geksgaqi_splice	<i>Extending the multilateral GEKS-GAQI price index by using window splicing methods.</i>
-----------------	---

Description

This function returns a value (or values) of the multilateral GEKS-GAQI price index extended by using window splicing methods. Available splicing methods are: movement splice, window splice, half splice, mean splice and their additional variants: window splice on published indices (WISP), half splice on published indices (HASP) and mean splice on published indices (see References).

Usage

```
geksgaqi_splice(
  data,
  start,
  end,
  window = 13,
  splice = "movement",
  interval = FALSE
)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
window	The length of the time window (as positive integer: typically multilateral methods are based on the 13-month time window).

splice	A character string indicating the splicing method. Available options are: "movement", "window", "half", "mean", "window_published", "half_published", "mean_published".
interval	A logical value indicating whether the function is to provide the price index comparing the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base multilateral indices are to be presented (the fixed base month is defined by start).

Value

This function returns a value or values (depending on interval parameter) of the multilateral GEKS-GAQI price index (the GEKS index based on the geometric asynchronous quality adjusted price index formula) extended by using window splicing methods. Available splicing methods are: movement splice, window splice, half splice, mean splice and their additional variants: window splice on published indices (WISP), half splice on published indices (HASP) and mean splice on published indices (see References). The time window starts in start and should consist of at least two months. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Chessa, A. G. (2019). *A Comparison of Index Extension Methods for Multilateral Methods*. Paper presented at the 16th Meeting of the Ottawa Group on Price Indices, 8-10 May 2019, Rio de Janeiro, Brazil.
- de Haan, J., van der Grient, H.A. (2011). *Eliminating chain drift in price indexes based on scanner data*. Journal of Econometrics, 161, 36-46.
- Krsinich, F. (2014). *The FEWS Index: Fixed Effects with a Window Splice? Non-Revisable Quality-Adjusted Price Indices with No Characteristic Information*. Paper presented at the UNECE-ILO Meeting of the Group of Experts on Consumer Price Indices, 2-4 May 2016, Geneva, Switzerland.
- de Haan, J.(2015). *A Framework for Large Scale Use of Scanner Data in the Dutch CPI*. Paper presented at the 14th Ottawa Group meeting, Tokyo, Japan.
- Diewert, W.E., and Fox, K.J. (2017). *Substitution Bias in Multilateral Methods for CPI Construction using Scanner Data*. Discussion paper 17-02, Vancouver School of Economics, The University of British Columbia, Vancouver, Canada.

Examples

```
geksgaqi_splice(milk, start="2018-12", end="2020-02", splice="half")
geksgaqi_splice(milk, start="2018-12", end="2020-02", window=10, interval=TRUE)
```

geksgl

*Calculating the multilateral GEKS-GL price index***Description**

This function returns a value of the multilateral GEKS-GL price index (to be more precise: the GEKS index based on the geometric Laspeyres formula).

Usage

```
geksgl(data, start, end, wstart = start, window = 13)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
wstart	The beginning of the time interval (which is used by multilateral methods) limited to the year and month, e.g. "2020-01".
window	The length of the time window (as positive integer: typically multilateral methods are based on the 13-month time window).

Value

This function returns a value of the multilateral GEKS-GL price index (to be more precise: the GEKS index based on the geometric Laspeyres formula) which considers the time window defined by wstart and window parameters. It measures the price dynamics by comparing period end to period start (both start and end must be inside the considered time window). To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.
- Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.
- Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.

Examples

```
geksgl(milk, start="2019-01", end="2019-08", window=10)
geksgl(milk, start="2018-12", end="2019-12")
```

geksgl_fbew	<i>Extending the multilateral GEKS-GL price index by using the FBEW method.</i>
-------------	---

Description

This function returns a value of the multilateral GEKS-GL price index extended by using the FBEW (Fixed Base Monthly Expanding Window) method.

Usage

```
geksgl_fbew(data, start, end)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".

Value

This function returns a value of the multilateral GEKS-GL price index (the GEKS index based on the geometric Laspeyres formula) extended by using the FBEW (Fixed Base Monthly Expanding Window) method. The FBEW method uses a time window with a fixed base month every year (December). The window is enlarged every month with one month in order to include information from a new month. The full window length (13 months) is reached in December of each year. The function measures the price dynamics between periods end and start. The month of the start parameter must be December. If the distance between end and start exceeds 13 months, then internal Decembers play a role of chain-linking months. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.

Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.

Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.

Chessa, A.G. (2016). *A New Methodology for Processing Scanner Data in the Dutch CPI*. Eurona 1/2016, 49-69.

Examples

```
geksgl_fbew(milk, start="2018-12", end="2019-08")
```

geksgl_fbmw	<i>Extending the multilateral GEKS-GL price index by using the FBMW method.</i>
-------------	---

Description

This function returns a value of the multilateral GEKS-GL price index extended by using the FBMW (Fixed Base Moving Window) method.

Usage

```
geksgl_fbmw(data, start, end)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".

Value

This function returns a value of the multilateral GEKS-GL price index (the GEKS index based on the geometric Laspeyres formula) extended by using the FBMW (Fixed Base Moving Window) method. It measures the price dynamics between periods end and start and it uses a 13-month time window with a fixed base month taken as year(end)-1. If the distance between end and start exceeds 13 months, then internal Decembers play a role of chain-linking months. The month of the start parameter must be December. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.
- Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.
- Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.
- Lamboray, C.(2017). *The Geary Khamis index and the Lehr index: how much do they differ?* Paper presented at the 15th Ottawa Group meeting, 10-12 May 2017, Elville am Rhein, Germany.

Examples

```
geksgl_fbmw(milk, start="2019-12", end="2020-04")
```

geksgl_splice	<i>Extending the multilateral GEKS-GL price index by using window splicing methods.</i>
---------------	---

Description

This function returns a value (or values) of the multilateral GEKS-GL price index extended by using window splicing methods. Available splicing methods are: movement splice, window splice, half splice, mean splice and their additional variants: window splice on published indices (WISP), half splice on published indices (HASP) and mean splice on published indices (see References).

Usage

```
geksgl_splice(
  data,
  start,
  end,
  window = 13,
  splice = "movement",
  interval = FALSE
)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
window	The length of the time window (as positive integer: typically multilateral methods are based on the 13-month time window).

splice	A character string indicating the splicing method. Available options are: "movement", "window", "half", "mean", "window_published", "half_published", "mean_published".
interval	A logical value indicating whether the function is to provide the price index comparing the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base multilateral indices are to be presented (the fixed base month is defined by start).

Value

This function returns a value or values (depending on interval parameter) of the multilateral GEKS-GL price index (the GEKS index based on the geometric Laspeyres formula) extended by using window splicing methods. Available splicing methods are: movement splice, window splice, half splice, mean splice and their additional variants: window splice on published indices (WISP), half splice on published indices (HASP) and mean splice on published indices (see References). The time window starts in start and should consist of at least two months. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Chessa, A. G. (2019). *A Comparison of Index Extension Methods for Multilateral Methods*. Paper presented at the 16th Meeting of the Ottawa Group on Price Indices, 8-10 May 2019, Rio de Janeiro, Brazil.
- de Haan, J., van der Grient, H.A. (2011). *Eliminating chain drift in price indexes based on scanner data*. Journal of Econometrics, 161, 36-46.
- Krsinich, F. (2014). *The FEWS Index: Fixed Effects with a Window Splice? Non-Revisable Quality-Adjusted Price Indices with No Characteristic Information*. Paper presented at the UNECE-ILO Meeting of the Group of Experts on Consumer Price Indices, 2-4 May 2016, Geneva, Switzerland.
- de Haan, J.(2015). *A Framework for Large Scale Use of Scanner Data in the Dutch CPI*. Paper presented at the 14th Ottawa Group meeting, Tokyo, Japan.
- Diewert, W.E., and Fox, K.J. (2017). *Substitution Bias in Multilateral Methods for CPI Construction using Scanner Data*. Discussion paper 17-02, Vancouver School of Economics, The University of British Columbia, Vancouver, Canada.

Examples

```
geksgl_splice(milk, start="2018-12", end="2020-02",splice="half")
geksgl_splice(milk, start="2018-12", end="2020-02",window=10,interval=TRUE)
```

geksj	<i>Calculating the multilateral GEKS price index based on the Jevons formula (typical notation: GEKS-J)</i>
-------	---

Description

This function returns a value of the multilateral GEKS-J price index (to be more precise: the GEKS index based on the Jevons formula).

Usage

```
geksj(data, start, end, wstart = start, window = 13)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character). A column quantities is needed because this function uses unit values as monthly prices.
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
wstart	The beginning of the time interval (which is used by multilateral methods) limited to the year and month, e.g. "2020-01".
window	The length of the time window (as positive integer: typically multilateral methods are based on the 13-month time window).

Value

This function returns a value of the multilateral GEKS-J price index (to be more precise: the GEKS index based on the Jevons formula) which considers the time window defined by wstart and window parameters. It measures the price dynamics by comparing period end to period start (both start and end must be inside the considered time window). To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product sub-groups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.

Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.

Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.

Examples

```
geksj(milk, start="2019-01", end="2019-08", window=10)
geksj(milk, start="2018-12", end="2019-12")
```

geksj_fbew	<i>Extending the multilateral GEKS-J price index by using the FBEW method.</i>
------------	--

Description

This function returns a value of the multilateral GEKS-J price index (i.e. the GEKS price index based on the Jevons formula) extended by using the FBEW (Fixed Base Monthly Expanding Window) method.

Usage

```
geksj_fbew(data, start, end)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character). A column quantities is needed because this function uses unit values as monthly prices.
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".

Value

This function returns a value of the multilateral GEKS-J price index (i.e. the GEKS price index based on the Jevons formula) extended by using the FBEW (Fixed Base Monthly Expanding Window) method. The FBEW method uses a time window with a fixed base month every year (December). The window is enlarged every month with one month in order to include information from a new month. The full window length (13 months) is reached in December of each year. The function measures the price dynamics between periods end and start. The month of the start parameter must be December. If the distance between end and start exceeds 13 months, then internal Decembers play a role of chain-linking months. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.
- Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.
- Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.
- Chessa, A.G. (2016). *A New Methodology for Processing Scanner Data in the Dutch CPI*. Eurona 1/2016, 49-69.

Examples

```
geksj_fbew(milk, start="2018-12", end="2019-08")
```

geksj_fbmw	<i>Extending the multilateral GEKS-J price index by using the FBMW method.</i>
------------	--

Description

This function returns a value of the multilateral GEKS-J price index (i.e. the GEKS price index based on the Jevons formula) extended by using the FBMW (Fixed Base Moving Window) method.

Usage

```
geksj_fbmw(data, start, end)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character). A column quantities is needed because this function uses unit values as monthly prices.
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".

Value

This function returns a value of the multilateral GEKS-J price index (i.e. the GEKS price index based on the Jevons formula) extended by using the FBMW (Fixed Base Moving Window) method. It measures the price dynamics between periods end and start and it uses a 13-month time window with a fixed base month taken as year(end)-1. If the distance between end and start exceeds 13 months, then internal Decembers play a role of chain-linking months. The month of the start parameter must be December. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.
- Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.
- Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.
- Lamboray, C.(2017). *The Geary Khamis index and the Lehr index: how much do they differ?* Paper presented at the 15th Ottawa Group meeting, 10-12 May 2017, Elville am Rhein, Germany.

Examples

```
geksj_fbmw(milk, start="2019-12", end="2020-04")
```

geksj_splice	<i>Extending the multilateral GEKS-J price index by using window splicing methods.</i>
--------------	--

Description

This function returns a value (or values) of the multilateral GEKS-J price index (GEKS based on the Jevons formula) extended by using window splicing methods. Available splicing methods are: movement splice, window splice, half splice, mean splice and their additional variants: window splice on published indices (WISP), half splice on published indices (HASP) and mean splice on published indices (see References).

Usage

```
geksj_splice(
  data,
  start,
  end,
  window = 13,
  splice = "movement",
  interval = FALSE
)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character). A column quantities is needed because this function uses unit values as monthly prices.
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".

window	The length of the time window (as positive integer: typically multilateral methods are based on the 13-month time window).
splice	A character string indicating the splicing method. Available options are: "movement", "window", "half", "mean", "window_published", "half_published", "mean_published".
interval	A logical value indicating whether the function is to provide the price index comparing the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base multilateral indices are to be presented (the fixed base month is defined by start).

Value

This function returns a value or values (depending on interval parameter) of the multilateral GEKS-J price index extended by using window splicing methods. Available splicing methods are: movement splice, window splice, half splice, mean splice and their additional variants: window splice on published indices (WISP), half splice on published indices (HASP) and mean splice on published indices (see References). The time window starts in start and should consist of at least two months. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Chessa, A. G. (2019). *A Comparison of Index Extension Methods for Multilateral Methods*. Paper presented at the 16th Meeting of the Ottawa Group on Price Indices, 8-10 May 2019, Rio de Janeiro, Brazil.
- de Haan, J., van der Grient, H.A. (2011). *Eliminating chain drift in price indexes based on scanner data*. Journal of Econometrics, 161, 36-46.
- Krsinich, F. (2014). *The FEWS Index: Fixed Effects with a Window Splice? Non-Revisable Quality-Adjusted Price Indices with No Characteristic Information*. Paper presented at the UNECE-ILO Meeting of the Group of Experts on Consumer Price Indices, 2-4 May 2016, Geneva, Switzerland.
- de Haan, J.(2015). *A Framework for Large Scale Use of Scanner Data in the Dutch CPI*. Paper presented at the 14th Ottawa Group meeting, Tokyo, Japan.
- Diewert, W.E., and Fox, K.J. (2017). *Substitution Bias in Multilateral Methods for CPI Construction using Scanner Data*. Discussion paper 17-02, Vancouver School of Economics, The University of British Columbia, Vancouver, Canada.

Examples

```
geksj_splice(milk, start="2018-12", end="2020-02",splice="half")
geksj_splice(milk, start="2018-12", end="2020-02",window=10,interval=TRUE)
```

geksl

*Calculating the multilateral GEKS-L price index***Description**

This function returns a value of the multilateral GEKS-L price index (to be more precise: the GEKS index based on the Laspeyres formula).

Usage

```
geksl(data, start, end, wstart = start, window = 13)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
wstart	The beginning of the time interval (which is used by multilateral methods) limited to the year and month, e.g. "2020-01".
window	The length of the time window (as positive integer: typically multilateral methods are based on the 13-month time window).

Value

This function returns a value of the multilateral GEKS-L price index (to be more precise: the GEKS index based on the Laspeyres formula) which considers the time window defined by wstart and window parameters. It measures the price dynamics by comparing period end to period start (both start and end must be inside the considered time window). To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product sub-groups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.
- Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.
- Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.

Examples

```
geksl(milk, start="2019-01", end="2019-08",window=10)
geksl(milk, start="2018-12", end="2019-12")
```

geksl_fbew	<i>Extending the multilateral GEKS-L price index by using the FBEW method.</i>
------------	--

Description

This function returns a value of the multilateral GEKS-L price index extended by using the FBEW (Fixed Base Monthly Expanding Window) method.

Usage

```
geksl_fbew(data, start, end)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".

Value

This function returns a value of the multilateral GEKS-L price index (the GEKS index based on the Laspeyres formula) extended by using the FBEW (Fixed Base Monthly Expanding Window) method. The FBEW method uses a time window with a fixed base month every year (December). The window is enlarged every month with one month in order to include information from a new month. The full window length (13 months) is reached in December of each year. The function measures the price dynamics between periods end and start. The month of the start parameter must be December. If the distance between end and start exceeds 13 months, then internal Decembers play a role of chain-linking months. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.

Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.

Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.

Chessa, A.G. (2016). *A New Methodology for Processing Scanner Data in the Dutch CPI*. Eurona 1/2016, 49-69.

Examples

```
geksl_fbmw(milk, start="2018-12", end="2019-08")
```

geksl_fbmw	<i>Extending the multilateral GEKS-L price index by using the FBMW method.</i>
------------	--

Description

This function returns a value of the multilateral GEKS-L price index extended by using the FBMW (Fixed Base Moving Window) method.

Usage

```
geksl_fbmw(data, start, end)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".

Value

This function returns a value of the multilateral GEKS-L price index (the GEKS index based on the Laspeyres formula) extended by using the FBMW (Fixed Base Moving Window) method. It measures the price dynamics between periods end and start and it uses a 13-month time window with a fixed base month taken as year(end)-1. If the distance between end and start exceeds 13 months, then internal Decembers play a role of chain-linking months. The month of the start parameter must be December. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.
- Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.
- Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.
- Lamboray, C.(2017). *The Geary Khamis index and the Lehr index: how much do they differ?* Paper presented at the 15th Ottawa Group meeting, 10-12 May 2017, Elville am Rhein, Germany.

Examples

```
geksl_fbmw(milk, start="2019-12", end="2020-04")
```

geksl_splice	<i>Extending the multilateral GEKS-L price index by using window splicing methods.</i>
--------------	--

Description

This function returns a value (or values) of the multilateral GEKS-L price index extended by using window splicing methods. Available splicing methods are: movement splice, window splice, half splice, mean splice and their additional variants: window splice on published indices (WISP), half splice on published indices (HASP) and mean splice on published indices (see References).

Usage

```
geksl_splice(
  data,
  start,
  end,
  window = 13,
  splice = "movement",
  interval = FALSE
)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
window	The length of the time window (as positive integer: typically multilateral methods are based on the 13-month time window).

splice	A character string indicating the splicing method. Available options are: "movement", "window", "half", "mean", "window_published", "half_published", "mean_published".
interval	A logical value indicating whether the function is to provide the price index comparing the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base multilateral indices are to be presented (the fixed base month is defined by start).

Value

This function returns a value or values (depending on interval parameter) of the multilateral GEKS-L price index (the GEKS index based on the Laspeyres formula) extended by using window splicing methods. Available splicing methods are: movement splice, window splice, half splice, mean splice and their additional variants: window splice on published indices (WISP), half splice on published indices (HASP) and mean splice on published indices (see References). The time window starts in start and should consist of at least two months. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product sub-groups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Chessa, A. G. (2019). *A Comparison of Index Extension Methods for Multilateral Methods*. Paper presented at the 16th Meeting of the Ottawa Group on Price Indices, 8-10 May 2019, Rio de Janeiro, Brazil.
- de Haan, J., van der Grient, H.A. (2011). *Eliminating chain drift in price indexes based on scanner data*. Journal of Econometrics, 161, 36-46.
- Krsinich, F. (2014). *The FEWS Index: Fixed Effects with a Window Splice? Non-Revisable Quality-Adjusted Price Indices with No Characteristic Information*. Paper presented at the UNECE-ILO Meeting of the Group of Experts on Consumer Price Indices, 2-4 May 2016, Geneva, Switzerland.
- de Haan, J.(2015). *A Framework for Large Scale Use of Scanner Data in the Dutch CPI*. Paper presented at the 14th Ottawa Group meeting, Tokyo, Japan.
- Diewert, W.E., and Fox, K.J. (2017). *Substitution Bias in Multilateral Methods for CPI Construction using Scanner Data*. Discussion paper 17-02, Vancouver School of Economics, The University of British Columbia, Vancouver, Canada.

Examples

```
geksl_splice(milk, start="2018-12", end="2020-02", splice="half")
geksl_splice(milk, start="2018-12", end="2020-02", window=10, interval=TRUE)
```

geksw	<i>Calculating the multilateral GEKS price index based on the Walsh formula (GEKS-W)</i>
-------	--

Description

This function returns a value of the multilateral GEKS-W price index, i.e. the GEKS price index based on the superlative Walsh index formula.

Usage

```
geksw(data, start, end, wstart = start, window = 13)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
wstart	The beginning of the time interval (which is used by multilateral methods) limited to the year and month, e.g. "2020-01".
window	The length of the time window (as positive integer: typically multilateral methods are based on the 13-month time window).

Value

This function returns a value of the multilateral GEKS-W price index (to be more precise: the GEKS index based on the Walsh formula) which considers the time window defined by wstart and window parameters. It measures the price dynamics by comparing period end to period start (both start and end must be inside the considered time window). To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product sub-groups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Walsh, C. M. (1901). *The Measurement of General Exchange Value*. The MacMillan Company, New York.
- Gini, C. (1931). *On the Circular Test of Index Numbers*. *Metron* 9:9, 3-24.
- Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. *Statisztikai Szemle* 42, 507-518.
- Szulc, B. (1983). *Linking Price Index Numbers*. In: *Price Level Measurement*, W. E. Diewert and C. Montmarquette (eds.), 537-566.

Examples

```
geksw(milk, start="2019-01", end="2019-08",window=10)
geksw(milk, start="2018-12", end="2019-12")
```

geksw_fbew	<i>Extending the multilateral GEKS-W price index by using the FBEW method.</i>
------------	--

Description

This function returns a value of the multilateral GEKS-W price index (GEKS based on the Walsh formula) extended by using the FBEW (Fixed Base Monthly Expanding Window) method.

Usage

```
geksw_fbew(data, start, end)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".

Value

This function returns a value of the multilateral GEKS-W price index extended by using the FBEW (Fixed Base Monthly Expanding Window) method. The FBEW method uses a time window with a fixed base month every year (December). The window is enlarged every month with one month in order to include information from a new month. The full window length (13 months) is reached in December of each year. The function measures the price dynamics between periods end and start. The month of the start parameter must be December. If the distance between end and start exceeds 13 months, then internal Decembers play a role of chain-linking months. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Walsh, C. M. (1901). *The Measurement of General Exchange Value*. The MacMillan Company, New York.

Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.

Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.

Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.

Chessa, A.G. (2016). *A New Methodology for Processing Scanner Data in the Dutch CPI*. Eurona 1/2016, 49-69.

Examples

```
geksw_fbew(milk, start="2018-12", end="2019-08")
```

geksw_fbmw	<i>Extending the multilateral GEKS-W price index by using the FBMW method.</i>
------------	--

Description

This function returns a value of the multilateral GEKS-W price index (GEKS based on the Walsh formula) extended by using the FBMW (Fixed Base Moving Window) method.

Usage

```
geksw_fbmw(data, start, end)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".

Value

This function returns a value of the multilateral GEKS-W price index extended by using the FBMW (Fixed Base Moving Window) method. It measures the price dynamics between periods end and start and it uses a 13-month time window with a fixed base month taken as year(end)-1. If the distance between end and start exceeds 13 months, then internal Decembers play a role of chain-linking months. The month of the start parameter must be December. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Walsh, C. M. (1901). *The Measurement of General Exchange Value*. The MacMillan Company, New York.
- Gini, C. (1931). *On the Circular Test of Index Numbers*. *Metron* 9:9, 3-24.
- Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. *Statisztikai Szemle* 42, 507-518.
- Szulc, B. (1983). *Linking Price Index Numbers*. In: *Price Level Measurement*, W. E. Diewert and C. Montmarquette (eds.), 537-566.
- Lamboray, C.(2017). *The Geary Khamis index and the Lehr index: how much do they differ?* Paper presented at the 15th Ottawa Group meeting, 10-12 May 2017, Elville am Rhein, Germany.

Examples

```
geksw_fbmw(milk, start="2019-12", end="2020-04")
```

geksw_splice	<i>Extending the multilateral GEKS-W price index by using window splicing methods.</i>
--------------	--

Description

This function returns a value (or values) of the multilateral GEKS-W price index (GEKS based on the Walsh formula) extended by using window splicing methods. Available splicing methods are: movement splice, window splice, half splice, mean splice and their additional variants: window splice on published indices (WISP), half splice on published indices (HASP) and mean splice on published indices (see References).

Usage

```
geksw_splice(
  data,
  start,
  end,
  window = 13,
  splice = "movement",
  interval = FALSE
)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".

end	The research period (as character) limited to the year and month, e.g. "2020-04".
window	The length of the time window (as positive integer: typically multilateral methods are based on the 13-month time window).
splice	A character string indicating the splicing method. Available options are: "movement", "window", "half", "mean", "window_published", "half_published", "mean_published".
interval	A logical value indicating whether the function is to provide the price index comparing the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base multilateral indices are to be presented (the fixed base month is defined by start).

Value

This function returns a value or values (depending on interval parameter) of the multilateral GEKS-W price index extended by using window splicing methods. Available splicing methods are: movement splice, window splice, half splice, mean splice and their additional variants: window splice on published indices (WISP), half splice on published indices (HASP) and mean splice on published indices (see References). The time window starts in start and should consist of at least two months. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Chessa, A. G. (2019). *A Comparison of Index Extension Methods for Multilateral Methods*. Paper presented at the 16th Meeting of the Ottawa Group on Price Indices, 8-10 May 2019, Rio de Janeiro, Brazil.
- de Haan, J., van der Grient, H.A. (2011). *Eliminating chain drift in price indexes based on scanner data*. Journal of Econometrics, 161, 36-46.
- Krsinich, F. (2014). *The FEWS Index: Fixed Effects with a Window Splice? Non-Revisable Quality-Adjusted Price Indices with No Characteristic Information*. Paper presented at the UNECE-ILO Meeting of the Group of Experts on Consumer Price Indices, 2-4 May 2016, Geneva, Switzerland.
- de Haan, J.(2015). *A Framework for Large Scale Use of Scanner Data in the Dutch CPI*. Paper presented at the 14th Ottawa Group meeting, Tokyo, Japan.
- Diewert, W.E., and Fox, K.J. (2017). *Substitution Bias in Multilateral Methods for CPI Construction using Scanner Data*. Discussion paper 17-02, Vancouver School of Economics, The University of British Columbia, Vancouver, Canada.

Examples

```
geksw_splice(milk, start="2018-12", end="2020-02",splice="half")
geksw_splice(milk, start="2018-12", end="2020-02",window=10,interval=TRUE)
```

geks_fbew	<i>Extending the multilateral GEKS price index by using the FBEW method.</i>
-----------	--

Description

This function returns a value of the multilateral GEKS price index extended by using the FBEW (Fixed Base Monthly Expanding Window) method.

Usage

```
geks_fbew(data, start, end)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".

Value

This function returns a value of the multilateral GEKS price index extended by using the FBEW (Fixed Base Monthly Expanding Window) method. The FBEW method uses a time window with a fixed base month every year (December). The window is enlarged every month with one month in order to include information from a new month. The full window length (13 months) is reached in December of each year. The function measures the price dynamics between periods end and start. The month of the start parameter must be December. If the distance between end and start exceeds 13 months, then internal Decembers play a role of chain-linking months. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.
- Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.
- Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.
- Chessa, A.G. (2016). *A New Methodology for Processing Scanner Data in the Dutch CPI*. Eurona 1/2016, 49-69.

Examples

```
geks_fbew(milk, start="2018-12", end="2019-08")
```

geks_fbmw	<i>Extending the multilateral GEKS price index by using the FBMW method.</i>
-----------	--

Description

This function returns a value of the multilateral GEKS price index extended by using the FBMW (Fixed Base Moving Window) method.

Usage

```
geks_fbmw(data, start, end)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".

Value

This function returns a value of the multilateral GEKS price index extended by using the FBMW (Fixed Base Moving Window) method. It measures the price dynamics between periods end and start and it uses a 13-month time window with a fixed base month taken as year(end)-1. If the distance between end and start exceeds 13 months, then internal Decembers play a role of chain-linking months. The month of the start parameter must be December. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.

Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.

Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.

Lamboray, C. (2017). *The Geary Khamis index and the Lehr index: how much do they differ?* Paper presented at the 15th Ottawa Group meeting, 10-12 May 2017, Elville am Rhein, Germany.

Examples

```
geks_fbmw(milk, start="2019-12", end="2020-04")
```

geks_splice	<i>Extending the multilateral GEKS price index by using window splicing methods.</i>
-------------	--

Description

This function returns a value (or values) of the multilateral GEKS price index extended by using window splicing methods. Available splicing methods are: movement splice, window splice, half splice, mean splice and their additional variants: window splice on published indices (WISP), half splice on published indices (HASP) and mean splice on published indices (see References).

Usage

```
geks_splice(
  data,
  start,
  end,
  window = 13,
  splice = "movement",
  interval = FALSE
)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
window	The length of the time window (as positive integer: typically multilateral methods are based on the 13-month time window).
splice	A character string indicating the splicing method. Available options are: "movement", "window", "half", "mean", "window_published", "half_published", "mean_published".
interval	A logical value indicating whether the function is to provide the price index comparing the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base multilateral indices are to be presented (the fixed base month is defined by start).

Value

This function returns a value or values (depending on interval parameter) of the multilateral GEKS price index extended by using window splicing methods. Available splicing methods are: movement splice, window splice, half splice, mean splice and their additional variants: window splice on published indices (WISP), half splice on published indices (HASP) and mean splice on published indices (see References). The time window starts in `start` and should consist of at least two months. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Chessa, A. G. (2019). *A Comparison of Index Extension Methods for Multilateral Methods*. Paper presented at the 16th Meeting of the Ottawa Group on Price Indices, 8-10 May 2019, Rio de Janeiro, Brazil.
- de Haan, J., van der Grient, H.A. (2011). *Eliminating chain drift in price indexes based on scanner data*. Journal of Econometrics, 161, 36-46.
- Krsinich, F. (2014). *The FEWS Index: Fixed Effects with a Window Splice? Non-Revisable Quality-Adjusted Price Indices with No Characteristic Information*. Paper presented at the UNECE-ILO Meeting of the Group of Experts on Consumer Price Indices, 2-4 May 2016, Geneva, Switzerland.
- de Haan, J.(2015). *A Framework for Large Scale Use of Scanner Data in the Dutch CPI*. Paper presented at the 14th Ottawa Group meeting, Tokyo, Japan.
- Diewert, W.E., and Fox, K.J. (2017). *Substitution Bias in Multilateral Methods for CPI Construction using Scanner Data*. Discussion paper 17-02, Vancouver School of Economics, The University of British Columbia, Vancouver, Canada.

Examples

```
geks_splice(milk, start="2018-12", end="2020-02", splice="half")
geks_splice(milk, start="2018-12", end="2020-02", window=10, interval=TRUE)
```

generate

Generating an artificial scanner dataset

Description

This function provides artificial scanner datasets where prices and quantities are lognormally distributed.

Usage

```
generate(
  pmi = c(),
  psigma = c(),
  qmi = c(),
```

```

    qsigma = c(),
    prec = c(2, 0),
    n = 100,
    n0 = 1,
    r = 1,
    r0 = 1,
    start,
    days = FALSE
  )

```

Arguments

<code>pmi</code>	A numeric vector indicating <code>mi</code> parameters for lognormally distributed prices from the subsequent months.
<code>psigma</code>	A numeric vector indicating <code>sigma</code> parameters for lognormally distributed prices from the subsequent months.
<code>qmi</code>	A numeric vector indicating <code>mi</code> parameters for lognormally distributed quantities from the subsequent months.
<code>qsigma</code>	A numeric vector indicating <code>sigma</code> parameters for lognormally distributed quantities from the subsequent months.
<code>prec</code>	A two-dimensional numeric vector indicating precision, i.e. the number of decimal places, for presenting prices and quantities.
<code>n</code>	An integer parameter indicating the number of products which are to be generated.
<code>n0</code>	An integer parameter indicating the first (the smallest) <code>prodID</code> .
<code>r</code>	An integer parameter indicating the number of outlets (retailer sale points) for which prices and quantities are to be generated.
<code>r0</code>	<code>n0</code> An integer parameter indicating the first (the smallest) <code>retID</code> .
<code>start</code>	The first period in the generated data frame (as character) limited to the year and month, e.g. '2019-12'.
<code>days</code>	A logical parameter indicating whether the trading day in a given month is to be randomised. The default value of <code>days</code> is <code>FALSE</code> , which means that each transaction for a given month takes place on the first day of the month.

Value

This function returns an artificial scanner dataset where prices and quantities are lognormally distributed. The characteristics for these lognormal distributions are set by `pmi`, `sigma`, `qmi` and `qsigma` parameters. This function works for a fixed number of products and outlets (see `n` and `r` parameters). The generated dataset is ready for further price index calculations.

Examples

```

generate(pmi=c(1.02,1.03,1.04),psigma=c(0.05,0.09,0.02),qmi=c(3,4,4),
qsigma=c(0.1,0.1,0.15),start="2020-01",days=TRUE)
generate(pmi=c(1.02,1.03,1.04),psigma=c(0.05,0.09,0.02),qmi=c(6,6,7),
qsigma=c(0.1,0.1,0.15),start="2020-01",n=1000,n0=132578,r=10)

```

geohybrid

*Calculating the bilateral geohybrid price index***Description**

This function returns a value (or vector of values) of the bilateral geohybrid price index. The geohybrid index was proposed by Bialek (2020) and it uses correlation coefficients between prices and quantities.

Usage

```
geohybrid(data, start, end, base = start, interval = FALSE)
```

Arguments

<code>data</code>	The user's data frame with information about sold products. It must contain columns: <code>time</code> (as Date in format: year-month-day, e.g. '2020-12-01'), <code>prices</code> (as positive numeric), <code>quantities</code> (as positive numeric) and <code>prodID</code> (as numeric, factor or character).
<code>start</code>	The base period (as character) limited to the year and month, e.g. "2020-03".
<code>end</code>	The research period (as character) limited to the year and month, e.g. "2020-04".
<code>base</code>	The prior period used in the geohybrid price index formula (as character) limited to the year and month, e.g. "2020-01"
<code>interval</code>	A logical value indicating whether the function is to compare the research period defined by <code>end</code> to the base period defined by <code>start</code> (then <code>interval</code> is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <code><start,end></code> are considered and <code>start</code> defines the base period (<code>interval</code> is set to TRUE).

Value

The function returns a value (or vector of values) of the bilateral geohybrid price index depending on the `interval` parameter. If the `interval` parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Bialek, J. (2020). *Proposition of a Hybrid Price Index Formula for the Consumer Price Index Measurement*. *Equilibrium. Quarterly Journal of Economics and Economic Policy*, 15(4), 697-716.

Examples

```
geohybrid(sugar, start="2019-12", end="2020-08", base="2018-12")
geohybrid(milk, start="2019-12", end="2020-08", base="2018-12", interval=TRUE)
```

geolaspeyres

*Calculating the bilateral geo-logarithmic Laspeyres price index***Description**

This function returns a value (or vector of values) of the bilateral geo-logarithmic Laspeyres price index.

Usage

```
geolaspeyres(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the bilateral geo-logarithmic Laspeyres price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Von der Lippe, P. (2007). *Index Theory and Price Statistics*. Peter Lang: Berlin, Germany.
(2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Examples

```
geolaspeyres(sugar, start="2018-12", end="2019-12")
geolaspeyres(milk, start="2018-12", end="2020-01", interval=TRUE)
```


geolowe

*Calculating the bilateral geometric Lowe price index***Description**

This function returns a value (or vector of values) of the bilateral geometric Lowe price index.

Usage

```
geolowe(data, start, end, base = start, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
base	The prior period used in the geometric Lowe price index formula (as character) limited to the year and month, e.g. "2020-01"
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the bilateral geometric Lowe price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

(2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Examples

```
geolowe(sugar, start="2019-01", end="2020-01", base="2018-12")
geolowe(milk, start="2018-12", end="2020-01", interval=TRUE)
```

geopaasche

*Calculating the bilateral geo-logarithmic Paasche price index***Description**

This function returns a value (or vector of values) of the bilateral geo-logarithmic Paasche price index.

Usage

```
geopaasche(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the bilateral geo-logarithmic Paasche price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Von der Lippe, P. (2007). *Index Theory and Price Statistics*. Peter Lang: Berlin, Germany.
(2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Examples

```
geopaasche(sugar, start="2018-12", end="2019-12")
geopaasche(milk, start="2018-12", end="2020-01", interval=TRUE)
```

geoyoung

*Calculating the bilateral geometric Young price index***Description**

This function returns a value (or vector of values) of the bilateral geometric Young price index.

Usage

```
geoyoung(data, start, end, base = start, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
base	The prior period used in the geometric Young price index formula (as character) limited to the year and month, e.g. "2020-01"
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the bilateral geometric Young price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Young, A. H. (1992). *Alternative Measures of Change in Real Output and Prices*. Survey of Current Business, 72, 32-48.

(2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Examples

```
geoyoung(sugar, start="2019-01", end="2020-01", base="2018-12")
geoyoung(milk, start="2018-12", end="2020-01", interval=TRUE)
```

gk

*Calculating the multilateral Geary-Khamis price index***Description**

This function returns a value of the multilateral Geary-Khamis price index.

Usage

```
gk(data, start, end, wstart = start, window = 13)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
wstart	The beginning of the time interval (which is used by multilateral methods) limited to the year and month, e.g. "2020-01".
window	The length of the time window (as positive integer: typically multilateral methods are based on the 13-month time window).

Value

This function returns a value of the multilateral Geary-Khamis price index which considers the time window defined by wstart and window parameters. The Geary-Khamis price index is calculated by using a special iterative algorithm from Chessa (2016). It measures the price dynamics by comparing period end to period start (both start and end must be inside the considered time window). To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Geary, R. G. (1958). *A Note on Comparisons of Exchange Rates and Purchasing Power between Countries*. Journal of the Royal Statistical Society, Series A, 121, 97-99.
- Khamis, S. H. (1970). *Properties and Conditions for the Existence of a new Type of Index Number*. Sankhya Series B32, 81-98.
- Chessa, A.G. (2016). *A New Methodology for Processing Scanner Data in the Dutch CPI*. Eurona 1/2016, 49-69.

Examples

```
gk(milk, start="2019-01", end="2019-08",window=10)
gk(milk, start="2018-12", end="2019-12")
```

gk_fbew	<i>Extending the multilateral Geary-Khamis price index by using the FBEW method.</i>
---------	--

Description

This function returns a value of the multilateral Geary-Khamis price index extended by using the FBEW (Fixed Base Monthly Expanding Window) method.

Usage

```
gk_fbew(data, start, end)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".

Value

This function returns a value of the multilateral Geary-Khamis price index extended by using the FBEW (Fixed Base Monthly Expanding Window) method. The FBEW method uses a time window with a fixed base month every year (December). The window is enlarged every month with one month in order to include information from a new month. The full window length (13 months) is reached in December of each year. The function measures the price dynamics between periods end and start. The month of the start parameter must be December. If the distance between end and start exceeds 13 months, then internal Decembers play a role of chain-linking months. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Geary, R. G. (1958). *A Note on Comparisons of Exchange Rates and Purchasing Power between Countries*. Journal of the Royal Statistical Society, Series A, 121, 97-99.

Khamis, S. H. (1970). *Properties and Conditions for the Existence of a new Type of Index Number*. Sankhya Series B32, 81-98.

Chessa, A.G. (2016). *A New Methodology for Processing Scanner Data in the Dutch CPI*. Eurona 1/2016, 49-69.

Examples

```
gk_fbew(milk, start="2018-12", end="2019-08")
```

gk_fbmw	<i>Extending the multilateral Geary-Khamis price index by using the FBMW method.</i>
---------	--

Description

This function returns a value of the multilateral Geary-Khamis price index extended by using the FBMW (Fixed Base Moving Window) method.

Usage

```
gk_fbmw(data, start, end)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".

Value

This function returns a value of the multilateral Geary-Khamis price index extended by using the FBMW (Fixed Base Moving Window) method. It measures the price dynamics between periods end and start and it uses a 13-month time window with a fixed base month taken as year(end)-1. If the distance between end and start exceeds 13 months, then internal Decembers play a role of chain-linking months. The month of the start parameter must be December. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Geary, R. G. (1958). *A Note on Comparisons of Exchange Rates and Purchasing Power between Countries*. Journal of the Royal Statistical Society, Series A, 121, 97-99.

Khamis, S. H. (1970). *Properties and Conditions for the Existence of a new Type of Index Number*. Sankhya Series B32, 81-98.

Lamboray, C.(2017). *The Geary Khamis index and the Lehr index: how much do they differ?* Paper presented at the 15th Ottawa Group meeting, 10-12 May 2017, Elville am Rhein, Germany.

Examples

```
gk_fbmw(milk, start="2019-12", end="2020-04")
```

gk_splice	<i>Extending the multilateral Geary-Khamis price index by using window splicing methods.</i>
-----------	--

Description

This function returns a value (or values) of the multilateral Geary-Khamis price index extended by using window splicing methods. Available splicing methods are: movement splice, window splice, half splice, mean splice and their additional variants: window splice on published indices (WISP), half splice on published indices (HASP) and mean splice on published indices (see References).

Usage

```
gk_splice(data, start, end, window = 13, splice = "movement", interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
window	The length of the time window (as positive integer: typically multilateral methods are based on the 13-month time window).
splice	A character string indicating the splicing method. Available options are: "movement", "window", "half", "mean", "window_published", "half_published", "mean_published".
interval	A logical value indicating whether the function is to provide the price index comparing the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base multilateral indices are to be presented (the fixed base month is defined by start).

Value

This function returns a value or values (depending on interval parameter) of the multilateral Geary-Khamis price index extended by using window splicing methods. Available splicing methods are: movement splice, window splice, half splice, mean splice and their additional variants: window splice on published indices (WISP), half splice on published indices (HASP) and mean splice on published indices (see References). The time window starts in start and should consist of at least two months. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Chessa, A. G. (2019). *A Comparison of Index Extension Methods for Multilateral Methods*. Paper presented at the 16th Meeting of the Ottawa Group on Price Indices, 8-10 May 2019, Rio de Janeiro, Brazil.

de Haan, J., van der Grient, H.A. (2011). *Eliminating chain drift in price indexes based on scanner data*. Journal of Econometrics, 161, 36-46.

Krsinich, F. (2014). *The FEWS Index: Fixed Effects with a Window Splice? Non-Revisable Quality-Adjusted Price Indices with No Characteristic Information*. Paper presented at the UNECE-ILO Meeting of the Group of Experts on Consumer Price Indices, 2-4 May 2016, Geneva, Switzerland.

de Haan, J.(2015). *A Framework for Large Scale Use of Scanner Data in the Dutch CPI*. Paper presented at the 14th Ottawa Group meeting, Tokyo, Japan.

Diewert, W.E., and Fox, K.J. (2017). *Substitution Bias in Multilateral Methods for CPI Construction using Scanner Data*. Discussion paper 17-02, Vancouver School of Economics, The University of British Columbia, Vancouver, Canada.

Examples

```
gk_splice(milk, start="2018-12", end="2020-02",splice="half")
gk_splice(milk, start="2018-12", end="2020-02",window=10,interval=TRUE)
```

harmonic	<i>Calculating the unweighted harmonic price index</i>
----------	--

Description

This function returns a value (or vector of values) of the unweighted "unnamed" harmonic price index.

Usage

```
harmonic(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric) and prodID (as numeric, factor or character). A column quantities (as positive numeric) is also needed because this function uses unit values as monthly prices.
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start,end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the unweighted bilateral harmonic price index depending on the `interval` parameter. If the `interval` parameter is set to `TRUE`, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Von der Lippe, P. (2007). *Index Theory and Price Statistics*. Peter Lang: Berlin, Germany.
(2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Examples

```
harmonic(sugar, start="2018-12", end="2019-12")
harmonic(milk, start="2018-12", end="2020-01", interval=TRUE)
```

 hybrid

Calculating the bilateral hybrid price index

Description

This function returns a value (or a vector of values) of the bilateral hybrid price index. The hybrid index was proposed by Bialek (2020) and it uses correlation coefficients between prices and quantities.

Usage

```
hybrid(data, start, end, base = start, interval = FALSE)
```

Arguments

<code>data</code>	The user's data frame with information about sold products. It must contain columns: <code>time</code> (as Date in format: year-month-day, e.g. '2020-12-01'), <code>prices</code> (as positive numeric), <code>quantities</code> (as positive numeric) and <code>prodID</code> (as numeric, factor or character).
<code>start</code>	The base period (as character) limited to the year and month, e.g. '2020-03'.
<code>end</code>	The research period (as character) limited to the year and month, e.g. '2020-04'.
<code>base</code>	The prior period used in the hybrid price index formula (as character) limited to the year and month, e.g. '2020-01'.
<code>interval</code>	A logical value indicating whether the function is to compare the research period defined by <code>end</code> to the base period defined by <code>start</code> (then <code>interval</code> is set to <code>FALSE</code>) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <code><start,end></code> are considered and <code>start</code> defines the base period (<code>interval</code> is set to <code>TRUE</code>).

Value

The function returns a value (or a vector of values) of the bilateral hybrid price index depending on the `interval` parameter. If the `interval` parameter is set to `TRUE`, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#), [final_index](#) or [final_index2](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or [final_index2](#) function).

References

Bialek, J. (2020). *Proposition of a Hybrid Price Index Formula for the Consumer Price Index Measurement*. Equilibrium. Quarterly Journal of Economics and Economic Policy, 15(4), 697-716.

Examples

```
hybrid(sugar, start="2019-12", end="2020-08", base="2018-12")
hybrid(milk, start="2019-12", end="2020-08", base="2018-12", interval=TRUE)
```

jevons	<i>Calculating the unweighted Jevons price index</i>
--------	--

Description

This function returns a value (or vector of values) of the unweighted bilateral Jevons price index.

Usage

```
jevons(data, start, end, interval = FALSE)
```

Arguments

<code>data</code>	The user's data frame with information about sold products. It must contain columns: <code>time</code> (as Date in format: year-month-day, e.g. '2020-12-01'), <code>prices</code> (as positive numeric) and <code>prodID</code> (as numeric, factor or character). A column <code>quantities</code> (as positive numeric) is also needed because this function uses unit values as monthly prices.
<code>start</code>	The base period (as character) limited to the year and month, e.g. "2020-03".
<code>end</code>	The research period (as character) limited to the year and month, e.g. "2020-04".
<code>interval</code>	A logical value indicating whether the function is to compare the research period defined by <code>end</code> to the base period defined by <code>start</code> (then <code>interval</code> is set to <code>FALSE</code>) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <code><start,end></code> are considered and <code>start</code> defines the base period (<code>interval</code> is set to <code>TRUE</code>).

Value

The function returns a value (or vector of values) of the unweighted bilateral Jevons price index depending on the `interval` parameter. If the `interval` parameter is set to `TRUE`, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Jevons, W. S., (1865). *The variation of prices and the value of the currency since 1782*. J. Statist. Soc. Lond., 28, 294-320.

(2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Examples

```
jevons(milk, start="2018-12", end="2020-01")
jevons(milk, start="2018-12", end="2020-01", interval=TRUE)
```

laspeyres

Calculating the bilateral Laspeyres price index

Description

This function returns a value (or vector of values) of the bilateral Laspeyres price index.

Usage

```
laspeyres(data, start, end, interval = FALSE)
```

Arguments

<code>data</code>	The user's data frame with information about sold products. It must contain columns: <code>time</code> (as Date in format: year-month-day, e.g. '2020-12-01'), <code>prices</code> (as positive numeric), <code>quantities</code> (as positive numeric) and <code>prodID</code> (as numeric, factor or character).
<code>start</code>	The base period (as character) limited to the year and month, e.g. "2020-03".
<code>end</code>	The research period (as character) limited to the year and month, e.g. "2020-04".
<code>interval</code>	A logical value indicating whether the function is to compare the research period defined by <code>end</code> to the base period defined by <code>start</code> (then <code>interval</code> is set to <code>FALSE</code>) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <code><start,end></code> are considered and <code>start</code> defines the base period (<code>interval</code> is set to <code>TRUE</code>).

Value

The function returns a value (or vector of values) of the bilateral Laspeyres price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Laspeyres, E. (1871). *Die Berechnung einer mittleren Waarenpreissteigerung*. Jahrbucher fur Nationalokonomie und Statistik 16, 296-314.

(2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Examples

```
laspeyres(sugar, start="2018-12", end="2019-12")
laspeyres(milk, start="2018-12", end="2020-01", interval=TRUE)
```

lehr

Calculating the bilateral Lehr price index

Description

This function returns a value (or vector of values) of the bilateral Lehr price index.

Usage

```
lehr(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the bilateral Lehr price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Lehr, J. (1885). *Beitrage zur Statistik der Preise, insbesondere des Geldes und des Holzes*. J. D. Sauerlander, Frankfurt am Main.

(2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Examples

```
lehr(sugar, start="2018-12", end="2019-12")
lehr(milk, start="2018-12", end="2020-01", interval=TRUE)
```

lloyd_moulton

Calculating the bilateral Lloyd-Moulton price index

Description

This function returns a value (or vector of values) of the bilateral Lloyd-Moulton price index.

Usage

```
lloyd_moulton(data, start, end, sigma = 0.7, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
sigma	The elasticity of substitution parameter (as numeric).
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the bilateral Lloyd-Moulton price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Lloyd, P. J. (1975). *Substitution Effects and Biases in Nontrue Price Indices*. The American Economic Review, 65, 301-313.
- Moulton, B. R. (1996). *Constant Elasticity Cost-of-Living Index in Share-Relative Form*. Washington DC: U. S. Bureau of Labor Statistics, mimeograph
- (2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.
- Von der Lippe, P. (2007). *Index Theory and Price Statistics*. Peter Lang: Berlin, Germany.

Examples

```
lloyd_moulton(sugar, start="2018-12", end="2019-12",sigma=0.9)
lloyd_moulton(milk, start="2018-12", end="2020-01", interval=TRUE)
```

load_model	<i>Loading the machine learning model from the disk</i>
------------	---

Description

This function loads a list of machine learning model elements from the disk, i.e. the needed 8 files are read.

Usage

```
load_model(dir = "ML_model")
```

Arguments

dir	The name of the directory from which the machine learning model is to be loaded. The directory must be in the working directory.
-----	--

Value

This function loads a list of ML model elements from the disk, i.e. the needed 8 files are read from the directory selected by dir. After loading the model it can be used for product classification by using [data_classifying](#) function.

Examples

```
#Setting a temporal directory as a working directory
## Not run: wd<-tempdir()
## Not run: setwd(wd)
#Building the model
## Not run: my.grid=list(eta=c(0.01,0.02,0.05),subsample=c(0.5))
## Not run: data_train<-dplyr::filter(dataCOICOP,dataCOICOP$time<=as.Date("2020-08-01"))
## Not run: data_test<-dplyr::filter(dataCOICOP,dataCOICOP$time>as.Date("2020-08-01"))
## Not run: ML<-model_classification(data_train,data_test,grid=my.grid,
  indicators=c("prodID","unit","description"),key_words=c("milk"),rounds=50)
## End(Not run)
#Saving the model
## Not run: save_model(ML, dir="My_model")
#Loading the model
## Not run: ML_fromPC<-load_model("My_model")
#COICOP predicting
## Not run: data_classifying(ML_fromPC, data_test)
```

lowe

Calculating the bilateral Lowe price index

Description

This function returns a value (or vector of values) of the bilateral Lowe price index.

Usage

```
lowe(data, start, end, base = start, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
base	The prior period used in the Lowe price index formula (as character) limited to the year and month, e.g. "2020-01".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start,end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the bilateral Lowe price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

(2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Examples

```
lowe(sugar, start="2019-01", end="2020-01", base="2018-12")
lowe(milk, start="2018-12", end="2020-01", interval=TRUE)
```

marshall_edgeworth	<i>Calculating the bilateral Marshall-Edgeworth price index</i>
--------------------	---

Description

This function returns a value (or vector of values) of the bilateral Marshall-Edgeworth price index.

Usage

```
marshall_edgeworth(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the bilateral Marshall-Edgeworth price index depending on the `interval` parameter. If the `interval` parameter is set to `TRUE`, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Marshall, A. (1887). *Remedies for Fluctuations of General Prices*. Contemporary Review, 51, 355-375.
- Edgeworth, F. Y. (1887). *Measurement of Change in Value of Money I*. The first Memorandum presented to the British Association for the Advancement of Science; reprinted in Papers Relating to Political Economy, Vol. 1, New York, Burt Franklin, s. 1925.
- (2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.
- Von der Lippe, P. (2007). *Index Theory and Price Statistics*. Peter Lang: Berlin, Germany.

Examples

```
marshall_edgeworth(sugar, start="2018-12", end="2019-12")
marshall_edgeworth(milk, start="2018-12", end="2020-01", interval=TRUE)
```

matched	<i>Providing values from the indicated column that occur simultaneously in the compared periods or in a given time interval.</i>
---------	--

Description

The function returns all values from the indicated column (defined by the `type` parameter) which occur simultaneously in the compared periods or in a given time interval.

Usage

```
matched(data, period1, period2, type = "prodID", interval = FALSE)
```

Arguments

- | | |
|----------------------|--|
| <code>data</code> | The user's data frame. It must contain a column <code>time</code> (as Date in format: year-month-day, e.g. '2020-12-01') and also a column indicated by the <code>type</code> parameter. |
| <code>period1</code> | The first period (as character) limited to the year and month, e.g. "2019-03". |
| <code>period2</code> | The second period (as character) limited to the year and month, e.g. "2019-04". |

type	This parameters defines the column which is used in the procedure. Possible values of the type parameter are: retID, prodID, codeIN, codeOUT or description.
interval	A logical parameter indicating whether the procedure is to work for the whole time period between period1 and period2 (then it is TRUE).

Value

The function returns all values from the indicated column (defined by the type parameter) which occur simultaneously in the compared periods or in a given time interval. Possible values of the type parameter are: retID, prodID, codeIN, codeOUT or description. If the interval parameter is set to FALSE, then the function compares only periods defined by period1 and period2. Otherwise the whole time period between period1 and period2 is considered.

Examples

```
matched(milk, period1="2018-12", period2="2019-12", interval=TRUE)
matched(milk, period1="2018-12", period2="2019-12", type="description")
```

matched_fig

Providing a time dependent matched_index() function

Description

The function provides a data frame or a figure presenting the [matched_index](#) function calculated for the column defined by the type parameter and for each month from the considered time interval

Usage

```
matched_fig(
  data,
  start,
  end,
  base = "start",
  type = "prodID",
  fixedbase = TRUE,
  figure = TRUE
)
```

Arguments

data	The user's data frame. It must contain a column time (as Date in format: year-month-day,e.g. '2020-12-01') and also a column indicated by the type parameter.
start	The beginning of a time interval (as character) limited to the year and month, e.g. "2019-03".

end	The end of a time interval (as character) limited to the year and month, e.g. "2019-04".
base	The base period (as character) for product comparisons. Its possible values are: "start" and "end".
type	This parameter defines the column which is used in the procedure. Possible values of the type parameter are: retID, prodID, codeIN, codeOUT or description.
fixedbase	A logical parameter indicating whether the procedure is to work for subsequent months from the considered time interval (fixedbase=FALSE). Otherwise the period defined by base plays a role of fixed base month (fixedbase=TRUE)
figure	A logical parameter indicating whether the function returns a figure (TRUE) or a data frame (FALSE) with <code>matched_index</code> values.

Value

The function returns a data frame or a figure presenting the `matched_index` function calculated for the column defined by the `type` parameter and for each month from the considered time interval. The interval is set by `start` and `end` parameters. The returned object (data frame or figure) depends on the value of `figure` parameter. The returned values belong to [0,1].

Examples

```
matched_fig(milk, start="2018-12", end="2019-12")
matched_fig(milk, start="2018-12", end="2019-12", figure=FALSE)
```

matched_index	<i>Providing the ratio of number of matched values from the indicated column to the number of all available values from this column</i>
---------------	---

Description

The function returns a ratio of number of values from the indicated column that occur simultaneously in the compared periods or in a given time interval to the number of all available values from the above-mentioned column (defined by the `type` parameter) at the same time.

Usage

```
matched_index(data, period1, period2, type = "prodID", interval = FALSE)
```

Arguments

data	The user's data frame. It must contain a column <code>time</code> (as Date in format: year-month-day, e.g. '2020-12-01') and also a column indicated by the <code>type</code> parameter.
period1	The first period (as character) limited to the year and month, e.g. "2019-03".
period2	The second period (as character) limited to the year and month, e.g. "2019-04".

type	This parameter defines the column which is used in the procedure. Possible values of the type parameter are: retID, prodID, codeIN, codeOUT or description.
interval	A logical parameter indicating whether the procedure is to work for the whole time period between period1 and period2 (then it is TRUE).

Value

The function returns a ratio of number of values from the indicated column that occur simultaneously in the compared periods or in a given time interval to the number of all available values from the above-mentioned column (defined by the type parameter) at the same time. Possible values of the type parameter are: retID, prodID or description. If the interval parameter is set to FALSE, then the function compares only periods defined by period1 and period2. Otherwise the whole time period between period1 and period2 is considered. The returned value belongs to [0,1].

Examples

```
matched_index(milk, period1="2018-12", period2="2019-12", interval=TRUE)
matched_index(milk, period1="2018-12", period2="2019-12", type="retID")
```

milk	<i>A real data set on sold milk</i>
------	-------------------------------------

Description

A collection of scanner data on the sale of milk in one of Polish supermarkets in the period from December 2018 to August 2020

Usage

```
milk
```

Format

A data frame with 6 columns and 4386 rows. The used variables are as follows:

time - Dates of transactions (Year-Month-Day)

prices - Prices of sold products [PLN]

quantities - Quantities of sold products [liters]

prodID - Unique product codes (data set contains 68 different prodIDs)

retID - Unique codes identifying outlets/retailer sale points (data set contains 5 different retIDs)

description Descriptions of sold milk products (data set contains 6 different product descriptions)

Description

This function provides a trained machine learning model to classify products into coicop groups. In addition, the function returns the characteristics of the model and figures describing the learning process.

Usage

```
model_classification(
  data_train = data.frame(),
  data_test = data.frame(),
  indicators = c(),
  key_words = c(),
  sensitivity = FALSE,
  p = 0.9,
  w = 0.2,
  rounds = 200,
  grid = list()
)
```

Arguments

data_train	Training data set for the model. This set must contain all the columns defined by the indicators parameter and the coicop column (with matched coicop groups to all products). If the key_words vector is non-empty, the set should also contain a description column. Ideally, the indicators should be of the numerical type. If the indicator is not of the numerical type, it will be converted to this type.
data_test	A test set that is used to validate the machine learning model. This set should have the same structure as the training set, but it is not obligatory. If the test set is not specified by the user then the test set is drawn from the training set (see p parameter).
indicators	A vector of column names to be considered in building a machine learning model.
key_words	A vector of keywords or phrases that will be recognized in the description column. For each such keyword and or phrase, a new binary variable (column) will be created and included in the machine model training process.
sensitivity	A logical parameter that indicates whether lowercase or uppercase letters are to be distinguished when the key_words vector is not empty.
p	A parameter related to creating the testing set, if it has not been specified by the user. The test set is then created on the basis of a coicop-balanced subsample of the training set. The size of this subsample is 100p percents of the training set size.

w	A parameter for determining the measure of choosing the optimal machine learning model. For each combination of parameters specified in the grid list, the error rate of the trained model is calculated on the basis of the error on the training set ($\text{error_L}=1-\text{accuracy_L}$) and the error on the testing set ($\text{error_T}=1-\text{accuracy_T}$). Final accuracy of the model is estimated as: $w \text{ accuracy_L} + (1-w) \text{ accuracy_T}$.
rounds	The maximum number of iterations during the training stage.
grid	The list of vectors of parameters which are taken into consideration during the Extreme Gradient Boosting training. The default value of this list is as follows: <code>grid=list(eta=c(0.05,0.1,0.2),max_depth=c(6),min_child_weight=c(1),max_delta_st</code> The complete list of parameters for the used Tree Booster is available online here .

Value

In general, this function provides a trained machine learning model to classify products into coicop groups. In addition, the function returns the characteristics of the model and figures describing the learning process. The machine learning process is based on the XGBoost algorithm (from the XGBoost package) which is an implementation of gradient boosted decision trees designed for speed and performance. The function takes into account each combination of model parameters (specified by the grid list) and provides, inter alia, an optimally trained model (a model that minimizes the error rate calculated on the basis of a fixed value of the w parameter). After all, the function returns a list of the following objects: `model` - the optimally trained model; `best_parameters` - a set of parameters of the optimal model; `indicators` - a vector of all indicators used; `key_words` - a vector of all key words and phrases used; `coicops` - a dataframe with categorized COICOPs; `sensitivity` - a value of the used 'sensitivity' parameter; `figure_training` - a plot of the error levels calculated for the training set and the testing set during the learning process of the returned model ($\text{error} = 1 - \text{accuracy}$); `figure_importance` - a plot of the relative importance of the used indicators.

References

Tianqi Chen and Carlos Guestrin (2016). *XGBoost: A Scalable Tree Boosting System*. 22nd SIGKDD Conference on Knowledge Discovery and Data Mining.

Examples

```
my.grid=list(eta=c(0.01,0.02,0.05),subsample=c(0.5))
data_train<-dplyr::filter(dataCOICOP,dataCOICOP$time<=as.Date("2020-08-01"))
data_test<-dplyr::filter(dataCOICOP,dataCOICOP$time>as.Date("2020-08-01"))
ML<-model_classification(data_train,data_test,grid=my.grid,
indicators=c("prodID","unit","description"),key_words=c("milk"),rounds=50)
ML$best_parameters
ML$indicators
ML$figure_training
ML$figure_importance
```

paasche

*Calculating the bilateral Paasche price index***Description**

This function returns a value (or vector of values) of the bilateral Paasche price index.

Usage

```
paasche(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the bilateral Paasche price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Paasche, H. (1874). *Über die Preisentwicklung der letzten Jahre nach den Hamburger Borsennotirungen*. Jahrbucher für Nationalökonomie und Statistik, 12, 168-178.

(2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Examples

```
paasche(sugar, start="2018-12", end="2019-12")
paasche(milk, start="2018-12", end="2020-01", interval=TRUE)
```

palgrave

Calculating the bilateral Palgrave price index

Description

This function returns a value (or vector of values) of the bilateral Palgrave price index.

Usage

```
palgrave(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the bilateral Palgrave price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Palgrave, R. H. I. (1886). *Currency and Standard of Value in England, France and India and the Rates of Exchange Between these Countries*. Memorandum submitted to the Royal Commission on Depression of trade and Industry, Third Report, Appendix B, 312-390.
- (2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.
- Von der Lippe, P. (2007). *Index Theory and Price Statistics*. Peter Lang: Berlin, Germany.

Examples

```
palgrave(sugar, start="2018-12", end="2019-12")
palgrave(milk, start="2018-12", end="2020-01", interval=TRUE)
```

pqcor	<i>Providing a correlation coefficient for price and quantity of sold products</i>
-------	--

Description

The function returns correlation between price and quantity of sold products with given IDs.

Usage

```
pqcor(data, period, set = c(), figure = FALSE)
```

Arguments

data	The user's data frame. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character) with unique product IDs.
period	The time period (as character) limited to the year and month, e.g. "2019-03".
set	The set of unique product IDs to be used for determining correlation between price and quantity of sold products (see also data_matching). If the set is empty, the function works for all products being available in period.
figure	A logical parameter indicating whether the function returns a figure (TRUE) or a data frame (FALSE) with correlations between price and quantity of sold products.

Value

The function returns Pearson's correlation coefficient between price and quantity of products with given IDs and sold in period.

Examples

```
pqcor(milk, period="2019-03")
pqcor(milk, period="2019-03", figure=TRUE)
```

pqcor_fig	<i>Providing correlations between price and quantity of sold products</i>
-----------	---

Description

The function returns Pearson's correlation coefficients between price and quantity of sold products with given IDs.

Usage

```
pqcor_fig(data, start, end, figure = TRUE, set = c())
```

Arguments

data	The user's data frame. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character) with unique product IDs.
start	The beginning of the considered time interval (as character) limited to the year and month, e.g. "2020-03".
end	The end of the considered time interval (as character) limited to the year and month, e.g. "2020-04".
figure	A logical parameter indicating whether the function returns a figure (TRUE) or a data frame (FALSE) with price-quantity correlations.
set	The set of unique product IDs to be used for determining correlation between prices and quantities of sold products (see also data_matching). If the set is empty, the function works for all products being available in period.

Value

The function returns Pearson's correlation coefficients between price and quantity of products with given IDs and sold in the time interval: <start,end>. Correlation coefficients are calculated for each month separately. Results are presented in tabular or graphical form depending on the figure parameter.

Examples

```
pqcor_fig(milk, start="2018-12", end="2019-12", figure=FALSE)
pqcor_fig(milk, start="2018-12", end="2019-12", figure=TRUE)
```

Description

The **PriceIndices** package is a tool for Bilateral and Multilateral Price Index Calculations. A demonstration of package functions is here: [README](#). The package documentation can be found [HERE](#). The list of package functions is as follows:

Data sets in the package and generating artificial scanner data sets

dataAGGR
dataMATCH
dataCOICOP
milk
sugar
coffee
dataU
generate
tindex

Functions for data processing

data_check
data_preparing
data_aggregating
data_unit
data_norm
data_selecting
data_classifying
model_classification
save_model
load_model
data_matching
data_filtering

Functions providing dataset characteristics

available
matched
matched_index
matched_fig
prices
quantities
sales
sales_groups
sales_groups2
pqcor
pqcor_fig
dissimilarity_fig

Functions for bilateral unweighted price index calculation

bmw
carli
cswd
dutot
jevons
harmonic

Functions for bilateral weighted price index calculation

agmean
banajree
bialek
davies
drobisch
fisher
geary_khamis
geolaspeyres
geolowe
geopaasche
geoyoung
geohybrid
hybrid
laspeyres
lehr
lloyd_moulton
lowe
marshall_edgeworth
paasche
palgrave
sato_vartia
stuvel
tornqvist
vartia
walsh
young

Functions for chain price index calculation

chbmw
chcarli
chcswd
chdutot
chjevons
chharmonic
chagmean
chbanajree
chbialek
davies
chdrobisch
chfisher
chgeary_khamis
chgeolaspeyres
chgeolowe
chgeopaasche
chgeoyoung
chgeohybrid
chhybrid
chlaspeyres
chlehr
chlloyd_moulton
chlowe
chmarshall_edgeworth
chpaasche
chpalgrave
chsato_vartia
chstuvel
chtornqvist
chvartia
chwalsh
chyoung

Functions for multilateral price index calculation

ccdi
geks
wgeks
geksl
wgeksl
geksgl
wgeksgl
geksequ
wgeksequ
geksequi
wgeksequi
geksgaqi
wgeksgaqi
geksgj
geksw
gk
QU
tpd
SPQ

Functions for extending multilateral price indices by using splicing methods

ccdi_splice
geks_splice
wgeks_splice
geksgj_splice
geksw_splice
geksgl_splice
wgeksgl_splice
geksgl_splice
wgeksgl_splice
geksequ_splice
wgeksequ_splice
geksequi_splice
wgeksequi_splice
geksgaqi_splice
wgeksgaqi_splice
gk_splice
tpd_splice

Functions for extending multilateral price indices by using the FBEW method

ccdi_fbew
geks_fbew
wgeks_fbew
geksj_fbew
geksw_fbew
geksl_fbew
wgeksl_fbew
geksgl_fbew
wgeksgl_fbew
geksequ_fbew
wgeksequ_fbew
geksequi_fbew
wgeksequi_fbew
geksgaqi_fbew
wgeksgaqi_fbew
gk_fbew
tpd_fbew

Functions for extending multilateral price indices by using the FBMW method

ccdi_fbmw
geks_fbmw
wgeks_fbmw
geksj_fbmw
geksw_fbmw
geksl_fbmw
wgeksl_fbmw
geksgl_fbmw
wgeksgl_fbmw
geksequ_fbmw
wgeksequ_fbmw
geksequi_fbmw
wgeksequi_fbmw
geksgaqi_fbmw
wgeksgaqi_fbmw
gk_fbmw
tpd_fbmw

General functions for price index calculations

price_index
price_indices
final_index
final_index2

Functions for comparisons of price indices

compare_indices
compare_final_indices
compare_distances

prices	<i>Providing prices (unit values) of sold products</i>
--------	--

Description

The function returns prices (unit values) of sold products with given IDs.

Usage

```
prices(data, period, set = c())
```

Arguments

data	The user's data frame. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character) with unique product IDs.
period	The time period (as character) limited to the year and month, e.g. "2019-03".
set	The set of unique product IDs to be used for determining prices of sold products (see also data_matching). If the set is empty, the function returns prices of all products being available in period.

Value

The function analyzes the user's data frame and returns prices (unit value) of products with given ID and being sold in the time period indicated by the period parameter.

Examples

```
prices(milk, period="2019-06")  
prices(milk, period="2019-12",set=c(400032, 71772, 82919))
```

price_index	<i>A general function to compute a price index</i>
-------------	--

Description

This function returns a value or values of the selected price index.

Usage

```
price_index(
  data,
  start,
  end,
  formula = "fisher",
  window = 13,
  splice = "movement",
  base = start,
  sigma = 0.7,
  interval = FALSE
)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric) and prodID (as numeric, factor or character). A column quantities (as positive numeric) is also essential even if the selected index is an unweighted formula (unit values are calculated).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
formula	The character string indicating the price index formula is to be calculated. To see available options please use the link: PriceIndices .
window	The length of the time window if the multilateral index is selected (as positive integer: typically multilateral methods are based on the 13-month time window).
splice	A character string indicating the splicing method (if the multilateral splicing index is selected). Available options are: "movement", "window", "half", "mean" and their additional variants: "window_published", "half_published" and "mean_published".
base	The prior period used in the Young- or Lowe-type price indices (as character) limited to the year and month, e.g. "2020-01".
sigma	The elasticity of substitution parameter used in the Lloyed-Moulton and AG Mean indices (as numeric).
interval	A logical value indicating whether the function is to provide the price index comparing the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be presented (the fixed base month is defined by start).

Value

This function returns a value or values of the selected price index. If the `interval` parameter is set to `TRUE` then it returns a data frame with two columns: dates and index values. The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the `final_index` or the `final_index2` function).

Examples

```
price_index(milk, start="2018-12", end="2020-02", formula="walsh", interval=FALSE)
price_index(milk, start="2018-12", end="2020-02", formula="tpd_splice",
splice="half", interval=TRUE)
```

price_indices

A very general function to compute one or more price indices

Description

This function returns a value or values of the selected price indices.

Usage

```
price_indices(
  data,
  start,
  end,
  bilateral = c(),
  bindex = c(),
  base = c(),
  cesindex = c(),
  sigma = c(),
  simindex = c(),
  fbmulti = c(),
  fbwindow = c(),
  splicemulti = c(),
  splicewindow = c(),
  splice = c(),
  namebilateral = bilateral,
  namebindex = bindex,
  namecesindex = cesindex,
  namesimindex = simindex,
  namefbmulti = fbmulti,
  namesplicemulti = splicemulti,
  interval = FALSE
)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric) and prodID (as numeric, factor or character). A column quantities (as positive numeric) is also essential even if the selected index is an unweighted formula (unit values are calculated).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
bilateral	A vector of character strings indicating bilateral price index formulas that are to be calculated. To see available options please use the link: PriceIndices .
bindex	A vector of character strings indicating Lowe- or Young-type price index formulas that are to be calculated. Available options are: young,geoyoung,lowe and geolowe.
base	The vector of prior periods used in the Young- or Lowe-type price indices. Each element of the vector (as character) must be limited to the year and month, e.g. "2020-01".
cesindex	A vector of character strings indicating CES price index formulas that are to be calculated. To see available options, please use the link: PriceIndices .
sigma	The vector of elasticity of substitution parameters used in the Lloyed-Moulton and AG Mean indices.
simindex	A vector of character strings indicating multilateral price index formulas based on relative price and quantity similarity that are to be calculated. To see available options, please use the link: PriceIndices .
fbmulti	A vector of character strings indicating multilateral price index formulas that are to be calculated. The available set of indices includes full-window multilateral indices or their FBEW and FBW extensions.To see available options, please use the link: PriceIndices .
fbwindow	A vector of integers. Each element of the vector defines the length of the time window of the corresponding multilateral index (if it is selected by fbmulti).
splicemulti	A vector of character strings indicating multilateral price index formulas that are to be extended by using splicing methods. To see available options. please use the link: PriceIndices .
splicewindow	A vector of integers. Each element of the vector defines the length of the time window of the corresponding multilateral index (if it is selected by splicemulti).
splice	A vector of character strings. Each element of the vector indicates the splicing method is to be used for the corresponding multilateral index (if it is selected by splicemulti). Available values of vector elements are: "movement", "window", "half", "mean" and their additional variants: "window_published", "half_published" and "mean_published".
namebilateral	A vector of character strings describing names of bilateral price indices that are to be displayed. If this vector is empty, then default names are used.
namebindex	A vector of character strings describing names of Young- and/or Lowe-type price indices are to be displayed. If this vector is empty, then default names are used.

namecesindex	A vector of character strings describing names of CES price indices that are to be displayed. If this vector is empty, then default names are used.
namesimindex	A vector of character strings describing names of multilateral price index formulas based on relative price and quantity similarity that are to be displayed. If this vector is empty, then default names are used.
namefbmulti	A vector of character strings describing names of full-window multilateral indices or their FBEW and FBMW extensions that are to be displayed. If this vector is empty, then default names are used.
namesplicemulti	A vector of character strings describing names of multilateral splice indices that are to be displayed. If this vector is empty, then default names are used.
interval	A logical value indicating whether the function is to provide the price index comparing the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be presented (the fixed base month is defined by start).

Value

This general function returns a value or values of the selected price indices. If the interval parameter is set to TRUE, then it returns a data frame where its first column indicates dates and the remaining columns show corresponding values of all selected price indices. The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the `final_index` or the `final_index2` function).

Examples

```
price_indices(milk, start="2018-12",end="2019-04",bilateral=c("jevons"),
fbmulti=c("tpd"),fbwindow=c(6),interval=TRUE)
price_indices(milk, start="2018-12", end="2019-05",
fbmulti=c("tpd","geks"),fbwindow=c(10,12),interval=TRUE)
```

QU	<i>Calculating the quality adjusted unit value index (QU index)</i>
----	---

Description

This function returns a value of the quality adjusted unit value index (QU index) for a given set of adjustment factors.

Usage

```
QU(data, start, end, v)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
v	The data frame with adjustment factors for at least all matched prodIDs. It must contain two columns: prodID (as numeric or character) with unique product IDs and values (as positive numeric) with corresponding adjustment factors.

Value

This function returns a value of the quality adjusted unit value index (QU index) for a given set of adjustment factors (adjusted factors must be available for all matched prodIDs).

References

Chessa, A.G. (2016). *A New Methodology for Processing Scanner Data in the Dutch CPI*. Eurona 1/2016, 49-69.

Examples

```
## Creating a data frame with artificial adjustment factors
## (random numbers from uniform distribution U[1,2])
prodID<-unique(milk$prodID)
values<-stats::runif(length(prodID),1,2)
v<-data.frame(prodID,values)
## Calculating the QU index for the created data frame 'v'
QU(milk, start="2018-12", end="2019-12", v)
```

quantities

Providing quantities of sold products

Description

The function returns quantities of sold products with given IDs.

Usage

```
quantities(data, period, set = c())
```

Arguments

data	The user's data frame. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), quantities (as positive numeric) and prodID (as numeric, factor or character) with unique product IDs.
period	The time period (as character) limited to the year and month, e.g. "2019-03".
set	The set of unique product IDs to be used for determining quantities of sold products (see also data_matching). If the set is empty, the function returns quantities of all products being available in period.

Value

The function analyzes the user's data frame and returns quantities of products with given ID and being sold in the time period indicated by the period parameter.

Examples

```
quantities(milk, period="2019-06")
quantities(milk, period="2019-12",set=c(400032, 71772, 82919))
```

sales	<i>Providing values of product sales</i>
-------	--

Description

The function returns values of sales of products with given IDs.

Usage

```
sales(data, period, set = c(), shares = FALSE, hist = FALSE)
```

Arguments

data	The user's data frame. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character) with unique product IDs.
period	The time period (as character) limited to the year and month, e.g. "2019-03".
set	The set of unique product IDs to be used for determining product sales values (see also data_matching). If the set is empty, then the function returns sale values of all products being available in period.
shares	A logical parameter indicating whether the function is to return shares of product sales.
hist	A logical parameter indicating whether the function is to return histogram of product sales.

Value

The function analyzes the user's data frame and returns values of sales of products with given IDs and being sold in time period indicated by the period parameter.

Examples

```
sales(milk, period="2019-06", shares=TRUE, hist=TRUE)
sales(milk, period="2019-12", set=unique(milk$prodID)[1])
```

sales_groups	<i>Providing information about sales of products from one or more datasets</i>
--------------	--

Description

The function returns values of sales of products from one or more datasets or the corresponding barplot for these sales.

Usage

```
sales_groups(
  datasets = list(),
  start,
  end,
  shares = FALSE,
  barplot = FALSE,
  names = c()
)
```

Arguments

datasets	A list of user's data frames. Each data frame must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric) and quantities (as positive numeric).
start	The beginning of the considered time interval (as character) limited to the year and month, e.g. "2020-03".
end	The end of the considered time interval (as character) limited to the year and month, e.g. "2020-04".
shares	A logical parameter indicating whether the function is to calculate shares of product sales
barplot	A logical parameter indicating whether the function is to return barplot for product sales.
names	A vector of characters describing product groups defined by datasets.

Value

The function returns values of sales of products from one or more datasets or the corresponding barplot for these sales (if barplot is TRUE). Alternatively, it calculates the sale shares (if shares is TRUE).

Examples

```
## Creating 3 subgroups of milk:
ctg<-unique(milk$description)
categories<-c(ctg[1],ctg[2],ctg[3])
milk1<-dplyr::filter(milk, milk$description==categories[1])
milk2<-dplyr::filter(milk, milk$description==categories[2])
milk3<-dplyr::filter(milk, milk$description==categories[3])
## Sample use of this function:
sales_groups(datasets=list(milk1,milk2,milk3),start="2019-04",end="2019-04",shares=TRUE)
sales_groups(datasets=list(milk1,milk2,milk3),start="2019-04",end="2019-07",
barplot=TRUE, names=categories)
```

sales_groups2

Providing information about sales of products

Description

The function returns values of sales of products or the corresponding barplot for these sales.

Usage

```
sales_groups2(
  data = data.frame(),
  by,
  start,
  end,
  shares = FALSE,
  barplot = FALSE,
  names = c()
)
```

Arguments

data	The user's data frame with subgroups of sold products (see by parameter). The data frame must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric) and quantities (as positive numeric). An additional column indicated via by parameter is also needed.
by	The column name indicating grouping variable, i.e. this column is used for creating subgroups of products.
start	The beginning of the considered time interval (as character) limited to the year and month, e.g. "2020-03".

end	The end of the considered time interval (as character) limited to the year and month, e.g. "2020-04".
shares	A logical parameter indicating whether the function is to calculate shares of product sales
barplot	A logical parameter indicating whether the function is to return barplot for product sales.
names	A vector of characters describing product groups defined by datasets.

Value

The function returns values of sales of products or the corresponding barplot for these sales (if barplot is TRUE). Alternatively, it calculates the sale shares (if shares is TRUE).

Examples

```
outlets<-as.character(unique(milk$retID))
sales_groups2(milk,by="retID",start="2019-04",end="2019-04",
shares=TRUE,barplot=TRUE,names=outlets)
```

sato_vartia

Calculating the bilateral Vartia-II (Sato-Vartia) price index

Description

This function returns a value (or vector of values) of the bilateral Vartia-II (Sato-Vartia) price index.

Usage

```
sato_vartia(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start,end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the bilateral Vartia-II (Sato-Vartia) price index depending on the `interval` parameter. If the `interval` parameter is set to `TRUE`, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Sato, K. (1976). *The Ideal Log-Change Index Number*. The Review of Economics and Statistics, 58(2), 223-228.
- Vartia, Y. O. (1976). *Ideal Log-Change Index Numbers*. Scandinavian Journal of Statistics 3(3), 121-126.
- (2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.
- Von der Lippe, P. (2007). *Index Theory and Price Statistics*. Peter Lang: Berlin, Germany.

Examples

```
sato_vartia(sugar, start="2018-12", end="2019-12")
sato_vartia(milk, start="2018-12", end="2020-01", interval=TRUE)
```

save_model

Saving the machine learning model on the disk

Description

This function saves a list of machine learning model elements on the disk, i.e. the resulting 8 files are written.

Usage

```
save_model(model = list(), dir = "ML_model")
```

Arguments

- | | |
|--------------------|--|
| <code>model</code> | A list of 8 elements which identify the previously built machine learning model (the list is obtained via the <code>model_classification</code> function). |
| <code>dir</code> | The name of the directory where the selected model should be saved. The directory with all necessary files will be created in the working directory. |

Value

This function saves a list of ML model elements on the disk, i.e. the resulting 8 files are written into the new directory specified by `dir`. The list should be obtained previously using the `model_classification` function. After saving the model, it can be loaded at any time by using the `load_model` function.

Examples

```
#Setting a temporal directory as a working director
## Not run: wd<-tempdir()
## Not run: setwd(wd)
#Building the model
#Building the model
## Not run: my.grid=list(eta=c(0.01,0.02,0.05),subsample=c(0.5))
## Not run: data_train<-dplyr::filter(dataCOICOP,dataCOICOP$time<=as.Date("2020-08-01"))
## Not run: data_test<-dplyr::filter(dataCOICOP,dataCOICOP$time>as.Date("2020-08-01"))
## Not run: ML<-model_classification(data_train,data_test,grid=my.grid,
indicators=c("prodID","unit","description"),key_words=c("milk"),rounds=50)
## End(Not run)
#Saving the model
## Not run: save_model(ML, dir="My_model")
```

SPQ	<i>Calculating the multilateral SPQ price index</i>
-----	---

Description

This function returns a value of the multilateral SPQ price index which is based on the relative price and quantity dissimilarity measure.

Usage

```
SPQ(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. '2019-03'.
end	The research period (as character) limited to the year and month, e.g. '2019-07'.
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start,end> are considered and start defines the base period (interval is set to TRUE).

Value

This function returns a value of the multilateral SPQ price index which is based on the relative price and quantity dissimilarity measure (see References). If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#),

[final_index](#) or [final_index2](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or [final_index2](#) function).

References

Diewert, E. (2020). *The Chain Drift Problem and Multilateral Indexes*. Chapter 6 in: Consumer Price Index Theory (draft)

Examples

```
SPQ(sugar, start="2018-12",end="2019-02")
SPQ(milk, start="2018-12",end="2019-12",interval=TRUE)
```

stuvel	<i>Calculating the bilateral Stuv​el price index</i>
--------	--

Description

This function returns a value (or vector of values) of the bilateral Stuv​el price index.

Usage

```
stuvel(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start,end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the bilateral Stuv​el price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Stuvel, G. (1957). *A New Index Number Formula*. *Econometrica*, 25, 123-131.
- (2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.
- Von der Lippe, P. (2007). *Index Theory and Price Statistics*. Peter Lang: Berlin, Germany.

Examples

```
stuvel(sugar, start="2018-12", end="2019-12")  
stuvel(milk, start="2018-12", end="2020-01", interval=TRUE)
```

sugar	<i>A real data set on sold sugar</i>
-------	--------------------------------------

Description

A collection of scanner data on the sale of sugar in one of Polish supermarkets in the period from December 2017 to October 2020

Usage

sugar

Format

A data frame with 6 columns and 7666 rows. The used variables are as follows:

time - Dates of transactions (Year-Month-Day)

prices - Prices of sold products [PLN]

quantities - Quantities of sold products [kg]

prodID - Unique product codes (data set contains 11 different prodIDs)

retID - Unique codes identifying outlets/retailer sale points (data set contains 20 different retIDs)

description Descriptions of sold sugar products (data set contains 3 different product descriptions)

tindex	<i>Calculating theoretical (expected) values of the unweighted price index</i>
--------	--

Description

This function calculates the theoretical value of the unweighted price index for lognormally distributed prices.

Usage

```
tindex(pmi = c(), psigma = c(), start, ratio = TRUE)
```

Arguments

pmi	A numeric vector indicating mi parameters for lognormally distributed prices from the subsequent months.
psigma	A numeric vector indicating sigma parameters for lognormally distributed prices from the subsequent months.
start	The first period in the generated data frame (as character) limited to the year and month, e.g. '2019-12'.
ratio	A logical parameter indicating how we define the theoretical unweighted price index. If it is set to TRUE, then the resulting value is a ratio of expected price values from compared months; otherwise the resulting value is the expected value of the ratio of prices from compared months.

Value

This function calculates the theoretical value of the unweighted price index for lognormally distributed prices (the month defined by start parameter plays a role of the fixed base period). The characteristics for these lognormal distributions are set by pmi and sigma parameters. The ratio parameter allows to control the definition of resulting theoretical price index values. The function provides a data frame consisting of dates and corresponding expected values of the theoretical unweighted price index. The generated dataset is ready for further price index calculations.

Examples

```
tindex(pmi=c(1,1.2,1.3),psigma=c(0.1,0.2,0.15),start="2020-01")
tindex(pmi=c(1,1.2,1.3),psigma=c(0.1,0.2,0.15),start="2020-01",ratio=FALSE)
```

tornqvist

*Calculating the bilateral Tornqvist price index***Description**

This function returns a value (or vector of values) of the bilateral Tornqvist price index.

Usage

```
tornqvist(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start, end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the bilateral Tornqvist price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Tornqvist, L. (1936). *The Bank of Finland's Consumption Price Index*. Bank of Finland Monthly Bulletin 10, 1-8.

(2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Examples

```
tornqvist(sugar, start="2018-12", end="2019-12")
tornqvist(milk, start="2018-12", end="2020-01", interval=TRUE)
```

tpd

*Calculating the multilateral TPD price index***Description**

This function returns a value of the multilateral TPD (Time Product Dummy) price index.

Usage

```
tpd(data, start, end, wstart = start, window = 13)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
wstart	The beginning of the time interval (which is used by multilateral methods) limited to the year and month, e.g. "2020-01".
window	The length of the time window (as positive integer: typically multilateral methods are based on the 13-month time window).

Value

This function returns a value of the multilateral TPD price index which considers the time window defined by wstart and window parameters. It measures the price dynamics by comparing period end to period start (both start and end must be inside the considered time window). Please note that a Weighted Least Squares (WLS) regression is run with the expenditure shares in each period serving as weights. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

de Haan, J. and F. Krsinich (2014). *Time Dummy Hedonic and Quality-Adjusted Unit Value Indexes: Do They Really Differ?* Paper presented at the Society for Economic Measurement Conference, 18-20 August 2014, Chicago, U.S.

Examples

```
tpd(milk, start="2019-01", end="2019-08", window=10)
tpd(milk, start="2018-12", end="2019-12")
```

tpd_fbew	<i>Extending the multilateral TPD price index by using the FBEW method.</i>
----------	---

Description

This function returns a value of the multilateral TPD price index (Time Product Dummy index) extended by using the FBEW (Fixed Base Monthly Expanding Window) method.

Usage

```
tpd_fbew(data, start, end)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".

Value

This function returns a value of the multilateral TPD price index extended by using the FBEW (Fixed Base Monthly Expanding Window) method. The FBEW method uses a time window with a fixed base month every year (December). The window is enlarged every month with one month in order to include information from a new month. The full window length (13 months) is reached in December of each year. The function measures the price dynamics between periods end and start. The month of the start parameter must be December. If the distance between end and start exceeds 13 months, then internal Decembers play a role of chain-linking months. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- de Haan, J. and F. Krsinich (2014). *Time Dummy Hedonic and Quality-Adjusted Unit Value Indexes: Do They Really Differ?* Paper presented at the Society for Economic Measurement Conference, 18-20 August 2014, Chicago, U.S.
- Chessa, A.G. (2016). *A New Methodology for Processing Scanner Data in the Dutch CPI*. Eurona 1/2016, 49-69.

Examples

```
tpd_fbew(milk, start="2018-12", end="2019-08")
```

tpd_fbmw	<i>Extending the multilateral TPD price index by using the FBMW method.</i>
----------	---

Description

This function returns a value of the multilateral TPD price index (Time Product Dummy index) extended by using the FBMW (Fixed Base Moving Window) method.

Usage

```
tpd_fbmw(data, start, end)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".

Value

This function returns a value of the multilateral TPD price index extended by using the FBMW (Fixed Base Moving Window) method. It measures the price dynamics between periods end and start and it uses a 13-month time window with a fixed base month taken as year(end)-1. If the distance between end and start exceeds 13 months, then internal Decembers play a role of chain-linking months. The month of the start parameter must be December. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

de Haan, J. and F. Krsinich (2014). *Time Dummy Hedonic and Quality-Adjusted Unit Value Indexes: Do They Really Differ?* Paper presented at the Society for Economic Measurement Conference, 18-20 August 2014, Chicago, U.S.

Lamboray, C.(2017). *The Geary Khamis index and the Lehr index: how much do they differ?* Paper presented at the 15th Ottawa Group meeting, 10-12 May 2017, Elville am Rhein, Germany.

Examples

```
tpd_fbmw(milk, start="2019-12", end="2020-04")
```

tpd_splice	<i>Extending the multilateral TPD price index by using window splicing methods.</i>
------------	---

Description

This function returns a value (or values) of the multilateral TPD price index (Time Product Dummy index) extended by using window splicing methods. Available splicing methods are: movement splice, window splice, half splice, mean splice and their additional variants: window splice on published indices (WISP), half splice on published indices (HASP) and mean splice on published indices (see References).

Usage

```
tpd_splice(
  data,
  start,
  end,
  window = 13,
  splice = "movement",
  interval = FALSE
)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
window	The length of the time window (as positive integer: typically multilateral methods are based on the 13-month time window).
splice	A character string indicating the splicing method. Available options are: "movement", "window", "half", "mean", "window_published", "half_published", "mean_published".
interval	A logical value indicating whether the function is to provide the price index comparing the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base multilateral indices are to be presented (the fixed base month is defined by start).

Value

This function returns a value or values (depending on interval parameter) of the multilateral TPD price index extended by using window splicing methods. Available splicing methods are: movement splice, window splice, half splice, mean splice and their additional variants: window splice on published indices (WISP), half splice on published indices (HASP) and mean splice on

published indices (see References). The time window starts in `start` and should consist of at least two months. To get information about both price index values and corresponding dates, please see functions: `price_index`, `price_indices` or `final_index`. The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the `final_index` or the `final_index2` function).

References

- Chessa, A. G. (2019). *A Comparison of Index Extension Methods for Multilateral Methods*. Paper presented at the 16th Meeting of the Ottawa Group on Price Indices, 8-10 May 2019, Rio de Janeiro, Brazil.
- de Haan, J., van der Grient, H.A. (2011). *Eliminating chain drift in price indexes based on scanner data*. Journal of Econometrics, 161, 36-46.
- de Haan, J. and F. Krsinich (2014). *Time Dummy Hedonic and Quality-Adjusted Unit Value Indexes: Do They Really Differ?* Paper presented at the Society for Economic Measurement Conference, 18-20 August 2014, Chicago, U.S.
- Krsinich, F. (2014). *The FEWS Index: Fixed Effects with a Window Splice? Non-Revisable Quality-Adjusted Price Indices with No Characteristic Information*. Paper presented at the UNECE-ILO Meeting of the Group of Experts on Consumer Price Indices, 2-4 May 2016, Geneva, Switzerland.
- de Haan, J.(2015). *A Framework for Large Scale Use of Scanner Data in the Dutch CPI*. Paper presented at the 14th Ottawa Group meeting, Tokyo, Japan.
- Diewert, W.E., and Fox, K.J. (2017). *Substitution Bias in Multilateral Methods for CPI Construction using Scanner Data*. Discussion paper 17-02, Vancouver School of Economics, The University of British Columbia, Vancouver, Canada.

Examples

```
tpd_splice(milk, start="2018-12", end="2020-02",splice="half")
tpd_splice(milk, start="2018-12", end="2020-02",window=10,interval=TRUE)
```

vartia

Calculating the bilateral Vartia-I price index

Description

This function returns a value (or vector of values) of the bilateral Vartia-I price index.

Usage

```
vartia(data, start, end, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start,end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the bilateral Vartia-I price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Vartia, Y. O. (1976). *Ideal Log-Change Index Numbers*. Scandinavian Journal of Statistics 3(3), 121-126.
- (2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.
- Von der Lippe, P. (2007). *Index Theory and Price Statistics*. Peter Lang: Berlin, Germany.

Examples

```
vartia(sugar, start="2018-12", end="2019-12")
vartia(milk, start="2018-12", end="2020-01", interval=TRUE)
```

walsh

Calculating the bilateral Walsh price index

Description

This function returns a value (or vector of values) of the bilateral Walsh price index.

Usage

```
walsh(data, start, end, interval = FALSE)
```

Arguments

<code>data</code>	The user's data frame with information about sold products. It must contain columns: <code>time</code> (as Date in format: year-month-day, e.g. '2020-12-01'), <code>prices</code> (as positive numeric), <code>quantities</code> (as positive numeric) and <code>prodID</code> (as numeric, factor or character).
<code>start</code>	The base period (as character) limited to the year and month, e.g. "2020-03".
<code>end</code>	The research period (as character) limited to the year and month, e.g. "2020-04".
<code>interval</code>	A logical value indicating whether the function is to compare the research period defined by <code>end</code> to the base period defined by <code>start</code> (then <code>interval</code> is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <code><start,end></code> are considered and <code>start</code> defines the base period (<code>interval</code> is set to TRUE).

Value

The function returns a value (or vector of values) of the bilateral Walsh price index depending on the `interval` parameter. If the `interval` parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Walsh, C. M. (1901). *The Measurement of General Exchange Value*. The MacMillan Company, New York.
- (2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.
- Von der Lippe, P. (2007). *Index Theory and Price Statistics*. Peter Lang: Berlin, Germany.

Examples

```
walsh(sugar, start="2018-12", end="2019-12")
walsh(milk, start="2018-12", end="2020-01", interval=TRUE)
```

wgeks

Calculating the multilateral WGEKS price index

Description

This function returns a value of the multilateral weighted WGEKS price index (to be more precise: the weighted GEKS index based on the Fisher formula).

Usage

```
wgeks(data, start, end, wstart = start, window = 13)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
wstart	The beginning of the time interval (which is used by multilateral methods) limited to the year and month, e.g. "2020-01".
window	The length of the time window (as positive integer: typically multilateral methods are based on the 13-month time window).

Value

This function returns a value of the multilateral weighted WGEKS price index (to be more precise: the weighted GEKS index based on the Fisher formula) which considers the time window defined by wstart and window parameters. It measures the price dynamics by comparing period end to period start (both start and end must be inside the considered time window). To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.
- Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.
- Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.

Examples

```
wgeks(milk, start="2019-01", end="2019-08",window=10)
wgeks(milk, start="2018-12", end="2019-12")
```

wgeksaqi

Calculating the multilateral WGEKS-AQI price index

Description

This function returns a value of the multilateral weighted WGEKS-AQI price index (to be more precise: the weighted GEKS index based on the asynchronous quality adjusted price index formula).

Usage

```
wgeksaqi(data, start, end, wstart = start, window = 13)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
wstart	The beginning of the time interval (which is used by multilateral methods) limited to the year and month, e.g. "2020-01".
window	The length of the time window (as positive integer: typically multilateral methods are based on the 13-month time window).

Value

This function returns a value of the multilateral weighted WGEKS-AQI price index (to be more precise: the weighted GEKS index based on the asynchronous quality adjusted price index formula) which considers the time window defined by wstart and window parameters. It measures the price dynamics by comparing period end to period start (both start and end must be inside the considered time window). To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.
- Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.
- Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.

Examples

```
wgeksaqi(milk, start="2019-01", end="2019-08",window=10)
wgeksaqi(milk, start="2018-12", end="2019-12")
```

wgeksaqi_fbew	<i>Extending the multilateral weighted GEKS-AQI price index by using the FBEW method.</i>
---------------	---

Description

This function returns a value of the multilateral weighted GEKS-AQI price index extended by using the FBEW (Fixed Base Monthly Expanding Window) method.

Usage

wgeksaqi_fbew(data, start, end)

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".

Value

This function returns a value of the multilateral weighted GEKS-AQI price index (the weighted GEKS index based on the asynchronous quality adjusted price index formula) extended by using the FBEW (Fixed Base Monthly Expanding Window) method. The FBEW method uses a time window with a fixed base month every year (December). The window is enlarged every month with one month in order to include information from a new month. The full window length (13 months) is reached in December of each year. The function measures the price dynamics between periods end and start. The month of the start parameter must be December. If the distance between end and start exceeds 13 months, then internal Decembers play a role of chain-linking months. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.

Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.

Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.

Chessa, A.G. (2016). *A New Methodology for Processing Scanner Data in the Dutch CPI*. Eurona 1/2016, 49-69.

Examples

```
wgeksaqi_fbew(milk, start="2018-12", end="2019-08")
```

wgeksaqi_fbmw	<i>Extending the multilateral weighted GEKS-AQI price index by using the FBMW method.</i>
---------------	---

Description

This function returns a value of the multilateral weighted GEKS-AQI price index extended by using the FBMW (Fixed Base Moving Window) method.

Usage

```
wgeksaqi_fbmw(data, start, end)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".

Value

This function returns a value of the multilateral weighted GEKS-AQI price index (the GEKS index based on the asynchronous quality adjusted price index formula) extended by using the FBMW (Fixed Base Moving Window) method. It measures the price dynamics between periods end and start and it uses a 13-month time window with a fixed base month taken as year(end)-1. If the distance between end and start exceeds 13 months, then internal Decembers play a role of chain-linking months. The month of the start parameter must be December. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.

Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.

Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.

Lamboray, C.(2017). *The Geary Khamis index and the Lehr index: how much do they differ?* Paper presented at the 15th Ottawa Group meeting, 10-12 May 2017, Elville am Rhein, Germany.

Examples

```
wgeksaqi_fbmw(milk, start="2019-12", end="2020-04")
```

wgeksaqi_splice	<i>Extending the multilateral weighted GEKS-AQI price index by using window splicing methods.</i>
-----------------	---

Description

This function returns a value (or values) of the multilateral weighted GEKS-AQI price index extended by using window splicing methods. Available splicing methods are: movement splice, window splice, half splice, mean splice and their additional variants: window splice on published indices (WISP), half splice on published indices (HASP) and mean splice on published indices (see References).

Usage

```
wgeksaqi_splice(
  data,
  start,
  end,
  window = 13,
  splice = "movement",
  interval = FALSE
)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
window	The length of the time window (as positive integer: typically multilateral methods are based on the 13-month time window).
splice	A character string indicating the splicing method. Available options are: "movement", "window", "half", "mean", "window_published", "half_published", "mean_published".
interval	A logical value indicating whether the function is to provide the price index comparing the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base multilateral indices are to be presented (the fixed base month is defined by start).

Value

This function returns a value or values (depending on interval parameter) of the multilateral weighted GEKS-AQI price index (the weighted GEKS index based on the asynchronous quality adjusted price index formula) extended by using window splicing methods. Available splicing methods are: movement splice, window splice, half splice, mean splice and their additional variants: window splice on published indices (WISP), half splice on published indices (HASP) and mean splice on published indices (see References). The time window starts in start and should consist of at least two months. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Chessa, A. G. (2019). *A Comparison of Index Extension Methods for Multilateral Methods*. Paper presented at the 16th Meeting of the Ottawa Group on Price Indices, 8-10 May 2019, Rio de Janeiro, Brazil.
- de Haan, J., van der Grient, H.A. (2011). *Eliminating chain drift in price indexes based on scanner data*. Journal of Econometrics, 161, 36-46.
- Krsinich, F. (2014). *The FEWS Index: Fixed Effects with a Window Splice? Non-Revisable Quality-Adjusted Price Indices with No Characteristic Information*. Paper presented at the UNECE-ILO Meeting of the Group of Experts on Consumer Price Indices, 2-4 May 2016, Geneva, Switzerland.
- de Haan, J.(2015). *A Framework for Large Scale Use of Scanner Data in the Dutch CPI*. Paper presented at the 14th Ottawa Group meeting, Tokyo, Japan.
- Diewert, W.E., and Fox, K.J. (2017). *Substitution Bias in Multilateral Methods for CPI Construction using Scanner Data*. Discussion paper 17-02, Vancouver School of Economics, The University of British Columbia, Vancouver, Canada.

Examples

```
wgeksaqi_splice(milk, start="2018-12", end="2020-02",splice="half")
wgeksaqi_splice(milk, start="2018-12", end="2020-02",window=10,interval=TRUE)
```

wgeksaqu

Calculating the multilateral WGEKS-AQU price index

Description

This function returns a value of the multilateral weighted WGEKS-AQU price index (to be more precise: the weighted GEKS index based on the asynchronous quality adjusted unit value formula).

Usage

```
wgeksaqu(data, start, end, wstart = start, window = 13)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
wstart	The beginning of the time interval (which is used by multilateral methods) limited to the year and month, e.g. "2020-01".
window	The length of the time window (as positive integer: typically multilateral methods are based on the 13-month time window).

Value

This function returns a value of the multilateral weighted WGEKS-AQU price index (to be more precise: the weighted GEKS index based on the asynchronous quality adjusted unit value formula) which considers the time window defined by wstart and window parameters. It measures the price dynamics by comparing period end to period start (both start and end must be inside the considered time window). To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.

Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.

Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.

Examples

```
wgeksaqu(milk, start="2019-01", end="2019-08",window=10)
wgeksaqu(milk, start="2018-12", end="2019-12")
```

wgeksaqu_fbew	<i>Extending the multilateral weighted GEKS-AQU price index by using the FBEW method.</i>
---------------	---

Description

This function returns a value of the multilateral weighted GEKS-AQU price index extended by using the FBEW (Fixed Base Monthly Expanding Window) method.

Usage

```
wgeksaqu_fbew(data, start, end)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".

Value

This function returns a value of the multilateral weighted GEKS-AQU price index (the weighted GEKS index based on the asynchronous quality adjusted unit value formula) extended by using the FBEW (Fixed Base Monthly Expanding Window) method. The FBEW method uses a time window with a fixed base month every year (December). The window is enlarged every month with one month in order to include information from a new month. The full window length (13 months) is reached in December of each year. The function measures the price dynamics between periods end and start. The month of the start parameter must be December. If the distance between end and start exceeds 13 months, then internal Decembers play a role of chain-linking months. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.
- Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.
- Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.
- Chessa, A.G. (2016). *A New Methodology for Processing Scanner Data in the Dutch CPI*. Eurona 1/2016, 49-69.

Examples

```
wgeksaqu_fbew(milk, start="2018-12", end="2019-08")
```

wgeksaqu_fbmw	<i>Extending the multilateral weighted GEKS-AQU price index by using the FBMW method.</i>
---------------	---

Description

This function returns a value of the multilateral weighted GEKS-AQU price index extended by using the FBMW (Fixed Base Moving Window) method.

Usage

wgeksaqu_fbmw(data, start, end)

Arguments

- | | |
|-------|---|
| data | The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character). |
| start | The base period (as character) limited to the year and month, e.g. "2019-12". |
| end | The research period (as character) limited to the year and month, e.g. "2020-04". |

Value

This function returns a value of the multilateral weighted GEKS-AQU price index (the GEKS index based on the asynchronous quality adjusted unit value formula) extended by using the FBMW (Fixed Base Moving Window) method. It measures the price dynamics between periods end and start and it uses a 13-month time window with a fixed base month taken as year(end)-1. If the distance between end and start exceeds 13 months, then internal Decembers play a role of chain-linking months. The month of the start parameter must be December. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.

Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.

Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.

Lamboray, C.(2017). *The Geary Khamis index and the Lehr index: how much do they differ?* Paper presented at the 15th Ottawa Group meeting, 10-12 May 2017, Elville am Rhein, Germany.

Examples

```
wgeksaqu_fbmw(milk, start="2019-12", end="2020-04")
```

wgeksaqu_splice	<i>Extending the multilateral weighted GEKS-AQU price index by using window splicing methods.</i>
-----------------	---

Description

This function returns a value (or values) of the multilateral weighted GEKS-AQU price index extended by using window splicing methods. Available splicing methods are: movement splice, window splice, half splice, mean splice and their additional variants: window splice on published indices (WISP), half splice on published indices (HASP) and mean splice on published indices (see References).

Usage

```
wgeksaqu_splice(
  data,
  start,
  end,
  window = 13,
  splice = "movement",
  interval = FALSE
)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
window	The length of the time window (as positive integer: typically multilateral methods are based on the 13-month time window).
splice	A character string indicating the splicing method. Available options are: "movement", "window", "half", "mean", "window_published", "half_published", "mean_published".
interval	A logical value indicating whether the function is to provide the price index comparing the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base multilateral indices are to be presented (the fixed base month is defined by start).

Value

This function returns a value or values (depending on interval parameter) of the multilateral weighted GEKS-AQU price index (the weighted GEKS index based on the asynchronous quality adjusted unit value formula) extended by using window splicing methods. Available splicing methods are: movement splice, window splice, half splice, mean splice and their additional variants: window splice on published indices (WISP), half splice on published indices (HASP) and mean splice on published indices (see References). The time window starts in start and should consist of at least two months. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Chessa, A. G. (2019). *A Comparison of Index Extension Methods for Multilateral Methods*. Paper presented at the 16th Meeting of the Ottawa Group on Price Indices, 8-10 May 2019, Rio de Janeiro, Brazil.
- de Haan, J., van der Grient, H.A. (2011). *Eliminating chain drift in price indexes based on scanner data*. Journal of Econometrics, 161, 36-46.
- Krsinich, F. (2014). *The FEWS Index: Fixed Effects with a Window Splice? Non-Revisable Quality-Adjusted Price Indices with No Characteristic Information*. Paper presented at the UNECE-ILO Meeting of the Group of Experts on Consumer Price Indices, 2-4 May 2016, Geneva, Switzerland.
- de Haan, J.(2015). *A Framework for Large Scale Use of Scanner Data in the Dutch CPI*. Paper presented at the 14th Ottawa Group meeting, Tokyo, Japan.
- Diewert, W.E., and Fox, K.J. (2017). *Substitution Bias in Multilateral Methods for CPI Construction using Scanner Data*. Discussion paper 17-02, Vancouver School of Economics, The University of British Columbia, Vancouver, Canada.

Examples

```
wgeksgaqi_splice(milk, start="2018-12", end="2020-02", splice="half")
wgeksgaqi_splice(milk, start="2018-12", end="2020-02", window=10, interval=TRUE)
```

wgeksgaqi

Calculating the multilateral WGEKS-GAQI price index

Description

This function returns a value of the multilateral weighted WGEKS-GAQI price index (to be more precise: the weighted GEKS index based on the geometric asynchronous quality adjusted price index formula).

Usage

```
wgeksgaqi(data, start, end, wstart = start, window = 13)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
wstart	The beginning of the time interval (which is used by multilateral methods) limited to the year and month, e.g. "2020-01".
window	The length of the time window (as positive integer: typically multilateral methods are based on the 13-month time window).

Value

This function returns a value of the multilateral weighted WGEKS-GAQI price index (to be more precise: the weighted GEKS index based on the geometric asynchronous quality adjusted price index formula) which considers the time window defined by wstart and window parameters. It measures the price dynamics by comparing period end to period start (both start and end must be inside the considered time window). To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.

Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.

Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.

Examples

```
wgeksgaqi(milk, start="2019-01", end="2019-08",window=10)
wgeksgaqi(milk, start="2018-12", end="2019-12")
```

wgeksgaqi_fbew	<i>Extending the multilateral weighted GEKS-GAQI price index by using the FBEW method.</i>
----------------	--

Description

This function returns a value of the multilateral weighted GEKS-GAQI price index extended by using the FBEW (Fixed Base Monthly Expanding Window) method.

Usage

```
wgeksgaqi_fbew(data, start, end)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".

Value

This function returns a value of the multilateral weighted GEKS-GAQI price index (the weighted GEKS index based on the geometric asynchronous quality adjusted price index formula) extended by using the FBEW (Fixed Base Monthly Expanding Window) method. The FBEW method uses a time window with a fixed base month every year (December). The window is enlarged every month with one month in order to include information from a new month. The full window length (13 months) is reached in December of each year. The function measures the price dynamics between periods end and start. The month of the start parameter must be December. If the distance between end and start exceeds 13 months, then internal Decembers play a role of chain-linking months. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.
- Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.
- Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.
- Chessa, A.G. (2016). *A New Methodology for Processing Scanner Data in the Dutch CPI*. Eurona 1/2016, 49-69.

Examples

```
wgeksgaqi_fbew(milk, start="2018-12", end="2019-08")
```

wgeksgaqi_fbmw	<i>Extending the multilateral weighted GEKS-GAQI price index by using the FBMW method.</i>
----------------	--

Description

This function returns a value of the multilateral weighted GEKS-GAQI price index extended by using the FBMW (Fixed Base Moving Window) method.

Usage

```
wgeksgaqi_fbmw(data, start, end)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".

Value

This function returns a value of the multilateral weighted GEKS-GAQI price index (the GEKS index based on the geometric asynchronous quality adjusted price index formula) extended by using the FBMW (Fixed Base Moving Window) method. It measures the price dynamics between periods end and start and it uses a 13-month time window with a fixed base month taken as year(end)-1. If the distance between end and start exceeds 13 months, then internal Decembers play a role of chain-linking months. The month of the start parameter must be December. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.

Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.

Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.

Lamboray, C.(2017). *The Geary Khamis index and the Lehr index: how much do they differ?* Paper presented at the 15th Ottawa Group meeting, 10-12 May 2017, Elville am Rhein, Germany.

Examples

```
wgeksgaqi_fbmw(milk, start="2019-12", end="2020-04")
```

wgeksgaqi_splice	<i>Extending the multilateral weighted GEKS-GAQI price index by using window splicing methods.</i>
------------------	--

Description

This function returns a value (or values) of the multilateral weighted GEKS-GAQI price index extended by using window splicing methods. Available splicing methods are: movement splice, window splice, half splice, mean splice and their additional variants: window splice on published indices (WISP), half splice on published indices (HASP) and mean splice on published indices (see References).

Usage

```
wgeksgaqi_splice(
  data,
  start,
  end,
  window = 13,
  splice = "movement",
  interval = FALSE
)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
window	The length of the time window (as positive integer: typically multilateral methods are based on the 13-month time window).
splice	A character string indicating the splicing method. Available options are: "movement", "window", "half", "mean", "window_published", "half_published", "mean_published".
interval	A logical value indicating whether the function is to provide the price index comparing the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base multilateral indices are to be presented (the fixed base month is defined by start).

Value

This function returns a value or values (depending on interval parameter) of the multilateral weighted GEKS-GAQI price index (the weighted GEKS index based on the geometric asynchronous quality adjusted price index formula) extended by using window splicing methods. Available splicing methods are: movement splice, window splice, half splice, mean splice and their additional variants: window splice on published indices (WISP), half splice on published indices (HASP) and mean splice on published indices (see References). The time window starts in start and should consist of at least two months. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Chessa, A. G. (2019). *A Comparison of Index Extension Methods for Multilateral Methods*. Paper presented at the 16th Meeting of the Ottawa Group on Price Indices, 8-10 May 2019, Rio de Janeiro, Brazil.
- de Haan, J., van der Grient, H.A. (2011). *Eliminating chain drift in price indexes based on scanner data*. Journal of Econometrics, 161, 36-46.
- Krsinich, F. (2014). *The FEWS Index: Fixed Effects with a Window Splice? Non-Revisable Quality-Adjusted Price Indices with No Characteristic Information*. Paper presented at the UNECE-ILO Meeting of the Group of Experts on Consumer Price Indices, 2-4 May 2016, Geneva, Switzerland.
- de Haan, J.(2015). *A Framework for Large Scale Use of Scanner Data in the Dutch CPI*. Paper presented at the 14th Ottawa Group meeting, Tokyo, Japan.
- Diewert, W.E., and Fox, K.J. (2017). *Substitution Bias in Multilateral Methods for CPI Construction using Scanner Data*. Discussion paper 17-02, Vancouver School of Economics, The University of British Columbia, Vancouver, Canada.

Examples

```
wgeksgaqi_splice(milk, start="2018-12", end="2020-02",splice="half")
wgeksgaqi_splice(milk, start="2018-12", end="2020-02",window=10,interval=TRUE)
```

wgeksgl

Calculating the multilateral WGEKS-GL price index

Description

This function returns a value of the multilateral weighted WGEKS-GL price index (to be more precise: the weighted GEKS index based on the geometric Laspeyres formula).

Usage

```
wgeksgl(data, start, end, wstart = start, window = 13)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
wstart	The beginning of the time interval (which is used by multilateral methods) limited to the year and month, e.g. "2020-01".
window	The length of the time window (as positive integer: typically multilateral methods are based on the 13-month time window).

Value

This function returns a value of the multilateral weighted WGEKS-GL price index (to be more precise: the weighted GEKS index based on the geometric Laspeyres formula) which considers the time window defined by wstart and window parameters. It measures the price dynamics by comparing period end to period start (both start and end must be inside the considered time window). To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.

Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.

Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.

Examples

```
wgeksgl(milk, start="2019-01", end="2019-08",window=10)
wgeksgl(milk, start="2018-12", end="2019-12")
```

wgeksgl_fbew	<i>Extending the multilateral weighted GEKS-GL price index by using the FBEW method.</i>
--------------	--

Description

This function returns a value of the multilateral weighted GEKS-GL price index extended by using the FBEW (Fixed Base Monthly Expanding Window) method.

Usage

```
wgeksgl_fbew(data, start, end)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".

Value

This function returns a value of the multilateral weighted GEKS-GL price index (the weighted GEKS index based on the geometric Laspeyres formula) extended by using the FBEW (Fixed Base Monthly Expanding Window) method. The FBEW method uses a time window with a fixed base month every year (December). The window is enlarged every month with one month in order to include information from a new month. The full window length (13 months) is reached in December of each year. The function measures the price dynamics between periods end and start. The month of the start parameter must be December. If the distance between end and start exceeds 13 months, then internal Decembers play a role of chain-linking months. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.
- Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.
- Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.
- Chessa, A.G. (2016). *A New Methodology for Processing Scanner Data in the Dutch CPI*. Eurona 1/2016, 49-69.

Examples

```
wgeksgl_fbew(milk, start="2018-12", end="2019-08")
```

wgeksgl_fbmw	<i>Extending the multilateral weighted GEKS-GL price index by using the FBMW method.</i>
--------------	--

Description

This function returns a value of the multilateral weighted GEKS-GL price index extended by using the FBMW (Fixed Base Moving Window) method.

Usage

```
wgeksgl_fbmw(data, start, end)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".

Value

This function returns a value of the multilateral weighted GEKS-GL price index (the GEKS index based on the geometric Laspeyres formula) extended by using the FBMW (Fixed Base Moving Window) method. It measures the price dynamics between periods end and start and it uses a 13-month time window with a fixed base month taken as year(end)-1. If the distance between end and start exceeds 13 months, then internal Decembers play a role of chain-linking months. The month of the start parameter must be December. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.
- Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.
- Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.
- Lamboray, C. (2017). *The Geary Khamis index and the Lehr index: how much do they differ?* Paper presented at the 15th Ottawa Group meeting, 10-12 May 2017, Elville am Rhein, Germany.

Examples

```
wgeksgl_fbmw(milk, start="2019-12", end="2020-04")
```

wgeksgl_splice	<i>Extending the multilateral weighted GEKS-GL price index by using window splicing methods.</i>
----------------	--

Description

This function returns a value (or values) of the multilateral weighted GEKS-GL price index extended by using window splicing methods. Available splicing methods are: movement splice, window splice, half splice, mean splice and their additional variants: window splice on published indices (WISP), half splice on published indices (HASP) and mean splice on published indices (see References).

Usage

```
wgeksgl_splice(
  data,
  start,
  end,
  window = 13,
  splice = "movement",
  interval = FALSE
)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
window	The length of the time window (as positive integer: typically multilateral methods are based on the 13-month time window).
splice	A character string indicating the splicing method. Available options are: "movement", "window", "half", "mean", "window_published", "half_published", "mean_published".
interval	A logical value indicating whether the function is to provide the price index comparing the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base multilateral indices are to be presented (the fixed base month is defined by start).

Value

This function returns a value or values (depending on interval parameter) of the multilateral weighted GEKS-GL price index (the weighted GEKS index based on the geometric Laspeyres formula) extended by using window splicing methods. Available splicing methods are: movement splice, window splice, half splice, mean splice and their additional variants: window splice on

published indices (WISP), half splice on published indices (HASP) and mean splice on published indices (see References). The time window starts in `start` and should consist of at least two months. To get information about both price index values and corresponding dates, please see functions: `price_index`, `price_indices` or `final_index`. The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the `final_index` or the `final_index2` function).

References

Chessa, A. G. (2019). *A Comparison of Index Extension Methods for Multilateral Methods*. Paper presented at the 16th Meeting of the Ottawa Group on Price Indices, 8-10 May 2019, Rio de Janeiro, Brazil.

de Haan, J., van der Grient, H.A. (2011). *Eliminating chain drift in price indexes based on scanner data*. Journal of Econometrics, 161, 36-46.

Krsinich, F. (2014). *The FEWS Index: Fixed Effects with a Window Splice? Non-Revisable Quality-Adjusted Price Indices with No Characteristic Information*. Paper presented at the UNECE-ILO Meeting of the Group of Experts on Consumer Price Indices, 2-4 May 2016, Geneva, Switzerland.

de Haan, J.(2015). *A Framework for Large Scale Use of Scanner Data in the Dutch CPI*. Paper presented at the 14th Ottawa Group meeting, Tokyo, Japan.

Diewert, W.E., and Fox, K.J. (2017). *Substitution Bias in Multilateral Methods for CPI Construction using Scanner Data*. Discussion paper 17-02, Vancouver School of Economics, The University of British Columbia, Vancouver, Canada.

Examples

```
wgeksgl_splice(milk, start="2018-12", end="2020-02",splice="half")
wgeksgl_splice(milk, start="2018-12", end="2020-02",window=10,interval=TRUE)
```

wgeksgl

Calculating the multilateral WGEKS-L price index

Description

This function returns a value of the multilateral weighted WGEKS-L price index (to be more precise: the weighted GEKS index based on the Laspeyres formula).

Usage

```
wgeksgl(data, start, end, wstart = start, window = 13)
```

Arguments

<code>data</code>	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
-------------------	---

start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
wstart	The beginning of the time interval (which is used by multilateral methods) limited to the year and month, e.g. "2020-01".
window	The length of the time window (as positive integer: typically multilateral methods are based on the 13-month time window).

Value

This function returns a value of the multilateral weighted WGEKS-L price index (to be more precise: the weighted GEKS index based on the Laspeyres formula) which considers the time window defined by wstart and window parameters. It measures the price dynamics by comparing period end to period start (both start and end must be inside the considered time window). To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.

Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.

Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.

Examples

```
wgeksl(milk, start="2019-01", end="2019-08",window=10)
wgeksl(milk, start="2018-12", end="2019-12")
```

wgeksl_fbew	<i>Extending the multilateral weighted GEKS-L price index by using the FBEW method.</i>
-------------	---

Description

This function returns a value of the multilateral weighted GEKS-L price index extended by using the FBEW (Fixed Base Monthly Expanding Window) method.

Usage

```
wgeksl_fbew(data, start, end)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".

Value

This function returns a value of the multilateral weighted GEKS-L price index (the weighted GEKS index based on the Laspeyres formula) extended by using the FBEW (Fixed Base Monthly Expanding Window) method. The FBEW method uses a time window with a fixed base month every year (December). The window is enlarged every month with one month in order to include information from a new month. The full window length (13 months) is reached in December of each year. The function measures the price dynamics between periods end and start. The month of the start parameter must be December. If the distance between end and start exceeds 13 months, then internal Decembers play a role of chain-linking months. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.

Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.

Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.

Chessa, A.G. (2016). *A New Methodology for Processing Scanner Data in the Dutch CPI*. Eurona 1/2016, 49-69.

Examples

```
wgeksl_fbmw(milk, start="2018-12", end="2019-08")
```

wgeksl_fbmw	<i>Extending the multilateral weighted GEKS-L price index by using the FBMW method.</i>
-------------	---

Description

This function returns a value of the multilateral weighted GEKS-L price index extended by using the FBMW (Fixed Base Moving Window) method.

Usage

```
wgeksl_fbmw(data, start, end)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".

Value

This function returns a value of the multilateral weighted GEKS-L price index (the GEKS index based on the Laspeyres formula) extended by using the FBMW (Fixed Base Moving Window) method. It measures the price dynamics between periods end and start and it uses a 13-month time window with a fixed base month taken as year(end)-1. If the distance between end and start exceeds 13 months, then internal Decembers play a role of chain-linking months. The month of the start parameter must be December. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.

Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.

Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.

Lamboray, C.(2017). *The Geary Khamis index and the Lehr index: how much do they differ?* Paper presented at the 15th Ottawa Group meeting, 10-12 May 2017, Elville am Rhein, Germany.

Examples

```
wgeksl_fbmw(milk, start="2019-12", end="2020-04")
```

wgeksl_splice	<i>Extending the multilateral weighted GEKS-L price index by using window splicing methods.</i>
---------------	---

Description

This function returns a value (or values) of the multilateral weighted GEKS-L price index extended by using window splicing methods. Available splicing methods are: movement splice, window splice, half splice, mean splice and their additional variants: window splice on published indices (WISP), half splice on published indices (HASP) and mean splice on published indices (see References).

Usage

```
wgeksl_splice(
  data,
  start,
  end,
  window = 13,
  splice = "movement",
  interval = FALSE
)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
window	The length of the time window (as positive integer: typically multilateral methods are based on the 13-month time window).
splice	A character string indicating the splicing method. Available options are: "movement", "window", "half", "mean", "window_published", "half_published", "mean_published".
interval	A logical value indicating whether the function is to provide the price index comparing the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base multilateral indices are to be presented (the fixed base month is defined by start).

Value

This function returns a value or values (depending on interval parameter) of the multilateral weighted GEKS-L price index (the weighted GEKS index based on the Laspeyres formula) extended by using window splicing methods. Available splicing methods are: movement splice, window splice, half splice, mean splice and their additional variants: window splice on published indices (WISP), half splice on published indices (HASP) and mean splice on published indices (see References). The time window starts in start and should consist of at least two months. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Chessa, A. G. (2019). *A Comparison of Index Extension Methods for Multilateral Methods*. Paper presented at the 16th Meeting of the Ottawa Group on Price Indices, 8-10 May 2019, Rio de Janeiro, Brazil.
- de Haan, J., van der Grient, H.A. (2011). *Eliminating chain drift in price indexes based on scanner data*. Journal of Econometrics, 161, 36-46.
- Krsinich, F. (2014). *The FEWS Index: Fixed Effects with a Window Splice? Non-Revisable Quality-Adjusted Price Indices with No Characteristic Information*. Paper presented at the UNECE-ILO Meeting of the Group of Experts on Consumer Price Indices, 2-4 May 2016, Geneva, Switzerland.
- de Haan, J.(2015). *A Framework for Large Scale Use of Scanner Data in the Dutch CPI*. Paper presented at the 14th Ottawa Group meeting, Tokyo, Japan.
- Diewert, W.E., and Fox, K.J. (2017). *Substitution Bias in Multilateral Methods for CPI Construction using Scanner Data*. Discussion paper 17-02, Vancouver School of Economics, The University of British Columbia, Vancouver, Canada.

Examples

```
wgeksl_splice(milk, start="2018-12", end="2020-02",splice="half")
wgeksl_splice(milk, start="2018-12", end="2020-02",window=10,interval=TRUE)
```

wgeks_fbew	<i>Extending the multilateral weighted GEKS price index by using the FBEW method.</i>
------------	---

Description

This function returns a value of the multilateral weighted GEKS price index extended by using the FBEW (Fixed Base Monthly Expanding Window) method.

Usage

```
wgeks_fbew(data, start, end)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".

Value

This function returns a value of the multilateral weighted GEKS price index (the weighted GEKS index based on the Fisher formula) extended by using the FBEW (Fixed Base Monthly Expanding Window) method. The FBEW method uses a time window with a fixed base month every year (December). The window is enlarged every month with one month in order to include information from a new month. The full window length (13 months) is reached in December of each year. The function measures the price dynamics between periods end and start. The month of the start parameter must be December. If the distance between end and start exceeds 13 months, then internal Decembers play a role of chain-linking months. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.
- Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.
- Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.
- Chessa, A.G. (2016). *A New Methodology for Processing Scanner Data in the Dutch CPI*. Eurona 1/2016, 49-69.

Examples

```
wgeks_fbmw(milk, start="2018-12", end="2019-08")
```

wgeks_fbmw	<i>Extending the multilateral weighted GEKS price index by using the FBMW method.</i>
------------	---

Description

This function returns a value of the multilateral weighted GEKS price index extended by using the FBMW (Fixed Base Moving Window) method.

Usage

```
wgeks_fbmw(data, start, end)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day, e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".

Value

This function returns a value of the multilateral weighted GEKS price index (the weighted GEKS index based on the Fisher formula) extended by using the FBMW (Fixed Base Moving Window) method. It measures the price dynamics between periods end and start and it uses a 13-month time window with a fixed base month taken as year(end)-1. If the distance between end and start exceeds 13 months, then internal Decembers play a role of chain-linking months. The month of the start parameter must be December. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Gini, C. (1931). *On the Circular Test of Index Numbers*. Metron 9:9, 3-24.
- Elteto, O., and Koves, P. (1964). *On a Problem of Index Number Computation Relating to International Comparisons*. Statisztikai Szemle 42, 507-518.
- Szulc, B. (1983). *Linking Price Index Numbers*. In: Price Level Measurement, W. E. Diewert and C. Montmarquette (eds.), 537-566.
- Lamboray, C.(2017). *The Geary Khamis index and the Lehr index: how much do they differ?* Paper presented at the 15th Ottawa Group meeting, 10-12 May 2017, Elville am Rhein, Germany.

Examples

```
wgeks_fbmw(milk, start="2019-12", end="2020-04")
```

wgeks_splice	<i>Extending the multilateral weighted GEKS price index by using window splicing methods.</i>
--------------	---

Description

This function returns a value (or values) of the multilateral weighted GEKS price index extended by using window splicing methods. Available splicing methods are: movement splice, window splice, half splice, mean splice and their additional variants: window splice on published indices (WISP), half splice on published indices (HASP) and mean splice on published indices (see References).

Usage

```
wgeks_splice(
  data,
  start,
  end,
  window = 13,
  splice = "movement",
  interval = FALSE
)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2019-12".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
window	The length of the time window (as positive integer: typically multilateral methods are based on the 13-month time window).
splice	A character string indicating the splicing method. Available options are: "movement", "window", "half", "mean", "window_published", "half_published", "mean_published".
interval	A logical value indicating whether the function is to provide the price index comparing the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base multilateral indices are to be presented (the fixed base month is defined by start).

Value

This function returns a value or values (depending on interval parameter) of the multilateral weighted GEKS price index (the weighted GEKS index based on the Fisher formula) extended by using window splicing methods. Available splicing methods are: movement splice, window splice, half splice, mean splice and their additional variants: window splice on published indices (WISP), half splice on published indices (HASP) and mean splice on published indices (see References). The time window starts in start and should consist of at least two months. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

- Chessa, A. G. (2019). *A Comparison of Index Extension Methods for Multilateral Methods*. Paper presented at the 16th Meeting of the Ottawa Group on Price Indices, 8-10 May 2019, Rio de Janeiro, Brazil.
- de Haan, J., van der Grient, H.A. (2011). *Eliminating chain drift in price indexes based on scanner data*. Journal of Econometrics, 161, 36-46.
- Krsinich, F. (2014). *The FEWS Index: Fixed Effects with a Window Splice? Non-Revisable Quality-Adjusted Price Indices with No Characteristic Information*. Paper presented at the UNECE-ILO Meeting of the Group of Experts on Consumer Price Indices, 2-4 May 2016, Geneva, Switzerland.
- de Haan, J.(2015). *A Framework for Large Scale Use of Scanner Data in the Dutch CPI*. Paper presented at the 14th Ottawa Group meeting, Tokyo, Japan.
- Diewert, W.E., and Fox, K.J. (2017). *Substitution Bias in Multilateral Methods for CPI Construction using Scanner Data*. Discussion paper 17-02, Vancouver School of Economics, The University of British Columbia, Vancouver, Canada.

Examples

```
wgeks_splice(milk, start="2018-12", end="2020-02",splice="half")
wgeks_splice(milk, start="2018-12", end="2020-02",window=10,interval=TRUE)
```

young	<i>Calculating the bilateral Young price index</i>
-------	--

Description

This function returns a value (or vector of values) of the bilateral Young price index.

Usage

```
young(data, start, end, base = start, interval = FALSE)
```

Arguments

data	The user's data frame with information about sold products. It must contain columns: time (as Date in format: year-month-day,e.g. '2020-12-01'), prices (as positive numeric), quantities (as positive numeric) and prodID (as numeric, factor or character).
start	The base period (as character) limited to the year and month, e.g. "2020-03".
end	The research period (as character) limited to the year and month, e.g. "2020-04".
base	The prior period used in the Young price index formula (as character) limited to the year and month, e.g. "2020-01"
interval	A logical value indicating whether the function is to compare the research period defined by end to the base period defined by start (then interval is set to FALSE) or all fixed base indices are to be calculated. In this latter case, all months from the time interval <start,end> are considered and start defines the base period (interval is set to TRUE).

Value

The function returns a value (or vector of values) of the bilateral Young price index depending on the interval parameter. If the interval parameter is set to TRUE, the function returns a vector of price index values without dates. To get information about both price index values and corresponding dates, please see functions: [price_index](#), [price_indices](#) or [final_index](#). The function does not take into account aggregating over outlets or product subgroups (to consider these types of aggregating, please use the [final_index](#) or the [final_index2](#) function).

References

Young, A. H. (1992). *Alternative Measures of Change in Real Output and Prices*. Survey of Current Business, 72, 32-48.

(2004). *Consumer Price Index Manual. Theory and practice*. ILO/IMF/OECD/UNECE/Eurostat/The World Bank, International Labour Office (ILO), Geneva.

Examples

```
young(sugar, start="2019-01", end="2020-01", base="2018-12")  
young(milk, start="2018-12", end="2020-01", interval=TRUE)
```

Index

* datasets

- coffee, [48](#)
 - dataAGGR, [54](#)
 - dataCOICOP, [55](#)
 - dataMATCH, [55](#)
 - dataU, [56](#)
 - milk, [140](#)
 - sugar, [165](#)
- agmean, [5](#), [148](#)
- available, [6](#), [147](#)
- banajree, [7](#), [148](#)
- bialek, [8](#), [148](#)
- bmw, [9](#), [148](#)
- carli, [10](#), [148](#)
- ccdi, [11](#), [150](#)
- ccdi_fbew, [12](#), [151](#)
- ccdi_fbmw, [13](#), [151](#)
- ccdi_splice, [14](#), [150](#)
- chagmean, [16](#), [149](#)
- chbanajree, [17](#), [149](#)
- chbialek, [18](#), [149](#)
- chbmw, [19](#), [149](#)
- chcarli, [20](#), [149](#)
- chcswd, [21](#), [149](#)
- chd Davies, [22](#)
- chdrobisch, [23](#), [149](#)
- chdutot, [24](#), [149](#)
- chfisher, [25](#), [149](#)
- chgeary_khamis, [26](#), [149](#)
- chgeohybrid, [27](#), [149](#)
- chgeolaspeyres, [28](#), [149](#)
- chgeolowe, [29](#), [149](#)
- chgeopaasche, [30](#), [149](#)
- chgeoyoung, [31](#), [149](#)
- chharmonic, [32](#), [149](#)
- chhybrid, [33](#), [149](#)
- chjevons, [34](#), [149](#)
- chlaspeyres, [35](#), [149](#)
- chlehr, [36](#), [149](#)
- chlloyd_moulton, [37](#), [149](#)
- chlowe, [38](#), [149](#)
- chmarshall_edgeworth, [39](#), [149](#)
- chpaasche, [40](#), [149](#)
- chpalgrave, [41](#), [149](#)
- chsato_vartia, [42](#), [149](#)
- chstuvel, [43](#), [149](#)
- chtornqvist, [44](#), [149](#)
- chvartia, [45](#), [149](#)
- chwalsh, [46](#), [149](#)
- chyoung, [47](#), [149](#)
- coffee, [48](#), [147](#)
- compare_distances, [49](#), [152](#)
- compare_final_indices, [50](#), [53](#), [152](#)
- compare_indices, [51](#), [152](#)
- cswd, [53](#), [148](#)
- data_aggregating, [57](#), [147](#)
- data_check, [57](#), [147](#)
- data_classifying, [58](#), [147](#)
- data_filtering, [59](#), [147](#)
- data_matching, [60](#), [64](#), [145–147](#), [152](#), [158](#)
- data_norm, [62](#), [147](#)
- data_preparing, [63](#), [147](#)
- data_selecting, [64](#), [65](#), [147](#)
- data_unit, [66](#), [147](#)
- dataAGGR, [54](#), [147](#)
- dataCOICOP, [55](#), [147](#)
- dataMATCH, [55](#), [147](#)
- dataU, [56](#), [147](#)
- davies, [67](#), [148](#), [149](#)
- dissimilarity, [68](#)
- dissimilarity_fig, [69](#), [147](#)
- drobisch, [70](#), [148](#)
- dutot, [71](#), [148](#)
- final_index, [6](#), [8–37](#), [39–48](#), [53](#), [54](#), [64](#), [67](#),
[70](#), [71](#), [72](#), [76–81](#), [83–86](#), [88–91](#),

- 93–96, 98–101, 103–106, 108–111,
 113–115, 117, 119–127, 129–134,
 136, 137, 143, 144, 152, 154, 156,
 162, 164, 167–170, 172–178,
 180–183, 185–188, 190–193,
 195–199, 201–204
 final_index2, 6, 8–37, 39–48, 54, 64, 67, 70,
 71, 74, 76–81, 83–86, 88–91, 93–96,
 98–101, 103–106, 108–111,
 113–115, 117, 119–127, 129–134,
 136, 137, 143, 144, 152, 154, 156,
 162, 164, 167–170, 172–178,
 180–183, 185–188, 190–193,
 195–199, 201–204
 fisher, 76, 148
 geary_khamis, 77, 148
 geks, 78, 150
 geks_fbew, 114, 151
 geks_fbmw, 115, 151
 geks_splice, 116, 150
 geksaqi, 79, 150
 geksaqi_fbew, 80, 151
 geksaqi_fbmw, 81, 151
 geksaqi_splice, 82, 150
 geksaqu, 84, 150
 geksaqu_fbew, 85, 151
 geksaqu_fbmw, 86, 151
 geksaqu_splice, 87, 150
 geksgaqi, 89, 150
 geksgaqi_fbew, 90, 151
 geksgaqi_fbmw, 91, 151
 geksgaqi_splice, 92, 150
 geksgl, 94, 150
 geksgl_fbew, 95, 151
 geksgl_fbmw, 96, 151
 geksgl_splice, 97, 150
 geksj, 99, 150
 geksj_fbew, 100, 151
 geksj_fbmw, 101, 151
 geksj_splice, 102, 150
 geksl, 104, 150
 geksl_fbew, 105, 151
 geksl_fbmw, 106, 151
 geksl_splice, 107, 150
 geksw, 109, 150
 geksw_fbew, 110, 151
 geksw_fbmw, 111, 151
 geksw_splice, 112, 150
 generate, 117, 147
 geohybrid, 119, 148
 geolaspeyres, 120, 148
 geolowe, 121, 148
 geopaasche, 122, 148
 geoyoung, 123, 148
 gk, 26, 77, 124, 150
 gk_fbew, 125, 151
 gk_fbmw, 126, 151
 gk_splice, 127, 150
 harmonic, 128, 148
 hybrid, 129, 148
 jevons, 130, 148
 laspeyres, 131, 148
 lehr, 132, 148
 lloyd_moulton, 133, 148
 load_model, 134, 147
 lowe, 135, 148
 marshall_edgeworth, 136, 148
 matched, 137, 147
 matched_fig, 138, 147
 matched_index, 138, 139, 139, 147
 milk, 140, 147
 model_classification, 141, 147
 paasche, 143, 148
 palgrave, 144, 148
 pqcor, 145, 147
 pqcor_fig, 145, 147
 price_index, 6, 8–37, 39–48, 54, 67, 70, 71,
 76–81, 83–86, 88–91, 93–96,
 98–101, 103–106, 108–111,
 113–115, 117, 119–127, 129–134,
 136, 137, 143, 144, 152, 153,
 162–164, 167–170, 172–178,
 180–183, 185–188, 190–193,
 195–199, 201–204
 price_indices, 6, 8–37, 39–48, 54, 67, 70,
 71, 76–81, 83–86, 88–91, 93–96,
 98–101, 103–106, 108–111,
 113–115, 117, 119–127, 129–134,
 136, 137, 143, 144, 152, 154,
 162–164, 167–170, 172–178,
 180–183, 185–188, 190–193,
 195–199, 201–204

PriceIndices, [52](#), [72](#), [75](#), [146](#), [153](#), [155](#)
prices, [147](#), [152](#)

QU, [150](#), [156](#)

quantities, [147](#), [157](#)

sales, [147](#), [158](#)

sales_groups, [147](#), [159](#)

sales_groups2, [147](#), [160](#)

sato_vartia, [148](#), [161](#)

save_model, [147](#), [162](#)

SPQ, [150](#), [163](#)

stuvel, [148](#), [164](#)

sugar, [147](#), [165](#)

tindex, [147](#), [166](#)

tornqvist, [148](#), [167](#)

tpd, [150](#), [168](#)

tpd_fbew, [151](#), [169](#)

tpd_fbmw, [151](#), [170](#)

tpd_splice, [150](#), [171](#)

vartia, [148](#), [172](#)

walsh, [148](#), [173](#)

wgeks, [150](#), [174](#)

wgeks_fbew, [151](#), [200](#)

wgeks_fbmw, [151](#), [201](#)

wgeks_splice, [150](#), [202](#)

wgeksaqi, [150](#), [175](#)

wgeksaqi_fbew, [151](#), [177](#)

wgeksaqi_fbmw, [151](#), [178](#)

wgeksaqi_splice, [150](#), [179](#)

wgeksaqu, [150](#), [180](#)

wgeksaqu_fbew, [151](#), [181](#)

wgeksaqu_fbmw, [151](#), [183](#)

wgeksaqu_splice, [150](#), [184](#)

wgeksgaqi, [150](#), [185](#)

wgeksgaqi_fbew, [151](#), [186](#)

wgeksgaqi_fbmw, [151](#), [188](#)

wgeksgaqi_splice, [150](#), [189](#)

wgeksgl, [150](#), [190](#)

wgeksgl_fbew, [151](#), [191](#)

wgeksgl_fbmw, [151](#), [193](#)

wgeksgl_splice, [150](#), [194](#)

wgekssl, [150](#), [195](#)

wgekssl_fbew, [151](#), [196](#)

wgekssl_fbmw, [151](#), [197](#)

wgekssl_splice, [150](#), [198](#)

young, [148](#), [204](#)