


**K.S. INSTITUTE OF TECHNOLOGY, BANGALORE - 560109****2nd SESSIONAL TEST QUESTION PAPER 2018-19 Even SEMESTER****SET - A/B**

USN

Degree : B.E**Semester : IV****Branch : Computer Science & Engineering****Subject Code : 17CS43****Subject Title : Design and Analysis of Algorithms****Date : 2019-04-16****Duration : 90 Minutes****Max Marks : 30****Note: Answer ONE full question from each part.**

Q No.	Question	Marks
PART-A		
1(a)	Use Divide and conquer approach and construct an algorithm to find k^{th} smallest element in the given sequence of n elements. Hint: Use the idea of quicksort except that only one sub-problem has to be solved. Identify which subsequence contains the k^{th} smallest element and use that subsequence to find the solution.	5
Sch & Ans	Sch:3 marks for identifying sub-problem and 2 marks for algo Ans: Take the first element as pivot and using quicksort identify its correct position in sorted order. Let this position be p . Now we have 3 choices. $p < k$: In this k^{th} element is in 2^{nd} partition, and its we need to search $(k-p)^{\text{th}}$ smallest element in 2^{nd} partition. $p = k$: This implies that we have found k^{th} smallest element $p > k$: This implies that k^{th} smallest element is in first partition and we need to find k^{th} smallest element if first partition. Thus, after the partition of the input using pivot, we are working with only 1 sub-problem. This would give a solution in $O(n)$ time.	
(b)	Make use of fractional knapsack algorithm to build a solution for the instance $n=7$, knapsack size $m=15$, profits $p_1=10, p_2=5, p_3=15, p_4=7, p_5=6, p_6=18, p_7=3$, and weights as $w_1=2, w_2=3, w_3=5, w_4=7, w_5=1, w_6=4, w_7=1$.	5
Sch & Ans	Sch:1 mark for sorting weights as per profit/weights, 4 marks for generating the solution Ans: Ordering weights in non-increasing order of profit are $p_5/w_5=6, p_1/w_1=5, p_6/w_6=4.5, p_3/w_3=3, p_7/w_7=3, p_2/w_2=1.5, p_4/w_4=1$ Thus picking up weights till it becomes 15 would be as follows $w_5=1, w_1=2, w_6=4, w_3=5, w_7=1, w_2=2$ (Take partial weight of w_2) Total profit: $6+10+18+15+3+2*5/3=3.33=55.33$	
(c)	Consider that a country has coins in the denominations of Rs 14, 12, 5, and 1. Show an example value to prove that greedy algorithm always does not generate change with minimum number of coins.	5
Sch & Ans	Sch:2 marks for identifying proper example value and 1 mark for generating change as per algo, 2 marks for optimal solution. Ans: Consider the change value to be given as 24.	

	<p>As per greedy algorithm, the change given would require 3 coins Rs 14: 1 coin Rs 5 : 2 coins</p> <p>The optimal solution for coin change would require 2 coins Rs 12: 2 coins</p>	
	OR	
2(a)	Analyze time complexity for QuickSort in worst case. Hint: Define and explain the recurrence relation for worst case and solve the same.	5
Sch & Ans	<p>Sch: 2 marks for identifying pivot position for worst case, 1 mark for writing recurrence relation and 2 marks for solving recurrence equation</p> <p>For worst case performance, portioning of input array of size k should split as skewed as possible i.e. one partition should have only 0 element, and other partition should have k-1 elements.</p> <p>Thus, the recurrence relation becomes $T(n) = T(n-1) + O(n)$ (after partition we need to merge n elements) Solving the recurrence relation gives $T(n) = O(n^2)$</p>	
(b)	<p>Consider <i>Dijkstra's</i> algorithm to find the single source shortest path for a weighted graph. Identify the changes that you need to make in this algorithm to find a shortest path between given two vertices i.e. develop the algorithm for single-pair-shortest-paths problem.</p>	5
Sch & Ans	<p>Sch: 2 marks for identifying changes and 3 marks for the algorithm.</p> <p>Ans: The major change is in the for loop where we iterate it $V -1$ times, Iterate this till destination node is discovered, The key part of algorithm would be as below for $i=0$ to $V -1$ do $u = \text{DeleteMin}(Q)$ //time implementation based $V_T = V_T \cup \{u\}$ If $u == \text{destination vertex}$ Break; //single source single dest path is found. for every vertex $w \in V - V_T$ adjacent to u, do if $d_u + \text{weight}(u, w) < d_w$, then $d_w \leftarrow d_u + \text{weight}(u, w)$ $p_w \leftarrow u$ Decrease(Q, w, d_w) //time implementation based fi end //for $w \in V - V_T$ end //for $i=0$</p>	
(c)	<p>Apply the algorithm developed in Q2(b) to find the shortest path from node F to node B. Compare the path thus found using this algorithm with actual shortest path and explain the difference.</p> 	5
Sch	Sch: 2 marks for computing path from F to B, 2 marks for identifying optimal path, and 1	

& Ans	marks difference explanation Ans: The path from F to B using Dijkstra's algorithm $F \rightarrow D \rightarrow B$ with a total path length 3. The optimal path from F to B is $F \rightarrow C \rightarrow A \rightarrow B$ with a total path length of -4. The difference arises because Dijkstra's algorithm does not work with negative weights for edges.	
	PART-B	
3(a)	Illustrate the product $P(x)*Q(x)$ computation manually using divide and conquer multiplication approach for following polynomials. $P(x) = 0+1x+2x^2+3x^3+...+7x^7$ $Q(x) = 8+7x+6x^2+5x^3+...+1x^7$	5
Sch & Ans	Sch: 2 marks for defining the approach and 3 marks for solving Ans: Write $P(x)$ and $Q(x)$ as $P(x)=P_1(x)+x^4P_2(x)$ $Q(x)=Q_1(x)+x^4Q_2(x)$ $C_1=P_1Q_1$ $C_2=P_2Q_2$ $C_3=[(P_1+P_2)*(Q_1+Q_2) - C_1 - C_2]$ Compute $P(x)*Q(x)$ as $C_1+x^7 C_2+x^4 C_3$, and proceed in this manner	
(b)	Construct a Minimum Cost Spanning Tree using Prim's algorithm for the graph shown in Q2(c) starting from node C as the root of the spanning tree. Please note that some edges have negative weights associated with them	5
Sch & Ans	Sch: 1 mark each for adding each node other than node C Ans: The nodes and edges will be added in below order C: B: {C,B} A: {B,A} D: {B,D} E: {D,E} F: {C,F}	
(c)	Analyze the time complexity of <i>Prim's</i> algorithm using both <i>Adjacency Martrix</i> and <i>Adjacency List</i> representation.	5
Sch & Ans	Sch: 3 marks for complexity analysis using Adjacency Matrix and 2 marks for using Adjacency List Ans: For prim's algorithm, for loop runs $ V $ times, and in each iteration we find next nodes having minimum cost edge. Each edge would contribute to change of node weight only 1 time. Thus, total number of times, weight of node is reduced is $O(E)$. When using Adjacency matrix, maintain the nodes in an unsorted array and finding a minimum weight node will take $O(V)$ time. Since there are $ V -1$ iterations, thus total time complexity using Adjacency matrix is $O(V ^2)$ When using Adjacency list, we maintain the node weights in a priority queue. Thus find min takes $O(1)$ time, but once find min node is removed and weights of other nodes are adjusted, each weight adjustment may take $O(\lg V)$ time. Since this weight adjustment can be done for each edge, the total time complexity is $O(E \lg V)$.	

	OR	
4(a)	<p>For the graph below, Identify and List all possible topological sorting orders.</p> <pre> graph TD B((B)) --> A((A)) B((B)) --> D((D)) E((E)) --> A((A)) E((E)) --> F((F)) D((D)) --> C((C)) C((C)) --> F((F)) </pre>	5
Sch & Ans	<p>Sch: 1 mark each for first 5 topological ordering list. Ans Order 1: B E A D C F Order 2: B E D A C F Order 3: B E D C A F Order 4: B E D C F A Order 5: E B A D C F Order 6: E B D A C F Order 7: E B D C A F Order 8: E B D C F A Order 9: B D C E A F Order 10: B D E C A F Order 11: B D E A C F</p>	
(b)	Analyze the time complexity of Kruskal's algorithm using <i>Union-Find</i> with fixed cost of Union operation as $O(1)$ and varying cost of Find operation.	5
Sch & Ans	<p>Sch: 2 marks for cost analysis using Union() operation, 2 marks for cost analysis using Find() operation and 1 marks total cost analysis Ans: Cycle checking is done for each edge i.e. top loop runs E times. Union operation is done $V -1$ times and thus total cost of union operation is $O(V)$ Find operation requires traversing the tree and depth of tree may be $O(\lg V)$. Thus, total find cost could be $O(V * \lg V)$ Thus, total time complexity is $O(E + V * \lg V)$ in addition to sorting all edge by their weights.</p>	
(c)	Consider the graph as shown in Q2(c), and develop Union Find trees to check for cycle formation when considering each edge for Minimum Cost Spanning Tree.	5
Sch & Ans	<p>Sch: 1 mark for taking each node and making it a union with other set except the first node. Ans: Following edges will be added to spanning tree (A, B)=-5, B→A(2), C→C(1), D→D(1), E→E(1), F→F(1) (D, E)=-3, B→A(2), C→C(1), E→D(2), F→F(1) (B, C)=-1, {B,C}→A(3), E→D(2), F→F(1) (B, D)=-1, {{{E→D}→B},C}→A(5), F→F(1) (C, F)=2, {{{E→D}→B},{F→C}}→A(6)</p>	