

UX-0002 — Butlerly Version 1 User Journey Map

Version 1.0

Purpose

This document defines the end-to-end user journeys for Butlerly Version 1. It converts the principles in UX-0001 into observable user behavior across smartphone, tablet, and desktop. The journeys are device-aware but share one mental model, one data model, and one trusted Butlerly identity.

Design Premise

Butlerly is mobile-first and supports three native experiences:

- Smartphone: capture, quick review, search, notifications, and short assistant interactions.
- Tablet: review, organize, compare, and continue work comfortably.
- Desktop: deep search, bulk operations, import, export, advanced settings, and complex corrections.

The experience principle is:

Capture anywhere. Continue anywhere. Finish anywhere.

Each device keeps an encrypted local copy of the user's data. Approved synchronization transports changes between trusted devices. Different records synchronize independently. Changes to different fields of the same record merge. When the same field changes on different devices, the most recent valid update wins. A recoverable version history is retained for important changes.

1. Journey Framework

Each journey is described through:

- User goal
- Trigger
- Entry point
- User actions
- Butlerly actions
- Decision points
- Device adaptation
- Trust and privacy requirements
- Completion state
- Recovery path
- Success measures

2. Primary Journey Map

The Version 1 lifecycle is:

Discover → Establish Trust → Capture or Import → Butlerly Understands → Review Exceptions
→ Organize → Retrieve → Continue Across Devices → Correct or Recover

The user should experience Butlerly as one assistant rather than separate applications.

3. Journey 1 — First Launch and Trust Establishment

User Goal

Understand what Butlerly does and begin without surrendering unnecessary data.

Trigger

The user installs and opens Butlerly for the first time.

Entry Point

Welcome screen on smartphone, tablet, or desktop.

User Journey

1. The user sees a concise promise: Butlerly helps organize and retrieve personal financial information while keeping the user in control.
2. Butlerly explains that data is stored locally by default.
3. Butlerly explains that optional synchronization and external AI services require explicit permission.
4. The user chooses a first action:
 - Capture a receipt.
 - Import a file.
 - Explore with sample data.
5. Butlerly requests only the permission required for the chosen action.
6. The user completes one useful task before being asked to configure advanced settings.

Butlerly Behavior

- Avoid a long setup wizard.
- Do not require account creation before local use.
- Explain data location in plain language.
- Provide a visible path to privacy and data controls.
- Offer sample data when the user is not ready to grant permissions.

Decision Points

- Local-only use or optional synchronization.
- Local AI or optional external AI when available.
- Grant or defer camera, file, notification, or account permissions.

Device Adaptation

Smartphone: prioritize receipt capture and quick value.

Tablet: offer capture, import, or sample workspace.

Desktop: prioritize file import, sample workspace, and device pairing.

Completion State

The user successfully captures, imports, or explores one item and understands where the data is stored.

Recovery

Permissions can be granted later. The user can restart onboarding explanations without deleting data.

Success Measures

- Time to first useful result.
- Percentage of users who understand local versus external processing.
- Permission acceptance after contextual explanation.
- Percentage of users who complete one task without creating an account.

4. Journey 2 — Capture a Receipt on Smartphone

User Goal

Save a receipt immediately with minimal typing.

Trigger

The user receives a paper or digital receipt.

Entry Points

- Global Capture action.
- Lock-screen or home-screen shortcut.
- Share sheet from another application.
- Camera entry inside Butlerly.

User Journey

1. The user opens Capture.

2. The camera detects receipt boundaries and image quality.
3. The user takes the photo or imports an image.
4. Butlerly confirms whether processing is local or external.
5. Butlerly extracts merchant, date, amount, tax, payment source, and likely category.
6. Butlerly checks for an existing matching transaction or duplicate receipt.
7. If confidence is high and the action is reversible, Butlerly saves the item and offers Undo.
8. If clarification is needed, Butlerly asks one focused question.
9. The user sees completion confirmation and may close the app.

Butlerly Behavior

- Preserve the original image even when extraction fails.
- Never force the user to complete every field.
- Show processing progress when it lasts more than a moment.
- Explain uncertainty briefly.
- Queue non-urgent questions for later review when possible.

Decision Points

- Image quality sufficient or retake required.
- Existing transaction match or standalone receipt.
- High confidence or exception review.
- Duplicate or new item.

Completion State

The receipt is encrypted, saved, searchable, and linked when possible.

Recovery

The user may retake the image, edit extracted values, unlink a transaction, restore a previous version, or delete the item.

Success Measures

- Median capture time.
- Percentage completed without typing.
- Extraction correction rate.
- Duplicate-detection precision.
- Abandonment before save.

5. Journey 3 — Import Records or Documents

User Goal

Bring existing financial information into Butlerly without reorganizing it manually.

Trigger

The user has statements, transaction files, receipt images, or exported records.

Entry Points

- Import on desktop or tablet.
- Share sheet on smartphone.
- Drag and drop on desktop.
- Files picker.

User Journey

1. The user selects one or more files.
2. Butlerly identifies supported formats and estimates the import scope.
3. Butlerly explains where processing occurs.
4. The import runs in the background where supported.
5. Butlerly summarizes:
 - Items imported.
 - Duplicates skipped or linked.
 - Items needing review.
 - Failures and recovery options.
6. The user reviews only meaningful exceptions.
7. Imported data becomes searchable and available on trusted devices after synchronization.

Device Adaptation

Smartphone: small imports and share-sheet intake.

Tablet: moderate import and review.

Desktop: bulk import, mapping, progress details, and recovery.

Completion State

All valid records are imported, duplicates are controlled, failures are explained, and exceptions are queued.

Recovery

The user can retry failed files, undo the import batch, inspect source files, or export an import report.

Success Measures

- Import completion rate.
- Duplicate rate.
- Mapping accuracy.
- Time to resolve exceptions.

- Successful rollback rate.

6. Journey 4 — Review Exceptions

User Goal

Resolve only the items that genuinely need attention.

Trigger

Butlerly detects uncertainty, conflict, missing information, duplicate risk, consent requirement, or processing failure.

Entry Points

- Review badge.
- Completion summary after capture or import.
- Contextual notification for time-sensitive issues.

User Journey

1. The user opens Review.
2. Items are ordered by consequence and urgency, not merely by date.
3. Each item states:
 - What Butlerly believes.
 - Why attention is needed.
 - The recommended action.
 - Other reasonable choices.
4. The user confirms, corrects, defers, or rejects.
5. Butlerly updates the record and learns from the correction when permitted.
6. The next relevant item appears.
7. The user can leave at any time without losing progress.

Design Rules

- One primary decision per item.
- Batch actions only for genuinely similar, reversible items.
- Do not require approval of routine high-confidence work.
- Preserve context when moving between Review and record detail.

Device Adaptation

Smartphone: one-at-a-time focused review.

Tablet: split view with item list and detail.

Desktop: list, detail, filters, keyboard navigation, and batch actions.

Completion State

The exception is resolved, deferred with a reason, or escalated with a clear next step.

Recovery

Undo, version history, and return to unresolved state.

Success Measures

- Exception resolution time.
- Deferral rate.
- Reversal rate.
- Percentage of items that should not have required review.

7. Journey 5 — Search and Retrieve

User Goal

Find a known receipt, transaction, or document within seconds.

Trigger

The user needs evidence, context, or an answer about past activity.

Entry Points

- Global search.
- Assistant question.
- Search from Records.

User Journey

1. The user enters natural language or structured filters.
2. Butlerly interprets people, merchants, dates, amounts, categories, locations, and record types.
3. Results appear with concise previews and match reasons.
4. The user refines or opens a result.
5. Butlerly shows the record, original source, related items, and change history when relevant.
6. The user may correct organization directly from the result.

Example Queries

- Costco receipt from last month.
- Hotel charges in Hawaii.
- Purchases over \$500.
- What did I pay for the laptop?
- Why was this categorized as travel?

Device Adaptation

Smartphone: quick search, recent queries, voice input, concise result cards.

Tablet: filters and preview pane.

Desktop: advanced filters, saved views, keyboard navigation, export.

Completion State

The user finds the intended information or receives a useful explanation of why it is unavailable.

Recovery

Search suggestions, filter reset, broader matching, source availability explanation, and manual browse.

Success Measures

- Time to first correct result.
- Search reformulation rate.
- Zero-result rate.
- Result correction rate.

8. Journey 6 — Ask Butlerly About a Record

User Goal

Understand an item without interpreting raw fields.

Trigger

A record is confusing, unfamiliar, or potentially important.

Entry Points

- Ask Butlerly from a record.
- Global Assistant.
- Suggested question in an exception.

User Journey

1. The user asks a question in natural language.
2. Butlerly uses the selected record and approved related context.
3. Butlerly answers with:
 - A direct conclusion.
 - Supporting evidence.
 - Confidence or uncertainty.
 - Available next actions.

4. The user may inspect the source or correct Butlerly.

Design Rules

- Preserve record context.
- Do not invent missing facts.
- Distinguish observation from recommendation.
- Clearly disclose external AI processing before data leaves the device.
- Keep answers brief by default and expandable.

Completion State

The user understands the record or knows what information is missing.

Success Measures

- Answer usefulness.
- Source-inspection rate.
- Correction rate.
- External-AI consent comprehension.

9. Journey 7 — Cross-Device Continuity

User Goal

Use Butlerly across smartphone, tablet, and desktop without thinking about synchronization.

Trigger

The user installs Butlerly on another device or continues a task elsewhere.

Entry Points

- My Devices.
- Apple synchronization setup.
- QR device pairing.
- AirDrop or encrypted archive import.

User Journey

1. The user opens My Devices.
2. Butlerly offers available continuity methods:
 - Apple synchronization for supported Apple devices.
 - Direct trusted-device pairing.
 - AirDrop or encrypted manual transfer.
3. The user authenticates and approves the new device.
4. Device-specific encryption keys are established.

5. The device receives the encrypted data set or required changes.
6. Butlerly shows synchronization status in plain language.
7. The user continues recent work where appropriate.

Synchronization Behavior

- Each device maintains an encrypted local database.
- Different records synchronize independently.
- Different fields changed on the same record merge.
- The same field changed on multiple devices is resolved using the most recent valid timestamp.
- Important superseded values remain recoverable through version history.
- Deleted records use a synchronized deletion marker so offline devices do not restore them accidentally.
- A lost device can be revoked without disabling other devices.

Device Roles

Smartphone: capture and immediate actions.

Tablet: review and organization.

Desktop: deep work and administration.

Completion State

The trusted device has the appropriate encrypted data and the user can continue without duplicate work.

Recovery

Retry synchronization, use manual encrypted transfer, review conflict history, revoke device, or restore a previous version.

Success Measures

- Pairing completion rate.
- Synchronization delay.
- Merge success rate.
- Conflict recovery rate.
- User understanding of device trust and data location.

10. Journey 8 — Offline Use and Later Synchronization

User Goal

Continue using Butlerly without a network connection.

Trigger

The user is offline, has poor connectivity, or intentionally disables cloud access.

User Journey

1. Butlerly opens normally using local encrypted data.
2. The user captures, searches, edits, and reviews supported records.
3. Butlerly indicates offline state without blocking local work.
4. Changes are stored in the local change queue.
5. When connectivity returns, approved synchronization resumes.
6. Non-competing changes merge automatically.
7. True same-field conflicts follow timestamp rules and remain recoverable.

Completion State

The user completes local work and later sees confirmation that changes are available on trusted devices.

Recovery

Manual retry, inspect pending changes, export local archive, or remain local-only.

Success Measures

- Percentage of core journeys usable offline.
- Failed synchronization recovery rate.
- Duplicate or lost-change incidents.

11. Journey 9 — Correct, Undo, and Restore

User Goal

Correct a mistake without fear of losing data.

Trigger

The user notices an incorrect extraction, category, link, merge, or deletion.

Entry Points

- Undo banner.
- Edit record.
- Version history.
- Recently deleted.

User Journey

1. The user selects the incorrect field or action.
2. Butlerly shows the current value and relevant source evidence.
3. The user corrects or restores.

4. Butlerly records the change, synchronizes it, and optionally learns from the correction.
5. The user receives confirmation.

Design Rules

- Undo should be immediate for recent reversible actions.
- Version history should be understandable, not engineering-oriented.
- Learning from corrections must be transparent and resettable.
- Restored records must not create duplicates.

Completion State

The intended value is active across trusted devices and the prior state remains recoverable according to retention rules.

Success Measures

- Successful correction rate.
- Undo usage.
- Restore success.
- Repeated correction frequency.

12. Journey 10 — Privacy, Data, and Device Control

User Goal

Understand and control where data is stored, processed, synchronized, exported, or deleted.

Entry Point

Settings → Privacy & Data.

User Journey

1. The user sees a plain-language summary of:
 - Local data.
 - Synchronized data.
 - Connected sources.
 - External AI providers.
 - Trusted devices.
2. The user can inspect each category.
3. The user may disable a provider, revoke a device, export data, delete selected records, or erase all data.
4. Butlerly explains consequences before irreversible actions.
5. The user confirms with device authentication when required.

Completion State

The requested privacy or data-control change is completed and clearly recorded.

Recovery

Re-enable reversible services, restore from an encrypted backup when available, or cancel before irreversible deletion.

Success Measures

- User comprehension.
- Successful export rate.
- Device revocation completion.
- Accidental deletion rate.

13. Journey 11 — Error Recovery

User Goal

Recover from failure without uncertainty about data loss or disclosure.

Common Errors

- Receipt image cannot be read.
- Import format unsupported.
- Synchronization unavailable.
- External AI provider unavailable.
- Permission denied.
- Connected source authentication expired.
- Storage full.

Required Error Message Structure

1. What failed.
2. What was preserved.
3. Whether data left the device.
4. What the user can do next.
5. Whether retrying is safe.

Example

“Receipt text could not be read. The image is saved locally and was not sent to an external provider. Retake the photo or enter the amount manually.”

Completion State

The user recovers, defers safely, or understands the remaining limitation.

14. Cross-Journey Experience Requirements

All journeys must:

- Work with local data first where practical.
- Use plain language.
- Present one clear next step.
- Explain material AI uncertainty.
- Avoid unnecessary confirmation.
- Support accessibility requirements.
- Preserve user progress when interrupted.
- Remain usable when AI is unavailable.
- Distinguish local, synchronized, connected-source, and external-AI data.
- Offer recovery for reversible changes.

15. Journey Priority for Version 1

Must Be Complete

1. First launch and trust.
2. Receipt capture.
3. File import.
4. Exception review.
5. Search and retrieval.
6. Correction and undo.
7. Offline operation.
8. Cross-device continuity for Apple devices.
9. Privacy and data control.
10. Error recovery.

May Be Limited in Initial Release

- Advanced saved searches.
- Large-scale batch editing.
- Non-Apple direct synchronization.
- Rich proactive insights.
- Complex collaboration.

16. Dependencies

UX-0002 depends on:

- UX-0001 — Butlerly Experience Blueprint.
- Product MVP scope and personas.

- Architecture decisions for local storage, encryption, identity, and synchronization.

UX-0002 governs:

- UX-0003 — Information Architecture and Navigation Model.
- UX-0004 — Core User Flows.
- UX-0005 — Screen and State Inventory.
- UX-0006 — AI Interaction and Explainability Specification.
- UX-0008 — Cross-Device Experience and Continuity.
- UX-0010 — Low-Fidelity Wireframe Specification.

17. Acceptance Criteria

This journey map is complete when:

- Every required Version 1 outcome has an end-to-end journey.
- Smartphone, tablet, and desktop roles are defined.
- Cross-device continuity is represented as a normal user experience.
- Encryption, trusted devices, offline operation, merge behavior, and timestamp conflict resolution are included.
- Every journey includes recovery and success measures.
- Later information architecture and wireframes can be derived without inventing major missing steps.

BDS-0000 / Finance V1 Scope Conformance

BDS-0000 — Butler Design System v1.0 governs visual tokens, theme values, typography, spacing/radius, responsive breakpoints, component/state contracts, accessibility implementation, localization/original-data presentation, and Flutter UI constraints. Finance V1 stable visible primary navigation is Home, Transactions, Review, Search, and Settings; Assistant is optional/non-primary.

Single-device local-first operation is authoritative for the Finance V1 MVP. The cross-device continuity, trusted-device, pairing, synchronization, merge, and revocation journeys retained in this document are future/optional design references and are not MVP completion requirements unless product scope explicitly enables them. They must not imply mandatory account creation or remote identity. UI-authored text follows the selected application language; user-entered/imported/scanned/source data preserves its original language and script by default. Original currency and amount remain authoritative, with reference-currency conversion shown separately when available.