量子论文雷达 · 2026年10月25日

> 量子算法（近最优优先） · 相干伊辛机 · 量子注意力 · quant-ph 每日精选

今日概览

数据源	状态	数量
Scirate quant-ph	⚠️ Cloudflare 拦截/抓取失败	0
arXiv quant-ph	✅（72h 内）	27 篇
DeepSeek 搜索	✅（10 组查询）	75 条

新增（未推送过）**0** 篇。

> ⚠️ Scirate 社区票数不可达，热榜改为按模型评分排序

🔥 今日量子热榜（AI 排序）

> Scirate 社区票数当前不可达，改为按模型对论文的重要性评分排序，仍取前 10 篇。

1. **玻色量子：相干伊辛机的中国答卷**
   `相干伊辛机` · #1 · 10-24

   > # 玻色量子：相干伊辛机的中国答卷
   >
   > …
   > 2026-10-25 09:
   > …
   > 在量子计算的全球赛道上，超导、离子阱、中性原子路线各擅胜场，而有一条路线另辟蹊径——用光子本身来做计算，不需要绝对零度，不需要巨型制冷机，在室温下就能稳定运转。这就是相干光量子计算，也叫相干伊辛机（Coherent Ising Mach…
   > `search`

2. **Ontological fidelity: High, in a specific sense**
   `相干伊辛机` · #2

   > Fault tolerance requires quantum error correction, which imposes an overhead of roughly (10^(2)) to (10^(3)) physical qubits per logical qubit.
   > …
   > Core id…

3. **Decoding quantum error correction with Ising model hardware — Lacuna**
   相干伊辛机 · #3

> # Decoding quantum error correction with Ising model hardware
>
> …

Abstract

Fault-tolerant quantum computers require efficient real-time decoding of quantum…
来源：Lacuna by Tiptree Systems

1. **hiyenwong**
   相干伊辛机 · #4

> 2026-06-16
> …
> علماء الأحياء، جميع الآخرون
> …
> boltzmann-attention-ising
> …
> Boltzmann Attention methodology — energy-based attention mechanism using learnable…
> 来源：SkillsMP

2. **boltzmann-attention | Agent Skill | SkillsMP**
   相干伊辛机 · #5 · 06-15

> # boltzmann-attention
>
> …
> Atualizado16 de junho de 2026 às 06:18

Boltzmann Attention methodology — energy-based generalization of attention using interacting…
来源：SkillsMP

1. **boltzmann-attention-ising Agent Skill | hiye/ai_coll~00rt9t3**
   相干伊辛机 · #6 · 07-12

> # boltzmann-attention-ising

Boltzmann Attention methodology — energy-based attention mechanism using learnable Ising model pairwise couplings for cooperative…
来源：SkillsMP

1. **Practical and scalable decoder for topological quantum error correction with an Ising machine | Semantic Scholar - 14 Citations**
   相干伊辛机 · #7 · 11-07

   > ## Weighted Range-Constrained Ising-Model Decoder for Quantum Error Correction

The Weighted Range-Constrained Ising Model-Based (WRIM) decoder uses a polygon…
来源：Semantic Scholar

1. **[PDF] QAMA: Scalable Quantum Annealing Multi-Head Attention Operator for Deep Learning | Semantic Scholar - QAMA: Scalable Quantum Annealing Multi-Head Attention Operator for Deep Learning**
   相干伊辛机 · #8 · 04-14

   > # QAMA: Scalable Quantum Annealing Multi-Head Attention Operator for Deep Learning
   >
   > @inproceedingsDu2025QAMASQ,
   > title=QAMA: Scalable Quantum Annealing Multi…
   > 来源：Semantic Scholar

2. **Near-Optimal Quantum Algorithm and Complexity Analysis for Riccati Problems - US⁢FkΠ<R0displaystyle U_S_(F)^(k)Π_(<)R_(0) | ←RieszBE(US⁢F,UI,Γ<,zk,UR0,η),displaystyle⩽ftarrowoperatornameRi...**
   量子算法 · #9 · 10-19

   > US⁢F−kΠ>displaystyle U_S_(F)^(-k)Π_(>) |
   > ←RieszBE(US⁢F,UI,Γ>,z−k,UI,η).displaystyle⩽ftarrowRieszBE(U_S_(F),U_maths…

3. **dblp: Scott Aaronson - PDQP/qpoly=ALL**
   量子算法 · #10 · 10-20

   > Quantum Inf.
   > ...
   > Quantum Lower Bound for Approximate Counting Via Laurent Polynomials. CoRR abs/

> 1808.02420 (2018)
> - [i102]Scott Aaronson, Daniel Grier, Luke Sc…
> 来源：dblp: computer science bibliography
