

This is unreleased documentation for alphaTab **1.5.0-alpha.1342** 🚧.

[API Reference](#)[API](#)

API

On many platforms an alphaTab API object can be used to bootstrap alphaTab within your UI. It takes over all responsibilities of linking your actions to the UI. Namely this object is called `AlphaTabApi` (Web) or `AlphaTabApiBase<>` (.net). This page describes all methods, properties and events exposed by this API object.

Name	Summary
Events - Core	
error JavaScript alphaTab.error jQuery alphaTab.error HTML Error .net error Android	This event is fired when an error within alphatab occurred.
postRenderFinished JavaScript alphaTab.postRenderFinished jQuery alphaTab.postRenderFinished HTML PostRenderFinished .net postRenderFinished Android	This event is fired when the rendering of the whole music sheet is finished, and all handlers of RenderFinished ran.
renderFinished JavaScript alphaTab.renderFinished jQuery alphaTab.renderFinished HTML RenderFinished .net renderFinished Android	This event is fired when the rendering of the whole music sheet is finished.

Name	Summary
renderStarted JavaScript alphaTab.renderStarted jQuery alphaTab.renderStarted HTML RenderStarted .net renderStarted Android	This event is fired when the rendering of the whole music sheet is starting.
resize JavaScript alphaTab.resize jQuery alphaTab.resize HTML Resize .net resize Android	This event is fired when alphaTab was resized and is about to rerender the music notation.
scoreLoaded JavaScript alphaTab.scoreLoaded jQuery alphaTab.scoreLoaded HTML ScoreLoaded .net scoreLoaded Android	This event is fired whenever a new song is loaded
Events - Player	
activeBeatsChanged JavaScript alphaTab.activeBeatsChanged jQuery alphaTab.activeBeatsChanged HTML ActiveBeatsChanged .net activeBeatsChanged Android	This event is fired when the currently active beats across all tracks change.
beatMouseDown JavaScript alphaTab.beatMouseDown jQuery alphaTab.beatMouseDown HTML BeatMouseDown .net beatMouseDown Android	This event is fired whenever a the user presses the mouse button on a beat.

Name	Summary
beatMouseMove JavaScript alphaTab.beatMouseMove jQuery alphaTab.beatMouseMove HTML BeatMouseMove .net beatMouseMove Android	This event is fired whenever the user moves the mouse over a beat after the user already pressed the button on a beat.
beatMouseUp JavaScript alphaTab.beatMouseUp jQuery alphaTab.beatMouseUp HTML BeatMouseUp .net beatMouseUp Android	This event is fired whenever the user releases the mouse after a mouse press on a beat.
midiEventsPlayed JavaScript alphaTab.midiEventsPlayed jQuery alphaTab.midiEventsPlayed HTML MidiEventsPlayed .net midiEventsPlayed Android	The midi events which will trigger the `midiEventsPlayed` event
midiLoad JavaScript alphaTab.midiLoad jQuery alphaTab.midiLoad HTML MidiLoad .net midiLoad Android	This event is fired when a Midi file is being loaded.
midiLoaded JavaScript alphaTab.midiLoaded jQuery alphaTab.midiLoaded HTML MidiLoaded .net midiLoaded Android	This event is fired when the Midi file needed for playback was loaded.
noteMouseDown JavaScript alphaTab.noteMouseDown jQuery alphaTab.noteMouseDown HTML NoteMouseDown .net noteMouseDown Android	This event is fired whenever a the user presses the mouse button on a note head/number.

Name	Summary
noteMouseMove JavaScript alphaTab.noteMouseMove jQuery alphaTab.noteMouseMove HTML NoteMouseMove .net noteMouseMove Android	This event is fired whenever the user moves the mouse over a note after the user already pressed the button on a note.
noteMouseUp JavaScript alphaTab.noteMouseUp jQuery alphaTab.noteMouseUp HTML NoteMouseUp .net noteMouseUp Android	This event is fired whenever the user releases the mouse after a mouse press on a note.
playbackRangeChanged JavaScript alphaTab.playbackRangeChanged jQuery alphaTab.playbackRangeChanged HTML PlaybackRangeChanged .net playbackRangeChanged Android	This event is fired when the playback range changed.
playedBeatChanged JavaScript alphaTab.playedBeatChanged jQuery alphaTab.playedBeatChanged HTML PlayedBeatChanged .net playedBeatChanged Android	This event is fired when the played beat changed.
playerFinished JavaScript alphaTab.playerFinished jQuery alphaTab.playerFinished HTML PlayerFinished .net playerFinished Android	This event is fired when the playback of the whole song finished.
playerPositionChanged JavaScript alphaTab.playerPositionChanged jQuery alphaTab.playerPositionChanged HTML	This event is fired when the playback state changed.

Name	Summary
PlayerPositionChanged .net playerPositionChanged Android	
playerReady JavaScript alphaTab.playerReady jQuery alphaTab.playerReady HTML PlayerReady .net playerReady Android	This event is fired when all required data for playback is loaded and ready.
playerStateChanged JavaScript alphaTab.playerStateChanged jQuery alphaTab.playerStateChanged HTML PlayerStateChanged .net playerStateChanged Android	This event is fired when the playback state changed.
soundFontLoad JavaScript alphaTab.soundFontLoad jQuery alphaTab.soundFontLoad HTML SoundFontLoad .net soundFontLoad Android	This event is fired when the SoundFont is being loaded.
soundFontLoaded JavaScript alphaTab.soundFontLoaded jQuery alphaTab.soundFontLoaded HTML SoundFontLoaded .net soundFontLoaded Android	This event is fired when the SoundFont needed for playback was loaded.
Methods - Core	
alphaTab() jQuery	Initializes AlphaTab.
destroy() JavaScript alphaTab('destroy') jQuery Destroy() .net destroy() Android	Destroys the alphaTab control and restores the initial state of the UI.

Name	Summary
downloadMidi() JavaScript alphaTab('downloadMidi') jQuery	Generates an SMF1.0 file and downloads it
load() JavaScript alphaTab('load') jQuery Load() .net load() Android	Initiates a load of the score using the given data.
print() JavaScript alphaTab('print') jQuery	Opens a popup window with the rendered music notation for printing.
render() JavaScript alphaTab('render') jQuery Render() .net render() Android	Initiates a re-rendering of the current setup.
renderScore() JavaScript alphaTab('renderScore') jQuery RenderScore() .net renderScore() Android	Initiates a rendering of the given score.
renderTracks() JavaScript alphaTab('renderTracks') jQuery RenderTracks() .net renderTracks() Android	Initiates a rendering of the given tracks.
tex() JavaScript alphaTab('tex') jQuery Tex() .net tex() Android	Tells alphaTab to render the given alphaTex.
updateSettings() JavaScript alphaTab('updateSettings') jQuery UpdateSettings() .net updateSettings() Android	Applies any changes that were done to the settings object and informs the Renderer about any new values to consider.

Name	Summary
Methods - Player	
changeTrackMute() JavaScript alphaTab('muteTracks') jQuery ChangeTrackMute() .net changeTrackMute() Android	Changes the given tracks to be muted or not.
changeTrackSolo() JavaScript alphaTab('soloTracks') jQuery ChangeTrackSolo() .net changeTrackSolo() Android	Changes the given tracks to be played solo or not.
changeTrackTranspositionPitch() JavaScript alphaTab('changeTrackTranspositionPitch') jQuery ChangeTrackTranspositionPitch() .net changeTrackTranspositionPitch() Android	Changes the pitch transpose applied to the given tracks.
changeTrackVolume() JavaScript alphaTab('trackVolume') jQuery ChangeTrackVolume() .net changeTrackVolume() Android	Changes the volume of the given tracks.
enumerateOutputDevices() JavaScript alphaTab('enumerateOutputDevices') jQuery EnumerateOutputDevices() .net enumerateOutputDevices() Android	Loads and lists the available output devices which can be used by the player.
getOutputDevice() JavaScript alphaTab('getOutputDevice') jQuery GetOutputDevice() .net getOutputDevice() Android	Gets the currently configured output device.

Name	Summary
loadSoundFont() JavaScript alphaTab('loadSoundFont') jQuery LoadSoundFont() .net loadSoundFont() Android	Triggers a load of the soundfont from the given data.
pause() JavaScript alphaTab('pause') jQuery Pause() .net pause() Android	Pauses the playback of the current song.
play() JavaScript alphaTab('play') jQuery Play() .net play() Android	Starts the playback of the current song.
playBeat() JavaScript alphaTab('playBeat') jQuery PlayBeat() .net playBeat() Android	Triggers the play of the given beat.
playNote() JavaScript alphaTab('playNote') jQuery PlayNote() .net playNote() Android	Triggers the play of the given note.
playPause() JavaScript alphaTab('playPause') jQuery PlayPause() .net playPause() Android	Toggles between play/pause depending on the current player state.
resetSoundFonts() JavaScript alphaTab('resetSoundFonts') jQuery ResetSoundFonts() .net resetSoundFonts() Android	Unloads all presets from previously loaded SoundFonts.
setOutputDevice() JavaScript alphaTab('setOutputDevice') jQuery	Changes the output device which should be used for playing the audio.

Name	Summary
SetOutputDevice() .net setOutputDevice() Android	
stop() JavaScript alphaTab('stop') jQuery Stop() .net stop() Android	Stops the playback of the current song, and moves the playback position back to the start.
Properties - Core	
container JavaScript alphaTab('container') jQuery Container .net container Android	The UI container that holds the whole alphaTab control.
renderer JavaScript alphaTab('renderer') jQuery Renderer .net renderer Android	The score renderer used for rendering the music sheet. This is the low-level API responsible for the actual rendering chain.
score JavaScript alphaTab('score') jQuery Score .net score Android	The score holding all information about the song being rendered
settings JavaScript alphaTab('settings') jQuery Settings .net settings Android	The settings that are used for rendering the music notation
alphaTab('api') jQuery	Returns the underlying API object.
tracks JavaScript alphaTab('tracks') jQuery Tracks .net tracks Android	A list of the tracks that should be rendered based on the Score and TrackIndexes properties
Properties - Player	

Name	Summary
countInVolume JavaScript alphaTab('countInVolume') jQuery CountInVolume .net countInVolume Android	The volume of the count-in metronome ticks
isLooping JavaScript alphaTab('looping') jQuery IsLooping .net isLooping Android	Whether the playback should automatically restart after it finished
isReadyForPlayback JavaScript alphaTab('isReadyForPlayback') jQuery IsReadyForPlayback .net isReadyForPlayback Android	Whether the player is ready for starting the playback.
masterVolume JavaScript alphaTab('masterVolume') jQuery MasterVolume .net masterVolume Android	The current master volume as percentage
metronomeVolume JavaScript alphaTab('metronomeVolume') jQuery MetronomeVolume .net metronomeVolume Android	The metronome volume as percentage
midiEventsPlayedFilter JavaScript alphaTab('midiEventsPlayedFilter') jQuery MidiEventsPlayedFilter .net midiEventsPlayedFilter Android	The midi events which will trigger the `midiEventsPlayed` event
playbackRange JavaScript alphaTab('playbackRange') jQuery PlaybackRange .net playbackRange Android	The range of the song that should be played

Name	Summary
playbackSpeed JavaScript alphaTab('playbackSpeed') jQuery PlaybackSpeed .net playbackSpeed Android	The current playback speed as percentage
player JavaScript alphaTab('player') jQuery Player .net player Android	The alphaSynth player used for playback. This is the low-level API to the Midi synthesizer used for playback.
playerState JavaScript alphaTab('playerState') jQuery PlayerState .net playerState Android	The current player state
tickCache JavaScript alphaTab('tickCache') jQuery TickCache .net tickCache Android	The tick cache allowing lookup of midi ticks to beats.
tickPosition JavaScript alphaTab('tickPosition') jQuery TickPosition .net tickPosition Android	The position within the song in midi ticks
timePosition JavaScript alphaTab('timePosition') jQuery TimePosition .net timePosition Android	The position within the song in milliseconds

 [Edit this page](#)