

This is unreleased documentation for alphaTab **1.5.0-alpha.1342** 🚧.

[API Reference](#)[AlphaSynth](#)

AlphaSynth

`AlphaSynth` is one of the low level APIs that can be used if no full alphaTab API object with UI interaction can be used or is needed. It is the audio synthesis engine of alphaTab which is used to play a midi file using a generated midi file and a SoundFont as input.

This page describes all methods, properties and events exposed by this class. Most of the API methods exposed by the `IAAlphaSynth` interface are also directly available on the normal API object. That's why many documentation pages delegate to the related documentation pages there.

Name	Summary
Events	
<code>finished</code> JavaScript <code>Finished</code> .net <code>finished</code> Android	This event is fired when the playback of the whole song finished.
<code>midiEventsPlayed</code> JavaScript <code>MidiEventsPlayed</code> .net <code>midiEventsPlayed</code> Android	The midi events which will trigger the `midiEventsPlayed` event
<code>midiLoadFailed</code> JavaScript <code>MidiLoadFailed</code> .net <code>midiLoadFailed</code> Android	This event is fired when the loading of the Midi failed.
<code>midiLoaded</code> JavaScript <code>MidiLoaded</code> .net <code>midiLoaded</code> Android	This event is fired when the Midi needed for playback was loaded.

Name	Summary
playbackRangeChanged JavaScript PlaybackRangeChanged .net playbackRangeChanged Android	This event is fired when the playback range changed.
positionChanged JavaScript PositionChanged .net positionChanged Android	This event is fired when the playback state changed.
ready JavaScript Ready .net ready Android	Fired when the player is ready to be interacted with.
readyForPlayback JavaScript ReadyForPlayback .net readyForPlayback Android	This event is fired when all required data for playback is loaded and ready.
soundFontLoadFailed JavaScript SoundFontLoadFailed .net soundFontLoadFailed Android	This event is fired when the loading of the SoundFont failed.
soundFontLoaded JavaScript SoundFontLoaded .net soundFontLoaded Android	This event is fired when the SoundFont needed for playback was loaded.
stateChanged JavaScript StateChanged .net stateChanged Android	This event is fired when the playback state changed.
Methods	
destroy() JavaScript Destroy() .net destroy() Android	Destroys the synthesizer and all related components.

Name	Summary
loadMidiFile() JavaScript LoadMidiFile() .net loadMidiFile() Android	Triggers a load of the given midi file.
loadSoundFont() JavaScript LoadSoundFont() .net loadSoundFont() Android	Triggers a load of the soundfont from the given data.
pause() JavaScript Pause() .net pause() Android	Pauses the playback of the current song.
play() JavaScript Play() .net play() Android	Starts the playback of the current song.
playPause() JavaScript PlayPause() .net playPause() Android	Toggles between play/pause depending on the current player state.
resetChannelStates() JavaScript ResetChannelStates() .net resetChannelStates() Android	Resets the mute/solo change of all channels.
setChannelMute() JavaScript SetChannelMute() .net setChannelMute() Android	Mutes or unmutes a single midi channel.
setChannelSolo() JavaScript SetChannelSolo() .net setChannelSolo() Android	Flags a single midi channel to be played solo or not.

Name	Summary
setChannelTranspositionPitch() JavaScript SetChannelTranspositionPitch() .net setChannelTranspositionPitch() Android	Sets the transposition pitch of a given channel.
setChannelVolume() JavaScript SetChannelVolume() .net setChannelVolume() Android	Sets the current and initial volume of the given channel.
stop() JavaScript Stop() .net stop() Android	Stops the playback of the current song, and moves the playback position back to the start.
Properties	
countInVolume JavaScript CountInVolume .net countInVolume Android	The volume of the count-in metronome ticks
isLooping JavaScript IsLooping .net isLooping Android	Whether the playback should automatically restart after it finished
isReady JavaScript IsReady .net isReady Android	If the synthesizer is ready for interaction.
isReadyForPlayback JavaScript IsReadyForPlayback .net isReadyForPlayback Android	If the synthesizer is ready for playback.
logLevel JavaScript LogLevel .net logLevel Android	The log level to use within alphaSynth.

Name	Summary
masterVolume JavaScript MasterVolume .net masterVolume Android	The current master volume as percentage
metronomeVolume JavaScript MetronomeVolume .net metronomeVolume Android	The metronome volume as percentage
midiEventsPlayedFilter JavaScript MidiEventsPlayedFilter .net midiEventsPlayedFilter Android	The midi events which will trigger the `midiEventsPlayed` event
playbackRange JavaScript PlaybackRange .net playbackRange Android	The range of the song that should be played
playbackSpeed JavaScript PlaybackSpeed .net playbackSpeed Android	The current playback speed as percentage
state JavaScript State .net state Android	The current player state.
tickPosition JavaScript TickPosition .net tickPosition Android	The position within the song in midi ticks
timePosition JavaScript TimePosition .net timePosition Android	The position within the song in milliseconds

 [Edit this page](#)