

This is unreleased documentation for alphaTab **1.5.0-alpha.1342** 🚧.

[API Reference](#)[Settings](#)

# Settings

This section contains a list of all properties that allow configuration of the alphaTab behavior.

There are multiple ways how settings in alphaTab can be specified. For .net, the normal classes are used and changes are signaled via an `UpdateSettings` call. For JavaScript, the interaction with the settings is a bit more sensitive due to the lack of type safety and the support of JSON based settings.

Not all settings contain reasonable examples as they often just activate something within alphaTab or change the display of some notation. If you have questions on certain settings, feel free to open a [Discussion on GitHub](#).

The first and most important rule is: when interacting with the settings object directly, the correct structure and data types must be followed to not break alphaTab or make the changes useless. In order to simplify things when configuring alphaTab via JavaScript there are 2 additional features:

1. AlphaTab can be configured via a simple plain JSON object. This JSON format supports some aliases and also some value conversions like for enums, fonts and colors. The JSON schema can only be used at selected places. Attempting to set JSON values on the derived `alphaTab.Settings` object can lead to unexpected side effects. The JSON schema can be used when initializing alphaTab or when calling `settings.fillFromJson( ... )`.
2. AlphaTab can be configured via HTML data attributes. All settings can also be added as data attributes on the element for which alphaTab is initialized. This is especially useful when multiple different instances of alphaTab are running on the same site but the main code to set up alphaTab is shared. Individual settings can be specified on HTML elements.

The following table contains all the properties as they can be set on the general settings object.

| Property                                                                                                                                                                                                                                                                                                                                          | Summary                                                                                                  |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|
| <b>Core</b>                                                                                                                                                                                                                                                                                                                                       |                                                                                                          |
| <div>core.engine   JavaScript</div> <div>engine   JavaScript</div> <div>core.engine   JSON</div> <div>engine   JSON</div> <div>data-core-engine   HTML</div> <div>data-engine   HTML</div> <div>Core.Engine   .net</div> <div>core.engine   Android</div>                                                                                         | The engine which should be used to render the the tablature.                                             |
| <div>core.includeNoteBounds   JavaScript</div> <div>includeNoteBounds   JavaScript</div> <div>core.includeNoteBounds   JSON</div> <div>includeNoteBounds   JSON</div> <div>data-core-includenotebounds   HTML</div> <div>data-includenotebounds   HTML</div> <div>Core.IncludeNoteBounds   .net</div> <div>core.includeNoteBounds   Android</div> | Gets or sets whether in the BoundsLookup also the position and area of each individual note is provided. |
| <div>core.logLevel   JavaScript</div> <div>logLevel   JavaScript</div> <div>core.logLevel   JSON</div> <div>logLevel   JSON</div> <div>data-core-loglevel   HTML</div> <div>data-loglevel   HTML</div> <div>Core.LogLevel   .net</div> <div>core.logLevel   Android</div>                                                                         | The log level to use within alphaTab.                                                                    |
| <div>core.useWorkers   JavaScript</div> <div>useWorkers   JavaScript</div> <div>core.useWorkers   JSON</div> <div>useWorkers   JSON</div> <div>data-core-useworkers   HTML</div> <div>data-useworkers   HTML</div> <div>Core.UseWorkers   .net</div> <div>core.useWorkers   Android</div>                                                         | Whether the rendering should be done in a worker if possible.                                            |
| <b>Core - JavaScript Specific</b>                                                                                                                                                                                                                                                                                                                 |                                                                                                          |
| <div>core.enableLazyLoading   JavaScript</div> <div>enableLazyLoading   JavaScript</div> <div>core.enableLazyLoading   JSON</div> <div>enableLazyLoading   JSON</div>                                                                                                                                                                             | Enables lazy loading of the rendered music sheet chunks.                                                 |

| Property                                                                                                                                                                                                                             | Summary                                                               |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------|
| <div>data-core-enablelazyloading   HTML</div> <div>data-enablelazyloading   HTML</div>                                                                                                                                               |                                                                       |
| <div>core.file   JavaScript</div> <div>file   JavaScript</div> <div>core.file   JSON</div> <div>file   JSON</div> <div>data-core-file   HTML</div> <div>data-file   HTML</div>                                                       | The full URL to the input file to be loaded.                          |
| <div>core.fontDirectory   JavaScript</div> <div>fontDirectory   JavaScript</div> <div>core.fontDirectory   JSON</div> <div>fontDirectory   JSON</div> <div>data-core-fontdirectory   HTML</div> <div>data-fontdirectory   HTML</div> | The full URL to the alphaTab font directory.                          |
| <div>core.scriptFile   JavaScript</div> <div>scriptFile   JavaScript</div> <div>core.scriptFile   JSON</div> <div>scriptFile   JSON</div> <div>data-core-scriptfile   HTML</div> <div>data-scriptfile   HTML</div>                   | The full URL to the alphaTab JavaScript file.                         |
| <div>core.tex   JavaScript</div> <div>tex   JavaScript</div> <div>core.tex   JSON</div> <div>tex   JSON</div> <div>data-core-tex   HTML</div> <div>data-tex   HTML</div>                                                             | Whether the contents of the DOM element should be loaded as alphaTex. |
| <div>core.tracks   JavaScript</div> <div>tracks   JavaScript</div> <div>core.tracks   JSON</div> <div>tracks   JSON</div> <div>data-core-tracks   HTML</div> <div>data-tracks   HTML</div>                                           | The tracks to display for the initially loaded file.                  |
| Display                                                                                                                                                                                                                              |                                                                       |

| Property                                                                                                                                                                                                                                                                                                                                                                                                         | Summary                                                               |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------|
| <div>display.accoladeBarPaddingRight   JavaScript</div> <div>accoladeBarPaddingRight   JavaScript</div> <div>display.accoladeBarPaddingRight   JSON</div> <div>accoladeBarPaddingRight   JSON</div> <div>data-display-accoladebarpaddingright   HTML</div> <div>data-accoladebarpaddingright   HTML</div> <div>Display.AccoladeBarPaddingRight   .net</div> <div>display.accoladeBarPaddingRight   Android</div> | The padding between the accolade bar and the start of the bar itself. |
| <div>display.barCount   JavaScript</div> <div>barCount   JavaScript</div> <div>display.barCount   JSON</div> <div>barCount   JSON</div> <div>data-display-barcount   HTML</div> <div>data-barcount   HTML</div> <div>Display.BarCount   .net</div> <div>display.barCount   Android</div>                                                                                                                         | The total number of bars that should be rendered from the song.       |
| <div>display.barCountPerPartial   JavaScript</div> <div>barCountPerPartial   JavaScript</div> <div>display.barCountPerPartial   JSON</div> <div>barCountPerPartial   JSON</div> <div>data-display-barcountperpartial   HTML</div> <div>data-barcountperpartial   HTML</div> <div>Display.BarCountPerPartial   .net</div> <div>display.barCountPerPartial   Android</div>                                         | The number of bars that should be placed within one partial render.   |
| <div>display.barsPerRow   JavaScript</div> <div>barsPerRow   JavaScript</div> <div>display.barsPerRow   JSON</div> <div>barsPerRow   JSON</div> <div>data-display-barsperrow   HTML</div> <div>data-barsperrow   HTML</div> <div>Display.BarsPerRow   .net</div> <div>display.barsPerRow   Android</div>                                                                                                         | Limit the displayed bars per row.                                     |
| <div>display.effectStaffPaddingBottom   JavaScript</div> <div>effectStaffPaddingBottom   JavaScript</div> <div>display.effectStaffPaddingBottom   JSON</div>                                                                                                                                                                                                                                                     | The bottom padding applied to effect annotation staves.               |

| Property                                                                                                                                                                                                                                                                                                                                                                                         | Summary                                                                                            |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|
| <div>effectStaffPaddingBottom   JSON</div> <div>data-display-effectstaffpaddingbottom   HTML</div> <div>data-effectstaffpaddingbottom   HTML</div> <div>Display.EffectStaffPaddingBottom   .net</div> <div>display.effectStaffPaddingBottom   Android</div>                                                                                                                                      |                                                                                                    |
| <div>display.effectStaffPaddingTop   JavaScript</div> <div>effectStaffPaddingTop   JavaScript</div> <div>display.effectStaffPaddingTop   JSON</div> <div>effectStaffPaddingTop   JSON</div> <div>data-display-effectstaffpaddingtop   HTML</div> <div>data-effectstaffpaddingtop   HTML</div> <div>Display.EffectStaffPaddingTop   .net</div> <div>display.effectStaffPaddingTop   Android</div> | The top padding applied to effect annotation staves.                                               |
| <div>display.firstStaffPaddingLeft   JavaScript</div> <div>firstStaffPaddingLeft   JavaScript</div> <div>display.firstStaffPaddingLeft   JSON</div> <div>firstStaffPaddingLeft   JSON</div> <div>data-display-firststaffpaddingleft   HTML</div> <div>data-firststaffpaddingleft   HTML</div> <div>Display.FirstStaffPaddingLeft   .net</div> <div>display.firstStaffPaddingLeft   Android</div> | The left padding applied between the left line and the first glyph in the first staff in a system. |
| <div>display.firstSystemPaddingTop   JavaScript</div> <div>firstSystemPaddingTop   JavaScript</div> <div>display.firstSystemPaddingTop   JSON</div> <div>firstSystemPaddingTop   JSON</div> <div>data-display-firstsystempaddingtop   HTML</div> <div>data-firstsystempaddingtop   HTML</div> <div>Display.FirstSystemPaddingTop   .net</div> <div>display.firstSystemPaddingTop   Android</div> | The top padding applied to first system                                                            |

| Property                                                                                                                                                                                                                                                                                                                                                                                                                                 | Summary                                                  |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------|
| <div>display.justifyLastSystem   JavaScript</div> <div>justifyLastSystem   JavaScript</div> <div>display.justifyLastSystem   JSON</div> <div>justifyLastSystem   JSON</div> <div>data-display-justifylastsystem   HTML</div> <div>data-justifylastsystem   HTML</div> <div>Display.JustifyLastSystem   .net</div> <div>display.justifyLastSystem   Android</div>                                                                         | Whether to justify also the last system in page layouts. |
| <div>display.lastSystemPaddingBottom   JavaScript</div> <div>lastSystemPaddingBottom   JavaScript</div> <div>display.lastSystemPaddingBottom   JSON</div> <div>lastSystemPaddingBottom   JSON</div> <div>data-display-lastsystempaddingbottom   HTML</div> <div>data-lastsystempaddingbottom   HTML</div> <div>Display.LastSystemPaddingBottom   .net</div> <div>display.lastSystemPaddingBottom   Android</div>                         | The bottom padding applied to the last system.           |
| <div>display.layoutMode   JavaScript</div> <div>layoutMode   JavaScript</div> <div>display.layoutMode   JSON</div> <div>layoutMode   JSON</div> <div>data-display-layoutmode   HTML</div> <div>data-layoutmode   HTML</div> <div>Display.LayoutMode   .net</div> <div>display.layoutMode   Android</div>                                                                                                                                 | The layouting mode used to arrange the the notation.     |
| <div>display.notationStaffPaddingBottom   JavaScript</div> <div>notationStaffPaddingBottom   JavaScript</div> <div>display.notationStaffPaddingBottom   JSON</div> <div>notationStaffPaddingBottom   JSON</div> <div>data-display-notationstaffpaddingbottom   HTML</div> <div>data-notationstaffpaddingbottom   HTML</div> <div>Display.NotationStaffPaddingBottom   .net</div> <div>display.notationStaffPaddingBottom   Android</div> | The bottom padding applied to main notation stoffs.      |

| Property                                                                                                                                                                                                                                                                                                                                                                                                         | Summary                                                                                                |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------|
| <div>display.notationStaffPaddingTop   JavaScript</div> <div>notationStaffPaddingTop   JavaScript</div> <div>display.notationStaffPaddingTop   JSON</div> <div>notationStaffPaddingTop   JSON</div> <div>data-display-notationstaffpaddingtop   HTML</div> <div>data-notationstaffpaddingtop   HTML</div> <div>Display.NotationStaffPaddingTop   .net</div> <div>display.notationStaffPaddingTop   Android</div> | The top padding applied to main notation staves.                                                       |
| <div>display.padding   JavaScript</div> <div>padding   JavaScript</div> <div>display.padding   JSON</div> <div>padding   JSON</div> <div>data-display-padding   HTML</div> <div>data-padding   HTML</div> <div>Display.Padding   .net</div> <div>display.padding   Android</div>                                                                                                                                 | Adjusts the padding between the music notation and the border                                          |
| <div>display.resources   JavaScript</div> <div>resources   JavaScript</div> <div>display.resources   JSON</div> <div>resources   JSON</div> <div>data-display-resources-*   HTML</div> <div>data-resources-*   HTML</div> <div>Display.Resources   .net</div> <div>display.resources   Android</div>                                                                                                             | Allows adjusting of the used fonts and colors for rendering.                                           |
| <div>display.scale   JavaScript</div> <div>scale   JavaScript</div> <div>display.scale   JSON</div> <div>scale   JSON</div> <div>data-display-scale   HTML</div> <div>data-scale   HTML</div> <div>Display.Scale   .net</div> <div>display.scale   Android</div>                                                                                                                                                 | The zoom level of the rendered notation.                                                               |
| <div>display.staffPaddingLeft   JavaScript</div> <div>staffPaddingLeft   JavaScript</div> <div>display.staffPaddingLeft   JSON</div> <div>staffPaddingLeft   JSON</div> <div>data-display-staffpaddingleft   HTML</div> <div>data-staffpaddingleft   HTML</div>                                                                                                                                                  | The left padding applied between the left line and the first glyph in the following staff in a system. |

| Property                                                                                                                                                                                                                                                                                                                                                                                                 | Summary                                                                |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------|
| <div>Display.StaffPaddingLeft   .net</div> <div>display.staffPaddingLeft   Android</div>                                                                                                                                                                                                                                                                                                                 |                                                                        |
| <div>display.startBar   JavaScript</div> <div>startBar   JavaScript</div> <div>display.startBar   JSON</div> <div>startBar   JSON</div> <div>data-display-startbar   HTML</div> <div>data-startbar   HTML</div> <div>Display.StartBar   .net</div> <div>display.startBar   Android</div>                                                                                                                 | The bar start index to start layouting with.                           |
| <div>display.staveProfile   JavaScript</div> <div>staveProfile   JavaScript</div> <div>display.staveProfile   JSON</div> <div>staveProfile   JSON</div> <div>data-display-staveprofile   HTML</div> <div>data-staveprofile   HTML</div> <div>Display.StaveProfile   .net</div> <div>display.staveProfile   Android</div>                                                                                 | The stave profile defining which staves are shown for the music sheet. |
| <div>display.stretchForce   JavaScript</div> <div>stretchForce   JavaScript</div> <div>display.stretchForce   JSON</div> <div>stretchForce   JSON</div> <div>data-display-stretchforce   HTML</div> <div>data-stretchforce   HTML</div> <div>Display.StretchForce   .net</div> <div>display.stretchForce   Android</div>                                                                                 | The default stretch force to use for layouting.                        |
| <div>display.systemLabelPaddingLeft   JavaScript</div> <div>systemLabelPaddingLeft   JavaScript</div> <div>display.systemLabelPaddingLeft   JSON</div> <div>systemLabelPaddingLeft   JSON</div> <div>data-display-systemlabelpaddingleft   HTML</div> <div>data-systemlabelpaddingleft   HTML</div> <div>Display.SystemLabelPaddingLeft   .net</div> <div>display.systemLabelPaddingLeft   Android</div> | The padding left to the track name label of the system.                |

| Property                                                                                                                                                                                                                                                                                                                                                                                                         | Summary                                                 |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------|
| <div>display.systemLabelPaddingRight   JavaScript</div> <div>systemLabelPaddingRight   JavaScript</div> <div>display.systemLabelPaddingRight   JSON</div> <div>systemLabelPaddingRight   JSON</div> <div>data-display-systemlabelpaddingright   HTML</div> <div>data-systemlabelpaddingright   HTML</div> <div>Display.SystemLabelPaddingRight   .net</div> <div>display.systemLabelPaddingRight   Android</div> | The padding left to the track name label of the system. |
| <div>display.systemPaddingBottom   JavaScript</div> <div>systemPaddingBottom   JavaScript</div> <div>display.systemPaddingBottom   JSON</div> <div>systemPaddingBottom   JSON</div> <div>data-display-systempaddingbottom   HTML</div> <div>data-systempaddingbottom   HTML</div> <div>Display.SystemPaddingBottom   .net</div> <div>display.systemPaddingBottom   Android</div>                                 | The bottom padding applied to systems.                  |
| <div>display.systemPaddingTop   JavaScript</div> <div>systemPaddingTop   JavaScript</div> <div>display.systemPaddingTop   JSON</div> <div>systemPaddingTop   JSON</div> <div>data-display-systempaddingtop   HTML</div> <div>data-systempaddingtop   HTML</div> <div>Display.SystemPaddingTop   .net</div> <div>display.systemPaddingTop   Android</div>                                                         | The top padding applied to systems.                     |
| <div>display.systemsLayoutMode   JavaScript</div> <div>systemsLayoutMode   JavaScript</div> <div>display.systemsLayoutMode   JSON</div> <div>systemsLayoutMode   JSON</div> <div>data-display-systemslayoutmode   HTML</div> <div>data-systemslayoutmode   HTML</div>                                                                                                                                            | The mode used to arrange staves and systems.            |

| Property                                                                                                                                                                                                                                                                                         | Summary                                                                            |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|
| <div>Display.SystemsLayoutMode   .net</div> <div>display.systemsLayoutMode   Android</div>                                                                                                                                                                                                       |                                                                                    |
| Importer                                                                                                                                                                                                                                                                                         |                                                                                    |
| <div>importer.beatTextAsLyrics   JavaScript</div> <div>importer.beatTextAsLyrics   JSON</div> <div>data-importer-beattextaslyrics   HTML</div> <div>Importer.BeatTextAsLyrics   .net</div> <div>importer.beatTextAsLyrics   Android</div>                                                        | Enables detecting lyrics from beat texts                                           |
| <div>importer.encoding   JavaScript</div> <div>importer.encoding   JSON</div> <div>data-importer-encoding   HTML</div> <div>Importer.Encoding   .net</div> <div>importer.encoding   Android</div>                                                                                                | The text encoding to use when decoding strings.                                    |
| <div>importer.mergePartGroupsInMusicXml   JavaScript</div> <div>importer.mergePartGroupsInMusicXml   JSON</div> <div>data-importer-mergepartgroupsinmusicxml   HTML</div> <div>Importer.MergePartGroupsInMusicXml   .net</div> <div>importer.mergePartGroupsInMusicXml   Android</div>           | If part-groups should be merged into a single track (MusicXML).                    |
| Notation                                                                                                                                                                                                                                                                                         |                                                                                    |
| <div>notation.displayTranspositionPitches   JavaScript</div> <div>notation.displayTranspositionPitches   JSON</div> <div>data-notation-displaytranspositionpitches   HTML</div> <div>Notation.DisplayTranspositionPitches   .net</div> <div>notation.displayTranspositionPitches   Android</div> | The transposition pitch offsets for the individual tracks used for rendering only. |
| <div>notation.elements   JavaScript</div> <div>notation.elements   JSON</div> <div>data-notation-elements   HTML</div>                                                                                                                                                                           | Render the song information or not.                                                |

| Property                                                                                                                                                                                                                                                                                         | Summary                                                                                                                       |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| <div>Notation.Elements   .net</div> <div>notation.elements   Android</div>                                                                                                                                                                                                                       |                                                                                                                               |
| <div>notation.extendBendArrowsOnTiedNotes   JavaScript</div> <div>notation.extendBendArrowsOnTiedNotes   JSON</div> <div>data-notation-extendbendarrowsontiednotes   HTML</div> <div>Notation.ExtendBendArrowsOnTiedNotes   .net</div> <div>notation.extendBendArrowsOnTiedNotes   Android</div> | <p>If set to true bend arrows expand to the end of the last tied note of the string. Otherwise they end on the next beat.</p> |
| <div>notation.extendLineEffectsToBeatEnd   JavaScript</div> <div>notation.extendLineEffectsToBeatEnd   JSON</div> <div>data-notation-extendlineeffectstobeatend   HTML</div> <div>Notation.ExtendLineEffectsToBeatEnd   .net</div> <div>notation.extendLineEffectsToBeatEnd   Android</div>      | <p>If set to true, line effects like w/bar and let-ring are drawn until the end of the beat instead of the start</p>          |
| <div>notation.fingeringMode   JavaScript</div> <div>notation.fingeringMode   JSON</div> <div>data-notation-fingeringmode   HTML</div> <div>Notation.FingeringMode   .net</div> <div>notation.fingeringMode   Android</div>                                                                       | <p>The fingering mode to use.</p>                                                                                             |
| <div>notation.notationMode   JavaScript</div> <div>notation.notationMode   JSON</div> <div>data-notation-notationmode   HTML</div> <div>Notation.NotationMode   .net</div> <div>notation.notationMode   Android</div>                                                                            | <p>The mode to use for display and play music notation elements.</p>                                                          |
| <div>notation.rhythmHeight   JavaScript</div> <div>notation.rhythmHeight   JSON</div> <div>data-notation-rhythmheight   HTML</div> <div>Notation.RhythmHeight   .net</div> <div>notation.rhythmHeight   Android</div>                                                                            | <p>Controls how high the rythm notation is rendered below the tab staff</p>                                                   |

| Property                                                                                                                                                                                                                                                                | Summary                                                                                    |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|
| <div>notation.rhythmMode   JavaScript</div> <div>notation.rhythmMode   JSON</div> <div>data-notation-rhythmmode   HTML</div> <div>Notation.RhythmMode   .net</div> <div>notation.rhythmMode   Android</div>                                                             | Controls how the rhythm notation is rendered for tab staves.                               |
| <div>notation.slurHeight   JavaScript</div> <div>notation.slurHeight   JSON</div> <div>data-notation-slurheight   HTML</div> <div>Notation.SlurHeight   .net</div> <div>notation.slurHeight   Android</div>                                                             | The height scale factor for slurs                                                          |
| <div>notation.smallGraceTabNotes   JavaScript</div> <div>notation.smallGraceTabNotes   JSON</div> <div>data-notation-smallgracetabnotes   HTML</div> <div>Notation.SmallGraceTabNotes   .net</div> <div>notation.smallGraceTabNotes   Android</div>                     | If set to true the guitar tabs on grace beats are rendered smaller.                        |
| <div>notation.transpositionPitches   JavaScript</div> <div>notation.transpositionPitches   JSON</div> <div>data-notation-transpositionpitches   HTML</div> <div>Notation.TranspositionPitches   .net</div> <div>notation.transpositionPitches   Android</div>           | The transposition pitch offsets for the individual tracks used for rendering and playback. |
| Player                                                                                                                                                                                                                                                                  |                                                                                            |
| <div>player.bufferTimeInMilliseconds   JavaScript</div> <div>player.bufferTimeInMilliseconds   JSON</div> <div>data-player-buffertimeinmilliseconds   HTML</div> <div>Player.BufferTimeInMilliseconds   .net</div> <div>player.bufferTimeInMilliseconds   Android</div> | The number of milliseconds the player should buffer.                                       |

| Property                                                                                                                                                                                                                                                                     | Summary                                                                           |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|
| <div>player.enableAnimatedBeatCursor   JavaScript</div> <div>player.enableAnimatedBeatCursor   JSON</div> <div>data-player-enableanimatedbeatcursor   HTML</div> <div>Player.EnableAnimatedBeatCursor   .net</div> <div>player.enableAnimatedBeatCursor   Android</div>      | Whether the beat cursor should be animated or just ticking.                       |
| <div>player.enableCursor   JavaScript</div> <div>player.enableCursor   JSON</div> <div>data-player-enablecursor   HTML</div> <div>Player.EnableCursor   .net</div> <div>player.enableCursor   Android</div>                                                                  | Whether playback cursors should be displayed.                                     |
| <div>player.enableElementHighlighting   JavaScript</div> <div>player.enableElementHighlighting   JSON</div> <div>data-player-enableelementhighlighting   HTML</div> <div>Player.EnableElementHighlighting   .net</div> <div>player.enableElementHighlighting   Android</div> | Whether the notation elements of the currently played beat should be highlighted. |
| <div>player.enablePlayer   JavaScript</div> <div>player.enablePlayer   JSON</div> <div>data-player-enableplayer   HTML</div> <div>Player.EnablePlayer   .net</div> <div>player.enablePlayer   Android</div>                                                                  | Whether the player should be enabled.                                             |
| <div>player.enableUserInteraction   JavaScript</div> <div>player.enableUserInteraction   JSON</div> <div>data-player-enableuserinteraction   HTML</div> <div>Player.EnableUserInteraction   .net</div> <div>player.enableUserInteraction   Android</div>                     | Whether the default user interaction behavior should be active or not.            |
| <div>player.nativeBrowserSmoothScroll   JavaScript</div> <div>player.nativeBrowserSmoothScroll   JSON</div> <div>data-player-nativebrowsersmoothscroll   HTML</div>                                                                                                          | Whether the native browser smooth scroll mechanism                                |

| Property                                                                                                                                                                                                                   | Summary                                                      |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------|
|                                                                                                                                                                                                                            | should be used over a custom animation.                      |
| <div>player.playTripletFeel   JavaScript</div> <div>player.playTripletFeel   JSON</div> <div>data-player-playtripletfeel   HTML</div> <div>Player.PlayTripletFeel   .net</div> <div>player.playTripletFeel   Android</div> | Whether the triplet feel should be played or only displayed. |
| <div>player.playerOffsetX   JavaScript</div> <div>player.playerOffsetX   JSON</div> <div>data-player-playeroffsetx   HTML</div> <div>Player.PlayerOffsetX   .net</div> <div>player.playerOffsetX   Android</div>           | The X-offset to add when scrolling.                          |
| <div>player.scrollMode   JavaScript</div> <div>player.scrollMode   JSON</div> <div>data-player-scrollmode   HTML</div> <div>Player.ScrollMode   .net</div> <div>player.scrollMode   Android</div>                          | The mode how to scroll.                                      |
| <div>player.scrollToOffsetY   JavaScript</div> <div>player.scrollToOffsetY   JSON</div> <div>data-player-scrolloffsety   HTML</div> <div>Player.ScrollToOffsetY   .net</div> <div>player.scrollToOffsetY   Android</div>   | The Y-offset to add when scrolling.                          |
| <div>player.scrollSpeed   JavaScript</div> <div>player.scrollSpeed   JSON</div> <div>data-player-scrollspeed   HTML</div> <div>Player.ScrollSpeed   .net</div> <div>player.scrollSpeed   Android</div>                     | How fast the scrolling to the new position should happen.    |

| Property                                                                                                                                                                                                                                            | Summary                                                                                     |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|
| <div>player.slide   JavaScript</div> <div>player.slide   JSON</div> <div>data-player-slide   HTML</div> <div>Player.Slide   .net</div> <div>player.slide   Android</div>                                                                            | The slide settings allow control how the different slide types are generated for audio.     |
| <div>player.songBookBendDuration   JavaScript</div> <div>player.songBookBendDuration   JSON</div> <div>data-player-songbookbendduration   HTML</div> <div>Player.SongBookBendDuration   .net</div> <div>player.songBookBendDuration   Android</div> | The bend duration in milliseconds for songbook bends.                                       |
| <div>player.songBookDipDuration   JavaScript</div> <div>player.songBookDipDuration   JSON</div> <div>data-player-songbookdipduration   HTML</div> <div>Player.SongBookDipDuration   .net</div> <div>player.songBookDipDuration   Android</div>      | The duration of whammy dips in milliseconds for songbook whammys.                           |
| <div>player.vibrato   JavaScript</div> <div>player.vibrato   JSON</div> <div>data-player-vibrato   HTML</div> <div>Player.Vibrato   .net</div> <div>player.vibrato   Android</div>                                                                  | The Vibrato settings allow control how the different vibrato types are generated for audio. |
| Player - JavaScript Specific                                                                                                                                                                                                                        |                                                                                             |
| <div>player.outputMode   JavaScript</div> <div>player.outputMode   JSON</div> <div>data-player-outputmode   HTML</div>                                                                                                                              | The mode used for playing audio samples                                                     |
| <div>player.scrollElement   JavaScript</div> <div>player.scrollElement   JSON</div> <div>data-player-scrollelement   HTML</div>                                                                                                                     | The element to apply the scrolling on.                                                      |

| Property                                                                                                            | Summary                                     |
|---------------------------------------------------------------------------------------------------------------------|---------------------------------------------|
| <div>player.soundFont   JavaScript</div> <div>player.soundFont   JSON</div> <div>data-player-soundfont   HTML</div> | The sound font file to load for the player. |

 [Edit this page](#)