RENTALS, SALES AND SERVICE NEW and USED • AERIAL PLATFORMS • DIGGER-DERRICK TRUCKS • SPECIALTY EQUIPMENT

HYDRAULIC PULLER—TENSIONER

THE CONDUX AFS404 HYDRAULIC PULLER/ TENSIONER PROVIDES UP TO 10,100 LBS. OF PULLING AND TENSIONING FORCE. DESIGNED FOR STRINGING ONE ROPE OR ONE CONDUCTOR. INDUSTRY LEADING FEATURES LIKE NEGATIVE SELF—ACTING HYDRAULIC BRAKE, HYDRAULIC DYNAMOMETER, HYDRAULIC COOLING SYSTEM AND 3 POSITION GEAR BOX. THE AFS404 HYDRAULICALLY CONTROLLED SYSTEM HELPS ELIMINATE CONDUCTOR GALLOPING, MAKING THIS ONE OF THE SAFEST TENSIONERS ON THE MARKET TODAY. POWERED BY A 85 H.P. DIESEL ENGINE. CLOSED HYDRAULIC SYSTEM THAT ALLOWS STEPLESS SPEED VARIATION IN BOTH DIRECTIONS. BULL WHEEL DIAM. 60 IN.
MAX. CONDUCTOR DIAM. 1 5/16 IN.
HYDRAULIC ROPE / CONDUCTOR CLAMP FOR REEL CHANGE OPERATIONS.

MIRK # 040M

PULLER PERFORMANCE:
MAX PULL: 10,100 LBS.
CONT. PULL: 1.7 MPH
MAX SPEED: 3.1 MPH
PULL AT MAX. SPEED: 5,600 LBS.

TENSIONER PERFORMANCE:
MAX TENSION: 10,100 LBS.
MAX SPEED: 3.1 MPH

NEGATIVE SELF ACTING HYDRAULIC BRAKE
HYDRAULIC DYNAMOMETER
HYDRAULIC OIL COOLING SYSTEM
GEAR BOX WITH 2 OPERATING POSITIONS &
1 NEUTRAL POSITION
LOW PULL/TENSION POSITION (350- 1800 LBS.)
HIGH PULL/ TENSION POSITION (1350- 10,100 LBS.)
HYDRAULIC ACTUATED FRONT PLOW

CALL US FOR ALL YOUR EQUIPMENT NEEDS:BUCKETS*DIGGERS*PULLERS*CRANES*SKIDDERS TRACK MACHINES*TRAILERS*CHIPPERS*REEL CARRIERS AND MUCH, MUCH MORE!!!!!!!!!