

Multiple AI Competition in Self Developed Game  
Term 2 Report  
ESTR4998/4999

April 13, 2021

Partners:                   XIAO Tianyi  
                                  LUO Lu  
Instructor: Prof. Andrej Bogdanov

## **Abstract**

(some abstract)

# **1 Background**

## **1.1 Previous Progress**

In the last semester, we have implemented the preliminary version of the game environment and  $Q$ -Learning agent. In this section, we will briefly re-iterate our previous progress before introducing new progress and our opinions.

### **1.1.1 Environment**

When we started to draft our proposal, original considerations for designing our environment included complexity, scalability and implemental difficulty. We hoped to design an environment which is easy to implement, complex enough to distinguish the power of different algorithms and can be reused for different game modes, including 1 player, 1 versus 1, and multi-players against multi-players.

Therefore, we designed a game similar to football, and the graph user interface for 1 versus 1 version can be found in figure 1. In this environment, each agent controls one player which is represented as a blue(team 0) or an orange(team 1) rounded rectangle. And the purpose of players is to shoot the ball, which is represented as a white ball, to goal of opponent team, which is represent as white rectangle in the left border(for team 0) and right border(for team 1).

The environment can output a list to represent the game state. For 1 versus 1 mode, the list will contain the position of the current player, the position

of the opponent player and the position of the ball.

The environment can receive a list with size equal 2 from a player as input, the first element represents the direction and the second element represents the action, shoot or not.

After receiving an action, we can call the reward function to calculate the reward of the given action, and return the reward as a scalar number to that agent.

### **1.1.2 Agent**

In the last semester, we have finished the design of Q-Learning agent by following the algorithm provided in the background theory section. Moreover, our conclusion of the last term is that our game is too complicated to be trained by Q-Learning even for 1 vs 1 mode, even if we simplified input states.

The reason to simplify states is that the number of raw game states is an enormous figure even without considering the action space. The simplify function will replace the positions of opponent player and ball by logarithms of relative positions(distances) with base 10, which will compress the range of these 4 parameters from several hundred to 7. This will significantly reduce the size of Q-Table and make some simpler situations trainable, and we will discuss this later.

## **2 Implementation**

### **2.1 Single Player Mode**

In the beginning stage of our project in this term, we found that it's hard to train AI to play our game with DQN. So to simplify the issue and solve

our problem better, we first implement a single player mode. Then with the experience from single player mode, we are finally able to train DQN AI that could play 1v1 mode with logic.

In this mode, we randomize the initialization of our player and ball. They will be put on the soccer field randomly when each episode begins.

```
def reset_random(ball, player):
    ball.rect.centerx = screen_rect.centerx + (np_random.rand() - 0.5) * conf.width * 0.65
    ball.rect.centery = screen_rect.centery + (np_random.rand() - 0.5) * conf.height * 0.65
    ball.if_caught = False
    ball.catcher = -1
    ball.v.x = 0
    ball.v.y = 0
    player.rect.centerx = screen_rect.centerx + (np_random.rand() - 0.5) * conf.width * 0.65
    player.rect.centery = screen_rect.centery + (np_random.rand() - 0.5) * conf.height * 0.65
    player.v.x = 0
    player.v.y = 0
```

Figure 1: implementation of reset\_random

## 2.2 Agent State

The state of agent represent the features sent to neural network. We add one more item into the agent state, which shows if the player is catching the ball or not. In the soccer game, there is cool down time for each player to prevent it to get the ball back as soon as it just shoots the ball. Therefore the coincidence of positions of player and ball doesn't mean that player could catch and shoot the ball. So one more item in agent state could help AI better understand its situation.

## 2.3 Reward Function

Reward function is crucial in reinforcement learning. As a soccer game, when a team get a goal, it will get huge reward. Besides, when a player catch a ball, it will also receive reward. Besides, to encourage player to keep the ball longer, once the player shoot the ball, it will get punishment.

However, only these basic rewards are not enough for training. Below are our modification for other part of reward function.

### 2.3.1 Original Reward Function

In our original reward function, we give reward to the agent if it's closer to the ball than other player. Otherwise, the agent would get punishment. Besides, if the ball get closer to one door, the team attacking this door would get reward, and other team would get punishment.

---

**Algorithm 1** Original Reward(*Agent1*, *Agent2*, *Ball*)

---

```
Closer_Agent(Agent1, Agent2, Ball).reward += 200
Further_Agent(Agent1, Agent2, Ball).reward -= 200
if Ball Moves right then
    Agent1.reward += 600
    Agent2.reward -= 600
if Ball Moves left then
    Agent2.reward += 600
    Agent1.reward -= 600
if Ball goes into right door then
    Agent1.reward += 100000
    Agent2.reward -= 10000
if Ball goes into left door then
    Agent2.reward += 100000
    Agent1.reward -= 10000
if Agent shoot the ball then
    Agent-shoot-ball.reward -= 1000
```

---

### 2.3.2 Reward Function For Single Mode

With Single Player Mode, we need a new reward function. This one is simple. If the player is moving closer to the ball, it will get reward, otherwise it will get punishment. Also, if the player shoot the ball to the direction to the right door, it will get reward. But if it shoots to wrong direction, it will get punishment. Then to encourage the player to keep the ball, it will also have reward when it keeps the ball.

---

**Algorithm 2** Single Mode Reward(*Agent*, *Ball*)

---

```
if Closer(Agent, Ball) or Keep(Agent, Ball) then
    Agent.reward + = 200
else
    Agent.reward - = 200
if Ball goes into right door then
    Agent.reward + = 100000
if Ball goes into left door then
    Agent.reward - = 10000
if Agent shoot the ball then
    team-of-the-agent.reward - = 1000
```

---

### 2.3.3 New Reward Function

Then, with experience from single player mode, we modify our original reward function. We cancel the comparison of distance to ball between two agents, instead we only care if the agent is closer to the ball. Also, we cancel some punishment to avoid agent playing to negatively. And we adjust the amount of reward during our test.

---

**Algorithm 3** Original Reward(*Agent1, Agent2, Ball*)

---

```
if Closer(Agent1, Ball) then
    Agent1.reward + = 100
else
    Agent1.reward - = 100
if Closer(Agent2, Ball) then
    Agent2.reward + = 100
else
    Agent2.reward - = 100
if Ball Moves right then
    Agent1.reward + = 100
if Ball Moves left then
    Agent2.reward + = 100
if Ball goes into right door then
    Agent1.reward + = 100000
    Agent2.reward - = 10000
if Ball goes into left door then
    Agent2.reward + = 100000
    Agent1.reward - = 10000
if Agent shoot the ball then
    Agent-shoot-ball.reward - = 1000
```

---

## 2.4 Neural Network

## 2.5 Measurement of Performance

# 3 Result

## 3.1 Single Player Mode

## 3.2 1v1 Mode

# 4 Discussion

# References

- [1] Silver, David, et al. "Mastering the game of Go with deep neural networks and tree search." *nature* 529.7587 (2016): 484-489.

- [2] Mnih, Volodymyr, et al. "Playing atari with deep reinforcement learning." arXiv preprint arXiv:1312.5602 (2013).
- [3] Berner, Christopher, et al. "Dota 2 with large scale deep reinforcement learning." arXiv preprint arXiv:1912.06680 (2019).
- [4] Zoph, Barret, and Quoc V. Le. "Neural architecture search with reinforcement learning." arXiv preprint arXiv:1611.01578 (2016).
- [5] Mnih, Volodymyr, et al. "Human-level control through deep reinforcement learning." nature 518.7540 (2015): 529-533.