



Query - postgres on postgres@localhost:5432 \*

File Edit Query Favourites Macros View Help

postgres on postgres@localhost:5432

SQL Editor Graphical Query Builder

Previous queries

select \* from customers;

select \* from agents;

select \* from products;

select \* from orders;

Scratch pad

Output pane

Data Output Explain Messages History

	pid	name	city	quantity	priceusd
	character(3)	character varying(16)	character varying(20)	integer	numeric(10,2)
1	p01	comb	Dallas	111400	0.50
2	p02	brush	Newark	203000	0.50
3	p03	razor	Duluth	150600	1.00
4	p04	pen	Duluth	125300	1.00
5	p05	pencil	Dallas	221400	1.00
6	p06	folder	Dallas	123100	2.00
7	p07	case	Newark	100500	1.00
8	p08	clip	Newark	200600	1.25

OK. Unix Ln 5, Col 1, Ch 50 23 chars 8 rows. 75 ms

pgAdmin III

Properties Statistics Dependencies Dependents

Properties

Property	Value
name	postgres
id	12029
owner	postgres
encoding	pg_default
tablespace	pg_default
collation	UTF8
locale	English_United States.1252
character type	English_United States.1252
default schema	public
default table ACL	
default sequence ACL	
default function ACL	
allow connections?	Yes
is_superuser?	Yes
connection limit	-1
is template database?	No
comment	default administrative connection database

Database: postgres

DROP DATABASE postgres;

CREATE DATABASE postgres

WITH OWNER = postgres

ENCODING = 'UTF8'

TABLESPACE = pg\_default

LC\_COLLATE = 'English\_United States.1252'

LC\_CTYPE = 'English\_United States.1252'

CONNECTION LIMIT = -1;

0.40 secs

Query - postgres on postgres@localhost:5432 \*

File Edit Query Favourites Macros View Help

postgres on postgres@localhost:5432

SQL Editor Graphical Query Builder

Previous queries

select \* from customers;

select \* from agents;

select \* from products;

select \* from orders;

Scratch pad

Output pane

Data Output Explain Messages History

	ordno	mon	cid	aid	pid	qty	dollars
	integer	character(3)	character(4)	character(3)	character(3)	integer	numeric(12,2)
1	1011	jan	c001	a01	p01	1000	450.00
2	1013	jan	c002	a03	p03	1000	680.00
3	1015	jan	c003	a03	p05	1200	1104.00
4	1017	feb	c001	a06	p03	600	540.00
5	1018	feb	c001	a03	p04	600	540.00
6	1019	feb	c001	a02	p02	400	180.00
7	1020	feb	c006	a03	p07	600	600.00
8	1021	feb	c004	a06	p01	1000	460.00
9	1022	mar	c001	a05	p06	400	720.00
10	1023	mar	c001	a04	p05	500	450.00
11	1024	mar	c006	a06	p01	800	400.00
12	1025	apr	c001	a05	p07	800	720.00
13	1026	may	c002	a05	p03	800	704.00
14	1016	jan	c006	a01	p01	1000	999.99

OK. Unix Ln 7, Col 1, Ch 75 21 chars 14 rows. 65 ms

pgAdmin III

Properties Statistics Dependencies Dependents

Properties

Property	Value
name	postgres
id	12029
owner	postgres
encoding	pg_default
tablespace	pg_default
collation	UTF8
locale	English_United States.1252
character type	English_United States.1252
default schema	public
default table ACL	
default sequence ACL	
default function ACL	
allow connections?	Yes
is_superuser?	Yes
connection limit	-1
is template database?	No
comment	default administrative connection database

Database: postgres

DROP DATABASE postgres;

CREATE DATABASE postgres

WITH OWNER = postgres

ENCODING = 'UTF8'

TABLESPACE = pg\_default

LC\_COLLATE = 'English\_United States.1252'

LC\_CTYPE = 'English\_United States.1252'

CONNECTION LIMIT = -1;

0.40 secs