BrainAge Connect

API Endpoint Summary

Complete catalogue of all 35 HTTP method/resource operations.

Student	Module	Assessment
Boyu Yuan B01089181	COM661 Full Stack Strategies and Development	CW1 - Back-end API

Derived from docs/openapi.json and checked against the Flask route design. This is a concise operation and validation catalogue; the companion collection reference contains observed examples.

Prepared 28 October 2026, 01:46 (UTC+08:00)

Application: infant MRI metadata and user-supplied precomputed result management. No MRI inference or clinical diagnosis is claimed.

Contents

API Endpoint Summary 1

Contents 2

1. Service and common contract 4

2. Complete operation catalogue 5

3. Request field definitions 7

- SampleInput . . . 7
- NoteInput . . . 7
- AnalysisInput . . . 7
- Login . . . 7
- Register . . . 8
- PasswordChange . . . 8
- UserUpdate . . . 8

4. Operation details 8

- POST /api/v1/auth/register . . . 8
- POST /api/v1/auth/login . . . 8
- POST /api/v1/auth/logout . . . 8
- GET /api/v1/auth/me . . . 8
- PUT /api/v1/auth/password . . . 8
- GET /api/v1/samples . . . 9
- POST /api/v1/samples . . . 9
- GET /api/v1/samples/{sample_id} . . . 9
- PATCH /api/v1/samples/{sample_id} . . . 9
- PUT /api/v1/samples/{sample_id} . . . 9
- DELETE /api/v1/samples/{sample_id} . . . 9
- GET /api/v1/samples/{sample_id}/notes . . . 9
- POST /api/v1/samples/{sample_id}/notes . . . 10
- DELETE /api/v1/samples/{sample_id}/notes/{child_id} . . . 10
- GET /api/v1/samples/{sample_id}/notes/{child_id} . . . 10
- PATCH /api/v1/samples/{sample_id}/notes/{child_id} . . . 10
- PUT /api/v1/samples/{sample_id}/notes/{child_id} . . . 10
- GET /api/v1/samples/{sample_id}/analyses . . . 10
- POST /api/v1/samples/{sample_id}/analyses . . . 10
- DELETE /api/v1/samples/{sample_id}/analyses/{child_id} . . . 10
- GET /api/v1/samples/{sample_id}/analyses/{child_id} . . . 11
- PATCH /api/v1/samples/{sample_id}/analyses/{child_id} . . . 11
- PUT /api/v1/samples/{sample_id}/analyses/{child_id} . . . 11
- GET /api/v1/statistics/overview . . . 11

GET /api/v1/statistics/cohorts . . . 11
GET /api/v1/statistics/maturity . . . 11
GET /api/v1/statistics/comparison . . . 11
GET /api/v1/exports/cohorts . . . 12
GET /api/v1/users . . . 12
GET /api/v1/users/{user_id} . . . 12
PATCH /api/v1/users/{user_id} . . . 12
PUT /api/v1/users/{user_id} . . . 12
GET /api/v1/audit-logs . . . 12
GET /api/v1/health . . . 12
GET /api/v1/openapi.json . . . 12

5. Worked workflow 13

6. Scope and documentation limits 13

1. Service and common contract

Base path /api/v1. Real service: http://127.0.0.1:5000; synthetic demo: http://127.0.0.1:5001. Authentication uses Authorization: Bearer <access_token>. JSON bodies require Content-Type: application/json.

All age fields are postmenstrual weeks. Public resource IDs are 24 hexadecimal characters; dates are UTC ISO 8601. Lists use data plus pagination; details use data. PUT and PATCH update supplied fields only. Unknown/read-only body fields and invalid/repeated list query parameters are rejected.

Status	Meaning
200 / 201	Read or update successful / resource created
204	Successful delete or logout; empty body
400 / 415	Invalid input / JSON content type required
401 / 403	Missing, expired or revoked session / permission denied or inactive login
404 / 409	Missing or inaccessible resource / duplicate, concurrent write or dependent-modality conflict
413 / 503	Request too large / database temporarily unavailable

2. Complete operation catalogue

Method	Resource	Access
POST	/api/v1/auth/register	Public
POST	/api/v1/auth/login	Public
POST	/api/v1/auth/logout	Approved user; visible samples only
GET	/api/v1/auth/me	Approved user; visible samples only
PUT	/api/v1/auth/password	Approved user; visible samples only
GET	/api/v1/samples	Approved user; visible samples only
POST	/api/v1/samples	Approved user; visible samples only
GET	/api/v1/samples/{sample_id}	Approved user; visible samples only
PATCH	/api/v1/samples/{sample_id}	Owner/admin
PUT	/api/v1/samples/{sample_id}	Owner/admin
DELETE	/api/v1/samples/{sample_id}	Owner/admin
GET	/api/v1/samples/{sample_id}/notes	Approved user; visible samples only
POST	/api/v1/samples/{sample_id}/notes	Approved user; visible samples only
DELETE	/api/v1/samples/{sample_id}/notes/{child_id}	Author/admin
GET	/api/v1/samples/{sample_id}/notes/{child_id}	Approved user; visible samples only
PATCH	/api/v1/samples/{sample_id}/notes/{child_id}	Author/admin
PUT	/api/v1/samples/{sample_id}/notes/{child_id}	Author/admin
GET	/api/v1/samples/{sample_id}/analyses	Approved user; visible samples only
POST	/api/v1/samples/{sample_id}/analyses	Approved user; visible samples only
DELETE	/api/v1/samples/{sample_id}/analyses/{child_id}	Author/admin
GET	/api/v1/samples/{sample_id}/analyses/{child_id}	Approved user; visible samples only
PATCH	/api/v1/samples/{sample_id}/analyses/{child_id}	Author/admin
PUT	/api/v1/samples/{sample_id}/analyses/{child_id}	Author/admin
GET	/api/v1/statistics/overview	Approved user; visible samples only
GET	/api/v1/statistics/cohorts	Approved user; visible samples only
GET	/api/v1/statistics/maturity	Approved user; visible samples only
GET	/api/v1/statistics/comparison	Approved user; visible samples only
GET	/api/v1/exports/cohorts	Approved user; visible samples only
GET	/api/v1/users	Administrator
GET	/api/v1/users/{user_id}	Administrator
PATCH	/api/v1/users/{user_id}	Administrator

Method	Resource	Access
PUT	/api/v1/users/{user_id}	Administrator
GET	/api/v1/audit-logs	Administrator
GET	/api/v1/health	Public
GET	/api/v1/openapi.json	Public

3. Request field definitions

SampleInput

Field	Constraints
sample_code	string; maxLength: 120; pattern: ^[A-Za-z0-9_.-]+$
age_at_scan_weeks	number; nullable; minimum: 20; maximum: 80
birth_age_weeks	number; nullable; minimum: 20; maximum: 45
sex	string; allowed: Female, Male, Unknown
has_dmri	boolean
has_fmri	boolean
status	string; allowed: registered, ready, processing, completed, failed
visibility	string; allowed: private, shared
description	string; maxLength: 2000

NoteInput

Field	Constraints
text	string; minLength: 1; maxLength: 4000
category	string; allowed: research, quality, review

AnalysisInput

Field	Constraints
modality	string; allowed: dmri, fmri, combined
estimated_age_weeks	number; minimum: 20; maximum: 80
method	string; minLength: 1; maxLength: 120
model_version	string; minLength: 1; maxLength: 120
provenance	string; minLength: 1; maxLength: 1000
quality_score	number; nullable; minimum: 0; maximum: 1

Login

Field	Constraints
username	string
password	string; format: password

Register

Field	Constraints
username	string
password	string; format: password
display_name	string

PasswordChange

Field	Constraints
current_password	string; format: password
new_password	string; format: password

UserUpdate

Field	Constraints
active	boolean
role	string; allowed: admin, researcher

4. Operation details

POST /api/v1/auth/register

Access: Public. New accounts are inactive researchers. Reject role escalation; approval is required before login.

Body fields: username, password, display_name. Required: username, password, display_name.

Success: 201. See common contract for applicable errors; individual authorization and validation paths determine which errors can occur.

POST /api/v1/auth/login

Access: Public. The response describes the current service. This endpoint does not expose raw MRI files or perform prediction.

Body fields: username, password. Required: username, password.

Success: 200. See common contract for applicable errors; individual authorization and validation paths determine which errors can occur.

POST /api/v1/auth/logout

Access: Approved user; visible samples only. Revokes the current jti immediately. The TTL index eventually removes expired revocation records; no response body is returned.

Success: 204. See common contract for applicable errors; individual authorization and validation paths determine which errors can occur.

GET /api/v1/auth/me

Access: Approved user; visible samples only. The response describes the current service. This endpoint does not expose raw MRI files or perform prediction.

Success: 200. See common contract for applicable errors; individual authorization and validation paths determine which errors can occur.

PUT /api/v1/auth/password

Access: Approved user; visible samples only. Changing the password increments auth_version, invalidating all existing sessions. Passwords: at least 10 characters, at most 72 UTF-8 bytes.

Body fields: current_password, new_password. Required: current_password, new_password.

Success: 200. See common contract for applicable errors; individual authorization and validation paths determine which errors can occur.

GET /api/v1/samples

Access: Approved user; visible samples only. A session record is the main resource. Creation assigns caller ownership, manual source and private visibility by default. Imported identity and modality-presence fields cannot be changed through the API. Changing reference age recomputes derived differences.

Parameters: q (query): string | age_min (query): number; minimum: 20; maximum: 80 | age_max (query): number; minimum: 20; maximum: 80 | modality (query): string; allowed: dmri, fmri, both, neither | source (query): string; allowed: dhcp_local, manual, synthetic | status (query): string; allowed: registered, ready, processing, completed, failed | sex (query): string; allowed: Female, Male, Unknown | page (query): integer; minimum: 1; maximum: 1000000; default: 1 | page_size (query): integer; minimum: 1; maximum: 100; default: 20 | sort (query): string; allowed: sample_code, age_at_scan_weeks, created_at, updated_at; default: sample_code | order (query): string; allowed: asc, desc; default: asc

Success: 200. See common contract for applicable errors; individual authorization and validation paths determine which errors can occur.

POST /api/v1/samples

Access: Approved user; visible samples only. A session record is the main resource. Creation assigns caller ownership, manual source and private visibility by default. Imported identity and modality-presence fields cannot be changed through the API. Changing reference age recomputes derived differences.

Body fields: sample_code, age_at_scan_weeks, birth_age_weeks, sex, has_dmri, has_fmri, status, visibility, description. Required: sample_code, age_at_scan_weeks.

Success: 201. See common contract for applicable errors; individual authorization and validation paths determine which errors can occur.

GET /api/v1/samples/{sample_id}

Access: Approved user; visible samples only. A session record is the main resource. Creation assigns caller ownership, manual source and private visibility by default. Imported identity and modality-presence fields cannot be changed through the API. Changing reference age recomputes derived differences.

Parameters: sample_id (path): string; pattern: ^[a-fA-F0-9]{24}$

Success: 200. See common contract for applicable errors; individual authorization and validation paths determine which errors can occur.

PATCH /api/v1/samples/{sample_id}

Access: Owner/admin. A session record is the main resource. Creation assigns caller ownership, manual source and private visibility by default. Imported identity and modality-presence fields cannot be changed through the API. Changing reference age recomputes derived differences.

Body fields: sample_code, age_at_scan_weeks, birth_age_weeks, sex, has_dmri, has_fmri, status, visibility, description. Required: at least one editable field for update.

Parameters: sample_id (path): string; pattern: ^[a-fA-F0-9]{24}$

Success: 200. See common contract for applicable errors; individual authorization and validation paths determine which errors can occur.

PUT /api/v1/samples/{sample_id}

Access: Owner/admin. A session record is the main resource. Creation assigns caller ownership, manual source and private visibility by default. Imported identity and modality-presence fields cannot be changed through the API. Changing reference age recomputes derived differences.

Body fields: sample_code, age_at_scan_weeks, birth_age_weeks, sex, has_dmri, has_fmri, status, visibility, description. Required: at least one editable field for update.

Parameters: sample_id (path): string; pattern: ^[a-fA-F0-9]{24}$

Success: 200. See common contract for applicable errors; individual authorization and validation paths determine which errors can occur.

DELETE /api/v1/samples/{sample_id}

Access: Owner/admin. A session record is the main resource. Creation assigns caller ownership, manual source and private visibility by default. Imported identity and modality-presence fields cannot be changed through the API. Changing reference age recomputes derived differences.

Parameters: sample_id (path): string; pattern: ^[a-fA-F0-9]{24}$

Success: 204. See common contract for applicable errors; individual authorization and validation paths determine which errors can occur.

GET /api/v1/samples/{sample_id}/notes

Access: Approved user; visible samples only. Notes have an independent ID, author, category and timestamps. A user who can see a sample can add a note; mutation requires the note author or admin. At most 200 notes per session.

Parameters: sample_id (path): string; pattern: ^[a-fA-F0-9]{24}$ | page (query): integer; minimum: 1; maximum: 1000000; default: 1 | page_size (query): integer; minimum: 1; maximum: 100; default: 20 | sort (query): string; allowed: created_at, updated_at; default: created_at | order (query): string; allowed: asc, desc; default: asc

Success: 200. See common contract for applicable errors; individual authorization and validation paths determine which errors can occur.

POST /api/v1/samples/{sample_id}/notes

Access: Approved user; visible samples only. Notes have an independent ID, author, category and timestamps. A user who can see a sample can add a note; mutation requires the note author or admin. At most 200 notes per session.

Body fields: text, category. Required: text.

Parameters: sample_id (path): string; pattern: ^[a-fA-F0-9]{24}$

Success: 201. See common contract for applicable errors; individual authorization and validation paths determine which errors can occur.

DELETE /api/v1/samples/{sample_id}/notes/{child_id}

Access: Author/admin. Notes have an independent ID, author, category and timestamps. A user who can see a sample can add a note; mutation requires the note author or admin. At most 200 notes per session.

Parameters: sample_id (path): string; pattern: ^[a-fA-F0-9]{24}$ | child_id (path): string; pattern: ^[a-fA-F0-9]{24}$

Success: 204. See common contract for applicable errors; individual authorization and validation paths determine which errors can occur.

GET /api/v1/samples/{sample_id}/notes/{child_id}

Access: Approved user; visible samples only. Notes have an independent ID, author, category and timestamps. A user who can see a sample can add a note; mutation requires the note author or admin. At most 200 notes per session.

Parameters: sample_id (path): string; pattern: ^[a-fA-F0-9]{24}$ | child_id (path): string; pattern: ^[a-fA-F0-9]{24}$

Success: 200. See common contract for applicable errors; individual authorization and validation paths determine which errors can occur.

PATCH /api/v1/samples/{sample_id}/notes/{child_id}

Access: Author/admin. Notes have an independent ID, author, category and timestamps. A user who can see a sample can add a note; mutation requires the note author or admin. At most 200 notes per session.

Body fields: text, category. Required: at least one editable field for update.

Parameters: sample_id (path): string; pattern: ^[a-fA-F0-9]{24}$ | child_id (path): string; pattern: ^[a-fA-F0-9]{24}$

Success: 200. See common contract for applicable errors; individual authorization and validation paths determine which errors can occur.

PUT /api/v1/samples/{sample_id}/notes/{child_id}

Access: Author/admin. Notes have an independent ID, author, category and timestamps. A user who can see a sample can add a note; mutation requires the note author or admin. At most 200 notes per session.

Body fields: text, category. Required: at least one editable field for update.

Parameters: sample_id (path): string; pattern: ^[a-fA-F0-9]{24}$ | child_id (path): string; pattern: ^[a-fA-F0-9]{24}$

Success: 200. See common contract for applicable errors; individual authorization and validation paths determine which errors can occur.

GET /api/v1/samples/{sample_id}/analyses

Access: Approved user; visible samples only. Store a supplied result, never run a model. Required modality availability is checked. Difference = estimated_age_weeks - age_at_scan_weeks, or null when reference age is unknown. At most 200 analyses per session.

Parameters: sample_id (path): string; pattern: ^[a-fA-F0-9]{24}$ | page (query): integer; minimum: 1; maximum: 1000000; default: 1 | page_size (query): integer; minimum: 1; maximum: 100; default: 20 | sort (query): string; allowed: created_at, updated_at; default: created_at | order (query): string; allowed: asc, desc; default: asc

Success: 200. See common contract for applicable errors; individual authorization and validation paths determine which errors can occur.

POST /api/v1/samples/{sample_id}/analyses

Access: Approved user; visible samples only. Store a supplied result, never run a model. Required modality availability is checked. Difference = estimated_age_weeks - age_at_scan_weeks, or null when reference age is unknown. At most 200 analyses per session.

Body fields: modality, estimated_age_weeks, method, model_version, provenance, quality_score. Required: modality, estimated_age_weeks, method, model_version, provenance.

Parameters: sample_id (path): string; pattern: ^[a-fA-F0-9]{24}$

Success: 201. See common contract for applicable errors; individual authorization and validation paths determine which errors can occur.

DELETE /api/v1/samples/{sample_id}/analyses/{child_id}

Access: Author/admin. Store a supplied result, never run a model. Required modality availability is checked. Difference = estimated_age_weeks - age_at_scan_weeks, or null when reference age is unknown. At most 200 analyses per session.

Parameters: sample_id (path): string; pattern: ^[a-fA-F0-9]{24}$ | child_id (path): string; pattern: ^[a-fA-F0-9]{24}$

Success: 204. See common contract for applicable errors; individual authorization and validation paths determine which errors can occur.

GET /api/v1/samples/{sample_id}/analyses/{child_id}

Access: Approved user; visible samples only. Store a supplied result, never run a model. Required modality availability is checked. Difference = estimated_age_weeks - age_at_scan_weeks, or null when reference age is unknown. At most 200 analyses per session.

Parameters: sample_id (path): string; pattern: ^[a-fA-F0-9]{24}$ | child_id (path): string; pattern: ^[a-fA-F0-9]{24}$

Success: 200. See common contract for applicable errors; individual authorization and validation paths determine which errors can occur.

PATCH /api/v1/samples/{sample_id}/analyses/{child_id}

Access: Author/admin. Store a supplied result, never run a model. Required modality availability is checked. Difference = estimated_age_weeks - age_at_scan_weeks, or null when reference age is unknown. At most 200 analyses per session.

Body fields: modality, estimated_age_weeks, method, model_version, provenance, quality_score. Required: at least one editable field for update.

Parameters: sample_id (path): string; pattern: ^[a-fA-F0-9]{24}$ | child_id (path): string; pattern: ^[a-fA-F0-9]{24}$

Success: 200. See common contract for applicable errors; individual authorization and validation paths determine which errors can occur.

PUT /api/v1/samples/{sample_id}/analyses/{child_id}

Access: Author/admin. Store a supplied result, never run a model. Required modality availability is checked. Difference = estimated_age_weeks - age_at_scan_weeks, or null when reference age is unknown. At most 200 analyses per session.

Body fields: modality, estimated_age_weeks, method, model_version, provenance, quality_score. Required: at least one editable field for update.

Parameters: sample_id (path): string; pattern: ^[a-fA-F0-9]{24}$ | child_id (path): string; pattern: ^[a-fA-F0-9]{24}$

Success: 200. See common contract for applicable errors; individual authorization and validation paths determine which errors can occur.

GET /api/v1/statistics/overview

Access: Approved user; visible samples only. The response describes the current service. This endpoint does not expose raw MRI files or perform prediction.

Parameters: q (query): string | age_min (query): number; minimum: 20; maximum: 80 | age_max (query): number; minimum: 20; maximum: 80 | modality (query): string; allowed: dmri, fmri, both, neither | source (query): string; allowed: dhcp_local, manual, synthetic | status (query): string; allowed: registered, ready, processing, completed, failed | sex (query): string; allowed: Female, Male, Unknown

Success: 200. See common contract for applicable errors; individual authorization and validation paths determine which errors can occur.

GET /api/v1/statistics/cohorts

Access: Approved user; visible samples only. Counts are scan sessions. Age bins: <32, 32-<37, 37-<42, >=42 weeks and unknown; sources separated. Null ages do not contribute to mean scan age. CSV includes a header and Content-Disposition.

Parameters: q (query): string | age_min (query): number; minimum: 20; maximum: 80 | age_max (query): number; minimum: 20; maximum: 80 | modality (query): string; allowed: dmri, fmri, both, neither | source (query): string; allowed: dhcp_local, manual, synthetic | status (query): string; allowed: registered, ready, processing, completed, failed | sex (query): string; allowed: Female, Male, Unknown

Success: 200. See common contract for applicable errors; individual authorization and validation paths determine which errors can occur.

GET /api/v1/statistics/maturity

Access: Approved user; visible samples only. Select optional method and version before newest CREATED result per session/modality. Optional age bands and non-null difference counts are available. Unfiltered models may be mixed.

Parameters: q (query): string | age_min (query): number; minimum: 20; maximum: 80 | age_max (query): number; minimum: 20; maximum: 80 | modality (query): string; allowed: dmri, fmri, both, neither | source (query): string; allowed: dhcp_local, manual, synthetic | status (query): string; allowed: registered, ready, processing, completed, failed | sex (query): string; allowed: Female, Male, Unknown | method (query): string; maxLength: 120 | model_version (query): string; maxLength: 120 | group_by (query): string; allowed: overall, age_group; default: overall

Success: 200. See common contract for applicable errors; individual authorization and validation paths determine which errors can occur.

GET /api/v1/statistics/comparison

Access: Approved user; visible samples only. Paired sessions only: optional separate method/version filters precede newest dMRI and fMRI selection. Grouped by source; unfiltered models may be mixed.

Parameters: q (query): string | age_min (query): number; minimum: 20; maximum: 80 | age_max (query): number; minimum: 20; maximum: 80 | modality (query): string; allowed: dmri, fmri, both, neither | source (query): string; allowed: dhcp_local, manual, synthetic | status (query): string; allowed: registered, ready, processing, completed, failed | sex (query): string; allowed: Female, Male, Unknown | dmri_method (query): string; maxLength: 120 | dmri_model_version (query): string; maxLength: 120 | fmri_method (query): string; maxLength: 120 | fmri_model_version (query): string; maxLength: 120

Success: 200. See common contract for applicable errors; individual authorization and validation paths determine which errors can occur.

GET /api/v1/exports/cohorts

Access: Approved user; visible samples only. Counts are scan sessions. Age bins: <32, 32-<37, 37-<42, >=42 weeks and unknown; sources separated. Null ages do not contribute to mean scan age. CSV includes a header and Content-Disposition.

Parameters: q (query): string | age_min (query): number; minimum: 20; maximum: 80 | age_max (query): number; minimum: 20; maximum: 80 | modality (query): string; allowed: dmri, fmri, both, neither | source (query): string; allowed: dhcp_local, manual, synthetic | status (query): string; allowed: registered, ready, processing, completed, failed | sex (query): string; allowed: Female, Male, Unknown | format (query): string; allowed: json, csv; default: json

Success: 200. See common contract for applicable errors; individual authorization and validation paths determine which errors can occur.

GET /api/v1/users

Access: Administrator. Administrator-only accounts. Public JSON excludes password_hash/auth_version. Role/activation changes invalidate sessions. An administrator cannot use this route to alter their own role or activation.

Parameters: page (query): integer; minimum: 1; maximum: 1000000; default: 1 | page_size (query): integer; minimum: 1; maximum: 100; default: 20

Success: 200. See common contract for applicable errors; individual authorization and validation paths determine which errors can occur.

GET /api/v1/users/{user_id}

Access: Administrator. Administrator-only accounts. Public JSON excludes password_hash/auth_version. Role/activation changes invalidate sessions. An administrator cannot use this route to alter their own role or activation.

Parameters: user_id (path): string; pattern: ^[a-fA-F0-9]{24}$

Success: 200. See common contract for applicable errors; individual authorization and validation paths determine which errors can occur.

PATCH /api/v1/users/{user_id}

Access: Administrator. Administrator-only accounts. Public JSON excludes password_hash/auth_version. Role/activation changes invalidate sessions. An administrator cannot use this route to alter their own role or activation.

Body fields: active, role. Required: at least one editable field for update.

Parameters: user_id (path): string; pattern: ^[a-fA-F0-9]{24}$

Success: 200. See common contract for applicable errors; individual authorization and validation paths determine which errors can occur.

PUT /api/v1/users/{user_id}

Access: Administrator. Administrator-only accounts. Public JSON excludes password_hash/auth_version. Role/activation changes invalidate sessions. An administrator cannot use this route to alter their own role or activation.

Body fields: active, role. Required: at least one editable field for update.

Parameters: user_id (path): string; pattern: ^[a-fA-F0-9]{24}$

Success: 200. See common contract for applicable errors; individual authorization and validation paths determine which errors can occur.

GET /api/v1/audit-logs

Access: Administrator. Read-only paginated mutation events. Resource writes and audit writes are separate operations on the standalone database, not an atomic cross-collection transaction.

Parameters: page (query): integer; minimum: 1; maximum: 1000000; default: 1 | page_size (query): integer; minimum: 1; maximum: 100; default: 20

Success: 200. See common contract for applicable errors; individual authorization and validation paths determine which errors can occur.

GET /api/v1/health

Access: Public. The response describes the current service. This endpoint does not expose raw MRI files or perform prediction.

Success: 200. See common contract for applicable errors; individual authorization and validation paths determine which errors can occur.

GET /api/v1/openapi.json

Access: Public. The response describes the current service. This endpoint does not expose raw MRI files or perform prediction.

Success: 200. See common contract for applicable errors; individual authorization and validation paths determine which errors can occur.

5. Worked workflow

Register a temporary researcher; approve it with an administrator; log in; create a session; create and update a note and supplied result; retrieve filtered sessions and summaries; delete child records and the parent; confirm 404; change password and verify old-token rejection; log out and verify revocation. The Postman collection automates this lifecycle.

6. Scope and documentation limits

No raw MRI upload/download or inference endpoint is provided. Optional model filters and age-group maturity are documented above. OpenAPI success schemas are conservative descriptions derived from observed synthetic examples, not exhaustive formal contracts.