

## 15 Arrays (2) — Sorting and Searching

*Instructor:* Ke Wei (柯韋)

▶▶ A319    ☎ Ext. 6452    ✉ wke@ipm.edu.mo

<http://brouwer.ipm.edu.mo/COMP112/18/>

Bachelor of Science in Computing, School of Public Administration, Macao Polytechnic Institute

November 7, 2018



# Outline

- 1 Bubble Sort
- 2 Binary Search

## Reading Homework

### Textbook

- Section 7.10–7.12.

### Internet


- Bubble Sort ([http://www.algolist.net/Algorithms/Sorting/Bubble\\_sort](http://www.algolist.net/Algorithms/Sorting/Bubble_sort)).
- Binary Search  
(<https://www.hackerearth.com/practice/algorithms/searching/binary-search/tutorial/>).

# Bubble Sort

- Sometimes we need to arrange the array elements according to their order, that is, smaller elements positioned at lower indices.
- This is called sorting the array ascendingly.



- Bubble sort arranges an array by checking each pair of adjacent elements, if they are out of order, then swaps the two elements.
- Doing this for one pass will move the largest element to the end of the array. Thus,  $a.length - 1$  passes sorts the array.




# Bubble Sort

- Sometimes we need to arrange the array elements according to their order, that is, smaller elements positioned at lower indices.
- This is called sorting the array ascendingly.



- Bubble sort arranges an array by checking each pair of adjacent elements, if they are out of order, then swaps the two elements.
- Doing this for one pass will move the largest element to the end of the array. Thus,  $a.length - 1$  passes sorts the array.




# Bubble Sort

- Sometimes we need to arrange the array elements according to their order, that is, smaller elements positioned at lower indices.
- This is called sorting the array ascendingly.



- Bubble sort arranges an array by checking each pair of adjacent elements, if they are out of order, then swaps the two elements.
- Doing this for one pass will move the largest element to the end of the array. Thus,  $a.length - 1$  passes sorts the array.




# Bubble Sort

- Sometimes we need to arrange the array elements according to their order, that is, smaller elements positioned at lower indices.
- This is called sorting the array ascendingly.



- Bubble sort arranges an array by checking each pair of adjacent elements, if they are out of order, then swaps the two elements.
- Doing this for one pass will move the largest element to the end of the array. Thus,  $a.length - 1$  passes sorts the array.



# Bubble Sort

- Sometimes we need to arrange the array elements according to their order, that is, smaller elements positioned at lower indices.
- This is called sorting the array ascendingly.



- Bubble sort arranges an array by checking each pair of adjacent elements, if they are out of order, then swaps the two elements.
- Doing this for one pass will move the largest element to the end of the array. Thus,  $a.length - 1$  passes sorts the array.




# Bubble Sort

- Sometimes we need to arrange the array elements according to their order, that is, smaller elements positioned at lower indices.
- This is called sorting the array ascendingly.



- Bubble sort arranges an array by checking each pair of adjacent elements, if they are out of order, then swaps the two elements.
- Doing this for one pass will move the largest element to the end of the array. Thus,  $a.length - 1$  passes sorts the array.






# Bubble Sort

- Sometimes we need to arrange the array elements according to their order, that is, smaller elements positioned at lower indices.
- This is called sorting the array ascendingly.



- Bubble sort arranges an array by checking each pair of adjacent elements, if they are out of order, then swaps the two elements.
- Doing this for one pass will move the largest element to the end of the array. Thus,  $a.length - 1$  passes sorts the array.




# Bubble Sort

- Sometimes we need to arrange the array elements according to their order, that is, smaller elements positioned at lower indices.
- This is called sorting the array ascendingly.



- Bubble sort arranges an array by checking each pair of adjacent elements, if they are out of order, then swaps the two elements.
- Doing this for one pass will move the largest element to the end of the array. Thus,  $a.length - 1$  passes sorts the array.




# Bubble Sort

- Sometimes we need to arrange the array elements according to their order, that is, smaller elements positioned at lower indices.
- This is called sorting the array ascendingly.



- Bubble sort arranges an array by checking each pair of adjacent elements, if they are out of order, then swaps the two elements.
- Doing this for one pass will move the largest element to the end of the array. Thus,  $a.length - 1$  passes sorts the array.




# Bubble Sort

- Sometimes we need to arrange the array elements according to their order, that is, smaller elements positioned at lower indices.
- This is called sorting the array ascendingly.



- Bubble sort arranges an array by checking each pair of adjacent elements, if they are out of order, then swaps the two elements.
- Doing this for one pass will move the largest element to the end of the array. Thus,  $a.length - 1$  passes sorts the array.




# Bubble Sort

- Sometimes we need to arrange the array elements according to their order, that is, smaller elements positioned at lower indices.
- This is called sorting the array ascendingly.



- Bubble sort arranges an array by checking each pair of adjacent elements, if they are out of order, then swaps the two elements.
- Doing this for one pass will move the largest element to the end of the array. Thus,  $a.length - 1$  passes sorts the array.




# Bubble Sort

- Sometimes we need to arrange the array elements according to their order, that is, smaller elements positioned at lower indices.
- This is called sorting the array ascendingly.



- Bubble sort arranges an array by checking each pair of adjacent elements, if they are out of order, then swaps the two elements.
- Doing this for one pass will move the largest element to the end of the array. Thus,  $a.length - 1$  passes sorts the array.




# Bubble Sort

- Sometimes we need to arrange the array elements according to their order, that is, smaller elements positioned at lower indices.
- This is called sorting the array ascendingly.



- Bubble sort arranges an array by checking each pair of adjacent elements, if they are out of order, then swaps the two elements.
- Doing this for one pass will move the largest element to the end of the array. Thus,  $a.length - 1$  passes sorts the array.




# Bubble Sort

- Sometimes we need to arrange the array elements according to their order, that is, smaller elements positioned at lower indices.
- This is called sorting the array ascendingly.



- Bubble sort arranges an array by checking each pair of adjacent elements, if they are out of order, then swaps the two elements.
- Doing this for one pass will move the largest element to the end of the array. Thus,  $a.length - 1$  passes sorts the array.






# Bubble Sort

- Sometimes we need to arrange the array elements according to their order, that is, smaller elements positioned at lower indices.
- This is called sorting the array ascendingly.



- Bubble sort arranges an array by checking each pair of adjacent elements, if they are out of order, then swaps the two elements.
- Doing this for one pass will move the largest element to the end of the array. Thus,  $a.length - 1$  passes sorts the array.




# Bubble Sort

- Sometimes we need to arrange the array elements according to their order, that is, smaller elements positioned at lower indices.
- This is called sorting the array ascendingly.



- Bubble sort arranges an array by checking each pair of adjacent elements, if they are out of order, then swaps the two elements.
- Doing this for one pass will move the largest element to the end of the array. Thus,  $a.length - 1$  passes sorts the array.




# Bubble Sort

- Sometimes we need to arrange the array elements according to their order, that is, smaller elements positioned at lower indices.
- This is called sorting the array ascendingly.



- Bubble sort arranges an array by checking each pair of adjacent elements, if they are out of order, then swaps the two elements.
- Doing this for one pass will move the largest element to the end of the array. Thus,  $a.length - 1$  passes sorts the array.



# Bubble Sort

- Sometimes we need to arrange the array elements according to their order, that is, smaller elements positioned at lower indices.
- This is called sorting the array ascendingly.



- Bubble sort arranges an array by checking each pair of adjacent elements, if they are out of order, then swaps the two elements.
- Doing this for one pass will move the largest element to the end of the array. Thus,  $a.length - 1$  passes sorts the array.




# Bubble Sort

- Sometimes we need to arrange the array elements according to their order, that is, smaller elements positioned at lower indices.
- This is called sorting the array ascendingly.



- Bubble sort arranges an array by checking each pair of adjacent elements, if they are out of order, then swaps the two elements.
- Doing this for one pass will move the largest element to the end of the array. Thus,  $a.length - 1$  passes sorts the array.




# Bubble Sort

- Sometimes we need to arrange the array elements according to their order, that is, smaller elements positioned at lower indices.
- This is called sorting the array ascendingly.



- Bubble sort arranges an array by checking each pair of adjacent elements, if they are out of order, then swaps the two elements.
- Doing this for one pass will move the largest element to the end of the array. Thus,  $a.length - 1$  passes sorts the array.




# Bubble Sort

- Sometimes we need to arrange the array elements according to their order, that is, smaller elements positioned at lower indices.
- This is called sorting the array ascendingly.



- Bubble sort arranges an array by checking each pair of adjacent elements, if they are out of order, then swaps the two elements.
- Doing this for one pass will move the largest element to the end of the array. Thus,  $a.length - 1$  passes sorts the array.




# Bubble Sort

- Sometimes we need to arrange the array elements according to their order, that is, smaller elements positioned at lower indices.
- This is called sorting the array ascendingly.



- Bubble sort arranges an array by checking each pair of adjacent elements, if they are out of order, then swaps the two elements.
- Doing this for one pass will move the largest element to the end of the array. Thus,  $a.length - 1$  passes sorts the array.






# Bubble Sort

- Sometimes we need to arrange the array elements according to their order, that is, smaller elements positioned at lower indices.
- This is called sorting the array ascendingly.



- Bubble sort arranges an array by checking each pair of adjacent elements, if they are out of order, then swaps the two elements.
- Doing this for one pass will move the largest element to the end of the array. Thus,  $a.length - 1$  passes sorts the array.




# Bubble Sort

- Sometimes we need to arrange the array elements according to their order, that is, smaller elements positioned at lower indices.
- This is called sorting the array ascendingly.



- Bubble sort arranges an array by checking each pair of adjacent elements, if they are out of order, then swaps the two elements.
- Doing this for one pass will move the largest element to the end of the array. Thus,  $a.length - 1$  passes sorts the array.



# Bubble Sort

- Sometimes we need to arrange the array elements according to their order, that is, smaller elements positioned at lower indices.
- This is called sorting the array ascendingly.



- Bubble sort arranges an array by checking each pair of adjacent elements, if they are out of order, then swaps the two elements.
- Doing this for one pass will move the largest element to the end of the array. Thus,  $a.length - 1$  passes sorts the array.




# Bubble Sort

- Sometimes we need to arrange the array elements according to their order, that is, smaller elements positioned at lower indices.
- This is called sorting the array ascendingly.



- Bubble sort arranges an array by checking each pair of adjacent elements, if they are out of order, then swaps the two elements.
- Doing this for one pass will move the largest element to the end of the array. Thus,  $a.length - 1$  passes sorts the array.




# Bubble Sort

- Sometimes we need to arrange the array elements according to their order, that is, smaller elements positioned at lower indices.
- This is called sorting the array ascendingly.



- Bubble sort arranges an array by checking each pair of adjacent elements, if they are out of order, then swaps the two elements.
- Doing this for one pass will move the largest element to the end of the array. Thus,  $a.length - 1$  passes sorts the array.




# Bubble Sort

- Sometimes we need to arrange the array elements according to their order, that is, smaller elements positioned at lower indices.
- This is called sorting the array ascendingly.



- Bubble sort arranges an array by checking each pair of adjacent elements, if they are out of order, then swaps the two elements.
- Doing this for one pass will move the largest element to the end of the array. Thus,  $a.length - 1$  passes sorts the array.




# Bubble Sort

- Sometimes we need to arrange the array elements according to their order, that is, smaller elements positioned at lower indices.
- This is called sorting the array ascendingly.



- Bubble sort arranges an array by checking each pair of adjacent elements, if they are out of order, then swaps the two elements.
- Doing this for one pass will move the largest element to the end of the array. Thus,  $a.length - 1$  passes sorts the array.




# Bubble Sort

- Sometimes we need to arrange the array elements according to their order, that is, smaller elements positioned at lower indices.
- This is called sorting the array ascendingly.



- Bubble sort arranges an array by checking each pair of adjacent elements, if they are out of order, then swaps the two elements.
- Doing this for one pass will move the largest element to the end of the array. Thus,  $a.length - 1$  passes sorts the array.






# Bubble Sort

- Sometimes we need to arrange the array elements according to their order, that is, smaller elements positioned at lower indices.
- This is called sorting the array ascendingly.



- Bubble sort arranges an array by checking each pair of adjacent elements, if they are out of order, then swaps the two elements.
- Doing this for one pass will move the largest element to the end of the array. Thus,  $a.length - 1$  passes sorts the array.




# Bubble Sort

- Sometimes we need to arrange the array elements according to their order, that is, smaller elements positioned at lower indices.
- This is called sorting the array ascendingly.



- Bubble sort arranges an array by checking each pair of adjacent elements, if they are out of order, then swaps the two elements.
- Doing this for one pass will move the largest element to the end of the array. Thus,  $a.length - 1$  passes sorts the array.




# Bubble Sort

- Sometimes we need to arrange the array elements according to their order, that is, smaller elements positioned at lower indices.
- This is called sorting the array ascendingly.



- Bubble sort arranges an array by checking each pair of adjacent elements, if they are out of order, then swaps the two elements.
- Doing this for one pass will move the largest element to the end of the array. Thus,  $a.length - 1$  passes sorts the array.




# Bubble Sort

- Sometimes we need to arrange the array elements according to their order, that is, smaller elements positioned at lower indices.
- This is called sorting the array ascendingly.



- Bubble sort arranges an array by checking each pair of adjacent elements, if they are out of order, then swaps the two elements.
- Doing this for one pass will move the largest element to the end of the array. Thus,  $a.length - 1$  passes sorts the array.




# Bubble Sort

- Sometimes we need to arrange the array elements according to their order, that is, smaller elements positioned at lower indices.
- This is called sorting the array ascendingly.



- Bubble sort arranges an array by checking each pair of adjacent elements, if they are out of order, then swaps the two elements.
- Doing this for one pass will move the largest element to the end of the array. Thus,  $a.length - 1$  passes sorts the array.



## Bubble Sort (Code)


The *bubbleSort* method sorts an `int` array *in-place* by the Bubble Sort algorithm.

```
1  static void bubbleSort(int[] a) {  
2      for ( int i = a.length-1; i > 0; --i ) {  
3          boolean swapped = false;  
4          for ( int j = 0; j < i; ++j )  
5              if ( a[j] > a[j+1] ) {  
6                  int t = a[j];  
7                  a[j] = a[j+1];  
8                  a[j+1] = t;  
9                  swapped = true;  
10             }  
11         if ( !swapped )  
12             break;  
13     }  
14 }
```

# Binary Search

- If we have a sorted array, we may employ this useful clue — the ordering — to search for an element in the array.
- We may pick up any element in the array, and compare the given element  $k$  with it. We have two possible outcomes, if unequal:
  - 1 less than:  $k$  can only appear on the left;
  - 2 greater than:  $k$  can only appear on the right.


In either case, we can recursively find the element in the smaller array, until the array becomes empty.



# Binary Search

- If we have a sorted array, we may employ this useful clue — the ordering — to search for an element in the array.
- We may pick up any element in the array, and compare the given element  $k$  with it. We have two possible outcomes, if unequal:
  - 1 less than:  $k$  can only appear on the left;
  - 2 greater than:  $k$  can only appear on the right.

In either case, we can recursively find the element in the smaller array, until the array becomes empty.





## Binary Search (Code)

The following defines the method that searches for an element  $k$  in an `int` array  $a$  by the binary search algorithm. The method returns the index of  $k$  if it is found, otherwise  $-1$ .

---

```
1  int binarySearch(int[] a, int k) {
2      int l = 0, r = a.length;
3      while ( l < r ) {
4          int m = (l+r)/2;
5          if ( k == a[m] ) return m;
6          else if ( k < a[m] ) r = m;
7          else l = m+1;
8      }
9      return -1;
10 }
```

---

