EE6641 Analysis and Synthesis of Audio Signals

Lab3: Spectrogram

Due Oct. 13, 2015

Brought to you by Yi-Wen Liu

Objectives: In this lab, you will utilize a wave file to generate a time-frequency figure. Also, the concept of windowing is also introduced. In fact, besides taking related courses, you may have already been familiar with such a format of viewing. Music scores or sheets are common examples. While sweeping a sheet from left to right, different notes or frequencies are indicated to be sung or played in different time. After finishing this task, you should understand more about the analysis of audio.

Tasking description:

- 1. You are given a MATLAB script to begin with. You will use given equations and functions to implement windows. Later, you are asked to implement a spectrogram using different lengths of windows.
- 2. Please implement at least three different kinds of windows. Here we provide three windows which are commonly used:

Rectangular window:

$$w(n) = 1$$

Hamming window:

$$w(n) = 0.54 - 0.46\cos(\frac{2\pi n}{N-1})$$

Hann window:

$$w(n) = 0.5(1 - \cos(\frac{2\pi n}{N - 1}))$$

Please use the equation above to implement three different window functions (N=1000).

- 3. Fortunately we also have rectwin(), hamming(), and hann() function to carry out the work. Please use help to see the detail. Are the functions derived from different method the same?
- 4. Now, let's begin to implement the spectrogram, we have helped a little on your work. What does the figure look like if the windows do <u>not</u> have overlaps? How about 20%? 50%? You can also tune different percentage to inspect the differences.
- 5. If the duration of the window is small, say 0.02 second, what will the figure look like? How about another larger number like 0.2 second? What is the difference? Why?
- 6. (optional) Note that we also have spectrogram() in Matlab. You are welcomed to get familiar with it.

Things to turn in on LMS:

Please turn in the implemented code and a PDF file. The PDF file should contain the brief answers to the questions above. 只需回答問題即可,不必使用很正式的報告格式.

A further question leaving for you:

- 1. If you want to enhance the resolution in y-axis (frequency domain), what can you do? What side effects may occur?
- 2. If using different windows implementing a spectrogram in the same audio, what are the differences and why? How do we choose a window "properly"?