

Contents

1	Basic	1
1.1	default	1
1.2	奇妙的東西	1
1.3	random	1
2	Math	1
2.1	basic	1
2.2	快速幂	1
2.3	ExGCD	1
2.4	Phi	1
3	Binary Search	2
3.1	二分搜	2
3.2	三分搜	2
4	DataStructure	2
4.1	DSU(並查集)	2
4.2	FenwickTree/BIT	2
4.3	二維 BIT	2
4.4	Seg/線段樹	3
5	Graph	3
5.1	Topo/拓撲	3
5.2	bellman/邊長鬆弛	3
5.3	ola/歐拉	4
5.4	LCA/最近公共祖先	4
5.5	km/二分圖最大權匹配	4
5.6	Scc/強連通分量	4
6	dynamic programming	5
6.1	SOS DP	5
7	Computational Geometry	5
7.1	default	5
7.2	極座標排序	5
7.3	ConvexHull/凸包	5
7.4	PtSegDist	5
7.5	點是否在多邊形內	5
8	Flow	5
8.1	Dinic	5
9	String	6
9.1	SAIS	6
9.2	KMP	6
10	酷東西可能會用到	6
10.1	areaofrect/矩形聯集面積	6
11	Math2	7
11.1	Theorem	7
11.2	Prime	7

1 Basic

1.1 default

```
#include <bits/stdc++.h>
using namespace std;
#define int long long
#define idonhavegirlfriend ios::sync_with_stdio(0),cin.tie(0);
#define pb push_back
#define endl "\n"
#define all(v) (v).begin(),(v).end()
void solve(){
}
signed main(){
    idonhavegirlfriend
    int _=1;
    //cin>>_;
    while(--){
        solve();
    }
}
```

1.2 奇妙的東西

```
priority_queue<T> //由大到小
priority_queue<T,vector<T>,greater<T>> //由小到大
__builtin_popcountll // 二進位有幾個1(記得這是long long)
__builtin_clzll // 左起第一個1之前0的個數
__builtin_parityll // 1的個數的奇偶性
__builtin_mul_overflow(a,b,&h) // a*b是否溢位,h = a * b;
__builtin_add_overflow(a,b,&h)
```

1.3 random

```
mt19937 mt(chrono::steady_clock::now().time_since_epoch().count());
//mt19937_64 mt() -> return randnum
int randint(int l, int r){
    uniform_int_distribution<> dis(l, r); return dis(mt);
}
```

2 Math

2.1 basic

[a,b] 有包含
(a,b) 沒包含

2.2 快速幂

```
int ksm(int x, int y) {
    int ans = 1;
    while (y) {
        if (y & 1)
            ans = ans * x;
        x = x * x;
        y >>= 1;
    }
    return ans;
}

// 矩陣乘法
vector<vector<int>> mul(const vector<vector<int>> &A,
                      const vector<vector<int>> &B) {
    int n = A.size();
    vector<vector<int>> C(n, vector<int>(n, 0));

    for (int i = 0; i < n; i++) {
        for (int k = 0; k < n; k++) if (A[i][k]) {
            for (int j = 0; j < n; j++) {
                C[i][j] = (C[i][j] + A[i][k] * B[k][j])
                    % MOD;
            }
        }
    }
    return C;
}
```

2.3 ExGCD

```
// 矩陣快速幂
vector<vector<int>> ksm(vector<vector<int>> base, int exp) {
    int n = base.size();
    vector<vector<int>> res(n, vector<int>(n, 0));

    for (int i = 0; i < n; i++) res[i][i] = 1;

    while (exp > 0) {
        if (exp & 1) res = mul(res, base);
        base = mul(base, base);
        exp >>= 1;
    }
    return res;
}
```

2.4 Phi

```
//ax+by=gcd(a,b)
PII gcd(int a, int b){
    if(b == 0) return {1, 0};
    PII q = gcd(b, a % b);
    return {q.second, q.first - q.second * (a / b)};
}
```

2.4 Phi

```
//歐拉函數 phi(n) 是指<=n中與n互質的數的個數
int _phi(int n) { // O(sqrtN)
    int res = n, a = n;
    for (int i = 2; i * i <= a; i++) {
        if (a % i == 0) {
            res = res / i * (i - 1);
            while (a % i == 0) a /= i;
        }
    }
}
```

```

    }
    if (a > 1) res = res / a * (a - 1);
    return res;
}

int phi[MXN]; // 建表 最大 1e7
void phi_table(int n) {
    phi[1] = 1;
    for (int i = 2; i <= n; ++i) {
        if (phi[i]) continue;
        for (int j = i; j <= n; j += i) {
            if (phi[j] == 0) phi[j] = j;
            phi[j] = phi[j] / i * (i - 1);
        }
    }
}

```

3 Binary Search

3.1 二分搜

```

int bsearch_1(int l, int r)
{
    while (l < r)
    {
        int mid = l + r >> 1;
        if (check(mid)) r = mid;
        else l = mid + 1;
    }
    return l;
}

// .....0000000000
int bsearch_2(int l, int r)
{
    while (l < r)
    {
        int mid = l + r + 1 >> 1;
        if (check(mid)) l = mid;
        else r = mid - 1;
    }
    return l;
}

// 000000000.....
int m = *ranges::partition_point(views::iota(0LL, (int)1e9+9), [&](int a) {
    return check(a) > k;
});

//[begin,last)
//11111111000000000000
//搜左邊數過來第一個 0
//都是 1 會回傳 last
int partitionpoint(int L, int R, function<bool(int)> chk)
{
    int l = L, r = R - 1;
    while (r - l > 10) {
        int m = l + (r - l) / 2;
        if (chk(m)) l = m;
        else r = m;
    }
    int m = l;
    while (m <= r) {
        if (!chk(m)) break;
        ++m;
    }
    if (!chk(m)) return m;
    else return R;
}

//手工

```

3.2 三分搜

```

int l = 1, r = 100;
while (l < r) {
    int lmid = l + (r - l) / 3; // l + 1/3區間大小
    int rmid = r - (r - l) / 3; // r - 1/3區間大小
    lans = cal(lmid), rans = cal(rmid);
    // 求凹函數極小值
    if (lans <= rans) r = rmid - 1;
    else l = lmid + 1;
}

```

4 DataStructure

4.1 DSU(並查集)

```

struct DSU {
    vector<int> f, sz;
    int cnt;
    DSU(int n) : f(n), sz(n) {
        for (int i = 0; i < n; i++) {
            f[i] = i;
            sz[i] = 1;
        }
    }
    int find(int x) {
        if (x == f[x]) return x;
        return f[x] = find(f[x]);
    }
    void merge(int x, int y) {
        x = find(x); y = find(y);
        if (x == y) return;
        if (sz[x] < sz[y])
            swap(x, y);
        f[y] = x;
        sz[x] += sz[y];
        cnt--;
    }
    bool same(int a, int b) {
        return find(a) == find(b);
    }
    int groups() { // 找有幾群
        return cnt;
    }
};

```

4.2 FenwickTree/BIT

```

struct Fenwick { // 這個是1base的
    int n;
    vector<int> s;
    int lowbit(int x) { return x & -x; }
    Fenwick(int _n) {
        n = _n + 1;
        s.clear(), s.resize(n, 0);
    }
    void update(int i, int v) { // 更新數值
        for (; i < n; i += lowbit(i))
            s[i] += v;
    }
    int query(int x) { // 查詢前綴和(有包含)
        int pre = 0;
        for (; x; x -= lowbit(x))
            pre += s[x];
        return pre;
    }
    Fenwick(vector<int> a) { // 建構資料結構
        n = a.size(); // a 是 0-based
        s.clear(), s.resize(n + 1, 0); // s 是 1-based
        for (int i = 1; i <= n; i++)
            update(i, a[i - 1]);
    }
};

//使用:
Fenwick fw(a); // a is vector
Fenwick fw(n); // n is int

```

4.3 二維 BIT

```

struct BIT {
    int n;
    vector<vector<ll>> bit;
    int lowbit(int x) { return x & -x; }
    BIT(int _n) : n(_n + 1) {
        bit.assign(n, vector<ll>(n, 0));
    }
    void update(int x, int y, ll val) { // 更新 (x, y)
        for (int i = x; i < n; i += lowbit(i))
            for (int j = y; j < n; j += lowbit(j))
                bit[i][j] += val;
    }
    ll query(int x, int y) { // 查詢 (1, 1) ~ (x, y) 的和

```

```

ll ans = 0;
for (int i = x; i; i -= lowbit(i))
    for (int j = y; j; j -= lowbit(j)) ans += bit[i][j];
return ans;
}
ll range_query(int a, int b, int x, int y) {
    return query(x, y) - query(x, b - 1) -
        query(a - 1, y) + query(a - 1, b - 1);
}
};

```

4.4 Seg/線段樹

```

struct Seg {
#define cl(x) (x << 1)
#define cr(x) (x << 1) + 1
    int _n;
    vector<int> f, tag;
    vector<int> arr;
    //Seg(int n) : _n(n), f(4 * n), tag(4 * n) {}
    Seg(vector<int> a) {
        _n = a.size();
        f.resize(4 * _n + 1, 0);
        tag.resize(4 * _n + 1, 0);
        arr.resize(_n);
        for (int i = 0; i < _n; i++) {
            arr[i] = a[i];
        }

        build(1, 0, _n - 1);
    }
    Seg(int x){
        _n = x;
        f.resize(4 * _n + 1, 0);
        tag.resize(4 * _n + 1, 0);
        arr.resize(_n);
    }

    void build(int id, int l, int r) {
        if (l == r) {
            f[id] = arr[l];
            return;
        }
        int mid = (l + r) >> 1;
        build(cl(id), l, mid);
        build(cr(id), mid + 1, r);
        pull(id, l, r);
    }

    void pull(int id, int l, int r) {
        int mid = (l + r) >> 1;
        push(cl(id), l, mid);
        push(cr(id), mid + 1, r);
        f[id] = f[cl(id)] + f[cr(id)];
    }

    void push(int id, int l, int r) {
        if (tag[id]) {
            f[id] += tag[id] * (r - l + 1);
            if (l != r) {
                tag[cl(id)] += tag[id];
                tag[cr(id)] += tag[id];
            }
            tag[id] = 0;
        }
    }

    void update(int id, int l, int r, int x, int v) {
        if (l == r) {
            f[id] = v;
            return;
        }
        int mid = (l + r) >> 1;
        if (x <= mid) update(cl(id), l, mid, x, v);
        if (mid < x) update(cr(id), mid + 1, r, x, v);
        pull(id, l, r);
    }

    void update(int id, int l, int r, int ql, int qr,
        int v) {

```

```

        push(id, l, r);
        if (ql <= l and qr >= r) {
            tag[id] += v;
            return;
        }
        int mid = (l + r) >> 1;
        if (ql <= mid) {
            update(cl(id), l, mid, ql, qr, v);
        }
        if (qr > mid) {
            update(cr(id), mid + 1, r, ql, qr, v);
        }
        pull(id, l, r);
    }

    int query(int id, int l, int r, int sl, int sr) {
        push(id, l, r);
        if (sl <= l and sr >= r) {
            return f[id];
        }
        int res = 0;
        int mid = (l + r) >> 1;
        int ll = 0;
        int rr = 0;
        if (sl <= mid) {
            ll = query(cl(id), l, mid, sl, sr);
        }
        if (sr > mid) {
            rr = query(cr(id), mid + 1, r, sl, sr);
        }
        res = ll + rr;
        return res;
    }
};

```

5 Graph

5.1 Topo/拓樸

```

vector<int> edge[MAXN], ans;
int deg[MAXN];

void topo(int n) {
    queue<int> q;

    for (int i = 1; i <= n; i++)
        if (!deg[i])
            q.push(i);

    while (!q.empty()) {
        int u = q.front();
        q.pop();
        ans.push_back(u);

        for (int v : edge[u]) {
            deg[v]--;
            if (!deg[v])
                q.push(v);
        }
    }
}

```

5.2 bellman/邊長鬆弛

```

struct Edge {
    int from, to, weight;
} edge[MAXN];
int dis[MAXN];
void bellman_ford(int n, int m) {
    dis[1] = 0; // 起點的距離一定是 0
    for (int j = 0; j < n - 1; j++) { // n 個節點要跑 n - 1 次
        for (int i = 0; i < m; i++) { // 對於所有邊都嘗試鬆弛
            if (dis[edge[i].to] >
                dis[edge[i].from] + edge[i].weight)
                dis[edge[i].to] =
                    dis[edge[i].from] + edge[i].weight;
        }
    }
}

```

5.3 ola/歐拉

```
//歐拉路徑(無向圖)兩個奇數點或者全偶點
//歐拉路徑(有向圖)條件:起點out=in+1,終點in=out+1,其他點
in=out
//歐拉迴路(無向圖)所有點偶數點
//歐拉迴路(有向圖)所有點in=out
vector<int> anse;//邊
vector<int> ansp;//點
vector<bool> vis(m,false);
function<void(int)> dfs=[&](int u){
    while(!mp[u].empty()){
        auto [x,e]=mp[u].back();
        mp[u].pop_back();
        if(vis[e]){
            continue;
        }
        vis[e]=true;
        dfs(x);
        anse.pb(e);
    }
    ansp.pb(u);
};
```

5.4 LCA/最近公共祖先

```
struct{
    int n, logN;
    vector<vector<int>>> jump;
    vector<int> in, out;
    bool is_ancestor(int x, int y){
        if(x == -1 || y == -1) return 1;
        return in[x] <= in[y] && out[y] <= out[x];
    }
    int query(int x, int y){
        if(is_ancestor(x, y)) return x;
        if(is_ancestor(y, x)) return y;
        for(int i = logN - 1; i >= 0; i--){
            if(!is_ancestor(jump[x][i], y)) x = jump[x][i];
        }
        return jump[x][0];
    }
    void init(int _n, vector<vector<int>>>&v){//size,
        adj array 0base
        n = _n;
        logN = log2(n) + 1;

        jump.resize(n, vector<int>(logN, -1));
        in.resize(n); out.resize(n);

        int timing = 1;
        auto dfs = [&](auto &&self, int x) -> void{
            in[x] = timing++;
            for(auto &i : v[x]){
                jump[i][0] = x;
                self(self, i);
            }
            out[x] = timing++;
            return;
        }; dfs(dfs, 0);

        for(int i = 1; i < logN; i++){
            for(int now = 1; now < n; now++){
                if(jump[now][i-1] == -1) continue;
                jump[now][i] = jump[jump[now][i-1]][i-1];
            }
        }
    }
}LCA;
```

5.5 km/二分圖最大權匹配

```
struct KM{ // max weight, for min negate the weights
    int n, mx[MXN], my[MXN], pa[MXN];
    ll g[MXN][MXN], lx[MXN], ly[MXN], sy[MXN];
    bool vx[MXN], vy[MXN];
    void init(int _n) { // 1-based, N個節點
        n = _n;
        for(int i=1; i<=n; i++) fill(g[i], g[i]+n+1, 0);
    }
```

```

    }
    void addEdge(int x, int y, ll w) {g[x][y] = w;} //左
        邊的集合節點x連邊右邊集合節點y權重為w
    void augment(int y) {
        for(int x, z; y; y = z)
            x=pa[y], z=mx[x], my[y]=x, mx[x]=y;
    }
    void bfs(int st) {
        for(int i=1; i<=n; ++i) sy[i]=INF, vx[i]=vy[i]=0;
        queue<int> q; q.push(st);
        for(;;) {
            while(q.size()) {
                int x=q.front(); q.pop(); vx[x]=1;
                for(int y=1; y<=n; ++y) if(!vy[y]){
                    ll t = lx[x]+ly[y]-g[x][y];
                    if(t==0){
                        pa[y]=x;
                        if(!my[y]){augment(y);return;}
                        vy[y]=1, q.push(my[y]);
                    }else if(sy[y]>t) pa[y]=x,sy[y]=t;
                }
            }
            ll cut = INF;
            for(int y=1; y<=n; ++y)
                if(!vy[y]&&cut>sy[y]) cut=sy[y];
            for(int j=1; j<=n; ++j){
                if(vx[j]) lx[j] -= cut;
                if(vy[j]) ly[j] += cut;
                else sy[j] -= cut;
            }
            for(int y=1; y<=n; ++y) if(!vy[y]&&sy[y]==0){
                if(!my[y]){augment(y);return;}
                vy[y]=1, q.push(my[y]);
            }
        }
    }
    ll solve(){ // 回傳值為完美匹配下的最大總權重
        fill(mx, mx+n+1, 0); fill(my, my+n+1, 0);
        fill(ly, ly+n+1, 0); fill(lx, lx+n+1, -INF);
        for(int x=1; x<=n; ++x) for(int y=1; y<=n; ++y) //
            1-base
            lx[x] = max(lx[x], g[x][y]);
        for(int x=1; x<=n; ++x) bfs(x);
        ll ans = 0;
        for(int y=1; y<=n; ++y) ans += g[my[y]][y];
        return ans;
    } }graph;
```

5.6 Scc/強連通分量

```
//同一團u,v之間有路徑
//bln:在哪個分輪 E原圖
struct Scc{
    int n, nScc, vst[MXN], bln[MXN];
    vector<int> E[MXN], rE[MXN], vec;
    void init(int _n){
        n = _n;
        for (int i=0; i<= n; i++)
            E[i].clear(), rE[i].clear();
    }
    void addEdge(int u, int v){
        E[u].PB(v); rE[v].PB(u);
    }
    void DFS(int u){
        vst[u]=1;
        for (auto v : E[u]) if (!vst[v]) DFS(v);
        vec.PB(u);
    }
    void rDFS(int u){
        vst[u] = 1; bln[u] = nScc;
        for (auto v : rE[u]) if (!vst[v]) rDFS(v);
    }
    void solve(){
        nScc = 0;
        vec.clear();
        fill(vst, vst+n+1, 0);
        for (int i=0; i<n; i++)
            if (!vst[i]) DFS(i);
        reverse(vec.begin(), vec.end());
        fill(vst, vst+n+1, 0);
        for (auto v : vec)
            if (!vst[v]){
                rDFS(v); nScc++;
            }
    }
};
```

```
};
```

6 dynamic programming

6.1 SOS DP

```
// 求子集和 或超集和 -> !(mask & (1 << i))
for(int i = 0; i < (1 << N); ++i) F[i] = A[i]; //預處理 狀態權重

for(int i = 0; i < N; ++i)
for (int s = 0; s < (1 << N); ++s)
    if (s & (1 << i))
        F[s] += F[s ^ (1 << i)];

//窮舉子集
for(int s = mask; s; s = (s-1)&mask;)
//放這個做啥我不會用QAQ
```

7 Computational Geometry

7.1 default

```
int sgn(double x) { return (x > -eps) - (x < eps); }
template<class T>
struct pt{
    T x,y;
    pt(T _x,T _y):x(_x),y(_y){}
    pt():x(0),y(0){}
    pt operator * (T c){ return pt(x * c, y * c); }
    pt operator / (T c){ return pt(x / c, y / c); }
    pt operator + (pt a){ return pt(x + a.x, y + a.y); }
    pt operator - (pt a){ return pt(x - a.x, y - a.y); }
    T operator * (pt a){ return x * a.x + y * a.y; } //內積
    T operator ^ (pt a){ return x * a.y - y * a.x; } //外積
    bool operator < (pt a) const { return x < a.x || (x == a.x && y < a.y); } //按照x排
    bool operator==(const pt<T>& a) const { return x == a.x && y == a.y; }
};
template<class T>
ld abs(pt<T> a) { //返回向量長度
    return sqrt((ld)(a.x * a.x + a.y * a.y));
}
template<class T>
struct Line { //直線
    pt<T> a, b;
    pt<T> dir()const{return b-a;}
};
template<class T> //線段
T ori(pt<T> a, pt<T> b, pt<T> c){ return (b - a) ^ (c - a); }
template<class T> //判斷點是否在線段上
bool PtOnSeg(pt<T> p, Line<T> L) {
    return sgn(ori(L.a, L.b, p)) == 0 and sgn((p - L.a) * (p - L.b)) <= 0;
}
```

7.2 極座標排序

```
//由+x軸往逆時針排序
struct point {
    int x, y;
};
long long cross(const point &a, const point &b) {
    return (long long) a.x * b.y - (long long) a.y * b.x;
}
bool cmp(const point &a, const point &b) {
    int ah = (a.y < 0 or (a.y == 0 and a.x < 0));
    int bh = (b.y < 0 or (b.y == 0 and b.x < 0));
    if (ah != bh) return ah < bh;
    return cross(a, b) > 0;
}
void argument_sort(vector<point> &points) {
    sort(points.begin(), points.end(), cmp);
}
```

7.3 ConvexHull/凸包

```
template<class T>
vector<pt<T>> Hull(vector<pt<T>> P) {
    sort(all(P));
    P.erase(unique(all(P)), P.end());
    P.insert(P.end(), P.rbegin() + 1, P.rend());
    vector<pt<T>> stk;
    for (auto p : P) {
        auto it = stk.rbegin();
        while (stk.rend() - it >= 2 and \
            ori(*next(it), *it, p) <= 0 and \
            (*next(it) < *it) == (*it < p)) {
            it++;
        }
        stk.resize(stk.rend() - it);
        stk.push_back(p);
    }
    stk.pop_back();
    return stk;
}
```

7.4 PtSegDist

```
template<class T> //計算點到線段的距離
ld PtSegDist(pt<T> p, Line<T> l) {
    ld ans = min(abs(p - l.a), abs(p - l.b));
    if (sgn(abs(l.a - l.b)) == 0) return ans;
    if (sgn((l.a - l.b) * (p - l.b)) < 0) return ans;
    // case1
    if (sgn((l.b - l.a) * (p - l.a)) < 0) return ans;
    // case1
    return min(ans, abs(ori(p, l.a, l.b)) / abs(l.a - l.b)); // case2
}
```

7.5 點是否在多邊形內

```
template<class T> //判斷點是否在多邊形內
int inPoly(pt<T> p, const vector<pt<T>> &P) {
    const int n = P.size();
    int cnt = 0;
    for (int i = 0; i < n; i++) {
        pt<T> a = P[i], b = P[(i + 1) % n];
        if (PtOnSeg(p, {a, b})) return 1; // on edge
        if ((sgn(a.y - p.y) == 1) ^ (sgn(b.y - p.y) == 1))
            cnt += sgn(ori(a, b, p));
    }
    return cnt == 0 ? 0 : 2; // out, in
}
```

8 Flow

8.1 Dinic

```
struct Dinic{
    struct Edge{ int v,f,re; };
    int n,s,t,level[MXN];
    vector<Edge> E[MXN];
    void init(int _n, int _s, int _t){
        n = _n; s = _s; t = _t;
        for (int i=0; i<n; i++) E[i].clear();
    }
    void add_edge(int u, int v, int f){
        E[u].PB({v,f,SZ(E[v])});
        E[v].PB({u,0,SZ(E[u])-1});
    }
    bool BFS(){
        for (int i=0; i<n; i++) level[i] = -1;
        queue<int> que;
        que.push(s);
        level[s] = 0;
        while (!que.empty()){
            int u = que.front(); que.pop();
            for (auto it : E[u]){
                if (it.f > 0 && level[it.v] == -1){
                    level[it.v] = level[u]+1;
                    que.push(it.v);
                }
            }
        }
        return level[t] != -1;
    }
}
```

```

int DFS(int u, int nf){
    if (u == t) return nf;
    int res = 0;
    for (auto &it : E[u]){
        if (it.f > 0 && level[it.v] == level[u]+1){
            int tf = DFS(it.v, min(nf, it.f));
            res += tf; nf -= tf; it.f -= tf;
            E[it.v][it.re].f += tf;
            if (nf == 0) return res;
        }
    }
    if (!res) level[u] = -1;
    return res;
}
int flow(int res=0){
    while ( BFS() )
        res += DFS(s, 2147483647);
    return res;
}
} } flow;
/*flow.init(n, source, sink); : 初始化點數、源點、匯點
flow.add_edge(u, v, w); : 加入一條點u連到點v容量為w的邊
flow.flow(); : 回傳值為最大流量
*/

```

9 String

9.1 SAIS

```

// 此為後綴陣列模板
// 用法:
// 把要處理的字串轉成整數陣列傳入suffix_array(), 會得到
// SA與H維結果
const int N = 500010; // 有可能要在這就寫原本字串的兩
// 倍長
struct SA {
#define REP(i, n) for (int i = 0; i < int(n); i++)
#define REP1(i, a, b) for (int i = (a); i <= int(b); i
// ++
    bool _t[N * 2];
    int _s[N * 2], _sa[N * 2], _c[N * 2], x[N], _p[N],
        _q[N * 2], hei[N], r[N];
    int operator[](int i) { return _sa[i]; }
    void build(int* s, int n, int m) {
        memcpy(_s, s, sizeof(int) * n);
        sais(_s, _sa, _p, _q, _t, _c, n, m);
        mkhei(n);
    }
    void mkhei(int n) {
        REP(i, n) r[_sa[i]] = i;
        hei[0] = 0;
        REP(i, n) if (r[i]) {
            int ans = i > 0 ? max(hei[r[i] - 1] - 1, 0) : 0;
            while (_s[i + ans] == _s[_sa[r[i] - 1] + ans])
                ans++;
            hei[r[i]] = ans;
        }
    }
    void sais(int* s, int* sa, int* p, int* q, bool* t,
        int* c, int n, int z) {
        bool uniq = t[n - 1] = true, neq;
        int nn = 0, nmxx = -1, *nsa = sa + n, *ns = s + n,
            lst = -1;
#define MS0(x, n) memset((x), 0, n * sizeof(*(x)))
#define MAGIC(XD) \
        MS0(sa, n); \
        memcpy(x, c, sizeof(int) * z); \
        XD; \
        memcpy(x + 1, c, sizeof(int) * (z - 1)); \
        REP(i, n) \
        if (sa[i] && !t[sa[i] - 1]) \
            sa[x[sa[i] - 1]++] = sa[i] - 1; \
        memcpy(x, c, sizeof(int) * z); \
        for (int i = n - 1; i >= 0; i--) \
            if (sa[i] && t[sa[i] - 1]) \
                sa[--x[sa[i] - 1]] = sa[i] - 1; \
        MS0(c, z); \
        REP(i, n) uniq &= ++c[s[i]] < 2; \
        REP(i, z - 1) c[i + 1] += c[i]; \
        if (uniq) { \
            REP(i, n) sa[--c[s[i]]] = i; \
            return; \
        }
    }
}

```

```

for (int i = n - 2; i >= 0; i--)
    t[i] = (s[i] == s[i + 1] ? t[i + 1] : s[i] < s[i + 1]);
MAGIC(REP1(i, 1, n - 1) if (t[i] && !t[i - 1])
    sa[--x[s[i]]] = p[q[i] = nn++] = i);
REP(i, n) if (sa[i] && t[sa[i]] && !t[sa[i] - 1]) {
    neq = lst < 0 || memcmp(s + sa[i], s + lst,
        (p[q[sa[i]] + 1] - sa[i])
        * sizeof(int));
    ns[q[lst = sa[i]]] = nmxx += neq;
}
sais(ns, nsa, p + nn, q + n, t + n, c + z, nn,
    nmxx + 1);
MAGIC(for (int i = nn - 1; i >= 0; i--)
    sa[--x[s[p[nsa[i]]]]] = p[nsa[i]]);
}
} sa;
int H[N], SA[N]; // SA: 後綴陣列的length
// H[i]: SA[i]與SA[i - 1]的共同子字串
// 長
void suffix_array(int* ip, int len) {
    // should padding a zero in the back
    // ip is int array, len is array length
    // ip[0..n-1] != 0, and ip[len] = 0
    ip[len++] = 0;
    sa.build(ip, len, 128);
    for (int i = 0; i < len; i++) {
        H[i] = sa.hei[i + 1];
        SA[i] = sa._sa[i + 1];
    }
    // resulting height, sa array \in [0, len)
}

```

9.2 KMP

```

int failure[MXN];
vector<int> KMP(vector<int>& t, vector<int>& p){
    vector<int> ret;
    if (p.size() > t.size()) return {};
    for (int i=1, j=failure[0]=-1; i<p.size(); ++i){
        while (j >= 0 && p[j+1] != p[i])
            j = failure[j];
        if (p[j+1] == p[i]) j++;
        failure[i] = j;
    }
    for (int i=0, j=-1; i<t.size(); ++i){
        while (j >= 0 && p[j+1] != t[i])
            j = failure[j];
        if (p[j+1] == t[i]) j++;
        if (j == p.size()-1){
            ret.push_back(i - p.size() + 1);
            j = failure[j];
        }
    }
    return ret;
}
/*
vector<int> prefunc(const string& s){
    int n = s.size();
    vector<int> pi(n);
    for(int i=1, j=0; i<n; ++i){
        j = pi[i-1];
        while(j && s[j] != s[i]) j = pi[j-1]; // 往下找藍框
        if(s[j] == s[i]) ++j; // 相等會多一格
        pi[i] = j;
    }
    return pi;
}
*/

```

10 酷東西可能會用到

10.1 areaofrect/矩形聯集面積

```

struct AreaofRectangles{
#define cl(x) (x<<1)
#define cr(x) (x<<1|1)
    int n, id, sid;
    pair<int, int> tree[MXN<<3]; // count, area
    vector<int> ind;
    tuple<int, int, int, int> scan[MXN<<1];
}

```



```

void print(int i, int l, int r){
    if(tree[i].first) tree[i].second = ind[r+1] -
        ind[l]; //當前區間有被做加值
    else if(l != r){ //沒有就直接拿兩個子節點的第二
        個數字
        int mid = (l+r)>>1;
        tree[i].second = tree[cl(i)].second + tree[
            cr(i)].second;
    }
    else tree[i].second = 0;
}
void upd(int i, int l, int r, int ql, int qr, int v
){
    if(ql <= l && r <= qr){
        tree[i].first += v;
        print(i, l, r); return;
    }
    int mid = (l+r) >> 1;
    if(ql <= mid) upd(cl(i), l, mid, ql, qr, v);
    if(qr > mid) upd(cr(i), mid+1, r, ql, qr, v);
    print(i, l, r);
}
void init(int _n){
    n = _n; id = sid = 0;
    ind.clear(); ind.resize(n<<1);
    fill(tree, tree+(n<<2), make_pair(0, 0));
}
void addRectangle(int lx, int ly, int rx, int ry){
    ind[id++] = lx; ind[id++] = rx;
    scan[sid++] = make_tuple(ly, 1, lx, rx);
    scan[sid++] = make_tuple(ry, -1, lx, rx);
}
int solve(){
    sort(ind.begin(), ind.end());
    ind.resize(unique(ind.begin(), ind.end()) - ind
        .begin()); //離散化
    sort(scan, scan + sid);
    int area = 0, pre = get<0>(scan[0]);
    for(int i = 0; i < sid; i++){
        auto [x, v, l, r] = scan[i];
        area += tree[1].second * (x-pre); //
        upd(1, 0, ind.size()-1, lower_bound(ind.
            begin(), ind.end(), l)-ind.begin(),
            lower_bound(ind.begin(), ind.end(), r)-
            ind.begin()-1, v);
        pre = x;
    }
    return area;
}
} rect;

```

- Polya' theorem (c is number of color, m is the number of cycle size):

$$(\sum_{i=1}^m c^{gcd(i,m)})/m$$
- Burnside lemma:

$$|X/G| = \frac{1}{|G|} \sum_{g \in G} |X^g|$$
- 錯排公式: (n 個人中, 每個人皆不再原來位置的組合數):

$$dp[0] = 1; dp[1] = 0;$$

$$dp[i] = (i-1) * (dp[i-1] + dp[i-2]);$$
- Bell 數 (有 n 個人, 把他們拆組的方法總數):

$$B_0 = 1$$

$$B_n = \sum_{k=0}^n s(n, k) \quad (\text{second - stirling})$$

$$B_{n+1} = \sum_{k=0}^n \binom{n}{k} B_k$$
- Wilson's theorem:

$$(p-1)! \equiv -1 \pmod{p}$$
- Fermat's little theorem:

$$a^p \equiv a \pmod{p}$$
- Euler's totient function:

$$A^{B^C} \bmod p = \text{pow}(A, \text{pow}(B, C, p-1)) \bmod p$$
- 歐拉函數降冪公式:

$$A^B \bmod C = A^{B \bmod \phi(C) + \phi(C)} \bmod C$$
- 6 的倍數:

$$(a-1)^3 + (a+1)^3 + (-a)^3 + (-a)^3 = 6a$$
- Standard young tableau (標準楊表):
 $\lambda = (\lambda_1 \geq \dots \geq \lambda_k), \sum \lambda_i = n$ denoted by $\lambda \vdash n$
 $\lambda \vdash n$ 意思為 λ 整數拆分 n eg. $n = 10, \lambda = (6, 4)$ 此拆分可表示一種楊表形狀。
 楊表: 第 1 列 λ_1 行 $\dots$ 第 k 列 λ_k 行的方格圖。
 標準楊表: 每列從左到右遞增, 每行從上到下遞增。
 Let T 為某一 Permutation 跑 RSK 後的標準楊表, 則此 Permutation 的 LDS、LIS 長度分別為 T 的列、行數。
- RSK Correspondence:
 A permutation is bijective to (P, Q) 一對標準楊表
 P : Permutation 跑 RSK 算法的結果, 可為半標準楊表。
 Q : 可用來還原 Permutation (像排列矩陣)。
- Hook length formula (形狀為 λ 的標準楊表個數):

$$f^\lambda = \frac{n!}{\prod h_\lambda(i, j)}$$

$$h_\lambda(i, j) = \text{number of pair } (x, y) \text{ where } (x = i \vee y = j) \wedge (x, y) \geq (i, j)$$
 且 (x, y) 落在形狀為 λ 的表上。
 Recursion:
 (i) $f^{(0, \dots, 0)} = 1$
 (ii) $f^{(\lambda_1, \dots, \lambda_m)} = \sum_{k=1}^m f^{(\lambda_1, \dots, \lambda_{k-1}, \lambda_k-1, \lambda_{k+1}, \dots, \lambda_m)}$
- 一個環上相鄰顏色不同的染色數量:

$$f(n, k) = (k-1)^n + (-1)^n (k-1)$$
 n 是點的數量, k 是顏色的數量

11 Math2

11.1 Theorem

- Lucas's Theorem:
 For $n, m \in \mathbb{Z}^*$ and prime P , $C(m, n) \bmod P = \prod C(m_i, n_i)$ where m_i is the i -th digit of m in base P .
- Stirling approximation:

$$n! \approx \sqrt{2\pi n} \left(\frac{n}{e}\right)^n e^{\frac{1}{12n}}$$
- Stirling Numbers(permutation $|P| = n$ with k cycles):

$$S(n, k) = \text{coefficient of } x^k \text{ in } \prod_{i=0}^{n-1} (x+i)$$
- Stirling Numbers(Partition n elements into k non-empty set):

$$S(n, k) = \frac{1}{k!} \sum_{j=0}^k (-1)^{k-j} \binom{k}{j} j^n$$
- Pick's Theorem: $A = i + b/2 - 1$
 A : Area, i : grid number in the inner, b : grid number on the side
- Catalan number: $C_n = \binom{2n}{n} / (n+1)$

$$C_n^{n+m} - C_{n+1}^{n+m} = (m+n)! \frac{n-m+1}{n+1} \quad \text{for } n \geq m$$

$$C_n = \frac{1}{n+1} \binom{2n}{n} = \frac{(2n)!}{(n+1)!n!}$$

$$C_0 = 1 \text{ and } C_{n+1} = 2 \binom{2n+1}{n+2} C_n$$

$$C_0 = 1 \text{ and } C_{n+1} = \sum_{i=0}^n C_i C_{n-i} \quad \text{for } n \geq 0$$
- Euler Characteristic:
 planar graph: $V - E + F - C = 1$
 convex polyhedron: $V - E + F = 2$
 V, E, F, C : number of vertices, edges, faces(regions), and components
- Kirchhoff's theorem:
 $A_{ii} = \deg(i), A_{ij} = (i, j) \in E ? -1 : 0$, Deleting any one row, one column, and cal the $\det(A)$

11.2 Prime

```

/* 12721, 13331, 14341, 75577, 123457, 222557, 556679
* 999983, 1097774749, 1076767633, 100102021, 999997771 *
1001010013, 1000512343, 987654361, 999991231 * 999888733,
98789101, 987777733, 999991921, 1010101333 * 1010102101,
1000000000039, 100000000000037 * 2305843009213693951,
4611686018427387847 * 9223372036854775783, 18446744073709551557 */

```



為什麼要演奏春日影!

