

UC Berkeley · CSW182 | [Deep Learning]

Designing, Visualizing and Understanding Deep Neural Networks (2021)

CSW182 (2021) · 课程资料包 @ShowMeAI



视频
中英双语字幕



课件
一键打包下载



笔记
官方笔记翻译



代码
作业项目解析



视频 · B 站 [扫码或点击链接]
<https://www.bilibili.com/video/BV1Ff4y1n7ar>



课件 & 代码 · 博客 [扫码或点击链接]
<http://blog.showmeai.tech/berkeley-csw182>

Berkeley
Q-Learning
计算机视觉

循环神经网络
风格迁移
机器学习基础

可视化
模仿学习
生成模型

梯度策略
元学习
卷积网络

Awesome AI Courses Notes Cheatsheets 是 [ShowMeAI](#) 资料库的分支系列，覆盖最具知名度的 **TOP50+** 门 AI 课程，旨在为读者和学习者提供一整套高品质中文学习笔记和速查表。

点击课程名称，跳转至课程**资料包**页面，**一键下载**课程全部资料！

机器学习	深度学习	自然语言处理	计算机视觉
Stanford · CS229	Stanford · CS230	Stanford · CS224n	Stanford · CS231n
# Awesome AI Courses Notes Cheatsheets · 持续更新中			
知识图谱	图机器学习	深度强化学习	自动驾驶
Stanford · CS520	Stanford · CS224W	UCBerkeley · CS285	MIT · 6.S094



微信公众号

资料下载方式 2：扫码点击**底部菜单栏**
称为 **AI 内容创作者**？回复 [添砖加瓦]

Sequence to Sequence Models

Designing, Visualizing and Understanding Deep Neural Networks


CS W182/282A

Instructor: Sergey Levine
UC Berkeley




Last time: RNNs and LSTMs


one to one




one to many




many to one



many to many



many to many



e.g., activity recognition

e.g., frame-level video annotation

e.g., image captioning

e.g., machine translation

A basic neural language model

training data: natural sentences

I think therefore I am

I like machine learning

I am not just a neural network


in reality there could be several million of these

how are these represented?

tokenize the sentence (each word is a token)

simplest: one-hot vector

more complex: word embeddings (we'll cover this later)



We'll talk about **real** language models much more later


$$x_{1,1} = \begin{bmatrix} 0 \\ 0 \\ \cdot \\ 0 \\ 1 \\ 0 \\ \cdot \\ 0 \end{bmatrix}$$

dimensionality = number of possible words

index of this word

A few details


Question: how do we use such a model to **complete** a sequence (e.g., give it “I think...” and have it finish it?)



train model to output <EOS> token when sequence ends

If we want to come up with an entirely new sequence, start with a special <START> token


A conditional language model




What do we expect the training data to look like?

How do we tell the RNN **what** to generate?

What if we condition on *another* sequence?




Sequence to sequence models



typically two **separate** RNNs (with different weights)

trained **end-to-end** on paired data (e.g., pairs of French & English sentences)

A more realistic example



- Multiple RNN layers
- Each RNN layer uses LSTM cells (or GRU)
- Trained end-to-end on pairs of sequences
- Sequences can be different lengths


Not just for cute puppies!

- Translate **one language** into **another language**
- Summarize a **long sentence** into a **short sentence**
- Respond to a **question** with an **answer**
- Code generation? **text** to **Python code**


For more, see: Ilya Sutskever, Oriol Vinyals, Quoc V. Le.
Sequence to Sequence Learning with Neural Networks. 2014.

Decoding with beam search

Decoding the most likely sequence




What we *should* have done



$$p(y_{i,1:T_y} | x_{i,1:T}) = \prod_{t=1}^{T_y} p(y_{i,t} | x_{i,1:T}, y_{i,0:t-1})$$

probabilities at each time step


How many possible decodings are there?



for M words, in general there are M^T sequences of length T

any one of these might be the optimal one!

Decoding is a **search** problem



We could use *any* tree search algorithm

But exact search in this case is **very** expensive

Fortunately, the **structure** of this problem makes some simple **approximate search** methods work **very well**

Decoding with approximate search

Basic intuition: while choosing the **highest-probability** word on the first step may not be optimal, choosing a **very low-probability** word is very unlikely to lead to a good result

Equivalently: we can't be greedy, but we can be *somewhat* greedy


This is not true in general! This is a guess based on what we know about sequence decoding.

Beam search intuition: store the **k** best sequences **so far**, and update each of them.

special case of **k** = 1 is just greedy decoding

often use **k** around 5-10

Decoding is a **search** problem



Beam search example

$$p(y_{i,1:T_y} | x_{i,1:T}) = \prod_{t=1}^{T_y} p(y_{i,t} | x_{i,1:T}, y_{i,0:t-1})$$


$$\log p(y_{i,1:T_y} | x_{i,1:T}) = \sum_{t=1}^{T_y} \log p(y_{i,t} | x_{i,1:T}, y_{i,0:t-1})$$

in practice, we **sum up** the log probabilities as we go (to avoid underflow)

Example (CS224n, Christopher Manning): **translate (Fr->En):** il a m'entarté (he hit me with a pie)

k = 2 (track the 2 most likely hypotheses)

no perfectly equivalent English word, makes this hard




Beam search summary

$$\log p(y_{i,1:T_y} | x_{i,1:T}) = \sum_{t=1}^{T_y} \log p(y_{i,t} | x_{i,1:T}, y_{i,0:t-1})$$

there are k of these

at each time step t :



1. for each hypothesis $y_{1:t-1,i}$ that we are tracking:

find the top k tokens $y_{t,i,1}, \dots, y_{t,i,k}$

very easy, we get this from the softmax log-probs

2. sort the resulting k^2 length t sequences by their *total* log-probability

3. keep the top k


4. advance each hypothesis to time $t + 1$

When do we stop decoding?

Let's say one of the highest-scoring hypotheses ends in <END>

Save it, along with its score, but do **not** pick it to expand further (there is nothing to expand)

Keep expanding the **k** remaining best hypotheses



Continue until either some cutoff length **T** or until we have **N** hypotheses that end in <EOS>

Which sequence do we pick?

At the end we might have something like this:

he hit me with a pie

$\log p = -4.5$

he threw a pie

$\log p = -3.2$

I was hit with a pie that he threw

$\log p = -7.2$

this is best, right?




$$\log p(y_{i,1:T}|x_{i,1:T}) = \sum_{t=1}^T \log p(y_{i,t}|x_{i,1:T}, y_{i,0:t-1})$$

Problem: $p < 1$ **always**, hence $\log p < 0$ **always**

The **longer** the sequence the **lower** its total score (more negative numbers added together)

Simple “fix”:


just divide by sequence length

$$\text{score}(y_{i,1:T}|x_{i,1:T}) = \frac{1}{T} \sum_{t=1}^T \log p(y_{i,t}|x_{i,1:T}, y_{i,0:t-1})$$


Beam search summary

$$\text{score}(y_{i,1:T}|x_{i,1:T}) = \frac{1}{T} \sum_{t=1}^T \log p(y_{i,t}|x_{i,1:T}, y_{i,0:t-1})$$

at each time step t :

- 
1. for each hypothesis $y_{1:t-1,i}$ that we are tracking:
find the top k tokens $y_{t,i,1}, \dots, y_{t,i,k}$
 2. sort the resulting k^2 length t sequences by their *total* log-probability
 3. save any sequences that end in EOS
 4. keep the top k
 5. advance each hypothesis to time $t + 1$ if $t < H$


return saved sequence with highest score

Attention

The bottleneck problem

all information about the source sequence
is contained in these activations


this forms a bottleneck



Idea: what if we could somehow “peek” at the source sentence while decoding?


Can we “peek” at the input?

compare **query** to each **key** to find the closest one




In reality what keys and queries mean is **learned** – we do not have to select it manually!


Attention




Attention Walkthrough (Example)



Attention Walkthrough (Example)



Attention Walkthrough (Example)



Attention Equations

Encoder-side:

$$k_t = k(h_t)$$

Decoder-side:

$$q_l = q(s_l)$$

$$e_{t,l} = k_t \cdot q_l$$

$$\alpha_{t,l} = \frac{\exp(e_{t,l})}{\sum_{t'} \exp(e_{t',l})}$$


$$a_l = \sum_t \alpha_t h_t$$

Could use this in various ways:

concatenate to hidden state: $\begin{bmatrix} s_{l-1} \\ a_{l-1} \\ x_l \end{bmatrix}$

use for readout, e.g.: $\hat{y}_l = f(s_l, a_l)$

concatenate as input to next RNN layer



Attention Variants

Simple key-query choice: k and q are identity functions


$$k_t = h_t \quad q_l = s_l$$

Decoder-side:

$$e_{t,l} = h_t \cdot s_l$$

$$\alpha_{t,l} = \frac{\exp(e_{t,l})}{\sum_{t'} \exp(e_{t',l})}$$

$$a_l = \sum_t \alpha_t h_t$$



Attention Variants

Linear multiplicative attention:


$$k_t = W_k h_t \quad q_l = W_q s_l$$

Decoder-side: just learn this matrix

$$e_{t,l} = h_t^T W_k^T W_q s_l = h_t^T W_e s_l$$

$$\alpha_{t,l} = \frac{\exp(e_{t,l})}{\sum_{t'} \exp(e_{t',l})}$$

$$a_l = \sum_t \alpha_t h_t$$



Attention Variants

Learned value encoding:

Encoder-side:

$$k_t = k(h_t)$$

Decoder-side:


$$q_l = q(s_l)$$

$$e_{t,l} = k_t \cdot q_l$$

$$\alpha_{t,l} = \frac{\exp(e_{t,l})}{\sum_{t'} \exp(e_{t',l})}$$

$$a_l = \sum_t \alpha_t v(h_t)$$

some learned function



Attention Summary

Every encoder step t produces a key k_t


Every decoder step l produces a query q_l

Decoder gets “sent” encoder activation h_t
corresponding to largest value of $k_t \cdot q_l$

actually gets $\sum_t \alpha_t h_t$

Why is this **good**?

- Attention is **very** powerful, because now all decoder steps are connected to **all** encoder steps!
- Connections go from $O(T)$ to $O(1)$
- Gradients are much better behaved ($O(1)$ propagation length)
- Becomes very important for very long sequences
- Bottleneck is much less important
- This works much better in practice



UC Berkeley · CSW182 | [Deep Learning]

Designing, Visualizing and Understanding Deep Neural Networks (2021)

CSW182 (2021) · 课程资料包 @ShowMeAI



视频
中英双语字幕



课件
一键打包下载



笔记
官方笔记翻译



代码
作业项目解析



视频 · B 站 [扫码或点击链接]
<https://www.bilibili.com/video/BV1Ff4y1n7ar>



课件 & 代码 · 博客 [扫码或点击链接]
<http://blog.showmeai.tech/berkeley-csw182>

Berkeley
Q-Learning
计算机视觉

循环神经网络
风格迁移
机器学习基础

可视化
模仿学习
生成模型

梯度策略
元学习
卷积网络

Awesome AI Courses Notes Cheatsheets 是 [ShowMeAI](#) 资料库的分支系列，覆盖最具知名度的 **TOP50+** 门 AI 课程，旨在为读者和学习者提供一整套高品质中文学习笔记和速查表。

点击课程名称，跳转至课程**资料包**页面，**一键下载**课程全部资料！

机器学习	深度学习	自然语言处理	计算机视觉
Stanford · CS229	Stanford · CS230	Stanford · CS224n	Stanford · CS231n
# Awesome AI Courses Notes Cheatsheets · 持续更新中			
知识图谱	图机器学习	深度强化学习	自动驾驶
Stanford · CS520	Stanford · CS224W	UCBerkeley · CS285	MIT · 6.S094



微信公众号

资料下载方式 2：扫码点击**底部菜单栏**
称为 **AI 内容创作者**？回复 [添砖加瓦]