

# UC Berkeley · CSW182 | [Deep Learning]

## Designing, Visualizing and Understanding Deep Neural Networks (2021)

### CSW182 (2021) · 课程资料包 @ShowMeAI



视频  
中英双语字幕



课件  
一键打包下载



笔记  
官方笔记翻译



代码  
作业项目解析



视频 · B 站 [ 扫码或点击链接 ]  
<https://www.bilibili.com/video/BV1Ff4y1n7ar>



课件 & 代码 · 博客 [ 扫码或点击链接 ]  
<http://blog.showmeai.tech/berkeley-csw182>

Berkeley  
Q-Learning  
计算机视觉

循环神经网络  
风格迁移  
机器学习基础

可视化  
模仿学习  
生成模型

梯度策略  
元学习  
卷积网络

Awesome AI Courses Notes Cheatsheets 是 [ShowMeAI](#) 资料库的分支系列，覆盖最具知名度的 **TOP50+** 门 AI 课程，旨在为读者和学习者提供一整套高品质中文学习笔记和速查表。

点击课程名称，跳转至课程**资料包**页面，**一键下载**课程全部资料！

机器学习	深度学习	自然语言处理	计算机视觉
Stanford · CS229	Stanford · CS230	Stanford · CS224n	Stanford · CS231n
# Awesome AI Courses Notes Cheatsheets · 持续更新中			
知识图谱	图机器学习	深度强化学习	自动驾驶
Stanford · CS520	Stanford · CS224W	UCBerkeley · CS285	MIT · 6.S094



### 微信公众号

资料下载方式 2：扫码点击**底部菜单栏**  
称为 **AI 内容创作者**？回复 [ 添砖加瓦 ]

# Computer Vision


Designing, Visualizing and Understanding Deep Neural Networks

CS W182/282A

Instructor: Sergey Levine  
UC Berkeley



# So far...




**convolutional networks: map image to output value**

↑  
e.g., semantic category (“bicycle”)




# Standard computer vision problems




object classification



object localization



object detection



semantic segmentation  
a.k.a. scene understanding

# Object localization setup

Before:  $\mathcal{D} = \{(x_i, y_i)\}$

image      class label (categorical)




Now:  $\mathcal{D} = \{(x_i, y_i)\}$

image       $y_i = (\ell_i, x_i, y_i, w_i, h_i)$




# Measuring localization accuracy



**Did we get it right?**

Intersection over Union (IoU)



Different datasets have different protocols, but one reasonable one is: **correct if  $\text{IoU} > 0.5$**


If also outputting class label (usually the case): **correct if  $\text{IoU} > 0.5$  and class is correct**

This is **not** a loss function! Just an evaluation standard



# Object localization as regression


$$\mathcal{D} = \{(x_i, y_i)\} \quad y_i = (\ell_i, x_i, y_i, w_i, h_i)$$





- Very simple design
- Can either train jointly (multi-task), or train with classification first, then train regression head
- More or less works OK
- By itself, this is **not** the way it's usually done!
  - We'll see why shortly

# Sliding windows

$$\mathcal{D} = \{(x_i, y_i)\} \quad y_i = (\ell_i, x_i, y_i, w_i, h_i)$$



What if we classify **every** patch in the image?







# Sliding windows



$$\mathcal{D} = \{(x_i, y_i)\} \quad y_i = (\ell_i, x_i, y_i, w_i, h_i)$$

could just take the box with the **highest** class probability  
more generally: **non-maximal suppression**



# A practical approach: OverFeat


$$\mathcal{D} = \{(x_i, y_i)\} \quad y_i = (\ell_i, x_i, y_i, w_i, h_i)$$




provides a little "correction"  
to sliding window

- Pretrain on **just** classification
- Train regression head on top of classification features
- Pass over different regions at different scales
- "Average" together the boxes to get a single answer

# A practical approach: OverFeat



Sliding window **classification** outputs at each scale/position (yellow = bear)




Predicted box  $x, y, w, h$  at each scale/position (yellow = bear)



Final combined bounding box prediction (yellow = bear)

# Sliding windows & reusing calculations


**Problem:** sliding window is very expensive! (36 windows = 36x the compute cost)




This looks **a lot** like convolution...

Can we just **reuse** calculations across windows?

“Convolutional classification”



# Sliding windows & reusing calculations




This kind of calculation reuse is extremely powerful for localization problems with conv nets

We'll see variants of this idea in every method we'll cover today!



# Summary


**Building block:** conv net that outputs class and bounding box coordinates



**Evaluate** this network at multiple scales and for many different crops, each one producing a probability and bounding box



**Implement** the sliding window as just another convolution, with 1x1 convolutions for the classifier/regressor at the end, to save on computation



# Object detection architectures




# The problem setup

Before




$(x_i,$

Now



number of objects  $n_i$  different for each image  $x_i$ !



# How do we get multiple outputs?

**Sliding window:** each window can be a different object


Instead of selecting the window with the highest probability (or merging windows), just output an object in each window above some threshold

**Big problem:** a high-scoring window probably has **other** high-scoring windows nearby

**Non-maximal suppression:** (informally) kill off any detections that have other higher-scoring detections of the same class nearby


**Actually output multiple things:** output is a list of bounding boxes

**Obvious problem:** need to pick number, usually pretty small



{ “cat”: 0.21, “dog”: 0.54 }

$(x_1, y_1, w_1, h_1, x_2, y_2, w_2, h_2)$



non-maximal

maximal


works great if combined

not good by itself


# Case study: you only ~~live~~ once (YOLO) look

**Actually**, you look a few times (49 times to be exact...)

different output for each  
of the 7x7 (49) grid cells  
(a bit like sliding window)



use the same trick as  
before to reuse  
computation (cost is  
**not** 49x higher!)



for each cell, output:

$(x, y, w, h)$

IoU (confidence)

$\ell$  (class label)


zero if no object

output  $B$  of these

**some training details:**

need to assign which output is “responsible”  
for each true object during training

just use the “best-fit” object in that cell  
(i.e., the one with highest IoU)




What if we have too many objects?

Well, nothing... we just miss them


# CNNs + Region proposals

A smarter “sliding window”: region of interest proposals



This is really slow


But we already know how to fix this!







# CNNs + Region proposals

A smarter “sliding window”: region of interest proposals





Compare this to evaluating every location:



# CNNs + Region proposals

How to train region of interest proposals?

Very similar design to what we saw before (e.g., OverFeat, YOLO), but now for predicting if **any** object is present around that location



# Suggested readings


- Redmon et al. **“You Only Look Once: Unified, Real-Time Object Detection.”** 2015
  - Just regress to different bounding boxes in each cell
  - A few follow-ups (e.g., YOLO v5) that work better
- Girshick et al. **“Fast R-CNN.”** 2015
  - Uses region of interest proposals instead of sliding window/convolution
- Ren et al. **“Faster R-CNN.”** 2015
  - Same as above with a few improvements, like region of interest proposal learning
- Liu et al. **SSD: Single Shot MultiBox Detector.** 2015
  - Directly “classifies” locations with class and bounding box shape




Segmentation architectures

# The problem setup

Before



Simple solution:  
“per pixel” classifier



Now



Label **every single** pixel with its class

Actually simpler in some sense:


- No longer variable # of outputs
- Every pixel has a label

## Problem:

We want the output to have the same resolution as the input!

Not hard if we never downsample (i.e., zero padding, stride 1, no pooling), but that is very expensive

# The problem setup




object classes	building	grass	tree	cow	sheep	sky	airplane	water	face	car
bicycle	flower	sign	bird	book	chair	road	cat	dog	body	boat


Classify every point with a class

Don't worry for now about instances  
(e.g., two adjacent cows are just one "cow blob,"  
and that's OK for some reason)

**The challenge:** design a network architecture  
that makes this "per-pixel classification" problem  
computationally tractable



# Fully convolutional networks




Low-res (but high-depth) processing  
in the middle integrates context  
from the entire image

Up-sampling at the end turns these  
low-res feature vectors into high-res  
per-pixel predictions

# Up-sampling/transpose convolution

**Normal convolutions:** reduce resolution with **stride**

Stride = 2



input:  $H_f \times W_f \times C_{\text{in}}$


output:  $1 \times 1 \times C_{\text{out}}$

filter:  $H_f \times W_f \times C_{\text{in}} \times C_{\text{out}}$

**Transpose convolutions:** increase resolution with **fractional “stride”**

Stride = 1/2

we have two sets of values here! **just average them**




input:  $1 \times 1 \times C_{\text{in}}$


output:  $H_f \times W_f \times C_{\text{out}}$

filter:  $C_{\text{in}} \times H_f \times W_f \times C_{\text{out}}$

# Un-pooling




# Bottleneck architecture







# U-Net architecture




# Standard computer vision problems




object classification



object localization



object detection



semantic segmentation  
a.k.a. scene understanding

# UC Berkeley · CSW182 | [Deep Learning]

## Designing, Visualizing and Understanding Deep Neural Networks (2021)

### CSW182 (2021) · 课程资料包 @ShowMeAI



视频  
中英双语字幕



课件  
一键打包下载



笔记  
官方笔记翻译



代码  
作业项目解析



视频 · B 站 [ 扫码或点击链接 ]  
<https://www.bilibili.com/video/BV1Ff4y1n7ar>



课件 & 代码 · 博客 [ 扫码或点击链接 ]  
<http://blog.showmeai.tech/berkeley-csw182>

Berkeley  
Q-Learning  
计算机视觉

循环神经网络  
风格迁移  
机器学习基础

可视化  
模仿学习  
生成模型

梯度策略  
元学习  
卷积网络

Awesome AI Courses Notes Cheatsheets 是 [ShowMeAI](#) 资料库的分支系列，覆盖最具知名度的 **TOP50+** 门 AI 课程，旨在为读者和学习者提供一整套高品质中文学习笔记和速查表。

点击课程名称，跳转至课程**资料包**页面，**一键下载**课程全部资料！

机器学习	深度学习	自然语言处理	计算机视觉
Stanford · CS229	Stanford · CS230	Stanford · CS224n	Stanford · CS231n
# Awesome AI Courses Notes Cheatsheets · 持续更新中			
知识图谱	图机器学习	深度强化学习	自动驾驶
Stanford · CS520	Stanford · CS224W	UCBerkeley · CS285	MIT · 6.S094



### 微信公众号

资料下载方式 2：扫码点击**底部菜单栏**  
称为 **AI 内容创作者**？回复 [ 添砖加瓦 ]