

# Stanford·CS124 | From Languages to Information (2021)

## CS124(2021)·课程资料包 @ShowMeAI



视频  
中英双语字幕



课件  
一键打包下载



笔记  
官方笔记翻译



代码  
作业项目解析



视频·B 站 [ 扫码或点击链接 ]

<https://www.bilibili.com/video/BV1YA411w7ym>



课件 & 代码·博客 [ 扫码或点击链接 ]

<http://blog.showmeai.tech/cs124/>

文本处理

信息检索

编辑距离

推荐系统

神经嵌入

序列标注

社交网络分析

PageRank

倒排索引

对话系统

协同过滤

Awesome AI Courses Notes Cheatsheets 是 [ShowMeAI](#) 资料库的分支系列，覆盖最具知名度的 **TOP20+** 门 AI 课程，旨在为读者和学习者提供一整套高品质中文学习笔记和速查表。

**点击**课程名称，跳转至课程**资料包**页面，**一键下载**课程全部资料！

机器学习	深度学习	自然语言处理	计算机视觉
Stanford · CS229	Stanford · CS230	Stanford · CS224n	Stanford · CS231n
# Awesome AI Courses Notes Cheatsheets · 持续更新中			
知识图谱	图机器学习	深度强化学习	自动驾驶
Stanford · CS520	Stanford · CS224W	UCBerkeley · CS285	MIT · 6.S094



微信公众号

资料下载方式 2: 扫码点击**底部菜单栏**


称为 **AI 内容创作者**? 回复 [ 添砖加瓦 ]



# Web Anchor Text



# The Web as a Directed Graph



## Assumption 1:

A hyperlink between pages denotes  
author perceived relevance (quality signal)


## Assumption 2:

The anchor of the hyperlink describes  
the target page (textual context)



# Anchor Text

- For *ibm* how to distinguish between:
  - IBM's home page (mostly graphical)
  - IBM's copyright page (high term frequency for "ibm")
  - Rival's spam page (arbitrarily high term frequency)





# Indexing anchor text

When indexing a document  $D$ , include anchor text from links pointing to  $D$ .

Armonk, NY-based computer giant [IBM](#) announced today

[www.ibm.com](http://www.ibm.com)

Solutions, Services, Products, MyIBM

Question Answering Systems:

[Apple's](#) Siri

[IBM's](#) Watson

[Big Blue](#) today announced record profits for the quarter



# Indexing anchor text

- Can sometimes have unexpected side effects –
  - Google bombing
- Can score anchor text with weight depending on the authority of the anchor page's website
  - E.g., if we were to assume that content from cnn.com or yahoo.com is authoritative, then trust the anchor text from them



# Many NLP Applications of Anchor Text

- Finding synonyms
  - Federal Reserve: “Fed”, “U.S. Federal Reserve Board”, “U.S. Federal Reserve System”, “Federal Reserve Bank”
- Finding translations of named entities
- Providing constituent boundaries for parsers



# Web Anchor Text





# Networks and Link Analysis

# PageRank: Overview and Markov Chains




# Combining link structure with text

- A good search result looks at more than just query-document text overlap
- One factor: page **popularity**.
  - Pages that are pointed to by lots of other pages are popular.
  - We can use link counts as a measure of static goodness,
  - Combine link counts with the text match score



# Using link structure to measure page importance

- Simplest: use link counts as popularity measure
  - **Undirected popularity:**
    - Page score = **degree**: the number of in-links plus the number of out-links ( $3+2=5$ ).
  - **Directed popularity:**
    - Page score = number of in-links (3).






# Spamming simple popularity

- Simple popularity heuristics can be spammed to give your page a high score, whether it's:
  - the number of in-links plus the number of out-links
  - number of in-links



# Intuition of PageRank




C has higher PageRank than E, even though E has more inlinks



# PageRank scoring


- Imagine a browser doing a random walk on web pages:
  - Start at a random page
  - At each step, go out of the current page along one of the links on that page, equiprobably
- “In the steady state” each page has a long-term visit rate - use this as the page’s score.





# Not quite enough

- The web is full of dead-ends.
  - Random walk can get stuck in dead-ends.
  - Makes no sense to talk about long-term visit rates.





# Teleporting

- At a dead end, jump to a random web page.
- At any non-dead end, with probability 10%, jump to a random web page.
  - With remaining probability (90%), go out on a random link.
  - 10% - a parameter.






# Result of teleporting

- Now cannot get stuck locally.
- There is a long-term rate, the Pagerank, at which any page is visited



# Markov chains

- A Markov chain:
  - $N$  states,
  - An  $N \times N$  transition probability matrix  $\mathbf{P}$ .
- At each step, we are in exactly one of the states.
- For  $1 \leq i, j \leq n$ , the matrix entry  $P_{ij}$  tells us the probability of  $j$  being the next state, given we are currently in state  $i$ .




- For all  $i$ ,

$$\sum_{j=1}^n P_{ij} = 1.$$



# Markov chains



- Transition probability matrix  $P$

$$P = \begin{pmatrix} 0 & 0.5 & 0.5 \\ 1 & 0 & 0 \\ 1 & 0 & 0 \end{pmatrix}$$



# Random Surfers and Markov chains

- Markov chains are abstractions of random walks.
- Each state
  - represents one web page
- Each transition probability
  - represents the probability of moving from one page to another
- We can derive the transition probability  $P$  from the adjacency matrix  $A$  of the web graph.



# Teleporting, more formally

- If a node has no out-links, the random surfer teleports:
  - the transition probability to each node in the  $N$ -node graph is  $1/N$
- If a node has  $K > 0$  outgoing links:
  - with probability  $0 < \alpha < 1$  the surfer teleports to a random node
    - probability is  $\alpha/N$
  - with probability  $1 - \alpha$  the surfer takes a normal random walk
    - probability is  $(1 - \alpha)/K$




# Deriving transition probability matrix $P$ from adjacency matrix $A$

- $A$  is the adjacency matrix of the web graph
  - $A_{ij}$  is 1 if there is a hyperlink from page  $i$  to page  $j$
- If a row of  $A$  has no 1's, then replace each element by  $1/N$ .  
For all other rows proceed as follows.
- Divide each 1 in  $A$  by the number of 1's in its row. Thus, if there is a row with three 1's, then each of them is replaced by  $1/3$
- Multiply the resulting matrix by  $(1-\alpha)$
- Add  $\alpha/N$  to every entry of the resulting matrix, to obtain  $P$ .



# Computing P with teleportation



$$A = \begin{pmatrix} 0 & 1 & 0 \\ 1 & 0 & 1 \\ 0 & 1 & 0 \end{pmatrix}$$

$$P_{\alpha=0} = \begin{pmatrix} 0 & 1 & 0 \\ 0.5 & 0 & 0.5 \\ 0 & 1 & 0 \end{pmatrix}$$

$$P[1,*] = (1-\alpha) (0 \ 1 \ 0) + \alpha (1/N \ 1/N \ 1/N)$$

$$P[1,*] = 0.5 (0 \ 1 \ 0) + 0.5(1/3 \ 1/3 \ 1/3)$$


$$P_{\alpha=0.5} = \begin{pmatrix} 1/6 & 2/3 & 1/6 \\ 5/12 & 1/6 & 5/12 \\ 1/6 & 2/3 & 1/6 \end{pmatrix}$$



# Networks and Link Analysis

# PageRank: Overview and Markov Chains





# Networks and Link Analysis

# PageRank: Computation



The image cannot be displayed.  
Your computer may not have enough memory to open the image, or the image may have been corrupted. Restart your computer, and then open the file again. If the red x still appears, you may have to delete the image and then insert it again.

# Computing PageRank:

## The probability of being in a state

- A probability (row) vector  $\mathbf{x} = (x_1, \dots, x_n)$  tells us where the walk is at any point.
- E.g.,  $(\underset{1}{000}\dots\underset{i}{1}\dots\underset{n}{000})$  means we're in state  $i$ .

More generally, the vector  $\mathbf{x} = (x_1, \dots, x_n)$  means the walk is in state  $i$  with probability  $x_i$ .

$$\sum_{i=1}^n x_i = 1$$



The image cannot be displayed.  
Your computer may not have enough memory to open the image, or the image may have been corrupted. Restart your computer, and then open the file again. If the red x still appears, you may have to delete the image and then insert it again.

# Computing PageRank:

## Change in probability vector


- If the probability vector is  $\mathbf{x} = (x_1, \dots, x_n)$  at this step, what is it at the next step?
- Recall that row  $i$  of transition matrix  $\mathbf{P}$  tells us where we go next from state  $i$ .
- So from  $\mathbf{x}$ , our next state is distributed as  $\mathbf{xP}$ .



The image cannot be displayed.  
Your computer may not have enough memory to open the image, or the image may have been corrupted. Restart your computer, and then open the file again. If the red x still appears, you may have to delete the image and then insert it again.

# Ergodic Markov chains

- A Markov chain is **ergodic** if
  - you have a path from any state to any other
  - For any start state, after a finite transient time  $T_0$ , the **probability of being in any state at a fixed time  $T > T_0$  is nonzero.**





The image cannot be displayed.  
Your computer may not have enough memory to open the image, or the image may have been corrupted. Restart your computer, and then open the file again. If the red x still appears, you may have to delete the image and then insert it again.

# Ergodic Markov chains


- For any ergodic Markov chain, there is a unique **long-term visit rate** for each state.
  - A steady-state probability distribution  $\boldsymbol{\pi} = (\pi_1, \dots, \pi_n)$ .
  - **Over a long time-period, we visit each state in proportion to this rate.**
  - Thus  $\pi_i$  is the PageRank of state  $i$ .
- It doesn't matter where we start.



The image cannot be displayed.  
Your computer may not have enough memory to open the image, or the image may have been corrupted. Restart your computer, and then open the file again. If the red x still appears, you may have to delete the image and then insert it again.

## Steady state example

- The steady state looks like a vector of probabilities  $\pi = (\pi_1, \dots, \pi_n)$ :
  - $\pi_i$  is the probability that we are in state  $i$ .



For this example,  $\pi_1 = 1/4$  and  $\pi_2 = 3/4$ .



The image cannot be displayed.  
Your computer may not have enough memory to open the image, or the image may have been corrupted. Restart your computer, and then open the file again. If the red x still appears, you may have to delete the image and then insert it again.

# How do we compute this vector?

- Let  $\pi = (\pi_1, \dots, \pi_n)$  denote the row vector of steady-state probabilities
- If our current position is described by  $\pi$ , then the next step is distributed as  $\pi P$ .
- But  $\pi$  is the steady state, so  $\pi = \pi P$ .
- Solving this matrix equation gives us  $\pi$ .
  - So  $\pi$  is the (left) eigenvector for  $P$ .
  - (Corresponds to the “principal” eigenvector of  $P$  with the largest eigenvalue.)
  - Transition probability matrices always have largest eigenvalue 1.

# The power iteration method of computing $\pi$

- Recall, regardless of where we start, we eventually reach the steady state  $\pi$ .
- Start with any distribution (say  $\mathbf{x}=(10...0)$ ).
- After one step, we're at  $\mathbf{xP}$ ;
- after two steps at  $\mathbf{xP}^2$ , then  $\mathbf{xP}^3$  and so on.
- “Eventually” means for “large”  $k$ ,  $\mathbf{xP}^k = \pi$ .
- Algorithm: multiply  $\mathbf{x}$  by increasing powers of  $\mathbf{P}$  until the product looks stable.





The image cannot be displayed.  
Your computer may not have enough memory to open the image, or the image may have been corrupted. Restart your computer, and then open the file again. If the red x still appears, you may have to delete the image and then insert it again.

# Example of power iteration

$$P_{\alpha=0.5} = \begin{pmatrix} 1/6 & 2/3 & 1/6 \\ 5/12 & 1/6 & 5/12 \\ 1/6 & 2/3 & 1/6 \end{pmatrix}$$

- Let's say surfer starts in state 1:

$$\vec{x}_0 = \begin{pmatrix} 1 & 0 & 0 \end{pmatrix}$$

$$\vec{x}_1 = \vec{x}_0 P = \begin{pmatrix} 1/6 & 2/3 & 1/6 \end{pmatrix}$$

$$\vec{x}_2 = \vec{x}_1 P = \begin{pmatrix} 1/6 & 2/3 & 1/6 \end{pmatrix} \begin{pmatrix} 1/6 & 2/3 & 1/6 \\ 5/12 & 1/6 & 5/12 \\ 1/6 & 2/3 & 1/6 \end{pmatrix} = \begin{pmatrix} 1/3 & 1/3 & 1/3 \end{pmatrix}$$



The image cannot be displayed.  
Your computer may not have enough memory to open the image, or the image may have been corrupted. Restart your computer, and then open the file again. If the red x still appears, you may have to delete the image and then insert it again.

## Power iteration example (continued)

$\vec{x}_0$	1	0	0
$\vec{x}_1$	1/6	2/3	1/6
$\vec{x}_2$	1/3	1/3	1/3
$\vec{x}_3$	1/4	1/2	1/4
$\vec{x}_4$	7/24	5/12	7/24
...	...	...	...
$\vec{x} = \vec{\pi}$	5/18	4/9	5/18

Node 1  
PageRank

Node 2  
PageRank


Node 3  
PageRank



The image cannot be displayed.  
Your computer may not have enough memory to open the image, or the image may have been corrupted. Restart your computer, and then open the file again. If the red x still appears, you may have to delete the image and then insert it again.

# PageRank summary

- Preprocessing:
  - Given graph of links, build matrix  $\mathbf{P}$ .
  - From it compute the PageRank vector  $\pi$ .
  - The PageRank of page  $i$ ,  $\pi_i$  is between 0 and 1
- Query processing:
  - Retrieve pages meeting query.
  - Rank them by their PageRank.
  - Order is *query-independent*.



# Networks and Link Analysis

# PageRank: Computation

# Stanford·CS124 | From Languages to Information (2021)

## CS124(2021)·课程资料包 @ShowMeAI



视频  
中英双语字幕



课件  
一键打包下载



笔记  
官方笔记翻译



代码  
作业项目解析



视频·B 站 [ 扫码或点击链接 ]

<https://www.bilibili.com/video/BV1YA411w7ym>



课件 & 代码·博客 [ 扫码或点击链接 ]

<http://blog.showmeai.tech/cs124/>

文本处理

信息检索

编辑距离

推荐系统

神经嵌入

序列标注

社交网络分析

PageRank

倒排索引

对话系统

协同过滤

Awesome AI Courses Notes Cheatsheets 是 [ShowMeAI](#) 资料库的分支系列，覆盖最具知名度的 **TOP20+** 门 AI 课程，旨在为读者和学习者提供一整套高品质中文学习笔记和速查表。

点击课程名称，跳转至课程**资料包**页面，**一键下载**课程全部资料！

机器学习	深度学习	自然语言处理	计算机视觉
Stanford · CS229	Stanford · CS230	Stanford · CS224n	Stanford · CS231n
# Awesome AI Courses Notes Cheatsheets · 持续更新中			
知识图谱	图机器学习	深度强化学习	自动驾驶
Stanford · CS520	Stanford · CS224W	UCBerkeley · CS285	MIT · 6.S094



微信公众号

资料下载方式 2: 扫码点击**底部菜单栏**

称为 **AI 内容创作者**? 回复 [ 添砖加瓦 ]