

Assignment #9: 图论：遍历，及 树算

Updated 1739 GMT+8 Apr 14, 2024

2024 spring, Compiled by ==同学的姓名、院系==

赵云天 生命科学学院

说明：

- 1) 请把每个题目解题思路（可选），源码Python, 或者C++（已经在Codeforces/Openjudge上AC），截图（包含Accepted），填写到下面作业模版中（推荐使用 typora <https://typoraio.cn>，或者用 word）。AC 或者没有AC，都请标上每个题目大致花费时间。
- 2) 提交时候先提交pdf文件，再把md或者doc文件上传到右侧“作业评论”。Canvas需要有同学清晰头像、提交文件有pdf、“作业评论”区有上传的md或者doc附件。
- 3) 如果不能在截止前提交作业，请写明原因。

编程环境

==（请改为同学的操作系统、编程环境等）==

操作系统：win10

Python编程环境：Spyder IDE 5.2.2

C/C++编程环境：

1. 题目

04081: 树的转换

<http://cs101.openjudge.cn/dsapre/04081/>

思路：还算简单

代码

```
def tree_heights(s):
    old_height = 0
    max_old = 0
    new_height = 0
    max_new = 0
    stack = []
    for c in s:
        if c == 'd':
            old_height += 1
            max_old = max(max_old, old_height)

            new_height += 1
```

```

        stack.append(new_height)
        max_new = max(max_new, new_height)
    else:
        old_height -= 1

        new_height = stack[-1]
        stack.pop()
    return f"{max_old} => {max_new}"

s = input().strip()
print(tree_heights(s))

```

代码运行截图 == (至少包含有"Accepted") ==

状态: Accepted

源代码

```

def tree_heights(s):
    old_height = 0
    max_old = 0
    new_height = 0
    max_new = 0
    stack = []
    for c in s:
        if c == 'd':
            old_height += 1
            max_old = max(max_old, old_height)

            new_height += 1
            stack.append(new_height)
            max_new = max(max_new, new_height)
        else:
            old_height -= 1

            new_height = stack[-1]
            stack.pop()
    return f"{max_old} => {max_new}"

s = input().strip()
print(tree_heights(s))

```

基本信息

#: 44769135
 题目: 04081
 提交人: 23n2300012140(zyt)
 内存: 3668kB
 时间: 30ms
 语言: Python3
 提交时间: 2024-04-23 22:10:57

08581: 扩展二叉树

<http://cs101.openjudge.cn/dsapre/08581/>

思路: 和之前的题较为类似

代码

```

def build_tree(preorder):
    if not preorder or preorder[0] == '.':
        return None, preorder[1:]
    root = preorder[0]
    left, preorder = build_tree(preorder[1:])
    right, preorder = build_tree(preorder)
    return (root, left, right), preorder

```

```

def inorder(tree):
    if tree is None:
        return ''
    root, left, right = tree
    return inorder(left) + root + inorder(right)

def postorder(tree):
    if tree is None:
        return ''
    root, left, right = tree
    return postorder(left) + postorder(right) + root

preorder = input().strip()
tree, _ = build_tree(preorder)

print(inorder(tree))
print(postorder(tree))

```

代码运行截图 == (至少包含有"Accepted") ==

状态: **Accepted**

源代码

```

def build_tree(preorder):
    if not preorder or preorder[0] == '.':
        return None, preorder[1:]
    root = preorder[0]
    left, preorder = build_tree(preorder[1:])
    right, preorder = build_tree(preorder)
    return (root, left, right), preorder

def inorder(tree):
    if tree is None:
        return ''
    root, left, right = tree
    return inorder(left) + root + inorder(right)

def postorder(tree):
    if tree is None:
        return ''
    root, left, right = tree
    return postorder(left) + postorder(right) + root

preorder = input().strip()
tree, _ = build_tree(preorder)

print(inorder(tree))
print(postorder(tree))

```

基本信息

#: 44769183
 题目: 08581
 提交人: 23n2300012140(zyt)
 内存: 3632kB
 时间: 27ms
 语言: Python3
 提交时间: 2024-04-23 22:14:11

22067: 快速堆猪

<http://cs101.openjudge.cn/practice/22067/>

思路: 比较简单

代码

```

a = []
m = []

while True:
    try:
        s = input().split()

        if s[0] == "pop":
            if a:
                a.pop()
            if m:
                m.pop()
        elif s[0] == "min":
            if m:
                print(m[-1])
        else:
            h = int(s[1])
            a.append(h)
            if not m:
                m.append(h)
            else:
                k = m[-1]
                m.append(min(k, h))
    except EOFError:
        break

```

代码运行截图 == (AC代码截图, 至少包含有"Accepted") ==

状态: **Accepted**

源代码

```

a = []
m = []

while True:
    try:
        s = input().split()

        if s[0] == "pop":
            if a:
                a.pop()
            if m:
                m.pop()
        elif s[0] == "min":
            if m:
                print(m[-1])
        else:
            h = int(s[1])
            a.append(h)
            if not m:
                m.append(h)
            else:
                k = m[-1]
                m.append(min(k, h))
    except EOFError:
        break

```

基本信息

#: 44769209
 题目: 22067
 提交人: 23n2300012140(zyt)
 内存: 6640kB
 时间: 317ms
 语言: Python3
 提交时间: 2024-04-23 22:15:31

04123: 马走日

dfs, <http://cs101.openjudge.cn/practice/04123>

思路：不算难的dfs

代码

```
maxn = 10;
sx = [-2,-1,1,2, 2, 1,-1,-2]
sy = [ 1, 2,2,1,-1,-2,-2,-1]

ans = 0;

def Dfs(dep: int, x: int, y: int):
    if n*m == dep:
        global ans
        ans += 1
        return

    for r in range(8):
        s = x + sx[r]
        t = y + sy[r]
        if chess[s][t]==False and 0<=s<n and 0<=t<m :
            chess[s][t]=True
            Dfs(dep+1, s, t)
            chess[s][t] = False;

for _ in range(int(input())):
    n,m,x,y = map(int, input().split())
    chess = [[False]*maxn for _ in range(maxn)]
    ans = 0
    chess[x][y] = True
    Dfs(1, x, y)
    print(ans)
```

代码运行截图 == (AC代码截图, 至少包含有"Accepted") ==

状态: Accepted

源代码

```
maxn = 10;
sx = [-2,-1,1,2, 2, 1,-1,-2]
sy = [ 1, 2,2,1,-1,-2,-2,-1]

ans = 0;

def Dfs(dep: int, x: int, y: int):
    if n*m == dep:
        global ans
        ans += 1
        return

    for r in range(8):
        s = x + sx[r]
        t = y + sy[r]
        if chess[s][t]==False and 0<=s<n and 0<=t<m :
            chess[s][t]=True
            Dfs(dep+1, s, t)
            chess[s][t] = False;

for _ in range(int(input())):
    n,m,x,y = map(int, input().split())
    chess = [[False]*maxn for _ in range(maxn)]
    ans = 0
    chess[x][y] = True
    Dfs(1, x, y)
    print(ans)
```

基本信息

#: 44769270
题目: 04123
提交人: 23n2300012140(zyt)
内存: 3624kB
时间: 3337ms
语言: Python3
提交时间: 2024-04-23 22:20:22

28046: 词梯

bfs, <http://cs101.openjudge.cn/practice/28046/>

思路: 感觉计概方法更舒服

代码

```
from collections import defaultdict
dic=defaultdict(list)
n,lis=int(input()),[]
for i in range(n):
    lis.append(input())
for word in lis:
    for i in range(len(word)):
        bucket=word[:i]+'_'+word[i+1:]
        dic[bucket].append(word)
def bfs(start,end,dic):
    queue=[(start,[start])]
    visited=[start]
    while queue:
        currentword,currentpath=queue.pop(0)
        if currentword==end:
            return ' '.join(currentpath)
        for i in range(len(currentword)):
            bucket=currentword[:i]+'_'+currentword[i+1:]
            for nbr in dic[bucket]:
                if nbr not in visited:
```

```

        visited.append(nbr)
        newpath=currentpath+[nbr]
        queue.append((nbr,newpath))

    return 'NO'
start,end=map(str,input().split())
print(bfs(start,end,dic))

```

代码运行截图 == (AC代码截图, 至少包含有"Accepted") ==

状态: Accepted

源代码

```

from collections import defaultdict
dic=defaultdict(list)
n,lis=int(input()),[]
for i in range(n):
    lis.append(input())
for word in lis:
    for i in range(len(word)):
        bucket=word[:i]+'_'+word[i+1:]
        dic[bucket].append(word)
def bfs(start,end,dic):
    queue=[(start,[start])]
    visited=[start]
    while queue:
        currentword,currentpath=queue.pop(0)
        if currentword==end:
            return ' '.join(currentpath)
        for i in range(len(currentword)):
            bucket=currentword[:i]+'_'+currentword[i+1:]
            for nbr in dic[bucket]:
                if nbr not in visited:
                    visited.append(nbr)
                    newpath=currentpath+[nbr]
                    queue.append((nbr,newpath))
    return 'NO'
start,end=map(str,input().split())
print(bfs(start,end,dic))

```

基本信息

#: 44769338
 题目: 28046
 提交人: 23n2300012140(zyt)
 内存: 5748kB
 时间: 1372ms
 语言: Python3
 提交时间: 2024-04-23 22:25:04

28050: 骑士周游

dfs, <http://cs101.openjudge.cn/practice/28050/>

思路: 看了题解后大概理解了整体思路

代码

```

import sys

class Graph:
    def __init__(self):
        self.vertices = {}
        self.num_vertices = 0

    def add_vertex(self, key):
        self.num_vertices = self.num_vertices + 1
        new_ertex = Vertex(key)
        self.vertices[key] = new_ertex

```

```

        return new_ertex

def get_vertex(self, n):
    if n in self.vertices:
        return self.vertices[n]
    else:
        return None

def __len__(self):
    return self.num_vertices

def __contains__(self, n):
    return n in self.vertices

def add_edge(self, f, t, cost=0):
    if f not in self.vertices:
        nv = self.add_vertex(f)
    if t not in self.vertices:
        nv = self.add_vertex(t)
    self.vertices[f].add_neighbor(self.vertices[t], cost)
    #self.vertices[t].add_neighbor(self.vertices[f], cost)

def getVertices(self):
    return list(self.vertices.keys())

def __iter__(self):
    return iter(self.vertices.values())

class Vertex:
    def __init__(self, num):
        self.key = num
        self.connectedTo = {}
        self.color = 'white'
        self.distance = sys.maxsize
        self.previous = None
        self.disc = 0
        self.fin = 0

    def __lt__(self, o):
        return self.key < o.key

    def add_neighbor(self, nbr, weight=0):
        self.connectedTo[nbr] = weight

    def get_neighbors(self):
        return self.connectedTo.keys()

    def __str__(self):
        return str(self.key) + ":color " + self.color + ":disc " + str(self.disc)
+ ":fin " + str(
            self.fin) + ":dist " + str(self.distance) + ":pred \n\t[" +
str(self.previous) + "]\n"

```



```

def knight_graph(board_size):
    kt_graph = Graph()
    for row in range(board_size):
        for col in range(board_size):
            node_id = pos_to_node_id(row, col, board_size)
            new_positions = gen_legal_moves(row, col, board_size)
            for row2, col2 in new_positions:
                other_node_id = pos_to_node_id(row2, col2, board_size)
                kt_graph.add_edge(node_id, other_node_id)
    return kt_graph

def pos_to_node_id(x, y, bdSize):
    return x * bdSize + y

def gen_legal_moves(row, col, board_size):
    new_moves = []
    move_offsets = [
        (-1, -2),
        (-1, 2),
        (-2, -1),
        (-2, 1),
        (1, -2),
        (1, 2),
        (2, -1),
        (2, 1),
    ]
    for r_off, c_off in move_offsets:
        if (
            0 <= row + r_off < board_size
            and 0 <= col + c_off < board_size
        ):
            new_moves.append((row + r_off, col + c_off))
    return new_moves

def knight_tour(n, path, u, limit):
    u.color = "gray"
    path.append(u)
    if n < limit:
        neighbors = ordered_by_avail(u)
        i = 0

        for nbr in neighbors:
            if nbr.color == "white" and \
                knight_tour(n + 1, path, nbr, limit):
                return True
        else:
            path.pop()
            u.color = "white"
            return False
    else:
        return True

def ordered_by_avail(n):
    res_list = []
    for v in n.get_neighbors():
        if v.color == "white":

```

```

        c = 0
        for w in v.get_neighbors():
            if w.color == "white":
                c += 1
        res_list.append((c,v))
    res_list.sort(key = lambda x: x[0])
    return [y[1] for y in res_list]
def main():
    def NodeToPos(id):
        return ((id//8, id%8))

    bdSize = int(input())
    *start_pos, = map(int, input().split())
    g = knight_graph(bdSize)
    start_vertex = g.get_vertex(pos_to_node_id(start_pos[0], start_pos[1],
bdSize))
    if start_vertex is None:
        print("fail")
        exit(0)

    tour_path = []
    done = knight_tour(0, tour_path, start_vertex, bdSize * bdSize-1)
    if done:
        print("success")
    else:
        print("fail")

    exit(0)
    cnt = 0
    for vertex in tour_path:
        cnt += 1
        if cnt % bdSize == 0:
            print()
        else:
            print(vertex.key, end=" ")
            #print(NodeToPos(vertex.key), end=" ")

if __name__ == '__main__':
    main()

```

代码运行截图 == (AC代码截图, 至少包含有"Accepted") ==

状态: Accepted

源代码

```
import sys

class Graph:
    def __init__(self):
        self.vertices = {}
        self.num_vertices = 0

    def add_vertex(self, key):
        self.num_vertices = self.num_vertices + 1
        new_ertex = Vertex(key)
        self.vertices[key] = new_ertex
        return new_ertex

    def get_vertex(self, n):
        if n in self.vertices:
            return self.vertices[n]
        else:
            return None

    def __len__(self):
        return self.num_vertices
```

基本信息

#: 44769399
题目: 28050
提交人: 23n2300012140(zyt)
内存: 4012kB
时间: 34ms
语言: Python3
提交时间: 2024-04-23 22:29:47

2. 学习总结和收获

==如果作业题目简单，有否额外练习题目，比如：OJ“2024spring每日选做”、CF、LeetCode、洛谷等网站题目。==

本周任务很多，用来学习数算的时间很少，幸好上学期学过dfs和bfs