


Identity

ASP.NET Core Identity, Authentication Types, Social Accounts, JWT



SoftUni Team
Technical Trainers



SoftUni



Software University

<https://softuni.bg>

Table of Contents

1. Gaining full control over Identity
2. Claims
3. Roles
4. Authentication Types
5. Social Accounts
6. JWT (JSON Web Tokens)



sli.do

#csharp-web



Gaining Full Control Over Identity

- **ApplicationUser.cs** – can add user functionality
- Extends the **user** information from the ASP.NET Core **IdentityUser**
- May hold **additional fields**
 - E.g., first name, last name, birthday

```
public class ApplicationUser
    : IdentityUser
{
    public string FirstName { get; set; }
    public string LastName { get; set; }
}
```

```
...public class IdentityUser<TKey> where TKey : IEquatable<TKey>
{
    ...public IdentityUser();
    ...public IdentityUser(string userName);

    ...public virtual DateTimeOffset? LockoutEnd { get; set; }
    ...public virtual bool TwoFactorEnabled { get; set; }
    ...public virtual bool PhoneNumberConfirmed { get; set; }
    ...public virtual string PhoneNumber { get; set; }
    ...public virtual string ConcurrencyStamp { get; set; }
    ...public virtual string SecurityStamp { get; set; }
    ...public virtual string PasswordHash { get; set; }
    ...public virtual bool EmailConfirmed { get; set; }
    ...public virtual string NormalizedEmail { get; set; }
    ...public virtual string Email { get; set; }
    ...public virtual string NormalizedUserName { get; set; }
    ...public virtual string UserName { get; set; }
    ...public virtual TKey Id { get; set; }
    ...public virtual bool LockoutEnabled { get; set; }
    ...public virtual int AccessFailedCount { get; set; }

    ...public override string ToString();
}
```

- The default identity behavior is replaced with a custom one

```
builder.Services.AddIdentity<IdentityUser, IdentityRole>()  
    // services.AddDefaultIdentity<IdentityUser>()  
    .AddEntityFrameworkStores<ApplicationDbContext>()  
    .AddDefaultTokenProviders();  
}
```

- You implement a custom **User** and a Custom **User Role**

Gaining Full Identity Control (2)

- The following sets the **LoginPath**, **LogoutPath**, **AccessDeniedPath**


```
builder.Services.ConfigureApplicationCookie(options =>
{
    options.LoginPath = $"/Identity/Account/Login";
    options.LogoutPath = $"/Identity/Account/Logout";
    options.AccessDeniedPath = $"/Identity/Account/AccessDenied";
});
```



Claims

Claim-based Identity In ASP.NET Core

- **Claim**-based identity is a common technique used in applications
 - Applications acquire identity info about their users through **Claims**
- A **Claim** is a statement that one subject makes about itself
 - It can be about a name, group, ethnicity, privilege, association etc.
 - The subject making the claim is a **provider**
- **Claim**-based identity **simplifies** authentication logic
 - No **account creation / modification** required



- In **ASP.NET Core**, **Claim**-based auth checks are **declarative**
 - The developer embeds them against a **Controller** or an **Action**
 - The developer specifies **required claims** to access the functionality
- **Claims requirements** are policy based
 - The developer must register a policy expressing claims requirements
- **Claims** are **name-value** pairs



- The simplest type of **claim policy** checks only for the **presence** of a claim
 - The **value** of the **claim** is not checked

```
builder.Services.AddAuthorization(options =>
{
    options.AddPolicy("EmployeeOnly", policy =>
        policy.RequireClaim("EmployeeNumber"));
});
```

```
//This action is accessible only by Identities with the "EmployeeOnly" Claim...
[Authorize(Policy = "EmployeeOnly")]
public IActionResult VacationBalance() => View();
```



Roles

- Role-based **authorization** in ASP.NET Core
 - An identity may belong to **one** or **more roles**
- Roles are claims, but **not** all claims are roles
- Enable **RoleManager** with

```
builder.Services.AddDefaultIdentity<IdentityUser>(...)  
                .AddRoles<IdentityRole>();
```

- Adding a **User** to an **existing Role**

```
public async Task<IActionResult> AddUserToRole()
{
    var roleName = "Administrator";
    var roleExists = await roleManager.RoleExistsAsync(roleName);

    if (roleExists)
    {
        var user = await userManager.GetUserAsync(User);
        var result = await userManager.AddToRoleAsync(user, roleName);

        if (result.Succeeded)
            // The user is now Administrator
    }
}
```

Require Logged-In User in Certain Role

- Give access only to Users in Role "**Administrator**"

```
[Authorize(Roles="Administrator")]  
public class AdminController : Controller  
{ ... }
```

- Give access if User's Role is "**User**", "**Student**" or "**Trainer**"

```
[Authorize(Roles="User, Student, Trainer")]  
public ActionResult Roles()  
{  
    ...  
}
```

Check the Currently Logged-In User's Role

```
// GET: /Home/Admin (for logged-in admins only)
[Authorize]
public ActionResult Admin()
{
    if (this.User.IsInRole("Administrator"))
    {
        ViewBag.Message = "Welcome to the admin area!";
        return View();
    }





    return this.View("Unauthorized");
}
```






Authentication Types

- **Cookie-based** Authentication & Authorization (Identity)
 - Authentication is entirely **Cookie-based**
 - The **Principal** is based on **claims**
- **Windows** Authentication & Authorization
 - Relies on the operating system to authenticate users
- **Cloud-based** Authentication & Authorization
 - An **external platform** handles the User functionality
- **JSON Web Tokens (JWT)** Authentication & Authorization



- **Cookie-Based** auth is the **ASP.NET Core** app auth mechanism
 - Authentication is entirely **Cookie-based**
 - This is a major difference from **ASP.NET MVC**
 - The **Principal** is based on **claims**



- **Windows** auth is a more complex auth mechanism
 - Relies on the operating system to authenticate users
 - Credentials are hashed before sent across the network
 - Best suited for intranet environments
 - Clients, Users, Servers belong to the same Windows domain (AD)




- **Cloud-based** auth is a more modern authentication approach
 - Authentication & Authorization work is outsourced
 - An **external platform** handles the User functionality
 - Ensures flexibility and speed
 - Greatly decouples the auth functionality from the others



- **JSON Web Tokens** is a modern JavaScript-based auth mechanism
 - Compact and self-contained
 - Focused on **signed tokens**
 - Work with claims
 - Data is encrypted
 - Used for auth & information exchange
 - Commonly used, when developing **REST**
 - Extremely simple to comprehend

JWT Authentication & Authorization (2)






Social Accounts

- Enabling users to sign in with their existing credentials is convenient
 - Shifts the complexities of managing the sign-in process to third party
 - Enhances user experience by minimizing their auth activities
- **ASP.NET Core** supports built-in external login providers for
 - Google
 - Facebook
 - Twitter
 - Microsoft

```
builder.Services.AddAuthentication()  
    .AddGoogle(googleOptions => { ... })  
    .AddFacebook(facebookOptions => { ... })  
    .AddTwitter(twitterOptions => { ... })  
    .AddMicrosoftAccount(microsoftOptions => { ... });
```

- Each **External Login provider** has some Developer API
 - You have to configure an application there before using it
 - That application will provide you with credentials
 - Application **ID** + Application **Secret**
- These credentials will be used by the external provider API
 - You authenticate yourself with them, when sending a request
 - They should **not** be stored in the **open world**



External Login Provider Developer API

facebook DEVELOPERS

Search

Documentation Support Blog Apps

Pat Patterson

Settings

BasicAuth DialogAdvanced

Open Graph

Roles

Credits

Insights

Related links

Use Debug Tool

Use Graph API Explorer

See App Timeline View

Promote with an Ad

Translate your App

Delete App

Apps > Force.com Toolkit App v3 > Basic

Force.com Toolkit App v3

App ID: 357898090905558

App Secret: 42835e36d6bf1eb127ec68112b91b72b (reset)

(edit icon)

Basic Info

App Display Name: [?] Force.com Toolkit App v3

App Namespace: [?] fdctkvthree

Contact Email: [?] pat@superpat.com

App Domain: [?] Enter your site domains and press enter

Category: [?] Other Choose a sub-category

Cloud Services

Hosting URL: [?] You have not generated a URL through one of our partners (Get one)

Select how your app integrates with Facebook

Website

Site URL: [?] https://fbtest-developer-edition.na14.force.com/

App on Facebook

I want people to run my app inside Facebook.com.

Configuring Social Accounts (1)

- On the back-end, it is quite simple, and quite clean
- Example: **Facebook**

```
builder.Services.AddAuthentication()  
    .AddFacebook(facebookOptions => {  
        facebookOptions.AppId =  
            configuration["Authentication:Facebook:AppId"];  
        facebookOptions.AppSecret =  
            configuration["Authentication:Facebook:AppSecret"];  
    });
```

- If you use the **default ASP.NET Core Login** page, this will add a **form**

Configuring Social Accounts (2)

WebApplication1 Home About Contact

Log in

Use a local account to log in.

Email

Password

☐ Remember me?

Log in

[Forgot your password?](#)

[Register as a new user](#)

Use another service to log in.


Facebook

Sends **POST** request to
/Identity/Account/ExternalLogin

Button submits a parameter:
name: **provider**
value: **{externalLogin}**

Name	Headers	Preview	Response	Cookies	Timing
<input type="checkbox"/> ExternalLogin?returnUrl=%2F/Identity/Account	▼ Form Data view source view URL encoded				
provider: Facebook					
__RequestVerificationToken: <input type="text"/>					

129 requests | 91.8 KB transferred | Finish: 1.0 min...



JSON Web Tokens

JWT

- **JWT** is a method for representing claims between two parties
 - An open, industry standard – RFC 7519
 - Easy to use, and at the same time – absolutely secured
- When the user successfully **authenticates** (login) using their credentials:
 - A **JSON Web Token** is generated and returned
 - It must be stored (in **local** / **session** storage, **cookies** are also an option)
- Whenever a protected route is accessed, the user agent sends the **JWT**
 - Typically in an **Authorization** header, using the **Bearer** schema

JSON Web Tokens (2)

- **JWT** is absolutely **stateless**, nothing is stored on the server
- Here is an example of an encoded and decoded **JSON Web Token**

The parts of the **token** are separated by **dots**

Encoded

```
eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.  
eyJzdWIiOiIxMjM0NTY3ODkwIiwibmFtZSI6IkpvaG4gRG9lIiwiaWF0IjoxNTE2MzkwMDIyLnQsInR5cCI6IkpXVCJ9.  
Sf1KxwRJSMeKKF2QT4fwpMeJf36P0k6yJV_adQssw5c
```

As any normal auth **JWT** also has an **expiration**

The parts of the **token** are in a strict **order**

The token data does not change the **token format**

Decoded

Header: (algorithm, token type)

```
{  
  "alg": "HS256",  
  "typ": "JWT"  
}
```

Payload: (data)

```
{  
  "sub": "1234567890",  
  "name": "John Doe",  
  "iat": 1516239022  
}
```

Verify Signature

```
HMACSHA256(base64UrlEncode(H...) +  
".", base64UrlEncode(P...), key)
```


JWT Configuration in ASP.NET Core (1)

- **JWT** in **ASP.NET Core** is configured in **Program.cs**
 - Install **Microsoft.AspNetCore.Authentication.JwtBearer**

```
{  
  "JWT": {  
    "ValidAudience": "http://localhost:4200",  
    "ValidIssuer": "http://localhost:61955",  
    "Secret": "super-secret-JWT-key"  
  },  
  ...  
}
```

appsettings.json

```
var auth = builder.Services.AddAuthentication(options =>  
{  
    options.DefaultAuthenticateScheme =  
        JwtBearerDefaults.AuthenticationScheme;  
    options.DefaultChallengeScheme =  
        JwtBearerDefaults.AuthenticationScheme;  
    options.DefaultScheme =  
        JwtBearerDefaults.AuthenticationScheme;  
});  
  
auth.AddJwtBearer(...);  
  
// Configure DI for application services  
builder.Services.AddScoped<IUserService, UserService>();
```

On the
next slide

JWT Configuration in ASP.NET Core (2)

```
auth.AddJwtBearer(options =>
{
    options.SaveToken = true;
    options.RequireHttpsMetadata = false;
    options.TokenValidationParameters = new TokenValidationParameters()
    {
        ValidateIssuer = true,
        ValidateAudience = true,
        ValidAudience = builder.Configuration["JWT:ValidAudience"],
        ValidIssuer = builder.Configuration["JWT:ValidIssuer"],
        IssuerSigningKey =
            new
SymmetricSecurityKey(Encoding.UTF8.GetBytes(builder.Configuration["JWT:Secret"]))
    };
});

...

// Don't forget to add app.UseAuthentication(); and app.UseAuthorization();
```

- The controller action (**Endpoint**) is kept "**thin**" to a maximum


```
[ApiController]
[Route("/api/[controller]")]
public class UsersController : ControllerBase
{
    private IUserService userService;

    public UsersController(IUserService userService) => this.userService = userService;

    [HttpPost("login")]
    public IActionResult Login([FromBody] LoginUserBindingModel loginUser)
    {
        var user = this.userService.Authenticate(loginUser.Username, loginUser.Password);

        if (user == null)
            return BadRequest(new { message = "Username or password is incorrect." });

        var tokenString = this.userService.GenerateJSONWebToken(user);
        return Ok(new { token = tokenString });
    }
}
```



Using services

- Configurations for **JWT** are injected into a service class constructor

```
public class UserService : IUserService
{
    private AppDbContext context;
    private UserManager<IdentityUser> userManager;
    private readonly IConfiguration configuration;

    public UserService(AppDbContext context, IConfiguration configuration)
    {
        this.context = context;
        this.configuration = configuration;
        ...
    }

    public IdentityUser Authenticate(string username, string password) { ... }
    public string GenerateJSONWebToken(IdentityUser user) { ... }
}
```

On the
next slides

JWT in ASP.NET Core in Services (3)

```
public IdentityUser Authenticate(string username, string password)
{
    var user = this.userManager.FindByNameAsync(username).Result;
    if (user != null && this.userManager.CheckPasswordAsync(user, password).Result)
        return user;

    return null;
}

public string GenerateJSONWebToken(IdentityUser user)
{
    var authClaims = new List<Claim>
    {
        new Claim(ClaimTypes.Name, user.UserName),
        new Claim(JwtRegisteredClaimNames.Jti, Guid.NewGuid().ToString()),
    };

    // Continues on the next slide...
```

JWT in ASP.NET Core in Services (4)

```
string jwtSecret = this.configuration["JWT:Secret"];
byte[] jwtSecretBytes = Encoding.UTF8.GetBytes(jwtSecret);
var authSigningKey = new SymmetricSecurityKey(jwtSecretBytes);


var token = new JwtSecurityToken(
    issuer: this.configuration["JWT:ValidIssuer"],
    audience: this.configuration["JWT:ValidAudience"],
    expires: DateTime.Now.AddHours(3),
    claims: authClaims,
    signingCredentials:
        new SigningCredentials(authSigningKey, SecurityAlgorithms.HmacSha256));

return new JwtSecurityTokenHandler().WriteToken(token);
}
```

- You can gain **full control** over Identity
- **Claims** == a statement that a user makes about themselves
- **Roles** are required to gain access to a specific resource
- There are different **authentication** types
- **Social Accounts** enable users to sign in with their existing credentials
- **JWT** = method for representing claims between two parties



Questions?



SoftUni Diamond Partners

**SUPER
HOSTING
.BG**



**Coca-Cola HBC
Bulgaria**



POKERSTARS
POKER | CASINO | SPORTS
a Flutter International brand

INDEAVR
Serving the high achievers



AMBITIONED

 **DRAFT
KINGS**



**SOFTWARE
GROUP**

createX



Postbank

Решения за твоето утре




BOSCH

DXC
TECHNOLOGY



SmartIT



- Software University – High-Quality Education, Profession and Job for Software Developers

- softuni.bg, softuni.org

- Software University Foundation

- softuni.foundation

- Software University @ Facebook

- facebook.com/SoftwareUniversity

- Software University Forums

- forum.softuni.bg



- This course (slides, examples, demos, exercises, homework, documents, videos and other assets) is **copyrighted content**
- Unauthorized copy, reproduction or use is illegal
- © SoftUni – <https://softuni.org>
- © Software University – <https://softuni.bg>

