



Stainless Steel 304 (1.4301 = V2A)



Note: RONDEC in sizes 60, 80, 100, and 125 is also available in stainless steel 316L (1.4404 = V4A). Contact customer service for price and availability.

Schluter®-RONDEC								
Length = 2.5 m - 8' 2-1/2"	Stainless steel 304 (1.4301 = V2A) (E)							
H = mm - in.	Profile	\$ / Length	Outside corner, 90°	\$ / Unit	Sink corner 3/8" (10 mm) radius	\$ / Unit	Sink corner 1-1/2" (38 mm) radius	\$ / Unit
4.5 - 3/16	RO 45 E	50.27	EV/RO 45 E	37.16	-	-	-	-
6 - 1/4	RO 60 E	52.32	EV/RO 60 E	37.16	-	-	-	-
7 - 9/32	RO 70 E	54.25	EV/RO 70 E	39.91	-	-	-	-
8 - 5/16	RO 80 E	54.62	EV/RO 80 E	39.91	I2S/RO 80 E/V2A	59.91	ISK/RO 80 E/38	31.20
9 - 11/32	RO 90 E	58.33	EV/RO 90 E	42.86	-	-	-	-
10 - 3/8	RO 100 E	58.65	EV/RO 100 E	42.86	I2S/RO 100 E/V2A	59.91	ISK/RO 100 E/38	31.20
11 - 7/16	RO 110 E	60.56	EV/RO 110 E	44.36	-	-	-	-
12.5 - 1/2	RO 125 E	62.48	EV/RO 125 E	44.36	I2S/RO 125 E/V2A	59.91	ISK/RO 125 E/38	31.20
15 - 9/16	RO 150 E	70.77	EV/RO 150 E	45.39	-	-	-	-

Length = 2.5 m - 8' 2-1/2"	Brushed stainless steel 304 (1.4301 = V2A) (EB)		Die cast metal with stainless steel appearance		
H = mm - in.	End cap	\$ / Unit	Outside corner, 90°	Inside corner, 90°	\$ / Unit
6 - 1/4	-	-	ED/RO 60 E	ID/RO 60 E	8.79
8 - 5/16	EK/RO 80 EB	5.33	ED/RO 80 E	ID/RO 80 E	8.79
10 - 3/8	EK/RO 100 EB	5.33	ED/RO 100 E	ID/RO 100 E	8.79
12.5 - 1/2	EK/RO 125 EB	5.33	ED/RO 125 E	ID/RO 125 E	8.79

Length = 2.5 m - 8' 2-1/2"	Brushed stainless steel 304 (1.4301 = V2A) (EB)							
H = mm - in.	Profile	\$ / Length	Outside corner, 90°	\$ / Unit	Sink corner 3/8" (10 mm) radius	\$ / Unit	End cap	\$ / Unit
6 - 1/4	RO 60 EB	80.24	EV/RO 60 EB	45.07	-	-	-	-
7 - 9/32	RO 70 EB	81.81	EV/RO 70 EB	45.07	-	-	-	-
8 - 5/16	RO 80 EB	83.75	EV/RO 80 EB	45.07	I2S/RO 80 EB/V2A	59.91	EK/RO 80 EB	5.33
9 - 11/32	RO 90 EB	85.43	EV/RO 90 EB	45.07	-	-	-	-
10 - 3/8	RO 100 EB	87.47	EV/RO 100 EB	52.01	I2S/RO 100 EB/V2A	59.91	EK/RO 100 EB	5.33
11 - 7/16	RO 110 EB	89.21	EV/RO 110 EB	52.01	-	-	-	-
12.5 - 1/2	RO 125 EB	91.28	EV/RO 125 EB	52.01	I2S/RO 125 EB/V2A	59.91	EK/RO 125 EB	5.33
15 - 9/16	RO 150 EB	100.44	EV/RO 150 EB	55.11	-	-	-	-

Stainless steel 304 (1.4301 = V2A) (E)		
H = mm - in.	Connector	\$ / Unit
6 - 1/4	V/RO 60 E	6.99
8 - 5/16	V/RO 80 E	6.99
10 - 3/8	V/RO 100 E	6.99
11 - 7/16	V/RO 110 E	6.99
12.5 - 1/2	V/RO 125 E	6.99



Brass

**Schluter®-RONDEC**

Length = 2.5 m - 8' 2-1/2"		Chrome-plated solid brass (MC)*	Aluminum with polished chrome finish		
H = mm - in.	Profile	\$ / Length	Outside corner, 90°	Inside corner, 90°	\$ / Unit
6 - 1/4	RO 60 MC	137.55	EV/RO 60 ACG	IV/RO 60 ACG	10.41
8 - 5/16	RO 80 MC	145.44	EV/RO 80 ACG	IV/RO 80 ACG	10.41
10 - 3/8	RO 100 MC	151.69	EV/RO 100 ACG	IV/RO 100 ACG	10.41
12.5 - 1/2	RO 125 MC	159.80	EV/RO 125 ACG	IV/RO 125 ACG	10.41

Anodized Aluminum

**Schluter®-RONDEC**

Length = 2.5 m - 8' 2-1/2"		Satin anodized aluminum (AE)					
H = mm - in.	Profile	\$ / Length	Outside corner, 90°	Inside corner, 90°	\$ / Unit	Connector	\$ / Unit
6 - 1/4	RO 60 AE	19.90	EV/RO 60 AE	IV/RO 60 AE	8.79	V/RO 60	2.92
8 - 5/16	RO 80 AE	20.76	EV/RO 80 AE	IV/RO 80 AE	8.79	V/RO 80	2.92
10 - 3/8	RO 100 AE	22.42	EV/RO 100 AE	IV/RO 100 AE	8.79	V/RO 100	2.92
12.5 - 1/2	RO 125 AE	25.04	EV/RO 125 AE	IV/RO 125 AE	8.79	V/RO 125	2.92

H = mm - in.	Double-leg outside corner, 90°	Double-leg inside corner, 90°	\$ / Unit
8 - 5/16	E2L/RO 80 AE	I2L/RO 80 AE	18.85
10 - 3/8	E2L/RO 100 AE	I2L/RO 100 AE	18.85
12.5 - 1/2	E2L/RO 125 AE	I2L/RO 125 AE	18.85

Length = 2.5 m - 8' 2-1/2"		Polished chrome anod. alu. (ACG)					
H = mm - in.	Profile	\$ / Length	Outside corner, 90°	Inside corner, 90°	\$ / Unit	Connector	\$ / Unit
6 - 1/4	RO 60 ACG	24.33	EV/RO 60 ACG	IV/RO 60 ACG	10.41	V/RO 60	2.92
8 - 5/16	RO 80 ACG	27.26	EV/RO 80 ACG	IV/RO 80 ACG	10.41	V/RO 80	2.92
10 - 3/8	RO 100 ACG	30.21	EV/RO 100 ACG	IV/RO 100 ACG	10.41	V/RO 100	2.92
12.5 - 1/2	RO 125 ACG	35.35	EV/RO 125 ACG	IV/RO 125 ACG	10.41	V/RO 125	2.92

H = mm - in.	Double-leg outside corner, 90°	Double-leg inside corner, 90°	\$ / Unit
8 - 5/16	E2L/RO 80 ACG	I2L/RO 80 ACG	18.13
10 - 3/8	E2L/RO 100 ACG	I2L/RO 100 ACG	18.13
12.5 - 1/2	E2L/RO 125 ACG	I2L/RO 125 ACG	18.13

Length = 2.5 m - 8' 2-1/2"		Brushed chrome anod. alu. (ACGB)					
H = mm - in.	Profile	\$ / Length	Outside corner, 90°	Inside corner, 90°	\$ / Unit	Connector	\$ / Unit
6 - 1/4	RO 60 ACGB	25.04	EV/RO 60 ACGB	IV/RO 60 ACGB	16.41	V/RO 60	2.92
8 - 5/16	RO 80 ACGB	28.00	EV/RO 80 ACGB	IV/RO 80 ACGB	16.41	V/RO 80	2.92
10 - 3/8	RO 100 ACGB	31.66	EV/RO 100 ACGB	IV/RO 100 ACGB	16.41	V/RO 100	2.92
12.5 - 1/2	RO 125 ACGB	36.84	EV/RO 125 ACGB	IV/RO 125 ACGB	16.41	V/RO 125	2.92

H = mm - in.	Double-leg outside corner, 90°	Double-leg inside corner, 90°	\$ / Unit
8 - 5/16	E2L/RO 80 ACGB	I2L/RO 80 ACGB	22.36
10 - 3/8	E2L/RO 100 ACGB	I2L/RO 100 ACGB	22.36
12.5 - 1/2	E2L/RO 125 ACGB	I2L/RO 125 ACGB	22.36

**Schluter®-RONDEC**

Length = 2.5 m - 8' 2-1/2"	Satin nickel anod. alu. (AT)						
H = mm - in.	Profile	\$ / Length	Outside corner, 90°	Inside corner, 90°	\$ / Unit	Connector	\$ / Unit
6 - 1/4	RO 60 AT	20.37	EV/RO 60 AT	IV/RO 60 AT	8.86	V/RO 60	2.92
8 - 5/16	RO 80 AT	21.75	EV/RO 80 AT	IV/RO 80 AT	8.86	V/RO 80	2.92
10 - 3/8	RO 100 AT	22.73	EV/RO 100 AT	IV/RO 100 AT	8.86	V/RO 100	2.92
12.5 - 1/2	RO 125 AT	25.79	EV/RO 125 AT	IV/RO 125 AT	8.86	V/RO 125	2.92

H = mm - in.	Double-leg outside corner, 90°	Double-leg inside corner, 90°	\$ / Unit
8 - 5/16	E2L/RO 80 AT	I2L/RO 80 AT	18.59
10 - 3/8	E2L/RO 100 AT	I2L/RO 100 AT	18.59
12.5 - 1/2	E2L/RO 125 AT	I2L/RO 125 AT	18.59

Length = 2.5 m - 8' 2-1/2"	Polished nickel anod. alu. (ATG)						
H = mm - in.	Profile	\$ / Length	Outside corner, 90°	Inside corner, 90°	\$ / Unit	Connector	\$ / Unit
6 - 1/4	RO 60 ATG	26.55	EV/RO 60 ATG	IV/RO 60 ATG	10.41	V/RO 60	2.92
8 - 5/16	RO 80 ATG	28.00	EV/RO 80 ATG	IV/RO 80 ATG	10.41	V/RO 80	2.92
10 - 3/8	RO 100 ATG	33.16	EV/RO 100 ATG	IV/RO 100 ATG	10.41	V/RO 100	2.92
12.5 - 1/2	RO 125 ATG	37.57	EV/RO 125 ATG	IV/RO 125 ATG	10.41	V/RO 125	2.92

H = mm - in.	Double-leg outside corner, 90°	Double-leg inside corner, 90°	\$ / Unit
8 - 5/16	E2L/RO 80 ATG	I2L/RO 80 ATG	18.85
10 - 3/8	E2L/RO 100 ATG	I2L/RO 100 ATG	18.85
12.5 - 1/2	E2L/RO 125 ATG	I2L/RO 125 ATG	18.85

Length = 2.5 m - 8' 2-1/2"	Brushed nickel anod. alu. (ATGB)						
H = mm - in.	Profile	\$ / Length	Outside corner, 90°	Inside corner, 90°	\$ / Unit	Connector	\$ / Unit
6 - 1/4	RO 60 ATGB	28.00	EV/RO 60 ATGB	IV/RO 60 ATGB	16.24	V/RO 60	2.92
8 - 5/16	RO 80 ATGB	30.94	EV/RO 80 ATGB	IV/RO 80 ATGB	16.24	V/RO 80	2.92
10 - 3/8	RO 100 ATGB	33.98	EV/RO 100 ATGB	IV/RO 100 ATGB	16.24	V/RO 100	2.92
12.5 - 1/2	RO 125 ATGB	39.41	EV/RO 125 ATGB	IV/RO 125 ATGB	16.24	V/RO 125	2.92

H = mm - in.	Double-leg outside corner, 90°	Double-leg inside corner, 90°	\$ / Unit
8 - 5/16	E2L/RO 80 ATGB	I2L/RO 80 ATGB	23.24
10 - 3/8	E2L/RO 100 ATGB	I2L/RO 100 ATGB	23.24
12.5 - 1/2	E2L/RO 125 ATGB	I2L/RO 125 ATGB	23.24

Length = 2.5 m - 8' 2-1/2"	Satin copper anod. alu. (AK)						
H = mm - in.	Profile	\$ / Length	Outside corner, 90°	Inside corner, 90°	\$ / Unit	Connector	\$ / Unit
6 - 1/4	RO 60 AK	21.37	EV/RO 60 AK	IV/RO 60 AK	8.79	V/RO 60	2.92
8 - 5/16	RO 80 AK	22.83	EV/RO 80 AK	IV/RO 80 AK	8.79	V/RO 80	2.92
10 - 3/8	RO 100 AK	24.30	EV/RO 100 AK	IV/RO 100 AK	8.79	V/RO 100	2.92
12.5 - 1/2	RO 125 AK	25.79	EV/RO 125 AK	IV/RO 125 AK	8.79	V/RO 125	2.92

H = mm - in.	Double-leg outside corner, 90°	Double-leg inside corner, 90°	\$ / Unit
8 - 5/16	E2L/RO 80 AK	I2L/RO 80 AK	18.30
10 - 3/8	E2L/RO 100 AK	I2L/RO 100 AK	18.30
12.5 - 1/2	E2L/RO 125 AK	I2L/RO 125 AK	18.30


Schluter®-RONDEC

Length = 2.5 m - 8' 2-1/2"	Polished copper anod. alu. (AKG)						
H = mm - in.	Profile	\$ / Length	Outside corner, 90°	Inside corner, 90°	\$ / Unit	Connector	\$ / Unit
6 - 1/4	RO 60 AKG	26.55	EV/RO 60 AKG	IV/RO 60 AKG	10.41	V/RO 60	2.92
8 - 5/16	RO 80 AKG	28.00	EV/RO 80 AKG	IV/RO 80 AKG	10.41	V/RO 80	2.92
10 - 3/8	RO 100 AKG	33.16	EV/RO 100 AKG	IV/RO 100 AKG	10.41	V/RO 100	2.92
12.5 - 1/2	RO 125 AKG	37.57	EV/RO 125 AKG	IV/RO 125 AKG	10.41	V/RO 125	2.92

H = mm - in.	Double-leg outside corner, 90°	Double-leg inside corner, 90°	\$ / Unit
8 - 5/16	E2L/RO 80 AKG	I2L/RO 80 AKG	18.66
10 - 3/8	E2L/RO 100 AKG	I2L/RO 100 AKG	18.66
12.5 - 1/2	E2L/RO 125 AKG	I2L/RO 125 AKG	18.66

Length = 2.5 m - 8' 2-1/2"	Brushed copper anod. alu. (AKGB)						
H = mm - in.	Profile	\$ / Length	Outside corner, 90°	Inside corner, 90°	\$ / Unit	Connector	\$ / Unit
6 - 1/4	RO 60 AKGB	28.00	EV/RO 60 AKGB	IV/RO 60 AKGB	16.41	V/RO 60	2.92
8 - 5/16	RO 80 AKGB	30.94	EV/RO 80 AKGB	IV/RO 80 AKGB	16.41	V/RO 80	2.92
10 - 3/8	RO 100 AKGB	34.63	EV/RO 100 AKGB	IV/RO 100 AKGB	16.41	V/RO 100	2.92
12.5 - 1/2	RO 125 AKGB	39.41	EV/RO 125 AKGB	IV/RO 125 AKGB	16.41	V/RO 125	2.92

H = mm - in.	Double-leg outside corner, 90°	Double-leg inside corner, 90°	\$ / Unit
8 - 5/16	E2L/RO 80 AKGB	I2L/RO 80 AKGB	22.78
10 - 3/8	E2L/RO 100 AKGB	I2L/RO 100 AKGB	22.78
12.5 - 1/2	E2L/RO 125 AKGB	I2L/RO 125 AKGB	22.78

Length = 2.5 m - 8' 2-1/2"	Brushed antique bronze anod. alu. (ABGB)						
H = mm - in.	Profile	\$ / Length	Outside corner, 90°	Inside corner, 90°	\$ / Unit	Connector	\$ / Unit
6 - 1/4	RO 60 ABGB	28.00	EV/RO 60 ABGB	IV/RO 60 ABGB	16.41	V/RO 60	2.92
8 - 5/16	RO 80 ABGB	30.94	EV/RO 80 ABGB	IV/RO 80 ABGB	16.41	V/RO 80	2.92
10 - 3/8	RO 100 ABGB	34.63	EV/RO 100 ABGB	IV/RO 100 ABGB	16.41	V/RO 100	2.92
12.5 - 1/2	RO 125 ABGB	39.41	EV/RO 125 ABGB	IV/RO 125 ABGB	16.41	V/RO 125	2.92

H = mm - in.	Double-leg outside corner, 90°	Double-leg inside corner, 90°	\$ / Unit
8 - 5/16	E2L/RO 80 ABGB	I2L/RO 80 ABGB	22.78
10 - 3/8	E2L/RO 100 ABGB	I2L/RO 100 ABGB	22.78
12.5 - 1/2	E2L/RO 125 ABGB	I2L/RO 125 ABGB	22.78

Length = 2.5 m - 8' 2-1/2"	Satin brass anod. alu. (AM)						
H = mm - in.	Profile	\$ / Length	Outside corner, 90°	Inside corner, 90°	\$ / Unit	Connector	\$ / Unit
6 - 1/4	RO 60 AM	21.37	EV/RO 60 AM	IV/RO 60 AM	8.86	V/RO 60	2.92
8 - 5/16	RO 80 AM	24.33	EV/RO 80 AM	IV/RO 80 AM	8.86	V/RO 80	2.92
10 - 3/8	RO 100 AM	27.26	EV/RO 100 AM	IV/RO 100 AM	8.86	V/RO 100	2.92
12.5 - 1/2	RO 125 AM	31.66	EV/RO 125 AM	IV/RO 125 AM	8.86	V/RO 125	2.92

H = mm - in.	Double-leg outside corner, 90°	Double-leg inside corner, 90°	\$ / Unit
8 - 5/16	E2L/RO 80 AM	I2L/RO 80 AM	18.30
10 - 3/8	E2L/RO 100 AM	I2L/RO 100 AM	18.30
12.5 - 1/2	E2L/RO 125 AM	I2L/RO 125 AM	18.30

**Schluter®-RONDEC**

Length = 2.5 m - 8' 2-1/2"	Polished brass anod. alu. (AMG)						
H = mm - in.	Profile	\$ / Length	Outside corner, 90°	Inside corner, 90°	\$ / Unit	Connector	\$ / Unit
6 - 1/4	RO 60 AMG	25.04	EV/RO 60 AMG	IV/RO 60 AMG	10.41	V/RO 60	2.92
8 - 5/16	RO 80 AMG	28.00	EV/RO 80 AMG	IV/RO 80 AMG	10.41	V/RO 80	2.92
10 - 3/8	RO 100 AMG	31.66	EV/RO 100 AMG	IV/RO 100 AMG	10.41	V/RO 100	2.92
12.5 - 1/2	RO 125 AMG	36.10	EV/RO 125 AMG	IV/RO 125 AMG	10.41	V/RO 125	2.92

H = mm - in.	Double-leg outside corner, 90°	Double-leg inside corner, 90°	\$ / Unit
8 - 5/16	E2L/RO 80 AMG	I2L/RO 80 AMG	18.30
10 - 3/8	E2L/RO 100 AMG	I2L/RO 100 AMG	18.30
12.5 - 1/2	E2L/RO 125 AMG	I2L/RO 125 AMG	18.30

Length = 2.5 m - 8' 2-1/2"	Brushed brass anod. alu. (AMGB)						
H = mm - in.	Profile	\$ / Length	Outside corner, 90°	Inside corner, 90°	\$ / Unit	Connector	\$ / Unit
6 - 1/4	RO 60 AMGB	26.52	EV/RO 60 AMGB	IV/RO 60 AMGB	16.71	V/RO 60	2.92
8 - 5/16	RO 80 AMGB	29.43	EV/RO 80 AMGB	IV/RO 80 AMGB	16.71	V/RO 80	2.92
10 - 3/8	RO 100 AMGB	33.16	EV/RO 100 AMGB	IV/RO 100 AMGB	16.71	V/RO 100	2.92
12.5 - 1/2	RO 125 AMGB	37.57	EV/RO 125 AMGB	IV/RO 125 AMGB	16.71	V/RO 125	2.92

H = mm - in.	Double-leg outside corner, 90°	Double-leg inside corner, 90°	\$ / Unit
8 - 5/16	E2L/RO 80 AMGB	I2L/RO 80 AMGB	23.24
10 - 3/8	E2L/RO 100 AMGB	I2L/RO 100 AMGB	23.24
12.5 - 1/2	E2L/RO 125 AMGB	I2L/RO 125 AMGB	23.24

Length = 2.5 m - 8' 2-1/2"	Graphite anod. alu. (AGR)						
H = mm - in.	Profile	\$ / Length	Outside corner, 90°	Inside corner, 90°	\$ / Unit	Connector	\$ / Unit
6 - 1/4	RO 60 AGR	21.80	EV/RO 60 AGR	IV/RO 60 AGR	8.97	V/RO 60	2.92
8 - 5/16	RO 80 AGR	23.30	EV/RO 80 AGR	IV/RO 80 AGR	8.97	V/RO 80	2.92
10 - 3/8	RO 100 AGR	24.81	EV/RO 100 AGR	IV/RO 100 AGR	8.97	V/RO 100	2.92
12.5 - 1/2	RO 125 AGR	26.30	EV/RO 125 AGR	IV/RO 125 AGR	8.97	V/RO 125	2.92

H = mm - in.	Double-leg outside corner, 90°	Double-leg inside corner, 90°	\$ / Unit
8 - 5/16	E2L/RO 80 AGR	I2L/RO 80 AGR	18.66
10 - 3/8	E2L/RO 100 AGR	I2L/RO 100 AGR	18.66
12.5 - 1/2	E2L/RO 125 AGR	I2L/RO 125 AGR	18.66

Length = 2.5 m - 8' 2-1/2"	Bright black anod. alu. (AGSG)						
H = mm - in.	Profile	\$ / Length	Outside corner, 90°	Inside corner, 90°	\$ / Unit	Connector	\$ / Unit
6 - 1/4	RO 60 AGSG	27.06	EV/RO 60 AGSG	IV/RO 60 AGSG	10.94	V/RO 60	2.92
8 - 5/16	RO 80 AGSG	28.54	EV/RO 80 AGSG	IV/RO 80 AGSG	10.94	V/RO 80	2.92
10 - 3/8	RO 100 AGSG	33.80	EV/RO 100 AGSG	IV/RO 100 AGSG	10.94	V/RO 100	2.92
12.5 - 1/2	RO 125 AGSG	38.32	EV/RO 125 AGSG	IV/RO 125 AGSG	10.94	V/RO 125	2.92

H = mm - in.	Double-leg outside corner, 90°	Double-leg inside corner, 90°	\$ / Unit
8 - 5/16	E2L/RO 80 AGSG	I2L/RO 80 AGSG	19.03
10 - 3/8	E2L/RO 100 AGSG	I2L/RO 100 AGSG	19.03
12.5 - 1/2	E2L/RO 125 AGSG	I2L/RO 125 AGSG	19.03


Schluter®-RONDEC

Length = 2.5 m - 8' 2-1/2"	Brushed black anod. alu. (AGSB)						
H = mm - in.	Profile	\$ / Length	Outside corner, 90°	Inside corner, 90°	\$ / Unit	Connector	\$ / Unit
6 - 1/4	RO 60 AGSB	28.00	EV/RO 60 AGSB	IV/RO 60 AGSB	16.55	V/RO 60	2.92
8 - 5/16	RO 80 AGSB	30.94	EV/RO 80 AGSB	IV/RO 80 AGSB	16.55	V/RO 80	2.92
10 - 3/8	RO 100 AGSB	34.63	EV/RO 100 AGSB	IV/RO 100 AGSB	16.55	V/RO 100	2.92
12.5 - 1/2	RO 125 AGSB	38.29	EV/RO 125 AGSB	IV/RO 125 AGSB	16.55	V/RO 125	2.92

H = mm - in.	Double-leg outside corner, 90°	Double-leg inside corner, 90°	\$ / Unit
8 - 5/16	E2L/RO 80 AGSB	I2L/RO 80 AGSB	22.78
10 - 3/8	E2L/RO 100 AGSB	I2L/RO 100 AGSB	22.78
12.5 - 1/2	E2L/RO 125 AGSB	I2L/RO 125 AGSB	22.78

10-foot (3.05 m) RONDEC Profiles – Anodized Aluminum

Length = 3.05 m - 10'	Satin anod. alu. (AE)		Polished chrome anod. alu. (ACG)		Satin nickel anod. alu. (AT)	
H = mm - in.	Profile	\$ / Length	Profile	\$ / Length	Profile	\$ / Length
8 - 5/16	RO 80 AE / 300	25.94	RO 80 ACG / 300	34.10	RO 80 AT / 300	27.17
10 - 3/8	RO 100 AE / 300	28.04	RO 100 ACG / 300	37.76	RO 100 AT / 300	28.41
12.5 - 1/2	RO 125 AE / 300	31.29	RO 125 ACG / 300	44.19	RO 125 AT / 300	32.25

Special shipping conditions apply, see pages 233-234.



RONDEC in brushed chrome (page 50)



Schluter®-TRENDLINE Textured Color-coated Aluminum



Schluter®-RONDEC

Length = 2.5 m - 8' 2-1/2"							
Textured color-coated aluminum (TS)							
H = mm - in.	Profile	\$ / Length	Outside corner, 90°	Inside corner, 90°	\$ / Unit	Connector	\$ / Unit
6 - 1/4	RO 60 + color*	46.05	EV/RO 60 + color*	IV/RO 60 + color*	16.42	V/RO 60	2.92
8 - 5/16	RO 80 + color*	46.99	EV/RO 80 + color*	IV/RO 80 + color*	16.42	V/RO 80	2.92
10 - 3/8	RO 100 + color*	48.51	EV/RO 100 + color*	IV/RO 100 + color*	16.42	V/RO 100	2.92
11 - 7/16	RO 110 + color*	49.06	EV/RO 110 + color*	IV/RO 110 + color*	16.42	V/RO 110	2.92
12.5 - 1/2	RO 125 + color*	49.54	EV/RO 125 + color*	IV/RO 125 + color*	16.42	V/RO 125	2.92

*Color Codes

TSI	TSBG	TSSG	TSC	TSB	TSR	TSOB	TSG	TSLA	TSDA
Ivory	Greige	Stone grey	Cream	Beige	Rustic brown	Bronze	Pewter	Light anthracite	Dark anthracite

* To complete the item number, add the color code (e.g., RO 60 TSC).

Matte White and Matte Black

Length = 2.5 m - 8' 2-1/2"							
Matte color-coated aluminum							
H = mm - in.	Profile	\$ / Length	Outside corner, 90° (die cast)	Inside corner, 90° (die cast)	\$ / Unit	Connector	\$ / Unit
6 - 1/4	RO 60 + color*	36.84	ED/RO 60 + color*	ID/RO 60 + color*	12.75	V/RO 60	2.92
8 - 5/16	RO 80 + color*	37.59	ED/RO 80 + color*	ID/RO 80 + color*	12.75	V/RO 80	2.92
10 - 3/8	RO 100 + color*	38.81	ED/RO 100 + color*	ID/RO 100 + color*	12.75	V/RO 100	2.92
11 - 7/16	RO 110 + color*	39.25	ED/RO 110 + color*	ID/RO 110 + color*	12.75	V/RO 110	2.92
12.5 - 1/2	RO 125 + color*	39.63	ED/RO 125 + color*	ID/RO 125 + color*	12.75	V/RO 125	2.92

*Color Codes

MBW	MGS
Matte white	Matte black

* To complete the item number, add the color code (e.g., RO 60 MGS).

10-foot (3.05 m) RONDEC Profiles – Textured Color-coated Aluminum

Length = 3.05 m - 10'						
Textured color-coated aluminum (TS)			Matte white (MBW)		Matte black (MGS)	
H = mm - in.	Profile	\$ / Length	Profile	\$ / Length	Profile	\$ / Length
6 - 1/4	RO 60 + color* / 300	57.56	RO 60 MBW / 300	46.05	RO 60 MGS / 300	46.05
8 - 5/16	RO 80 + color* / 300	58.74	RO 80 MBW / 300	46.99	RO 80 MGS / 300	46.99
10 - 3/8	RO 100 + color* / 300	60.66	RO 100 MBW / 300	48.51	RO 100 MGS / 300	48.51
11 - 7/16	RO 110 + color* / 300	61.31	RO 110 MBW / 300	49.07	RO 110 MGS / 300	49.07
12.5 - 1/2	RO 125 + color* / 300	61.94	RO 125 MBW / 300	49.54	RO 125 MGS / 300	49.54

Special shipping conditions apply, see pages 233-234.



Color-coated Aluminum



Schluter®-RONDEC

Color-coated aluminum (AC)							
Length = 2.5 m - 8' 2-1/2"	H = mm - in.	Profile	\$ / Length	Outside corner, 90° (die cast)	Inside corner, 90° (die cast)	\$ / Unit	Connector
	6 - 1/4	RO 60 + color*	23.41	ED/RO 60 + color*	ID/RO 60 + color*	5.28	V/RO 60
	8 - 5/16	RO 80 + color*	26.22	ED/RO 80 + color*	ID/RO 80 + color*	5.28	V/RO 80
	10 - 3/8	RO 100 + color*	28.76	ED/RO 100 + color*	ID/RO 100 + color*	5.28	V/RO 100
	12.5 - 1/2	RO 125 + color*	35.94	ED/RO 125 + color*	ID/RO 125 + color*	5.28	V/RO 125

*Color Codes

BW	W	SP	BH	HB	HG	PG	G	GM	SB	GS
Bright white	White	Sand pebble	Bahama	Light beige	Light grey	Classic grey	Grey	Metallic grey	Black brown	Black

* To complete the item number, add the color code (e.g., RO 60 G).

PVC



PVC (P)					
Length = 2.5 m - 8' 2-1/2"	H = mm - in.	Profile	\$ / Length	Outside corner, 90°	Inside corner, 90°
	6 - 1/4	PRO 60 + color*	8.12	E/PRO 60 + color*	I/PRO 60 + color*
	8 - 5/16	PRO 80 + color*	8.55	E/PRO 80 + color*	I/PRO 80 + color*
	10 - 3/8	PRO 100 + color*	9.12	E/PRO 100 + color*	I/PRO 100 + color*
	11 - 7/16	PRO 110 + color*	10.24	E/PRO 110 + color*	I/PRO 110 + color*
	12.5 - 1/2	PRO 125 + color*	11.40	E/PRO 125 + color*	I/PRO 125 + color*

*Color Codes

BW	W	SP	BH	HB	HG	PG	G	GS
Bright white	White	Sand pebble	Bahama	Light beige	Light grey	Classic grey	Grey	Black

* To complete the item number, add the color code (e.g., PRO 60 G).

