

Workflow and architecture patterns for working together 2: Architectures

Jacob Archambault

May 28, 2026

Outline

1 Current challenges and their canonical solutions

Outline

- 1 Current challenges and their canonical solutions
- 2 Branching: theory and statistics
 - Theory
 - Statistics
 - Devops Statistics recapitulation
 - Approximating DevOps metrics in our current setup
 - Velocity
 - Safety
 - Maintenance to value-adding work percentage

Outline

- 1 Current challenges and their canonical solutions
- 2 Branching: theory and statistics
 - Theory
 - Statistics
 - Devops Statistics recapitulation
 - Approximating DevOps metrics in our current setup
 - Velocity
 - Safety
 - Maintenance to value-adding work percentage
- 3 Going forward
 - Team Composition
 - Branching and committing
 - Testing
 - Pull Requests
 - Pipelines

Outline

- 1 Current challenges and their canonical solutions
- 2 Branching: theory and statistics
 - Theory
 - Statistics
 - Devops Statistics recapitulation
 - Approximating DevOps metrics in our current setup
 - Velocity
 - Safety
 - Maintenance to value-adding work percentage
- 3 Going forward
 - Team Composition
 - Branching and committing
 - Testing
 - Pull Requests
 - Pipelines
- 4 Architecture

Challenges

- multiple teams working in the same repository

Challenges

- multiple teams working in the same repository
- lack of direct collaboration, and occasionally trust, between development, operations, and testing

Challenges

- multiple teams working in the same repository
- lack of direct collaboration, and occasionally trust, between development, operations, and testing
- late integration of contributor code

Challenges

- multiple teams working in the same repository
- lack of direct collaboration, and occasionally trust, between development, operations, and testing
- late integration of contributor code
 - feedback delays

Challenges

- multiple teams working in the same repository
- lack of direct collaboration, and occasionally trust, between development, operations, and testing
- late integration of contributor code
 - feedback delays
 - merge conflict regressions

Challenges

- multiple teams working in the same repository
- lack of direct collaboration, and occasionally trust, between development, operations, and testing
- late integration of contributor code
 - feedback delays
 - merge conflict regressions
 - sunk costs fallacy risks

Challenges

- multiple teams working in the same repository
- lack of direct collaboration, and occasionally trust, between development, operations, and testing
- late integration of contributor code
 - feedback delays
 - merge conflict regressions
 - sunk costs fallacy risks
- coupling of all services at the database layer

Challenges

- multiple teams working in the same repository
- lack of direct collaboration, and occasionally trust, between development, operations, and testing
- late integration of contributor code
 - feedback delays
 - merge conflict regressions
 - sunk costs fallacy risks
- coupling of all services at the database layer
 - high storage costs

Challenges

- multiple teams working in the same repository
- lack of direct collaboration, and occasionally trust, between development, operations, and testing
- late integration of contributor code
 - feedback delays
 - merge conflict regressions
 - sunk costs fallacy risks
- coupling of all services at the database layer
 - high storage costs
 - single point of failure risk

Challenges

- multiple teams working in the same repository
- lack of direct collaboration, and occasionally trust, between development, operations, and testing
- late integration of contributor code
 - feedback delays
 - merge conflict regressions
 - sunk costs fallacy risks
- coupling of all services at the database layer
 - high storage costs
 - single point of failure risk
 - risk of cross-project interference

Challenges

- multiple teams working in the same repository
- lack of direct collaboration, and occasionally trust, between development, operations, and testing
- late integration of contributor code
 - feedback delays
 - merge conflict regressions
 - sunk costs fallacy risks
- coupling of all services at the database layer
 - high storage costs
 - single point of failure risk
 - risk of cross-project interference

Canonical solutions to these challenges

- multiple teams $\rightarrow$ inverse Conway maneuver

Canonical solutions to these challenges

- multiple teams → inverse Conway maneuver
- collaboration → business stream-aligned teams over activity oriented teams

Canonical solutions to these challenges

- multiple teams → inverse Conway maneuver
- collaboration → business stream-aligned teams over activity oriented teams
- late integration → adopting a true continuous integration workflow

Canonical solutions to these challenges

- multiple teams → inverse Conway maneuver
- collaboration → business stream-aligned teams over activity oriented teams
- late integration → adopting a true continuous integration workflow
- database coupling → Bezos API mandate/“Microservices”

Canonical solutions to these challenges

- multiple teams → inverse Conway maneuver
- collaboration → business stream-aligned teams over activity oriented teams
- late integration → adopting a true continuous integration workflow
- database coupling → Bezos API mandate/“Microservices”

Outline

- 1 Current challenges and their canonical solutions
- 2 Branching: theory and statistics
 - Theory
 - Statistics
 - Devops Statistics recapitulation
 - Approximating DevOps metrics in our current setup
 - Velocity
 - Safety
 - Maintenance to value-adding work percentage
- 3 Going forward
 - Team Composition
 - Branching and committing
 - Testing
 - Pull Requests
 - Pipelines
- 4 Architecture

A naive probability theory for merge consistency: isolated commits

- $C = \{a, b, c\}$

A naive probability theory for merge consistency: isolated commits

- $C = \{a, b, c\}$
- $\mathcal{P}(C) = \{\{\emptyset\}, \{a\}, \{b\}, \{c\}, \{a, b\}, \{a, c\}, \{b, c\}, \{a, b, c\}\}$

A naive probability theory for merge consistency: isolated commits

- $C = \{a, b, c\}$
- $\mathcal{P}(C) = \{\{\emptyset\}, \{a\}, \{b\}, \{c\}, \{a, b\}, \{a, c\}, \{b, c\}, \{a, b, c\}\}$
- $P(\text{no conflicts}) = \mathcal{P}(\emptyset) = \frac{1}{8} = 12.5\%$

A naive probability theory for merge consistency: isolated commits

- $C = \{a, b, c\}$
- $\mathcal{P}(C) = \{\{\emptyset\}, \{a\}, \{b\}, \{c\}, \{a, b\}, \{a, c\}, \{b, c\}, \{a, b, c\}\}$
- $P(\text{no conflicts}) = \mathcal{P}(\emptyset) = \frac{1}{8} = 12.5\%$
- $P(\text{no conflicts}) = \frac{1}{2^n}$ where $|C| = n$

A naive probability theory for merge consistency: isolated commits

- $C = \{a, b, c\}$
- $\mathcal{P}(C) = \{\{\emptyset\}, \{a\}, \{b\}, \{c\}, \{a, b\}, \{a, c\}, \{b, c\}, \{a, b, c\}\}$
- $P(\text{no conflicts}) = \mathcal{P}(\emptyset) = \frac{1}{8} = 12.5\%$
- $P(\text{no conflicts}) = \frac{1}{2^n}$ where $|C| = n$
 - $P(\text{no conflicts}) < 10\%$ where $n \geq 4$

A naive probability theory for merge consistency: isolated commits

- $C = \{a, b, c\}$
- $\mathcal{P}(C) = \{\{\emptyset\}, \{a\}, \{b\}, \{c\}, \{a, b\}, \{a, c\}, \{b, c\}, \{a, b, c\}\}$
- $P(\text{no conflicts}) = \mathcal{P}(\emptyset) = \frac{1}{8} = 12.5\%$
- $P(\text{no conflicts}) = \frac{1}{2^n}$ where $|C| = n$
 - $P(\text{no conflicts}) < 10\%$ where $n \geq 4$
 - $P(\text{no conflicts}) < 1\%$ where $n \geq 7$

A naive probability theory for merge consistency: isolated commits

- $C = \{a, b, c\}$
- $\mathcal{P}(C) = \{\{\emptyset\}, \{a\}, \{b\}, \{c\}, \{a, b\}, \{a, c\}, \{b, c\}, \{a, b, c\}\}$
- $P(\text{no conflicts}) = \mathcal{P}(\emptyset) = \frac{1}{8} = 12.5\%$
- $P(\text{no conflicts}) = \frac{1}{2^n}$ where $|C| = n$
 - $P(\text{no conflicts}) < 10\%$ where $n \geq 4$
 - $P(\text{no conflicts}) < 1\%$ where $n \geq 7$

A naive probability theory for merge consistency: modeling branches as sets of commits

- $A = A_1 \sqcup A_2 \sqcup A_3$ where $A_1 = \{a\}$, $A_2 = \{b, c\}$, $A_3 = \{d, e\}$

A naive probability theory for merge consistency: modeling branches as sets of commits

- $A = A_1 \sqcup A_2 \sqcup A_3$ where $A_1 = \{a\}$, $A_2 = \{b, c\}$, $A_3 = \{d, e\}$
- Assume $A_1 \cdots A_3$ are known good sets of commits. Then $P(\text{no conflicts}(A)) =$ probability of selecting the null set from the set containing both the null set and all remaining unchecked potential conflict sets

A naive probability theory for merge consistency: modeling branches as sets of commits

- $A = A_1 \sqcup A_2 \sqcup A_3$ where $A_1 = \{a\}$, $A_2 = \{b, c\}$, $A_3 = \{d, e\}$
- Assume $A_1 \cdots A_3$ are known good sets of commits. Then $P(\text{no conflicts}(A))$ = probability of selecting the null set from the set containing both the null set and all remaining unchecked potential conflict sets
 - $= \frac{1}{2^n - (2^{n_1} - 1) - (2^{n_2} - 1) - (2^{n_3} - 1)}$ where $n = |A|$ and $n_i = |A_i|$

A naive probability theory for merge consistency: modeling branches as sets of commits

- $A = A_1 \sqcup A_2 \sqcup A_3$ where $A_1 = \{a\}$, $A_2 = \{b, c\}$, $A_3 = \{d, e\}$
- Assume $A_1 \cdots A_3$ are known good sets of commits. Then $P(\text{no conflicts}(A))$ = probability of selecting the null set from the set containing both the null set and all remaining unchecked potential conflict sets
 - $= \frac{1}{2^n - (2^{n_1} - 1) - (2^{n_2} - 1) - (2^{n_3} - 1)}$ where $n = |A|$ and $n_i = |A_i|$
 - $= \frac{1}{2^n - 2^{n_1} - 2^{n_2} - 2^{n_3} + 3}$

A naive probability theory for merge consistency: modeling branches as sets of commits

- $A = A_1 \sqcup A_2 \sqcup A_3$ where $A_1 = \{a\}$, $A_2 = \{b, c\}$, $A_3 = \{d, e\}$
- Assume $A_1 \cdots A_3$ are known good sets of commits. Then $P(\text{no conflicts}(A))$ = probability of selecting the null set from the set containing both the null set and all remaining unchecked potential conflict sets
 - $= \frac{1}{2^n - (2^{n_1} - 1) - (2^{n_2} - 1) - (2^{n_3} - 1)}$ where $n = |A|$ and $n_i = |A_i|$
 - $= \frac{1}{2^n - 2^{n_1} - 2^{n_2} - 2^{n_3} + 3}$
 - $= \frac{1}{2^5 - 2^1 - 2^2 - 2^2 + 3}$

A naive probability theory for merge consistency: modeling branches as sets of commits

- $A = A_1 \sqcup A_2 \sqcup A_3$ where $A_1 = \{a\}$, $A_2 = \{b, c\}$, $A_3 = \{d, e\}$
- Assume $A_1 \cdots A_3$ are known good sets of commits. Then $P(\text{no conflicts}(A))$ = probability of selecting the null set from the set containing both the null set and all remaining unchecked potential conflict sets

- $= \frac{1}{2^n - (2^{n_1} - 1) - (2^{n_2} - 1) - (2^{n_3} - 1)}$ where $n = |A|$ and $n_i = |A_i|$
- $= \frac{1}{2^n - 2^{n_1} - 2^{n_2} - 2^{n_3} + 3}$
- $= \frac{1}{2^5 - 2^1 - 2^2 - 2^2 + 3}$
- $= \frac{1}{32 - 2 - 4 - 4 + 3}$

A naive probability theory for merge consistency: modeling branches as sets of commits

- $A = A_1 \sqcup A_2 \sqcup A_3$ where $A_1 = \{a\}$, $A_2 = \{b, c\}$, $A_3 = \{d, e\}$
- Assume $A_1 \cdots A_3$ are known good sets of commits. Then $P(\text{no conflicts}(A))$ = probability of selecting the null set from the set containing both the null set and all remaining unchecked potential conflict sets
 - $= \frac{1}{2^n - (2^{n_1} - 1) - (2^{n_2} - 1) - (2^{n_3} - 1)}$ where $n = |A|$ and $n_i = |A_i|$
 - $= \frac{1}{2^n - 2^{n_1} - 2^{n_2} - 2^{n_3} + 3}$
 - $= \frac{1}{2^5 - 2^1 - 2^2 - 2^2 + 3}$
 - $= \frac{1}{32 - 2 - 4 - 4 + 3}$
 - $= \frac{1}{32 - 7}$

A naive probability theory for merge consistency: modeling branches as sets of commits

- $A = A_1 \sqcup A_2 \sqcup A_3$ where $A_1 = \{a\}$, $A_2 = \{b, c\}$, $A_3 = \{d, e\}$
- Assume $A_1 \cdots A_3$ are known good sets of commits. Then $P(\text{no conflicts}(A))$ = probability of selecting the null set from the set containing both the null set and all remaining unchecked potential conflict sets

- $= \frac{1}{2^n - (2^{n_1} - 1) - (2^{n_2} - 1) - (2^{n_3} - 1)}$ where $n = |A|$ and $n_i = |A_i|$
- $= \frac{1}{2^n - 2^{n_1} - 2^{n_2} - 2^{n_3} + 3}$
- $= \frac{1}{2^5 - 2^1 - 2^2 - 2^2 + 3}$
- $= \frac{1}{32 - 2 - 4 - 4 + 3}$
- $= \frac{1}{32 - 7}$
- $= \frac{1}{25}$

A naive probability theory for merge consistency: modeling branches as sets of commits

- $A = A_1 \sqcup A_2 \sqcup A_3$ where $A_1 = \{a\}$, $A_2 = \{b, c\}$, $A_3 = \{d, e\}$
- Assume $A_1 \cdots A_3$ are known good sets of commits. Then $P(\text{no conflicts}(A))$ = probability of selecting the null set from the set containing both the null set and all remaining unchecked potential conflict sets

$$\begin{aligned} \bullet &= \frac{1}{2^n - (2^{n_1} - 1) - (2^{n_2} - 1) - (2^{n_3} - 1)} \text{ where } n = |A| \text{ and } n_i = |A_i| \\ \bullet &= \frac{1}{2^n - 2^{n_1} - 2^{n_2} - 2^{n_3} + 3} \\ \bullet &= \frac{1}{2^5 - 2^1 - 2^2 - 2^2 + 3} \\ \bullet &= \frac{1}{32 - 2 - 4 - 4 + 3} \\ \bullet &= \frac{1}{32 - 7} \\ \bullet &= \frac{1}{25} \\ \bullet &= 4\% \end{aligned}$$

A naive probability theory for merge consistency: modeling branches as sets of commits

- $A = A_1 \sqcup A_2 \sqcup A_3$ where $A_1 = \{a\}$, $A_2 = \{b, c\}$, $A_3 = \{d, e\}$
- Assume $A_1 \cdots A_3$ are known good sets of commits. Then $P(\text{no conflicts}(A))$ = probability of selecting the null set from the set containing both the null set and all remaining unchecked potential conflict sets

$$\begin{aligned} \bullet &= \frac{1}{2^n - (2^{n_1} - 1) - (2^{n_2} - 1) - (2^{n_3} - 1)} \text{ where } n = |A| \text{ and } n_i = |A_i| \\ \bullet &= \frac{1}{2^n - 2^{n_1} - 2^{n_2} - 2^{n_3} + 3} \\ \bullet &= \frac{1}{2^5 - 2^1 - 2^2 - 2^2 + 3} \\ \bullet &= \frac{1}{32 - 2 - 4 - 4 + 3} \\ \bullet &= \frac{1}{32 - 7} \\ \bullet &= \frac{1}{25} \\ \bullet &= 4\% \end{aligned}$$

A naive probability theory for merge consistency: general definition for distinct branches diverging from a common ancestor

- Let A be the set of unmerged commits across k distinct branches $A_1 \cdots A_k$, where $A = A_1 \sqcup A_2 \sqcup \cdots \sqcup A_k$, $n = |A|$, and $n_i = |A_i|$ for $1 \leq i \leq k$. Then

A naive probability theory for merge consistency: general definition for distinct branches diverging from a common ancestor

- Let A be the set of unmerged commits across k distinct branches $A_1 \cdots A_k$, where $A = A_1 \sqcup A_2 \sqcup \cdots \sqcup A_k$, $n = |A|$, and $n_i = |A_i|$ for $1 \leq i \leq k$. Then

$$P(\text{no conflicts}) = \frac{1}{2^n - (\sum_{i=1}^k 2^{n_i}) + k}$$

Outline

- 1 Current challenges and their canonical solutions
- 2 Branching: theory and statistics
 - Theory
 - Statistics
 - Devops Statistics recapitulation
 - Approximating DevOps metrics in our current setup
 - Velocity
 - Safety
 - Maintenance to value-adding work percentage
- 3 Going forward
 - Team Composition
 - Branching and committing
 - Testing
 - Pull Requests
 - Pipelines
- 4 Architecture

The State of DevOps Report: throughput metrics

- lead time for changes

The State of DevOps Report: throughput metrics

- lead time for changes
- deployment frequency

The State of DevOps Report: stability metrics

- change failure rate

The State of DevOps Report: stability metrics

- change failure rate
- mean time to restore

The State of DevOps Report: results

'Astonishingly, these results demonstrate that there is no trade-off between improving performance and achieving higher levels of stability and quality. Rather, high performers do better at all of these measures. This is precisely what the Agile and Lean movements predict, but much dogma in our industry still rests on the false assumption that moving faster means trading off against other performance goals, rather than enabling and reinforcing them.'
- Nicole Forsgren, Jez Humble, and Gene Kim, Accelerate (2017), p. 14

The State of DevOps Report: results

When compared to low performers, elite performers realize

127x

faster lead
time

182x

more
deployments
per year

8x

lower change
failure rate

2293x

faster failed
deployment
recovery times

- 2024 State of DevOps Report

Approximating DevOps metrics in our current environment

- deployment frequency → GitHub Actions run count

Approximating DevOps metrics in our current environment

- deployment frequency → GitHub Actions run count
- change failure rate → GitHub Actions pipeline failure rate

Approximating DevOps metrics in our current environment

- deployment frequency → GitHub Actions run count
- change failure rate → GitHub Actions pipeline failure rate
- mean time to restore → percentage of merge commits to value-adding commits

Approximating DevOps metrics in our current environment

- deployment frequency → GitHub Actions run count
- change failure rate → GitHub Actions pipeline failure rate
- mean time to restore → percentage of merge commits to value-adding commits

Velocity metrics

Branch	Runs	Earliest run
NG_Claims_837D_COB	74	23 Mar
PEDI-35120_837D_COB	85	15 Apr
Either COB branch	159	23 Mar
All other branches	123	23 Mar
	72	15 Apr
	266	21 Jan

- compare total commits across team branch vs. others
- compare time to merge across SpecFlow branches vs. others
- compare passing to failing pipeline runs across team branch vs. others, for both simulation pipeline and unit test pipeline
- compare non-merge commits to non-PR merge commits across team branch vs. others (this represents percentage of value-adding work to maintenance work) (`git log --oneline --merges | grep -iv`

“merge pull request” | wc -l)

Outline

- 1 Current challenges and their canonical solutions
- 2 Branching: theory and statistics
 - Theory
 - Statistics
 - Devops Statistics recapitulation
 - Approximating DevOps metrics in our current setup
 - Velocity
 - Safety
 - Maintenance to value-adding work percentage
- 3 Going forward
 - Team Composition
 - Branching and committing
 - Testing
 - Pull Requests
 - Pipelines

Team composition

- all teams working in same git repository are in the same daily scrum

Team composition

- all teams working in same git repository are in the same daily scrum
- each team in the above sense has its own Microsoft Teams chat with only its own contributors in it

Team composition

- all teams working in same git repository are in the same daily scrum
- each team in the above sense has its own Microsoft Teams chat with only its own contributors in it
- these teams are *stream-aligned*, i.e., they focus on a particular business area (in our case, either a transaction type or a closely related set of transaction types)

Team composition

- all teams working in same git repository are in the same daily scrum
- each team in the above sense has its own Microsoft Teams chat with only its own contributors in it
- these teams are *stream-aligned*, i.e., they focus on a particular business area (in our case, either a transaction type or a closely related set of transaction types)
- these teams are *autonomous*, i.e., they can move work forward without requiring outside assistance from another team

Team composition

- all teams working in same git repository are in the same daily scrum
- each team in the above sense has its own Microsoft Teams chat with only its own contributors in it
- these teams are *stream-aligned*, i.e., they focus on a particular business area (in our case, either a transaction type or a closely related set of transaction types)
- these teams are *autonomous*, i.e., they can move work forward without requiring outside assistance from another team

Team composition: enabling teams

- Strategy will be rolled out first for claims, then reimbursements, then other transactions

Team composition: enabling teams

- Strategy will be rolled out first for claims, then reimbursements, then other transactions
- the 837 COB team will serve as an enabling team for the new branching strategy

Team composition: enabling teams

- Strategy will be rolled out first for claims, then reimbursements, then other transactions
- the 837 COB team will serve as an enabling team for the new branching strategy

Outline

- 1 Current challenges and their canonical solutions
- 2 Branching: theory and statistics
 - Theory
 - Statistics
 - Devops Statistics recapitulation
 - Approximating DevOps metrics in our current setup
 - Velocity
 - Safety
 - Maintenance to value-adding work percentage
- 3 Going forward
 - Team Composition
 - Branching and committing
 - Testing
 - Pull Requests
 - Pipelines
- 4 Architecture

Branching and committing

- all commit work done by a given team, by both developers and testers, is committed directly to the same shared branch

Branching and committing

- all commit work done by a given team, by both developers and testers, is committed directly to the same shared branch
- every commit is pushed to origin after passing local testing

Branching and committing

- all commit work done by a given team, by both developers and testers, is committed directly to the same shared branch
- every commit is pushed to origin after passing local testing
- every git commit message begins with a Jira ticket number

Branching and committing

- all commit work done by a given team, by both developers and testers, is committed directly to the same shared branch
- every commit is pushed to origin after passing local testing
- every git commit message begins with a Jira ticket number

Outline

- 1 Current challenges and their canonical solutions
- 2 Branching: theory and statistics
 - Theory
 - Statistics
 - Devops Statistics recapitulation
 - Approximating DevOps metrics in our current setup
 - Velocity
 - Safety
 - Maintenance to value-adding work percentage
- 3 Going forward
 - Team Composition
 - Branching and committing
 - Testing
 - Pull Requests
 - Pipelines
- 4 Architecture

- Every change is tested by the test suite locally before committing

- tests are written against new code as that code is being written

Outline

- 1 Current challenges and their canonical solutions
- 2 Branching: theory and statistics
 - Theory
 - Statistics
 - Devops Statistics recapitulation
 - Approximating DevOps metrics in our current setup
 - Velocity
 - Safety
 - Maintenance to value-adding work percentage
- 3 Going forward
 - Team Composition
 - Branching and committing
 - Testing
 - Pull Requests
 - Pipelines
- 4 Architecture

- daily PRs - stacked PRs

Outline

- 1 Current challenges and their canonical solutions
- 2 Branching: theory and statistics
 - Theory
 - Statistics
 - Devops Statistics recapitulation
 - Approximating DevOps metrics in our current setup
 - Velocity
 - Safety
 - Maintenance to value-adding work percentage
- 3 **Going forward**
 - Team Composition
 - Branching and committing
 - Testing
 - Pull Requests
 - **Pipelines**
- 4 **Architecture**

- pipeline is definitive for deployment - daily stale branch job

Outline

- 1 Current challenges and their canonical solutions
- 2 Branching: theory and statistics
 - Theory
 - Statistics
 - Devops Statistics recapitulation
 - Approximating DevOps metrics in our current setup
 - Velocity
 - Safety
 - Maintenance to value-adding work percentage
- 3 Going forward
 - Team Composition
 - Branching and committing
 - Testing
 - Pull Requests
 - Pipelines
- 4 **Architecture**

Outline

- 1 Current challenges and their canonical solutions
- 2 Branching: theory and statistics
 - Theory
 - Statistics
 - Devops Statistics recapitulation
 - Approximating DevOps metrics in our current setup
 - Velocity
 - Safety
 - Maintenance to value-adding work percentage
- 3 Going forward
 - Team Composition
 - Branching and committing
 - Testing
 - Pull Requests
 - Pipelines
- 4 Architecture

Outline

- 1 Current challenges and their canonical solutions
- 2 Branching: theory and statistics
 - Theory
 - Statistics
 - Devops Statistics recapitulation
 - Approximating DevOps metrics in our current setup
 - Velocity
 - Safety
 - Maintenance to value-adding work percentage
- 3 Going forward
 - Team Composition
 - Branching and committing
 - Testing
 - Pull Requests
 - Pipelines
- 4 Architecture