


## 4. Algorithm Analysis

- Analysis of Algorithms and Data Structures
- Calculate the execution costs for non-recursive algorithms
- The big-Oh notation.
- Reasonable vs. Unreasonable Algorithms


## Analysis of Algorithms

- $O()$  Analysis of Algorithms and Data Structures
- Reasonable vs. Unreasonable Algorithms
- Using  $O()$  Analysis in Design



## Running Time

- ◆ The running time of an algorithm varies with the input and typically grows with the input size
- ◆ Average case difficult to determine
- ◆ We focus on the worst case running time
  - Easier to analyze
  - Crucial to applications such as games, finance and robotics




Analysis of Algorithm

3

## Experimental Studies

- ◆ Write a program implementing the algorithm
- ◆ Run the program with inputs of varying size and composition
- ◆ Use a function like `ctime()` to get an accurate measure of the actual running time
- ◆ Plot the results



Analysis of Algorithm

4

## Limitations of Experiments

- ◆ It is necessary to implement the algorithm, which may be difficult.
- ◆ Results may not be indicative of the running time on other inputs not included in the experiment.
- ◆ In order to compare two algorithms, the same hardware and software environments must be used.

Analysis of Algorithm

5

## Theoretical Analysis

- ◆ Uses a high-level description of the algorithm instead of an implementation
- ◆ Takes into account all possible inputs
- ◆ Allows us to evaluate the speed of an algorithm independent of the hardware/software environment

Analysis of Algorithm

6

## Pseudocode

- ◆ High-level description of an algorithm
- ◆ Less detailed than a program
- ◆ Preferred notation for describing algorithms
- ◆ Hides program design issues
- ◆ A language that is made up for expressing algorithms.
- ◆ Looks like English combined with C, Pascal, whatever suites you...

Example: find the max integer in an array

```
function arrayMax(A, n)
  Input: int A[n]
  Output: maximum element of A

  int currentMax = A[0];
  for (i = 1; i < n; i++){
    if (A[i] > currentMax) {
      currentMax = A[i]
    }
  }
  return currentMax
```

Analysis of Algorithm

7

## Pseudocode Details

- ◆ Control flow
  - if ... then ... [else ...]
  - while ...
  - do ...
  - for ...
  - Indentation and braces
- ◆ Function declaration
 

```
Function fname (arg [, arg...])
  Input: ...
  Output: ...
  body
```
- ◆ function call
 

```
fname(arg [, arg...])
```
- ◆ Return value
 

```
return expression
```
- ◆ Expressions(C-like)
- ◆ Or
 

$n^2$  Superscripts and other mathematical formatting allowed

Analysis of Algorithm

8

## Primitive Operations

- ◆ Basic computations performed by an algorithm
- ◆ Identifiable in pseudocode
- ◆ Largely independent of the programming language
- ◆ Examples:
  - Evaluating an expression
  - Assigning a value to a variable
  - Comparison
  - Calling a method

Analysis of Algorithm

9

## Counting Primitive Operations

- ◆ By inspecting the pseudocode, we can determine the maximum number of primitive operations executed by an algorithm, as a function of the input size

```
function arrayMax(A, n)
  currentMax = A[0];
  for (i = 1; i <= n-1; i++){
    if (A[i] > currentMax) {
      currentMax = A[i];
    }
  }
  return currentMax;
```

Analysis of Algorithm

10

## Analysis of nonrecursive algorithms

- ◆ Identify the input size  $n$
- ◆ Identify the primitive operation
- ◆ Set up a sum for the number of the times the primitive operation is executed
- ◆ Simplify the sum to generate a function of  $n$

Analysis of Algorithm

11

## Example: Set up a sum

Primitive operation: comparison

The sum:  $\sum_{i=1}^{n-1} 1$ , lower limit: initial loop condition  
upper limit: terminating condition  
one comparison each iteration

```
function arrayMax(A, n)
  currentMax = A[0];
  for (i = 1; i <= n-1; i++){
    if (A[i] > currentMax) {
      currentMax = A[i];
    }
  }
  return currentMax;
```

Analysis of Algorithm

12

## Example: Simplify a sum

- $\sum_{i=1}^u 1 = 1 + 1 + \dots + 1 = u - l + 1$
- $\sum_{i=1}^{n-1} 1 = n - 1 - 1 + 1 = n - 1$
- We thus have the number of comparison:  $n - 1$

```
function arrayMax(A, n)
    currentMax = A[0];
    for (i = 1; i <= n-1; i++){
        if (A[i] > currentMax) {
            currentMax = A[i];
        }
    }
    return currentMax;
```

Analysis of Algorithm

13

## Useful formulas of sum

$$\begin{aligned} \sum_{i=1}^u 1 &= 1 + 1 + \dots + 1 = u - l + 1 \\ \sum_{i=1}^u i &= 1 + 2 + \dots + n = n(n+1)/2 \approx n^2/2 \\ \sum_{i=1}^u i^2 &= 1^2 + 2^2 + \dots + n^2 = n(n+1)(2n+1)/6 \\ \sum_{i=1}^u i^k &= 1^k + 2^k + \dots + n^k = n^{k+1}/(k+1) \\ \sum_{i=1}^u a^i &= 1 + a + \dots + a^n = (a^{n+1} - 1)/(a - 1) \text{ for any } a \neq 1 \\ \sum (a_i \pm b_i) &= \sum a_i \pm \sum b_i \quad \sum ca_i = c \sum a_i \\ \sum_{i=l}^u a_i &= \sum_{i=l}^m a_i + \sum_{i=m+1}^u a_i \end{aligned}$$

Analysis of Algorithm

14

## Example:

- ◆ Primitive operation: comparison
- ◆ Set up the sum:  $f(n) = \sum_{i=0}^{n-2} \sum_{j=i+1}^{n-1} 1$

```
function uniqueElement(A, n)
    for (i = 0; i <= n-2; i++){
        for (j = i+1; j <= n-1; j++){
            if (A[i] == A[j]) {
                return false;
            }
        }
    }
    return true;
```

Analysis of Algorithm

15

## Example: simplify the sum

$$\begin{aligned} f(n) &= \sum_{i=0}^{n-2} \sum_{j=i+1}^{n-1} 1 \\ &= \sum_{i=0}^{n-2} (n - 1 - i - 1 + 1) = \sum_{i=0}^{n-2} (n - 1 - i) \\ &= \sum_{i=0}^{n-2} (n - 1) - \sum_{i=0}^{n-2} i \\ &= (n - 1) \sum_{i=0}^{n-2} 1 - (n - 2)(n - 1)/2 \\ &= (n - 1)^2 - (n - 2)(n - 1)/2 = (n - 1)n/2 \approx n^2/2 \end{aligned}$$


```
function uniqueElement(A, n)
    for (i = 0; i <= n-2; i++){
        for (j = i+1; j <= n-1; j++){
            if (A[i] == A[j]) {
                return false;
            }
        }
    }
    return true;
```

Analysis of Algorithm

16

## Big-Oh Notation

- ◆ Given functions  $f(n)$  and  $g(n)$ , we say that  $f(n)$  is  $O(g(n))$  if there are positive constants  $c$  and  $n_0$  such that  $f(n) \leq cg(n)$  for  $n \geq n_0$
- ◆ Example:  $2n + 10$  is  $O(n)$ 
  - $2n + 10 \leq cn$
  - $(c - 2)n \geq 10$
  - $n \geq 10/(c - 2)$
  - Pick  $c = 3$  and  $n_0 = 10$




Analysis of Algorithm

17

## Big-Oh Notation (cont.)

- ◆ Example: the function  $n^2$  is not  $O(n)$ 
  - $n^2 \leq cn$
  - $n \leq c$
  - The above inequality cannot be satisfied since  $c$  must be a constant



Analysis of Algorithm

18

## Big-Oh Rules

- ◆ If  $f(n)$  is a polynomial of degree  $d$ , then  $f(n)$  is  $O(n^d)$ , i.e.,
  1. Drop lower-order terms
  2. Drop constant factors
- ◆ Use the smallest possible class of functions
  - Say " $2n$  is  $O(n)$ " instead of " $2n$  is  $O(n^2)$ "
- ◆ Use the simplest expression of the class
  - Say " $3n + 5$  is  $O(n)$ " instead of " $3n + 5$  is  $O(3n)$ "

Analysis of Algorithm

19

## Big-Oh Algorithm Analysis

- ◆ The analysis of an algorithm determines the running time in big-Oh notation
- ◆ To perform the analysis
  - We find the worst-case number of primitive operations executed as a function of the input size
  - We express this function with big-Oh notation
- ◆ Example:
  - We determine that algorithm *arrayMax* executes at most  $n - 1$  primitive operations
  - We say that algorithm *arrayMax* "runs in  $O(n)$  time"
- ◆ Since constant factors and lower-order terms are eventually dropped anyhow, we can disregard them when counting primitive operations

Analysis of Algorithm

20

## Traversals

- ◆ Traversals involve visiting every node in a collection of size  $n$ .
- ◆ Because we must visit every node, a traversal must be  $O(n)$  for any data structure.
  - If we visit less than  $n$  elements, then it is not a traversal.
  - If we have to process every node during traversal, then  $O(\text{process}) * O(n)$

Analysis of Algorithm

21

## Searching for an Element

Searching involves determining if an element is a member of the collection.

- ◆ Simple/Linear Search:
  - If there is no ordering in the data structure
  - If the ordering is not applicable
- ◆ Binary Search:
  - If the data is ordered or sorted
  - Requires non-linear access to the elements

Analysis of Algorithm

22

## Simple Search


- ◆ Worst case: the element to be found is the  $n^{\text{th}}$  element examined, or an unsuccessful search
- ◆ Simple search must be used for:
  - Sorted or unsorted linked lists
  - Unsorted array
  - Binary tree (to be discussed)

Analysis of Algorithm

23

## Example: Linked List

- ◆ Let's determine if the value 83 is in the collection:



83 Not Found!

Analysis of Algorithm

24

## Big-O of Simple Search

- ◆ The algorithm has to examine every element in the collection
  - To return a false
  - If the element to be found is the  $n^{\text{th}}$  element
- ◆ Thus, simple search is  $O(n)$ .

Analysis of Algorithm

25

## Binary Search

- ◆ We may perform binary search on
  - Sorted arrays
  - Binary search trees
- ◆ Tosses out  $\frac{1}{2}$  the elements at each comparison.

Analysis of Algorithm

26

## Binary Search Example

7	12	42	59	71	86	104	212
---	----	----	----	----	----	-----	-----

Looking for 89

Analysis of Algorithm

27

## Binary Search Example

7	12	42	59	71	86	104	212
---	----	----	----	----	----	-----	-----

Looking for 89

Analysis of Algorithm

28

## Binary Search Example

7	12	42	59	71	86	104	212
---	----	----	----	----	----	-----	-----

Looking for 89

Analysis of Algorithm

29

## Binary Search Example

7	12	42	59	71	86	104	212
---	----	----	----	----	----	-----	-----

89 not found – 3 comparisons

$$3 = \log_2(8)$$

Analysis of Algorithm

30

## Binary Search Big-O

- ◆ An element can be found by comparing and cutting the work in half.
  - We cut work in  $\frac{1}{2}$  each time
  - How many times can we cut in half?
  - $\log_2 n$
- ◆ Thus binary search is  $O(\log n)$ .

Analysis of Algorithm

31

## Recall

$$\log_2 n = k \cdot \log_{10} n$$
$$k = 0.30103\dots$$

$$\text{So: } O(\lg n) = O(\log n)$$

In general:

$$O(C \cdot f(n)) = O(f(n))$$

if  $C$  is a constant

Analysis of Algorithm

32

## Insertion

- ◆ Inserting an element requires two steps:
  - Find the right location
  - Perform the instructions to insert
- ◆ If the data structure in question is **unsorted**, then it is  $O(1)$ 
  - Simply insert to the **front**
  - Simply insert to **end** in the case of an array
  - There is no work to find the right spot and only **constant work to actually insert**.

Analysis of Algorithm

33

## Insert into a Sorted Linked List

Finding the right spot is  $O(n)$

- Recurse/iterate until found

Performing the insertion is  $O(1)$

Total work is  $O(n + 1) = O(n)$

Analysis of Algorithm

34

## Inserting into a Sorted Array

Finding the right spot is  $O(\log n)$

- Binary search on the element to insert

Performing the insertion

- **Shuffle** the existing elements to make room for the new item

Analysis of Algorithm

35

## Shuffling Elements

Note – we must have at least one empty cell

5	12	35	77	101	
---	----	----	----	-----	--

↑  
Insert 29

Analysis of Algorithm

36

## Big-O of Shuffle

Worst case: inserting the smallest number

5	12	35	77	101	
---	----	----	----	-----	--

Would require moving N elements...  
Thus shuffle is  $O(n)$

Analysis of Algorithm

37

## Big-O of Inserting into Sorted Array

Finding the right spot is  $O(\log n)$

Performing the insertion (shuffle) is  $O(n)$

Sequential steps, so add:

Total work is  $O(\log n + n) = O(n)$

Analysis of Algorithm

38

## Two Sorting Algorithms

### ◆ Bubble-sort $O(n^2)$

- Brute-force method of sorting
- Loop inside of a loop

### ◆ Merge-sort $O(n \log n)$

- Divide and conquer approach
- Recursively call, splitting in half
- Merge sorted halves together

Analysis of Algorithm

39

## Bubble-sort Review

Bubble-sort works by comparing and swapping values in a list

1	2	3	4	5	6
77	42	35	12	101	5

Analysis of Algorithm

40

## Bubble-sort Review

Bubble-sort works by comparing and swapping values in a list

1	2	3	4	5	6
42	35	12	77	5	101

Largest value correctly placed

Analysis of Algorithm

41

```
void bubbleSort(int a[], int n){
    int temp;
    for (int i = 1; i < n; i++){
        for (int j = 0; j < n - i; j++){
            if (a[j] > a[j+1]){
                temp = a[j];
                a[j] = a[j+1];
                a[j+1] = temp;
            }
        }
    }
}
```

N-1 { to\_do }

Analysis of Algorithm

42

## Analysis of Bubblesort

- ◆ Step 1. ?
- ◆ Step 2. ?
- ◆ Step 3. ?
- ◆ Step 4. ?

Analysis of Algorithm

43

## Bubblesort Complexity

The complexity is:

$O(?)$

Analysis of Algorithm

44

## $O(n^2)$ Runtime Example

Assume you are sorting 250,000,000 items:

$n = 250,000,000$

$n^2 = 6.25 \times 10^{16}$

If you can do one operation per nanosecond ( $10^{-9}$  sec)

It will take  $6.25 \times 10^7$  seconds


So  $\frac{6.25 \times 10^7}{60 \times 60 \times 24 \times 365}$

$= 1.98 \text{ years}$

Analysis of Algorithm

45

## Mergesort



Analysis of Algorithm

46

## Analysis of Mergesort

### Phase I

- Divide the list of  $n$  numbers into two lists of  $n/2$  numbers
- Divide those lists in half until each list is size 1

$\log n$  steps for this stage.

### Phase II

- Build sorted lists from the decomposed lists
- Merge pairs of lists, doubling the size of the sorted lists each time

$\log n$  steps for this stage.

Analysis of Algorithm

47

## Mergesort Complexity

Each of the  $n$  numerical values is compared or copied during each pass

- The total work for each pass is  $O(n)$ .
- There are a total of  $\log n$  passes

Therefore the complexity is:

$$O(\underbrace{\log n}_{\text{Break apart}} + \underbrace{n * \log n}_{\text{Merging}}) = O(n * \log n)$$

**Break apart**    **Merging**

Analysis of Algorithm

48



## $O(n \log n)$ Runtime Example

Assume same 250,000,000 items

$$\begin{aligned} n \cdot \log(n) &= 250,000,000 \times 8.3 \\ &= 2,099,485,002 \end{aligned}$$

With the same processor as before

**2 seconds**

Analysis of Algorithm

49

## Reasonable vs. Unreasonable

Reasonable algorithms have polynomial factors

- $O(\log n)$
- $O(n)$
- $O(n^K)$  where  $K$  is a constant

Unreasonable algorithms have exponential factors

- $O(2^n)$
- $O(n!)$
- $O(n^n)$

Analysis of Algorithm

50

## Algorithmic Performance Thus Far

◆ Some examples thus far:

- $O(1)$  Insert to front of linked list
- $O(n)$  Simple/Linear Search
- $O(n \log n)$  MergeSort
- $O(n^2)$  BubbleSort

◆ But it could get worse:

- $O(n^5)$ ,  $O(n^{2000})$ , etc.

Analysis of Algorithm

51

## An $O(n^5)$ Example

For  $n = 256$

$$n^5 = 256^5 = 1,100,000,000,000$$

If we had a computer that could execute a million instructions per second...

◆ 1,100,000 seconds = **12.7 days** to complete  
But it could get worse...

Analysis of Algorithm

52

## The Power of Exponents

It is hard to understand the basic principles behind exponential growth. Perhaps it is easier to understand in terms of doubling time. In exponential growth, each time a value doubles the new value is greater than all previous values combined.


Consider the story of the peasant that did a great favor for a king. The king asked how he could repay the peasant. In response, the peasant asked the king to place two pieces of grain on a square of a chess board, and double the amount of grain on each following square (2 on the first, 4 on the second, 8 on the third, 16 on the fourth, and so on). "Sure," says the king thinking that would not require much grain. However, the king does not understand exponential growth.

Analysis of Algorithm

53

## The Power of Exponents

A rich king and a wise peasant...



Analysis of Algorithm

54

## The King has to Pay

Square( $n$ )	Pieces of Grain
1	2
2	4
3	8
4	16
...	
63	9,223,000,000,000,000
64	18,450,000,000,000,000

Analysis of Algorithm

55

## How Bad is $2^n$ ?


- Imagine being able to grow a billion (1,000,000,000) pieces of grain a second... ?
- It would take
  - 585 years to grow enough grain just for the 64<sup>th</sup> chess board square
  - Over a thousand years to fulfill the peasant's request!

Analysis of Algorithm

56

So the King cut off the peasant's head.

## Towers of Hanoi: Solution



Analysis of Algorithm

58

## Towers of Hanoi - Complexity

For 3 rings we have 7 operations.

In general, the cost is

$$2^n - 1 = O(2^n)$$

Each time we increment  $n$ , we double the amount of work.

This grows incredibly fast!

Analysis of Algorithm

59

## Towers of Hanoi ( $2^n$ ) Runtime

For  $n = 64$

$$2^n = 2^{64} = 18,450,000,000,000,000$$

If we had a computer that could execute a million instructions per second...

- It would take 584,000 years to complete

Analysis of Algorithm

60

## Where Does this Leave Us?

- Clearly algorithms have varying runtimes.
- We'd like a way to categorize them:
  - Reasonable, so it may be useful
  - Unreasonable, so why bother running

Analysis of Algorithm

61

## Performance Categories of Algorithms

Polynomial	Sub-linear	$O(\log n)$
	Linear	$O(n)$
	Nearly linear	$O(n \log n)$
	Quadratic	$O(n^2)$
Exponential		$O(2^n)$ $O(n!)$ $O(n^n)$

Analysis of Algorithm

62

## Reasonable vs. Unreasonable

Reasonable algorithms have polynomial factors

- $O(\log n)$
- $O(n)$
- $O(n^K)$  where  $K$  is a constant

Unreasonable algorithms have exponential factors

- $O(2^n)$
- $O(n!)$
- $O(n^n)$

Analysis of Algorithm

63

## Reasonable vs. Unreasonable

Reasonable algorithms

- May be usable depending upon the input size


Unreasonable algorithms

- Are impractical and useful to theorists
  - Demonstrate need for approximate solutions
- Remember we're dealing with large  $n$  (input size)

Analysis of Algorithm

64

## Two Categories of Algorithms



Analysis of Algorithm

65

## Properties of the O notation

- Constant factors may be ignored
  - $\forall k > 0, kf$  is  $O(f)$
- Fastest growing term dominates a sum
  - $f$  is  $O(g)$  and  $h$  is  $O(r)$  then  $f + h$  is  $O(\max(g, r))$   
 eg  $an^4 + \log n$  is  $O(\max(n^4, \log n)) \rightarrow O(n^4)$
- Polynomial's growth rate is determined by leading term
  - If  $f$  is a polynomial of degree  $d$ , then  $f$  is  $O(n^d)$   
 eg  $10n^4 + 5n^6 + n^2$  is  $O(n^6)$

Analysis of Algorithm

66

## Properties of the O notation

- ◆  $f$  is  $O(g)$  is transitive
  - If  $f$  is  $O(g)$  and  $g$  is  $O(h)$  then  $f$  is  $O(h)$
- ◆ Product of upper bounds is upper bound for the product
  - If  $f$  is  $O(g)$  and  $h$  is  $O(r)$  then  $f \cdot h$  is  $O(g \cdot r)$
- ◆ All logarithms grow at the same rate
  - $\log_b n$  is  $O(\log_d n) \forall b, d > 1$

Analysis of Algorithm

67

## Simple Examples:

- ◆ Simple statement sequence
  - $S_1; S_2; \dots; S_k$ 
    - $O(1)$  as long as  $k$  is constant
- ◆ Simple loops
  - for( $i=0; i < n; i++$ ) {  $S$ ; }
  - where  $S$  is  $O(1)$ 
    - Time complexity is  $n \cdot O(1)$  or  $O(n)$
- ◆ Nested loops
  - for( $i=0; i < n; i++$ )  
for( $j=0; j < n; j++$ ) {  $S$ ; }
  - Complexity is  $O(n^2)$

Analysis of Algorithm

68