One Symbolic Interaction Protocol, and What Fits Inside It

Jacob Valdez*

August 2026

Abstract

We define a single interaction protocol—an agent consumes symbolic observations, emits symbolic actions, and receives a reward and a next observation—and ask how much of machine learning fits inside it without distorting the tasks. We show, as an executable check rather than an argument, that language-model pretraining is the special case in which the action is a predictive distribution and the reward is $\log p(x_{t+1} \mid x_{\le t})$: on trained checkpoints and held-out text, the return accumulated through `Environment.step` and the log-likelihood computed by ordinary batched cross-entropy agree to $|\Delta| = 1.9 \times 10^{-5}$ over 512 token positions. Inside this protocol we compare a 13.97M-parameter transformer against *non-neural* learners—no gradients, no learned tensors, tens of discrete parameters, CPU only. A 26-parameter induced world model, fitted in 0.14 s, solves a gridworld 16× larger than any it was fitted on at 1.00 success where the transformer scores 0.00; a parameter-free program synthesizer scores 1.00 on rule families held out of training where a neural specialist scores exactly 0.00. We then build a 180-lesson procedurally generated language curriculum (179 admissible under a floor-and-determinism test) and use it as a measuring instrument: it reveals that symbolic induction is *bimodal* (exact where the capability lies inside its hypothesis space, at chance where it does not) while the neural arm is *uniformly mediocre* (above chance on 10/14 pilot lessons, master of none). The resulting capability map turns "what should we build next" into a measurement. We then close the loop: an unattended agent, guarded against the two ways such a loop can cheat, reads the map and builds the mechanism it names. We report the negative results—gradients still win decisively at natural-language modelling, 82 of 106 capabilities remain at chance—and two measurement bugs that the instrument caught in our own work.

1 Introduction

The agent–environment loop is old, and the claim that everything is an instance of it is cheap. What is not cheap is the glue: supervised learning ships a dataloader, reinforcement learning a `gym.Env`, LLM agents a rollout-and-rubric API, computer use a container protocol. Any claim about "one agent across everything" is therefore mostly a claim about integration code.

We take the glue seriously and put all of it at one boundary. Above the boundary there is exactly one contract; below it, every substrate keeps its own reset semantics, rewards, graders and canonical metrics. The contribution is not the formalism but what the formalism then lets us measure:

*Built with Claude Opus 5 in Claude Code; every commit records the collaboration. Code, data and the full result files: `https://github.com/JacobFV/symbolic-ai-old-A`.

1. that next-token pretraining is literally a special case, checked numerically on trained models (§3);
2. a like-for-like comparison of neural and non-neural learners inside one protocol, where the non-neural side wins decisively on extrapolation and loses decisively on language modelling (§5);
3. a 180-lesson procedurally generated curriculum with an admission test, used as an instrument rather than a benchmark (§6);
4. a capability map that selects the next mechanism to build by measurement (§7).

2 The protocol

A *symbol* is an immutable, hashable, typed node whose value may contain other symbols, so one primitive covers tokens, numbers, identifiers, predicates, relations, lists, AST nodes, graph references, records—and distributions over symbols. That last case is what lets supervised prediction be an *action* rather than a separate mode of the framework.

$$\begin{aligned} \text{Environment:} \quad & \text{reset}(\text{seed}) \to (O^*,\ \text{info}) \\ & \text{step}(A^*) \to (O^*, r, \text{term}, \text{trunc}, \text{info}) \\ \text{Agent:} \quad & A : (S_{\text{agent}}, O^*) \to (S_{\text{agent}}, A^*) \end{aligned}$$

Agent state is passed in and returned rather than hidden in the object, which is what makes agents forkable for search and replayable from a trajectory. Every environment declares typed, inspectable observation and action *spaces*; both discrete actions (`LEFT`) and structured ones (`Call(function="search", args={…})`) are first class.

We borrowed deliberately: from Gymnasium, `reset(seed)` and the `terminated`/`truncated` distinction; from Prime Intellect's `verifiers`, dataset-backed episodes and graders that own their reward semantics; from OpenEnv, an explicit `state()` view so a containerized backend can implement the same protocol. We did not borrow any commitment to an optimizer: the learner protocol is one method, `update(trajectories)`, and no environment knows it exists.

3 Prediction is interaction, checked

For a sequence $x_1 \dots x_n$, set $O_t^* = x_1 \dots x_t$, let A_t^* be a predictive distribution over the vocabulary, and let $r_t = \log p(x_{t+1} \mid x_{\le t})$. The transition appends x_{t+1} (teacher forcing) or the agent's own argmax (free running).

The claim that this "is" language modelling is easy to assert and easy to get subtly wrong, so we made it a test. At unit level, with a randomly initialized transformer, the episode return equals the batched sum of $\log p$ over the same positions to 2×10^{-3}; per step nll $= -r$ and ppl $= e^{\text{nll}}$; and a uniform predictive policy earns exactly $\log(1/V)$ per step, which is the calibration check that the reward really is a log-probability. End-to-end, on trained checkpoints and held-out FineWeb-Edu text restricted to identical positions:

model	positions	$\sum \log p$ (loop)	$\lvert\Delta\rvert$
mixture-trained	512	-2398.2746	1.9×10^{-5}
LM-only	512	-2324.7483	2.3×10^{-4}




Figure 1: Uniformity lives at the adapter boundary, not inside the substrates. Every environment keeps its native semantics; every agent sees only symbols.

Two consequences. Maximum-likelihood pretraining is not a different objective from RL-style credit assignment here; it is the case where every sample carries weight 1 and the transition ignores the action. And the trainer may use batched tensors for throughput without changing the objective, because this equality is what licenses the shortcut.

4 Two kinds of agent in one protocol

The neural arm. *symbolic-ai-old-A* is a 13.97M-parameter decoder-only transformer (6 layers, $d = 384$, context 512, byte-level BPE over FineWeb-Edu text *plus* serialized symbolic structures). It is trained by one loss over the action segment of a symbolic step, $L = -\sum_i w_i \log p_\theta(a_i \mid o_i)/\sum_i w_i|a_i|$, where the choice of w selects the paradigm: $w = 1$ on a token stream is next-token pretraining, $w = \exp((G-b)/\beta)$ on episodes is advantage-weighted regression. It was trained for 8,000 steps (16.0 min, one NVIDIA GB10) on a mixture of FineWeb-Edu, SST-2, a gridworld, MiniGrid, three reasoning environments and tool calls.

The symbolic arms. A learner qualifies as symbolic here if it uses no gradients, no learned real-valued tensor, keeps all fitted structure discrete and countable, prints as a program a person can read, and runs on a CPU. Six were built; the two that matter most are *world-model induction* (learn each action's effects, preconditions and the world's bounds, plus what the environment rewards, then plan inside the induced schema) and *query-program induction* (induce a program that computes the answer from the structure of the observation).

What world-model induction learns from 21,394 gridworld transitions, in **0.14 s of CPU** and 26 discrete parameters, is exactly the world's laws:

```
RIGHT : move(+1,0) unless wall(+1,0) within [0,size)
PICKUP: add holds(agent,key); del at(key,0,0)
GOAL  : at(goal,0,0) ∧ holds(agent,key)
```

The bound `[0,size)` is read from the observation, so the same operator is correct at any scale—which is the mechanism behind Figure 2.




Figure 2: Induced on 5×5 gridworlds with 3 walls, evaluated up to 20×20 with 24 walls (25 held-out episodes per cell). The induced schema is flat across a $16\times$ change in state-space size; the transformer is at zero the moment the world stops looking like its training data.

5 Generalization

Scaling. Figure 2. A non-learning planner given the *true* model but a bounded search budget degrades faster than the induced one ($0.80 \to 0.00$ across the same range), so learning the schema does not merely save data—it makes search tractable by abstracting it.

A goal nobody trained for. The same 26 parameters, re-aimed at three goals absent from training (*hold the key*; *stand on the goal square*; *stand where the key is*), achieve 1.00 each on the first attempt with no new data. A policy—symbolic or neural—has no mechanism for this: it would need fresh demonstrations per goal.

Held-out rule families. A sequence environment generates from a hidden rule. Five families appear in training; five structurally analogous ones appear only at evaluation:

agent	params	train fam.	held-out fam.
program synthesizer	**0**	**1.000**	**1.000**
neural specialist	13,969,152	0.975	**0.000**
random	0	0.025	0.000

The network reproduces its training families almost perfectly and scores *exactly zero* on families it has not seen. The synthesizer does not distinguish the two cases, because it has no training distribution to be off.

Imported knowledge. On SST-2, a 17-parameter rule list induced *on top of* an imported lexicon (12,065 terms, ∼100 kB) reaches 0.765 in 0.7 s of CPU, against 0.585 for the transformer. The ablation is the point: induction alone reaches 0.480 and the prior alone 0.600. Importing knowledge is not cheating if the system can still learn; it is refusing to spend petaflops rediscovering a dictionary.

Where gradients win. A counting-based variable-order model on the same corpus and vocabulary reaches held-out perplexity 179.4 (order 5, 20M tokens, 199 s CPU) against 51.9 for the transformer, and its memory grows with distinct contexts rather than with a parameter budget—a 40M-token configuration exhausted host memory. Natural-language modelling is a real loss for the symbolic side, and no framing changes that.

6 A curriculum as an instrument

We implemented a 170-environment curriculum spanning symbol grounding to open-world research, plus 14 pilot lessons: **180 lessons, 179 admissible**, one honestly marked `spec` because it is a loop rather than a question. Lessons are *procedural generators*, not datasets, so evaluation episodes are new worlds and vocabularies rather than a held-out sample, and ground truth is exact rather than annotated. Grammar and ontology travel in `info`, visible to the evaluator and never to the agent.

A lesson counts only if it passes an admission test: exact ground truth, answer in vocabulary, uniform guesser near chance, *constant (majority) guesser under threshold*, and determinism. Floors alone are far from sufficient. Most generators were additionally audited by an independent oracle that re-derives each answer from the observation alone, and by heuristic audits that simulate the shortcut an unthinking agent would take. That found real defects: one lesson was 100% solvable from distractor name suffixes; another fell to "pick the candidate with most variables" at 0.61; a third yielded 0.47 to averaging payoffs under the *wrong* dimension—noise masquerading as signal.

The shape, not the average. On the 14-lesson pilot, query-program induction solves 11/14 at ≥ 0.90 while a transformer finetuned on the whole curriculum solves *0* and is above chance on 10/14. Symbolic induction is bimodal; the network is uniformly mediocre. A single "language score" would hide exactly this. Figure 3 shows the same shape across all 179 lessons.

Profiling all 179 lessons across three arms costs **two minutes of CPU**, which is what makes the loop in §7 practical.

7 The capability map selects the next mechanism

Averaging each arm over the capabilities that lessons declare turns "what should we build?" into a measurement (Figure 4). The capabilities at chance were not a list of hard problems but a list of *absent mechanisms*. We built them and re-measured (Figure 5); each is a general combinator whose parameters are induced, never a lesson-specific rule.

Two episodes are worth reporting because they were informative rather than incidental.

Alignment failed three times. Positional zip fails because the translation lesson permutes word order; order-free co-occurrence intersection fails because the correspondence is underdetermined by co-occurrence; what works is searching the small space of reorderings and keeping those whose




Figure 3: Per-lesson accuracy above chance, lessons ranked. Symbolic induction is bimodal: exact where the capability lies inside its hypothesis space, at chance where it does not. (The rule-list curve covers fewer lessons because it errors on some.)

induced lexicon is consistent across every sentence pair. "Alignment between symbol systems" is therefore not one mechanism: it decomposes into lexical correspondence and structural reordering, which must be induced *jointly* because neither is identifiable alone.

A fitted mechanism made things worse. Adding a tree evaluator—which induces what each operator symbol *means* by fitting the assignment that reproduces the answers—lifted expression evaluation from 0.21 to 1.00 but regressed three other lessons. Most programs here are enumerated, so scoring them on the episodes used to choose them is honest; a program that fits parameters can beat a better unfitted one on the very episodes it was fitted to. Selecting on a held-out slice fixed it, at no cost to the enumerated programs.

8 Closing the loop

If the capability map names the next mechanism and a full re-measurement costs two minutes, the iteration can be automated. We ran an unattended agent that reads the deficit briefing, builds one general mechanism, and re-measures—with the verification held *outside* its control, because a loop optimising "lessons solved" has exactly two exploits: make the lessons easier, or weaken the admission test. A cycle is merged only if the tests pass, the verified and registered lesson counts hold, no lesson's chance floor moves, no arm's solved count falls, and the diff touches no lesson file or admission code at all.

In its first hour the loop read the map, identified stateful sequential execution as the largest gap, and built an abstract machine—store, sequencer, loop and branch—whose opcode semantics are induced rather than given. Verified independently before merging:




Figure 4: Mean accuracy above chance per declared capability (top eight and the six most-represented at chance). 82 of 106 capabilities remain at chance.

lesson	before	after
procedural language	0.10	**1.00**
interpreter learning	0.12	**1.00**
compiler construction	0.30	**1.00**
solved / 179	23	**26**

Its own note on the interpreter lesson is the sort of thing we wanted the loop to find: several opcode assignments reproduced every demonstration and then disagreed on the held-out program, so five demonstrations did not identify the hypothesis; requiring that two opcodes never mean the same thing made all sixty episodes uniquely determined, and *that constraint is itself an induced parameter*. Few-shot fitting is not few-shot learning unless the examples identify the hypothesis.

The guard also earned its place immediately, by rejecting a cycle that changed nothing—which is how we discovered the reproducibility defect in §9.

9 Negative results and threats to validity

We report these because a paper that reports only its wins is not measuring anything.

Gradients win at language. Perplexity 179.4 versus 51.9, and the counting model's memory is unbounded in a way a parameter budget is not.

Most of the curriculum is unsolved. 26 of 179 lessons at ≥ 0.90; the large majority of declared capabilities remain at chance. The curriculum is far ahead of the learner, which we consider the correct state for an instrument but which forecloses any claim of general competence.

Reactive policies cannot explore. A 5-parameter induced MiniGrid policy scores 1.00 at 5×5 and 0.00 at 8×8, because the goal leaves the egocentric view. One discrete knob (randomize




Figure 5: Each mechanism and the lesson it unlocked, measured on held-out episodes. Nine lessons moved; seven to exact.

when no rule fires) restores 0.96. At 16×16 the goal is never visible at reset and no memoryless policy can succeed—an architecture limit, not a scale limit, and the neural arm fails identically.

Data requirements invert. The first world model never learned that walls block movement, because the expert teacher avoids walls. Adding 400 random episodes took it from 0.60/0.30/0.25 to 1.00/1.00/1.00. Policy learners want expert data; model learners want diverse data. Separately, no amount of expert data reveals that `PICKUP` requires a key—a competent teacher never tries it—so that precondition had to come from the representation (STRIPS delete-lists are preconditions) rather than from data.

Two measurement bugs in our own work. The admission test condemned a lesson on sampling noise: a constant guesser's score is itself a random variable, and a balanced binary lesson trips a fixed threshold about one run in six. Borderline cases are now re-measured at 4×. More seriously, program induction was *not reproducible across processes*: facts live in a `frozenset`, so hash randomization changed enumeration order, which decided ties, so borderline lessons flipped between runs and every earlier number carried unacknowledged flap. This was caught by the guard on an automated cycle that changed nothing and was still rejected. Sorted iteration and a tie-break on program text fixed it; two full sweeps in separate processes now agree exactly.

Scope. Single seeds per cell; differences under ≈ 0.1 on 25–50 episodes are not resolvable. Energy was never measured in joules—the GPU was shared with an unrelated job throughout—so the efficiency claim is stated in time and parameters ($\approx 10^4$ in fit time, $\approx 10^6$ in parameters) and not in watts. The curriculum's generators and one of its learners were written by the same effort, which is a real threat to validity that only an external benchmark can address.

10 Related work

The protocol borrows lifecycle ideas from Gymnasium, from Prime Intellect's `verifiers` (the taskset, harness and runtime separation; graders that own their semantics), and from OpenEnv. The symbolic learners are recognisable classics: separate-and-conquer rule induction, STRIPS action-model learning, enumerative program synthesis with observational-equivalence pruning, variable-order Markov modelling. Our contribution is not any single algorithm but placing them and a transformer behind one contract so the comparison is like-for-like, and building an instrument sharp enough to say where each one ends. The closest contemporary motivation is the observation that per-task program induction, rather than amortization into weights, is what solves ARC-style tasks.

11 Conclusion

Inside a single symbolic interaction protocol, next-token pretraining is a special case that can be verified numerically; non-neural learners with tens of discrete parameters beat a 13.97M-parameter transformer decisively on extrapolation, novel goals and unseen rule families, at 10^{-4} of the fitting cost; and gradients remain decisively better at modelling natural language. The useful artefact is less any of these results than the instrument: a 180-lesson generator suite with an admission test, cheap enough to run in two minutes, whose capability map names the next mechanism to build. Following that map—by hand, and then by an unattended agent that built a working abstract machine on its first cycle—produced eight new capabilities in a day, and caught two bugs in our own measurements along the way.

Reproduction.

```
python -m symbolic.experiments.curriculum_full
python -m symbolic.experiments.symbolic_suite
pytest tests/ conftest.py -q
```