Using Neural Networks and Other Machine Learning Algorithms with Non-Standard Loss Functions in Realized Volatility Forecasting

lakov Grigoryev

New Economic School

January 29, 2021

• Why Is It Important?

- Why Is It Important?
- Theory
 - realized volatility and integrated variance

- Why Is It Important?
- Theory
 - realized volatility and integrated variance
 - models: HAR, MEM, Random Forest, LSTM

- Why Is It Important?
- Theory
 - realized volatility and integrated variance
 - models: HAR, MEM, Random Forest, LSTM
 - loss functions: MSE, LinEx, ALS

- Why Is It Important?
- Theory
 - realized volatility and integrated variance
 - models: HAR, MEM, Random Forest, LSTM
 - loss functions: MSE, LinEx, ALS
- Empirical Research
 - data

- Why Is It Important?
- Theory
 - realized volatility and integrated variance
 - models: HAR, MEM, Random Forest, LSTM
 - loss functions: MSE, LinEx, ALS
- Empirical Research
 - data
 - results

- Why Is It Important?
- Theory
 - realized volatility and integrated variance
 - models: HAR, MEM, Random Forest, LSTM
 - loss functions: MSE, LinEx, ALS
- Empirical Research
 - data
 - results
 - plots

- Why Is It Important?
- Theory
 - realized volatility and integrated variance
 - models: HAR, MEM, Random Forest, LSTM
 - loss functions: MSE, LinEx, ALS
- Empirical Research
 - data
 - results
 - plots
- Conclusion

Volatility Forecasting:

asset allocation

Volatility Forecasting:

- asset allocation
- risk management

Volatility Forecasting:

- asset allocation
- risk management
- pricing derivatives

Volatility Forecasting:

- asset allocation
- risk management
- pricing derivatives

Example:

Black–Scholes model¹

$$C(S_t,t) = N(d_1)S_t - N(d_2)PV(K),$$

where
$$d_1 = \frac{1}{\sigma\sqrt{T-1}}\left[\ln\left(\frac{S_t}{K}\right) + \left(r + \frac{\sigma^2}{2}\right)(T-t)\right]$$
 and $d_2 = d_1 - \sigma\sqrt{T-t}$

¹Black, F. & Scholes, M. (1973, Journal of Political Economy)

Notation:

- P_t is the asset price at time $t \in [0, T]$
- $p_t = \log P_t$
- $r_{t,\Delta t} = p_{t+\Delta t} p_t$ is the asset return

Notation:

- P_t is the asset price at time $t \in [0, T]$
- $p_t = \log P_t$
- $r_{t,\Delta t} = p_{t+\Delta t} p_t$ is the asset return

Diffusion equation:

$$dp_t = \mu_t dt + \sigma_t dW_t, \ 0 \le t \le T,$$

where

- \bullet W_t is Brownian motion
- μ_t and σ_t are predictable processes
- σ_t is independent of W_t

Asset return: $r_{t,\Delta t} = p_{t+\Delta t} - p_t$

Diffusion equation: $dp_t = \mu_t dt + \sigma_t dW_t$, $0 \le t \le T$

Integrated variance:

$$IV_t = \int\limits_0^{\Delta t} \sigma_{t+ au}^2 d au$$

Asset return: $r_{t,\Delta t} = p_{t+\Delta t} - p_t$

Diffusion equation: $dp_t = \mu_t dt + \sigma_t dW_t$, $0 \le t \le T$

Integrated variance:

$$IV_t = \int_0^{\Delta t} \sigma_{t+\tau}^2 d\tau$$

Realized variance:

$$RV_t = \sum_{i=0}^{m-1} r_{t+\frac{\Delta t}{m}\cdot i, \frac{\Delta t}{m}}^2$$

Asset return: $r_{t,\Delta t} = p_{t+\Delta t} - p_t$

Diffusion equation: $dp_t = \mu_t dt + \sigma_t dW_t$, $0 \le t \le T$

Integrated variance:

$$IV_t = \int\limits_0^{\Delta t} \sigma_{t+ au}^2 d au$$

Realized variance:

$$RV_t = \sum_{i=0}^{m-1} r_{t+\frac{\Delta t}{m}\cdot i, \frac{\Delta t}{m}}^2$$

Consistency: $m \to +\infty \Longrightarrow RV_t \stackrel{p}{\longrightarrow} IV_t$

Asset return: $r_{t,\Delta t} = p_{t+\Delta t} - p_t$

Diffusion equation: $dp_t = \mu_t dt + \sigma_t dW_t$, $0 \le t \le T$

Integrated variance:

$$IV_t = \int\limits_0^{\Delta t} \sigma_{t+\tau}^2 d\tau$$

Realized variance:

$$RV_t = \sum_{i=0}^{m-1} r_{t+\frac{\Delta t}{m}\cdot i, \frac{\Delta t}{m}}^2$$

Consistency: $m \to +\infty \Longrightarrow RV_t \stackrel{p}{\longrightarrow} IV_t$

Realized volatility:
$$\sqrt{RV_t} = \sqrt{\sum\limits_{i=0}^{m-1} r_{t+\frac{\Delta t}{m}\cdot i,\frac{\Delta t}{m}}^2} := RV_t$$

Denote:
$$RV_t^n = \frac{\sum_{i=0}^{n-1} RV_{t-i}}{n}$$

Denote:
$$RV_t^n = \frac{\sum_{i=0}^{n-1} RV_{t-i}}{n}$$

Daily HAR model:

$$RV_{t} = \beta_{0} + \beta_{d}RV_{t-1}^{1} + \beta_{w}RV_{t-1}^{5} + \beta_{m}RV_{t-1}^{22} + \epsilon_{t}$$

Denote:
$$RV_t^n = \frac{\sum_{i=0}^{n-1} RV_{t-i}}{n}$$

Daily HAR model:

$$RV_t = \beta_0 + \beta_d RV_{t-1}^1 + \beta_w RV_{t-1}^5 + \beta_m RV_{t-1}^{22} + \epsilon_t$$

• 'd' is 'day', 'w' is 'week', 'm' is 'month'

Denote:
$$RV_t^n = \frac{\sum_{i=0}^{n-1} RV_{t-i}}{n}$$

Daily HAR model:

$$RV_{t} = \beta_{0} + \beta_{d}RV_{t-1}^{1} + \beta_{w}RV_{t-1}^{5} + \beta_{m}RV_{t-1}^{22} + \epsilon_{t}$$

- 'd' is 'day', 'w' is 'week', 'm' is 'month'
- we use $\log RV_t$ instead of RV_t

Used only for time series with non-negative elements!

Used only for time series with non-negative elements!

Model:

• $RV_t = \psi_t \eta_t$

Used only for time series with non-negative elements!

Model:

- $RV_t = \psi_t \eta_t$
- $\eta_t \sim \exp(\lambda = 1)$

Used only for time series with non-negative elements!

Model:

- $RV_t = \psi_t \eta_t$
- $\eta_t \sim \exp(\lambda = 1)$
- $\psi_t = \beta_0 + \beta_1 RV_{t-1} + \beta_2 \psi_{t-1}$

Used only for time series with non-negative elements!

Model:

- $RV_t = \psi_t \eta_t$
- $\eta_t \sim \exp(\lambda = 1)$
- $\psi_t = \beta_0 + \beta_1 RV_{t-1} + \beta_2 \psi_{t-1}$
- $\beta_0 > 0 \ (\Rightarrow \psi_t > 0)$

Used only for time series with non-negative elements!

Model:

- $RV_t = \psi_t \eta_t$
- $\eta_t \sim \exp(\lambda = 1)$
- $\psi_t = \beta_0 + \beta_1 RV_{t-1} + \beta_2 \psi_{t-1}$
- $\beta_0 > 0 \ (\Rightarrow \psi_t > 0)$

Log-likelihood function:

$$L = -\sum_{t=1}^T \left(\frac{RV_t}{\psi_t} + \log \psi_t \right) \longrightarrow \max_{\beta_0, \beta_1, \beta_2},$$

where $\psi_t = \beta_0 + \beta_1 RV_{t-1} + \beta_2 \psi_{t-1}$.

Regressors: $RV_{t-1}, \dots, RV_{t-k}, t \in [k, T]$

Target: $RV_t, t \in [k, T]$

Regressors: $RV_{t-1}, \ldots, RV_{t-k}, \ t \in [k, T]$ Target: $RV_t, \ t \in [k, T]$

Decision tree:

Node N, data X

Regressors: $RV_{t-1}, \ldots, RV_{t-k}, \ t \in [k, T]$ Target: $RV_t, \ t \in [k, T]$

- Node N, data X
- Q(X, F, T) > 0?

Regressors: $RV_{t-1}, \ldots, RV_{t-k}, \ t \in [k, T]$ Target: $RV_t, \ t \in [k, T]$

- Node N, data X
- Q(X, F, T) > 0?
- Yes \Rightarrow feature F and threshold T (optimizing Q(X, F, T)):
 - $F < T \Rightarrow$ subtree with node N_{TRUE} , data X_{TRUE}
 - $F \geq T \Rightarrow$ subtree with node N_{FALSE} , data X_{FALSE}

Regressors: $RV_{t-1}, \ldots, RV_{t-k}, \ t \in [k, T]$ Target: $RV_t, \ t \in [k, T]$

- Node N, data X
- Q(X, F, T) > 0?
- Yes \Rightarrow feature F and threshold T (optimizing Q(X, F, T)):
 - $F < T \Rightarrow$ subtree with node N_{TRUE} , data X_{TRUE}
 - $F \geq T \Rightarrow$ subtree with node N_{FALSE} , data X_{FALSE}
- No \Rightarrow N is a leaf node

Regressors: $RV_{t-1}, \ldots, RV_{t-k}, \ t \in [k, T]$ Target: $RV_t, \ t \in [k, T]$

- Node N, data X
- Q(X, F, T) > 0?
- Yes \Rightarrow feature F and threshold T (optimizing Q(X, F, T)):
 - $F < T \Rightarrow$ subtree with node N_{TRUE} , data X_{TRUE}
 - $F \ge T \Rightarrow$ subtree with node N_{FALSE} , data X_{FALSE}
- No \Rightarrow N is a leaf node

$$\begin{split} Q(X,F,T) &= H(X) - \frac{|X_{TRUE}|}{|X|} H(X_{TRUE}) - \frac{|X_{FALSE}|}{|X|} H(X_{FALSE}), \\ \text{where } H(X) &= \min_{c \in \mathbb{R}} \frac{1}{|X|} \sum_{t=k}^{T} (y^t - c)^2 \end{split}$$

```
Regressors: RV_{t-1}, \ldots, RV_{t-k}, \ t \in [k, T]
Target: RV_t, \ t \in [k, T]
```

Random Forest:

• Bootstrap n_{tree} samples

Theory: The Random Forest Model

```
Regressors: RV_{t-1}, \ldots, RV_{t-k}, \ t \in [k, T]
Target: RV_t, \ t \in [k, T]
```

Random Forest:

- Bootstrap n_{tree} samples
- On each sample: decision tree with a reduced number of regressors

Theory: The Random Forest Model

```
Regressors: RV_{t-1}, \dots, RV_{t-k}, \ t \in [k, T]
Target: RV_t, \ t \in [k, T]
```

Random Forest:

- Bootstrap n_{tree} samples
- On each sample: decision tree with a reduced number of regressors
- Return the mean of n_{tree} predictions

General neural network:

• neurons, grouped in layers, connected to each other

General neural network:

- neurons, grouped in layers, connected to each other
- weights of neurons

General neural network:


- neurons, grouped in layers, connected to each other
- weights of neurons
- (non-linear) activation functions for each layer

General neural network:

- neurons, grouped in layers, connected to each other
- weights of neurons
- (non-linear) activation functions for each layer

A single hidden layer neural network can approximate any non-linear function given enough number of neurons in this hidden layer.²

Theory: The LSTM Model



Legend:

Layer Pointwize op Copy

\$\frac{1}{2}\$

Theory: Cost Function

Cost function:

$$C(y, \hat{y}) = \frac{1}{m} \sum_{i=1}^{m} L(y^{i} - \hat{y}^{i}),$$

where m is a number of examples, $L(\cdot)$ is a loss function.

Theory: The MSE Loss Function

MSE loss:
$$L(h) = h^2$$

• widely used in regression problems

Theory: The MSE Loss Function


MSE loss:
$$L(h) = h^2$$

- widely used in regression problems
- symmetric

Theory: The MSE Loss Function

MSE loss: $L(h) = h^2$

- widely used in regression problems
- symmetric



MSE loss

Theory: The LinEx Loss Function

LinEx loss:
$$L(h) = \exp(\alpha h) - \alpha h - 1$$

• $\alpha > 0 \Rightarrow$ it is smaller for overprediction than for underprediction

Theory: The LinEx Loss Function


LinEx loss: $L(h) = \exp(\alpha h) - \alpha h - 1$

- ullet $\alpha > 0 \Rightarrow$ it is smaller for overprediction than for underprediction
- $\alpha < 0 \Rightarrow$ vice versa

Theory: The LinEx Loss Function

LinEx loss: $L(h) = \exp(\alpha h) - \alpha h - 1$

- $\alpha > 0 \Rightarrow$ it is smaller for overprediction than for underprediction
- α < 0 \Rightarrow vice versa



LinEx loss, $\alpha = 0.5$

Theory: The ALS Loss Function

ALS loss:
$$L(h) = |\alpha - \mathbb{1}_{(h<0)}| \times h^2$$

• $\alpha > 0.5 \Rightarrow$ it is smaller for overprediction than for underprediction

Theory: The ALS Loss Function


ALS loss:
$$L(h) = |\alpha - 1|_{(h < 0)} \times h^2$$

- \bullet $\alpha>0.5\Rightarrow$ it is smaller for overprediction than for underprediction
- $\alpha < 0.5 \Rightarrow$ vice versa

Theory: The ALS Loss Function

ALS loss:
$$L(h) = |\alpha - 1_{(h<0)}| \times h^2$$

- \bullet $\alpha>0.5\Rightarrow$ it is smaller for overprediction than for underprediction
- $\alpha < 0.5 \Rightarrow \text{vice versa}$



ALS loss.
$$\alpha = 0.7$$

• from Oxford-Man Institute of Quantitative Finance library

- from Oxford-Man Institute of Quantitative Finance library
- daily realized volatility of S&P 500 Index (ticks of 5 minutes)


- from Oxford-Man Institute of Quantitative Finance library
- daily realized volatility of S&P 500 Index (ticks of 5 minutes)
- period from 1/3/2000 to 1/14/2021


- from Oxford-Man Institute of Quantitative Finance library
- daily realized volatility of S&P 500 Index (ticks of 5 minutes)
- period from 1/3/2000 to 1/14/2021
- in-sample to out-of-sample proportion: 7:3

Empirical Research: Results


Model	MSE for RV_t	MSE for $log(RV_t)$
MEM	4.67×10^{-6}	0.057
Random Forest	1.11×10^{-5}	0.136
HAR	1.21×10^{-5}	0.110
LSTM	3.96×10^{-5}	0.453


Model	LinEx for $log(RV_t)$	ALS for $log(RV_t)$
HAR	0.014	0.052
LSTM	0.067	0.246







The MEM model with QMLE (left) and the Random Forest model with MSE loss (right), one-step-ahead predictions







The HAR model (left) and the LSTM model (right) with MSE loss, one-step-ahead predictions





The HAR model (left) and the LSTM model (right) with LinEx loss, one-step-ahead predictions





The HAR model (left) and the LSTM model (right) with ALS loss, one-step-ahead predictions

- MSE criterion
 - The MEM model is the best by margin

- MSE criterion
 - The MEM model is the best by margin
 - The Random Forest and the HAR models are similar in terms of predictive power

- MSE criterion
 - The MEM model is the best by margin
 - The Random Forest and the HAR models are similar in terms of predictive power
 - The LSTM model is the worst

- MSE criterion
 - The MEM model is the best by margin
 - The Random Forest and the HAR models are similar in terms of predictive power
 - The LSTM model is the worst
- LinEx/ALS loss & criterion
 - The HAR model is better in both cases than the LSTM model

- MSE criterion
 - The MEM model is the best by margin
 - The Random Forest and the HAR models are similar in terms of predictive power
 - The LSTM model is the worst
- LinEx/ALS loss & criterion
 - The HAR model is better in both cases than the LSTM model
- Further research
 - New criteria and loss functions

- MSE criterion
 - The MEM model is the best by margin
 - The Random Forest and the HAR models are similar in terms of predictive power
 - The LSTM model is the worst
- LinEx/ALS loss & criterion
 - The HAR model is better in both cases than the LSTM model
- Further research
 - New criteria and loss functions
 - New models

- MSE criterion
 - The MEM model is the best by margin
 - The Random Forest and the HAR models are similar in terms of predictive power
 - The LSTM model is the worst
- LinEx/ALS loss & criterion
 - The HAR model is better in both cases than the LSTM model
- Further research
 - New criteria and loss functions
 - New models
 - Addition of jumps