

Deploying a Honeypot Server on the Network

Cyberwarfare: Information Operations in a Connected World, Second Edition - Lab 05

Student:

Devon Jacob

Email:

jacobd24@rowan.edu

Time on Task:

13 hours, 18 minutes

Progress:


87%

Report Generated: Tuesday, November 26, 2024 at 1:07 AM

Hands-On Demonstration

Part 1: Configure an SSH Honeypot


37. **Make a screen capture** showing all three services listening on their default ports.



```
user@Honeypot01: /home/cowrie/cowrie/
user@Honeypot01:/home/cowrie/cowrie$ ls -ld */
bin/ cowrie-env/ docker/ docs/ etc/ honeyfs/ share/ src/ test/
user@Honeypot01:/home/cowrie/cowrie$ sudo vi etc/cowrie.cfg
[sudo] password for user:
user@Honeypot01:/home/cowrie/cowrie$ :set number
bash: :set: command not found
user@Honeypot01:/home/cowrie/cowrie$ sudo vi etc/cowrie.cfg
user@Honeypot01:/home/cowrie/cowrie$ sudo vi etc/userdb.txt
user@Honeypot01:/home/cowrie/cowrie$ sudo touch /etc/authbind/byport/22
[sudo] password for user:
user@Honeypot01:/home/cowrie/cowrie$ sudo chown cowrie:cowrie /etc/authbind/byport/22
user@Honeypot01:/home/cowrie/cowrie$ sudo chmod 770 /etc/authbind/byport/22
user@Honeypot01:/home/cowrie/cowrie$ sudo vi /var/www/html/kippo-graph/config.php
user@Honeypot01:/home/cowrie/cowrie$ sudo su - cowrie
cowrie@Honeypot01: $ ./cowrie/bin/cowrie start
Using default Python virtual environment "/home/cowrie/cowrie/cowrie-env"
Starting cowrie: [twistd --umask=0022 --pidfile=/var/run/cowrie.pid --logger cowrie.python.logfile.logger cowrie ]...
Removing stale pidfile /home/cowrie/cowrie/var/run/cowrie.pid
cowrie@Honeypot01: $ exit
logout
user@Honeypot01:/home/cowrie/cowrie$ sudo netstat -antp
Active Internet connections (servers and established)
Proto Recv-Q Send-Q Local Address          Foreign Address         State       PID/Program name
tcp        0      0 0.0.0.0:22             0.0.0.0:*               LISTEN      1890/python3
tcp6       0      0 :::33060               :::*                    LISTEN      800/mysql
tcp6       0      0 :::3306                :::*                    LISTEN      800/mysql
tcp6       0      0 :::80                  :::*                    LISTEN      799/apache2
user@Honeypot01:/home/cowrie/cowrie$
```


Deploying a Honeypot Server on the Network

51. Make a screen capture showing the commands used per the accompanying table.



Part 2: Configure an HTTP Honeypot


6. Make a screen capture showing the current status of the Tanner, PHP sandbox, and Redis services.




Deploying a Honeypot Server on the Network

Cyberwarfare: Information Operations in a Connected World, Second Edition - Lab 05

34. Make a screen capture showing output from the successful LFI attack.



42. Make a screen capture showing your LFI payload threat actor session in Tannerweb.




Part 3: Simulate Attacks and Evaluate Threat Intelligence


Deploying a Honeypot Server on the Network

Cyberwarfare: Information Operations in a Connected World, Second Edition - Lab 05


15. **Make a screen capture** showing the updated Firewall / NAT / Port Forward rules table and the feedback indicating their successful application.




22. **Make a screen capture** showing the Server banner changed message in your Nikto output.



32. Make a screen capture showing MySQL, erlang, and NGINX processes in the output.



40. Make a screen capture showing the overall Snare-Stats.




46. Record the website the Red Team threat actor attempted to include in the path.

The Red Team threat actor attempted to include the website <http://cirt.net> in the path

Deploying a Honeypot Server on the Network

Cyberwarfare: Information Operations in a Connected World, Second Edition - Lab 05

53. **Make a screen capture** showing the contents of the file that the Red Team member uploaded to the SSH honeypot.



The screenshot shows a terminal window titled "user@Honeypot01: /home/cowrie/cowrie/var/lib/cowrie/downloads". The terminal displays the following text:


```
user@Honeypot01: /home/cowrie/cowrie/var/lib/cowrie/downloads$ cat 9e508ec45085128c906e2a0639a753ce588f023f94fef1792621bc7c8b4dd4a4
#!/bin/bash

# Destroy
# rm -rf *
```

58. **Record** the most popular username/password combination.

root/hackthegibson

61. Make a screen capture showing the Top 10 successful input commands.



Challenge and Analysis

Part 1: Identify XSS Attacks in Tannerweb

Make a screen capture showing the details of one cross-site scripting event.

Applications : Firefox

user@Honeypot01: /opt

Session(7a4b4a0f009b4065862e2316ec9a1c40)

Mon 25 Nov, 22:59 User Usererson

Example Domain

http://example.com/?eg=/e/

Session(7a4b4a0f009b4065862e2316ec9a1c40)

2024-11-25 22:59:01

localhost:8091/session/7a4b4a0f009b4065862e2316ec9a1c40

Devon Jacob

Home | Docs

Key	Value
UUID	7a4b4a0f009b4065862e2316ec9a1c40
IP	202.20.2.4
Location	{'country': 'New Zealand', 'country_code': 'NZ', 'city': 'Wellington', 'zip_code': '6011'}
Port	54068
User Agents	Mozilla/5.00 (Nikto/2.1.6) (Evasions:None) (Test:006195)
Snare UUID	725d0df1-ab40-44c2-ba4d-126fdc6bf461
Start time	1732592675.6964493
End time	1732592675.6964498
Requests/sec	2097152.0
Time between requests	0.0
Paths	1
Errors	0
Hidden Links	0
Attacks	xss - 1
Paths	{'path': '/scripts/message/message_dialog.tml?how_many_back=\\ "><script>alert(1)</script>', 'timestamp': 1732592675.6964307, 'response_status': 200, 'attack_type': 'xss'}

Part 2: Change SNARE's Web Server Header

Document the additional option(s) and argument(s) used to change the SNARE Web Server Header to Apache.

Incomplete

Make a screen capture showing that the SNARE Web Server Header is set to Apache (using output from Nikto).

Incomplete