





Ripatti's blog

A little bit of classics: dynamic programming over subsets and paths in graphs

By [Ripatti](#), 8 years ago, translation,  

Author thanks [adamax](#) for translation this article into English.

Introduction

After [Codeforces Beta Round #11](#) several participants expressed a wish to read something about problems similar to [problem D](#) of that round. The author of this article, for the purpose of helping them, tried searching for such information, but to his surprise couldn't find anything on the Internet. It is not known whether the search was not thorough or there's really nothing out there, but (just in case) the author decided to write his own article on this topic.

In some sense this article may be regarded as a tutorial for the [problem D](#) from Beta Round #11.

In this article quite well-known algorithms are considered: the search for optimal Hamiltonian walks and cycles, finding their number, check for existence and something more. The so-called "dynamic programming over subsets" is used. This method requires exponential time and memory and therefore can be used only if the graph is very small - typically 20 vertices or less.

DP over subsets

Consider a set of elements numbered from 0 to $N - 1$. Each subset of this set can be encoded by a sequence of N bits (we will call this sequence "a mask"). The i -th element belongs to the subset if and only if the i -th bit of the mask equals 1. For instance, the mask 00010011 means that the subset of the set $[0 \dots 7]$ consists of elements 0, 1 and 4. There are totally 2^N masks, and so 2^N subsets. Each mask is in fact an integer number written in binary notation.

The method is to assign a value to each mask (and, therefore, to each subset) and compute the values for new masks using already computed values. As a rule, to find the value for a subset A we remove an element in every possible way and use values for obtained subsets A'_1, A'_2, \dots, A'_k to compute the value for A . This means that the values for A'_i must have been computed already, so we need to establish an ordering in which masks will be considered. It's easy to see that the natural ordering will do: go over masks in increasing order of corresponding numbers.

We will use the following notation:

$bit(i, mask)$ - the i -th bit of $mask$

$count(mask)$ - the number of non-zero bits in $mask$

$first(mask)$ - the number of the lowest non-zero bit in $mask$

$(a ? b : c)$ - returns b if a holds, or c otherwise.

The elements of our set will be vertices of the graph. For the sake of simplicity we'll assume that the graph is undirected. Modification of the algorithms for directed graphs is left as an exercise for the reader.

1. Search for the shortest Hamiltonian walk

Let the graph $G = (V, E)$ have n vertices, and each edge $(i, j) \in E$ have a weight $d(i, j)$. We want to find a Hamiltonian walk for which the sum of weights of its edges is minimal.

→ Pay attention

Before contest

[Educational Codeforces Round 40](#)
(Rated for Div. 2)

21:25:33

Like

143 people like this. [Sign Up](#) to see what your friends like.

→ JacobianDet



Rating: **1290**

Contribution: **0**

- [Settings](#)
- [Blog](#)
- [Teams](#)
- [Submissions](#)
- [Favourites](#)
- [Groups](#)
- [Talks](#)
- [Contests](#)



JacobianDet

→ Top rated

#	User	Rating
1	Petr	3325
2	Um_nik	3284
3	Sylovialy	3258
4	tourist	3206
5	anta	3106
6	fateice	3099
7	mnbvmar	3096
8	00000000000000...0	3083
9	Radewoosh	3076
10	HYPERHYPERHYPERC...R	3071

[Countries](#) | [Cities](#) | [Organizations](#)

[View all →](#)

→ Top contributors

#	User	Contrib.
1	tourist	183
2	rng_58	169
3	csacademy	163
4	Petr	158
5	Swistakk	152
5	lewin	152
7	matthew99	146
8	Errichto	142
9	Zlobober	141
10	BledDest	140
10	adamant	140

[View all →](#)

→ Favourite groups



Let $dp[mask][i]$ be the length of the shortest Hamiltonian walk in the subgraph generated by vertices in $mask$, that ends in the vertex i .

The DP can be calculated by the following formulas:

$dp[mask][i] = 0$, if $count(mask) = 1$ and $bit(i, mask) = 1$;
 $dp[mask][i] = \min_{bit(j, mask)=1, (j,i) \in E} \{dp[mask \text{ xor } 2^i][j] + d(j, i)\}$, if $count(mask) > 1$ and $bit(i, mask) = 1$;
 $dp[mask][i] = \infty$ in other cases.

Now the desired minimal length is $p_{min} = \min_{i \in [0 \dots n-1]} \{dp[2^n - 1][i]\}$. If $p_{min} = \infty$, then there is no Hamiltonian walk in the graph. Otherwise it's easy to recover the walk itself.

Let the minimal walk end in the vertex i . Then the vertex $j \neq i$, for which $dp[2^n - 1][i] = dp[2^n - 1 \text{ xor } 2^i][j] + d(j, i)$, is the previous vertex in the path. Now remove i from the set and find the vertex previous to j in the same way. Continuing this process until only one vertex is left, we'll find the whole Hamiltonian walk.

This solution requires $O(2^n n)$ of memory and $O(2^n n^2)$ of time.

2. Finding the number of Hamiltonian walks

Let the graph $G = (V, E)$ be unweighted. We'll modify the previous algorithm. Let $dp[mask][i]$ be the number of Hamiltonian walks on the subset $mask$, which end in the vertex i . The DP is rewritten in the following way:

$dp[mask][i] = 1$, if $count(mask) = 1$ and $bit(i, mask) = 1$;
 $dp[mask][i] = \sum_{bit(j, mask)=1, (j,i) \in E} dp[mask \text{ xor } 2^i][j]$, if $count(mask) > 1$ and $bit(i, mask) = 1$;
 $dp[mask][i] = 0$ in other cases.

The answer is $\sum_{i \in [0 \dots n-1]} dp[2^n - 1][i]$.

This solution requires $O(2^n n)$ of memory and $O(2^n n^2)$ of time.

3. Finding the number of simple paths

Calculate the DP from the previous paragraph. The answer is $1/2 \sum_{i \in [0 \dots n-1], count(mask) \geq 2} dp[mask][i]$. The coefficient $1/2$ is required because each simple path is considered twice - in both directions. Also note that only paths of positive length are taken into account. You can add n zero-length paths, of course.

This solution requires $O(2^n n)$ of memory and $O(2^n n^2)$ of time.

4. Check for existence of Hamiltonian walk

We can use solution 2 replacing the sum with bitwise OR. $dp[mask][i]$ will contain a boolean value - whether there exists a Hamiltonian walk over the subset $mask$ which ends in the vertex i . DP is the following:

$dp[mask][i] = 1$, if $count(mask) = 1$ and $bit(i, mask) = 1$;
 $dp[mask][i] = \text{OR}_{bit(j, mask)=1, (j,i) \in E} dp[mask \text{ xor } 2^i][j]$, if $count(mask) > 1$ and $bit(i, mask) = 1$;
 $dp[mask][i] = 0$ in other cases.

This solution, like solution 2, requires $O(2^n n)$ of memory and $O(2^n n^2)$ of time. It can be improved in the following way.

Let $dp'[mask]$ be the mask of the subset consisting of those vertices j for which there exists a Hamiltonian walk over the subset $mask$ ending in j . In other words, we 'compress' the previous DP: $dp'[mask]$ equals $\sum_{i \in [0 \dots n-1]} dp[mask][i] \cdot 2^i$. For the graph G write out n masks M_i , which give the subset of vertices incident to the vertex i . That is,
 $M_i = \sum_{j \in [0 \dots n-1]} 2^j \cdot ((i, j) \in E ? 1 : 0)$.

DP will be rewritten in the following way:

$dp'[mask] = 2^i$, if $count(mask) = 1$ and $bit(i, mask) = 1$;
 $dp'[mask] = \sum_{i \in [0 \dots n-1]} 2^i \cdot ((dp[mask \text{ xor } 2^i] \text{ and } M_i) \neq 0 ? 1 : 0)$, if $count(mask) > 1$;
 $dp'[mask] = 0$ in other cases.

#	Name
1	ACM-OI
View all →	

→ Find user

Handle:

→ Recent actions

[joisino](#) → [Japanese Olympiad in Informatics \(JOI\) Spring Camp 2018](#)

[BledDest](#) → [Educational Codeforces Round 40 \[Rated for Div. 2\]](#)

[BledDest](#) → [Educational Codeforces Round 39 \[Rated for Div.2\]](#)

[dario-dsa](#) → [SPOJ Kquery](#)

[Vasiljko](#) → [Sum of elements in matrix module some value](#)

[DrSwad](#) → [MathMash — Round 6 \(First Collaborated Round\)](#)

[jiry_2](#) → [A simple introduction to "Segment tree beats"](#)

[Gilgamesh_01](#) → [Same code different time execution](#)

[rps](#) → [binary tree in python3](#)

[Dijkstra.](#) → [how to improve my skills](#)

[Iewin](#) → [Invitation to NAIPC 2018 / Grand Prix of America](#)

[Arpa](#) → [\[Tutorial\] Sack \(dsu on tree\)](#)

[xiaowuc1](#) → [USACO 2017-2018 US Open](#)

[Tommyr7](#) → [Codeforces Round #462 Editorial](#)

[toros](#) → [Help needed in QTREE SPOJ](#)

[Eagle-Eye](#) → [ANDRound problem](#)

[DrSwad](#) → [MathMash — Round 5](#)

[csacademy](#) → [Round #74 \(Div. 2\)](#)

[KAN](#) → [VK Cup 2018 — Wild-card Round 1](#)

[vazhadval](#) → [I dont understand what I do wrong \(C#\)](#)

[Vladik](#) → [TOP 15 most popular users on codeforces](#)

[MikeMirzayanov](#) → [Codeforces Round #277.5 \(Div. 2\) Editorial \[A-D for now\]](#)

[pandusonu](#) → [CodeCracker 2k18 editorials](#)

[DarthPrince](#) → [Codeforces Round #459 Editorial](#)

[satyaki3794](#) → [Google APAC Kickstart 2018 Round A](#)

[Detailed →](#)



Pay special attention to the expression $dp[mask \text{ xor } 2^i]$ and M_i . The first part of the expression is the subset of vertices j , for which there exists a Hamiltonian walk over the subset $mask$ minus vertex i , ending in j . The second part of the expression is the set of vertices incident to i . If these subsets have non-empty intersection (their bitwise AND is non-zero), then it's easy to see that there exists a Hamiltonian walk in $mask$ ending in the vertex i .

The final test is to compare $dp[2^n - 1]$ to 0.

This solution uses $O(2^n)$ of memory and $O(2^n n)$ of time.

5. Finding the shortest Hamiltonian cycle

Since we don't care at which vertex the cycle starts, assume that it starts at 0. Now use solution 1 for the subset of vertices, changing the formulas in the following way:

$dp[1][0] = 0;$
 $dp[mask][i] = \min_{bit(j, mask)=1, (j,i) \in E} \{dp[mask \text{ xor } 2^i][j] + d(j, i)\}, \text{ if } i > 0,$
 $bit(0, mask) = 1 \text{ and } bit(i, mask) = 1;$
 $dp[mask][i] = \infty$ in other cases.

So $dp[mask][i]$ contains the length of the shortest Hamiltonian walk over the subset $mask$, starting at 0 and ending at i .

The required minimum is calculated by the formula

$\min_{i \in [1 \dots n-1], (i,0) \in E} \{dp[2^n - 1][i] + d(i, 0)\}$. If it equals ∞ , there is no Hamiltonian cycle. Otherwise the Hamiltonian cycle can be restored by a method similar to solution 1.

6. Finding the number of Hamiltonian cycles

Using ideas from solutions 5 and 2 one can derive a DP calculating the number of Hamiltonian cycles requiring $O(2^n n^2)$ of time and $O(2^n n)$ of memory.

7. Finding the number of simple cycles

Let $dp[mask][i]$ be the number of Hamiltonian walks over the subset $mask$, starting at the vertex $first(mask)$ and ending at the vertex i . DP looks like this:

$dp[mask][i] = 1$, if $count(mask) = 1$ and $bit(i, mask) = 1;$
 $dp[mask][i] = \sum_{j \in [0 \dots n-1], (j,i) \in E} dp[mask \text{ xor } 2^i][j]$, if $count(mask) > 1$,
 $bit(i, mask) = 1$ and $i \neq first(mask);$
 $dp[mask][i] = 0$ otherwise.

The answer is $1/2 \sum_{i \in [0 \dots n-1], count(mask) \geq 3, (first(mask), i) \in E} dp[mask][i]$.

This solution requires $O(2^n n^2)$ of time and $O(2^n n)$ of memory.

8. Checking for existence of Hamiltonian cycle

We can modify solution 5 and, using the trick from solution 4, obtain an algorithm requiring $O(2^n n)$ of time and $O(2^n)$ of memory.

Exercises

CFBR11D

CCTOOLS

P.S. This article may be extended and fixed in future. The author would be grateful for supplementing the Exercises section and for pointing out any mistakes and inaccuracies.

🔗 [algorithms](#), [dynamic programming](#), [graphs](#)

▲ +22 ▼



👤 [Ripatti](#)

📅 8 years ago

💬 25



Comments (25)

[Write comment?](#)

<http://www.spoj.pl/problems/AC3131/>



AlexErofeev

For example

→ [Reply](#)

8 years ago, # ^ | ☆

▲ 0 ▼

спасибо, задача очень понравилась)) действительно, дп по подмножествам, только вот без графов и маршрутов в них. поэтому пока не знаю, стоит добавлять ее в статью или нет.



Ripatti

пусть пока повисит тут. потом, возможно, добавлю. возможно в новый раздел:)

→ [Reply](#)



jaher

8 years ago, # | ☆

▲ 0 ▼

Nice tutorial. You could also add an explanation on how to count hamiltonian circuits on a grid of size $n \times m$ with ($n \leq 7$ and $m \leq 10^9$) for example which is also fairly classical.

→ [Reply](#)

8 years ago, # ^ | ☆

▲ +1 ▼

Counting hamiltonian circuits on a grid is quite different from problems which was viewed there. In article I view foremost *masks over subsets* and paths in *graphs*. But in your problem motzkin words and matrix multiplication are used:)



Ripatti

Maybe I will view your problem in future article:)

→ [Reply](#)



gmark

8 years ago, # ^ | ☆

▲ 0 ▼

CouDo you have a reference to such a problem?

→ [Reply](#)



Ripatti

8 years ago, # ^ | ☆

▲ 0 ▼

http://www.cs.ust.hk/mjg_lib/Library/Kwong_Ham_94.pdf
it is very old paper:)

→ [Reply](#)



gionto35

7 years ago, # ^ | ☆

▲ 0 ▼

If the size of grid is 12×12 . Can we use DP over Subsets

→ [Reply](#)



gionto35

7 years ago, # ^ | ☆

▲ 0 ▼

Top up

→ [Reply](#)



havaliza

8 years ago, # | ☆

▲ 0 ▼

<http://www.codechef.com/problems/TOOLS>
is an example problem for part 5.

→ [Reply](#)



Ripatti

8 years ago, # ^ | ☆

▲ 0 ▼

Thanx! Very nice problem)) I added it.

→ [Reply](#)



4 years ago, # | ☆

▲ 0 ▼

Could you please further explain the recurrence in the first example (finding a

[__builtin__wolfy](#)

could you please further explain the recurrence in the first example (finding a shortest Hamiltonian walk)?

→ [Reply](#)

[bufferedReader](#)

4 years ago, # ^ | ☆

▲ 0 ▼

For me too, please.

→ [Reply](#)

4 years ago, # | ☆

← Rev. 3 ▲ 0 ▼

The following paper is potentially useful as reference:

"A Dynamic Programming Approach to Sequencing Problems" by Michael Held and Richard M. Karp, 1962. [[citation](#), [download](#)]

[niklasb](#)

It contains lots of preliminary analysis and at least the DP approaches described in 1. and 5. of your post. I believe the algorithm is actually called "Held–Karp algorithm" in academic literature, but it was described independently by Bellman et al. in another paper.

A list of optimal algorithms for TSP with better runtime complexity can be found [here](#).

→ [Reply](#)

[Jima](#)

20 months ago, # ^ | ☆

▲ 0 ▼

can't open first link it requires e-mail for link sites.can u help me and give pdf file?

→ [Reply](#)

20 months ago, # ^ | ☆

▲ 0 ▼

Took me two seconds to find another PDF source:

<http://people.cs.vt.edu/~gback/ICPCHandbook/book/copiesfromweb/held-karp-jsiam-1962.pdf>

[niklasb](#)

you're welcome.

→ [Reply](#)

[Jima](#)

20 months ago, # ^ | ☆

▲ 0 ▼

thanks,i am almost newbie on codeforces :d

→ [Reply](#)

[saurabh060792](#)

4 years ago, # | ☆

▲ 0 ▼

In 4th section's second dp formulation second part, the condition stated is **count(mask)>1** only. Isn't **bit(mask, i) == 1** condition should also be included?

→ [Reply](#)

[ank24ben](#)

21 month(s) ago, # | ☆

▲ 0 ▼

can anybody give me link to its implemented code for any of the above part. Rest I got stuck at bit masking in implementation. Thanks in advance whoever will give link.

→ [Reply](#)

21 month(s) ago, # ^ | ☆

← Rev. 2 ▲ 0 ▼

My solution for task D of CF beta round 11.

[reality420](#)

Btw,am i the only one who can't see the solution of others in this contest?i can't even open my solution.

→ [Reply](#)

[Tiny](#)

21 month(s) ago, # ^ | ☆

▲ 0 ▼

me too, something is wrong today, I can't open submission code, including myself, now I can only open my "official"

submissions



submissions.

→ [Reply](#)

21 month(s) ago, # ^ | ☆

▲ 0 ▼



poikniok

Yes also just encountered this problem. Why I try to open my own solution I get "You are not allowed to view the requested page" error.

→ [Reply](#)

21 month(s) ago, # ^ | ☆

▲ 0 ▼



poikniok

I actually have theory now for why this is. I think problem D might have been used in the VK Cup Finals — Trial Contest, and so they blocked solutions so we could not see submission from people in that contest.

→ [Reply](#)

18 months ago, # | ☆

← Rev. 2

▲ +3 ▼



coded_mind

In first Section, consider a graph with only two vertices and one edge of weight say w then the answer computed by the process, comes to be w but expected answer is $2*w$ as for a hamiltonian walk the starting and ending vertices must be same.

→ [Reply](#)

14 months ago, # | ☆

▲ -8 ▼



viralm

In the 7th section, how are those paths included in the answer where we use vertices $v < \text{first}(\text{mask})$. This means, if our bit representation of mask is 1101000, and we want to count no. of paths starting at $\text{first}(\text{mask})=3$ (3rd bit, 0-based indexing from right to left) and ending at vertex $v=5$ (0-based indexing from right to left), how will paths like the one starting from vertex 3 to vertex 5 with vertex 0 on the way (and similar) be counted if we use the dp meaning given in section 7?

→ [Reply](#)

4 days ago, # | ☆

▲ 0 ▼



mahi.mahidhar2

In a hamiltonian walk the vertices might repeat. On the other hand, in a simple path repetition of vertices is not allowed. How is it that using the same dp for ques 3 which was used for ques 2 works? Any insights would be highly appreciated.

→ [Reply](#)

[Codeforces](#) (c) Copyright 2010-2018 Mike Mirzayanov

The only programming contests Web 2.0 platform

Server time: Mar/21/2018 14:09:21^{UTC+5.5} (d3).

Desktop version, switch to [mobile version](#).

[Privacy Policy](#)