

LIUZHOU_101 BLOG TEAMS SUBMISSIONS CONTESTS PROBLEMSETTING

liouzhou_101's blog

Editorial of Codeforces Round #700

By [liouzhou_101](#), [history](#), 102 minutes ago,

1480A - Yet Another String Game

[Tutorial](#)

1480B - The Great Hero

[Tutorial](#)

1479A - Searching Local Minimum

[Tutorial](#)

[problem:1479A]

We maintain by binary search a range $[l, r]$ which has a local minimum. Moreover, we assume that $a_{l-1} > a_l$ and $a_r < a_{r+1}$. Initially, $[l, r] = [1, n]$.

In each iteration, let m be the midpoint of l and r .

Case 1. If $a_m < a_{m+1}$, then the range becomes $[l, m]$.

Case 2. If $a_m > a_{m+1}$, then the range becomes $[m + 1, r]$.

When $l = r$, we have found a local minimum a_l .

The number of queries to a_i is at most $2\lceil \log_2 n \rceil \leq 34 < 100$.

1479B1 - Painting the Array I

[Tutorial](#)

1479B2 - Painting the Array II

[Tutorial](#)

1479C - Continuous City

[Tutorial](#)

1479D - Odd Mineral Resource

[Tutorial](#)

1479E - School Clubs

[Tutorial](#)

Tutorial of Codeforces Round #700 (Div. 1)
 #tutorial

+11 [liouzhou_101](#) 102 minutes ago 49

→ Pay attention

Before contest
[Codeforces Round #701 \(Div. 2\)](#)
5 days

Like One person likes this. [Sign Up](#) to see who likes this post.

→ JacobianDet

Rating: 1426
Contribution: -5

JacobianDet

- [Settings](#)
- [Blog](#)
- [Favourites](#)
- [Teams](#)
- [Submissions](#)
- [Problemsetting](#)
- [Groups](#)
- [Talks](#)
- [Contests](#)

→ Top rated

#	User	Rating
1	tourist	3748
2	Benq	3550
3	maroonrk	3461
4	Um_nik	3437
5	ecnerwala	3386
6	Radewoosh	3352
7	jiangly	3328
8	scott_wu	3313
9	Petr	3309
10	boboniu	3289

[Countries](#) | [Cities](#) | [Organizations](#) [View all →](#)

→ Top contributors

#	User	Contrib.
1	1-gon	201
2	Errichto	198
3	rng_58	195
4	SecondThread	193
5	awoo	188
6	Um_nik	182
7	vovuh	180
8	Ashishgup	175
8	antontrygubO_o	175
10	-is-this-fft-	174