

Find the number of islands | Set 1 (Using DFS)

Given a boolean 2D matrix, find the number of islands. A group of connected 1s forms an island. For example, the below matrix contains 5 islands

3.2


```
Input : mat[][] = {{1, 1, 0, 0, 0},
                  {0, 1, 0, 0, 1},
                  {1, 0, 0, 1, 1},
                  {0, 0, 0, 0, 0},
                  {1, 0, 1, 0, 1}}
```

Output : 5

This is an variation of the standard problem: "Counting number of connected components in a undirected graph".

Before we go to the problem, let us understand what is a connected component. A **connected component** of an undirected graph is a subgraph in which every two vertices are connected to each other by a path(s), and which is connected to no other vertices outside the subgraph.

For example, the graph shown below has three connected components.



Recommended: Please solve it on "PRACTICE" first, before moving on to the solution.

A graph where all vertices are connected with each other, has exactly one connected component, consisting of the whole graph. Such graph with only one connected component is called as Strongly Connected Graph.

The problem can be easily solved by applying DFS() on each component. In each DFS() call, a component or a sub-graph is visited. We will call DFS on the next un-visited component. The number of calls to DFS() gives the number of connected components. BFS can also be used.

What is an island?

A group of connected 1s forms an island. For example, the below matrix contains 5 islands

```
{1, 1, 0, 0, 0},
{0, 1, 0, 0, 1},
{1, 0, 0, 1, 1},
{0, 0, 0, 0, 0},
{1, 0, 1, 0, 1}
```

Recommended: Please solve it on “PRACTICE” first, before moving on to the solution.

A cell in 2D matrix can be connected to 8 neighbors. So, unlike standard DFS(), where we recursively call for all adjacent vertices, here we can recursive call for 8 neighbors only. We keep track of the visited 1s so that they are not visited again.

C/C++

```
// Program to count islands in boolean 2D matrix
#include <stdio.h>
#include <string.h>
#include <stdbool.h>

#define ROW 5
#define COL 5

// A function to check if a given cell (row, col) can be included in DFS
int isSafe(int M[][COL], int row, int col, bool visited[][COL])
{
    // row number is in range, column number is in range and value is 1
    // and not yet visited
    return (row >= 0) && (row < ROW) &&
           (col >= 0) && (col < COL) &&
           (M[row][col] && !visited[row][col]);
}

// A utility function to do DFS for a 2D boolean matrix. It only considers
// the 8 neighbours as adjacent vertices
void DFS(int M[][COL], int row, int col, bool visited[][COL])
{
    // These arrays are used to get row and column numbers of 8 neighbours
    // of a given cell
    static int rowNbr[] = {-1, -1, -1, 0, 0, 1, 1, 1};
    static int colNbr[] = {-1, 0, 1, -1, 1, -1, 0, 1};

    // Mark this cell as visited
    visited[row][col] = true;

    // Recur for all connected neighbours
    for (int k = 0; k < 8; ++k)
        if (isSafe(M, row + rowNbr[k], col + colNbr[k], visited) )
            DFS(M, row + rowNbr[k], col + colNbr[k], visited);
}

// The main function that returns count of islands in a given boolean
// 2D matrix
int countIslands(int M[][COL])
{
    // Make a bool array to mark visited cells.
    // Initially all cells are unvisited
    bool visited[ROW][COL];
```



```

memset(visited, 0, sizeof(visited));

// Initialize count as 0 and traverse through the all cells of
// given matrix
int count = 0;
for (int i = 0; i < ROW; ++i)
    for (int j = 0; j < COL; ++j)
        if (M[i][j] && !visited[i][j]) // If a cell with value 1 is not
            {                           // visited yet, then new island found
                DFS(M, i, j, visited);   // Visit all cells in this island.
                ++count;                 // and increment island count
            }

return count;
}

// Driver program to test above function
int main()
{
    int M[][COL] = { {1, 1, 0, 0, 0},
                     {0, 1, 0, 0, 1},
                     {1, 0, 0, 1, 1},
                     {0, 0, 0, 0, 0},
                     {1, 0, 1, 0, 1}
    };

    printf("Number of islands is: %d\n", countIslands(M));

    return 0;
}

```

Run on IDE

Java

```

// Java program to count islands in boolean 2D matrix
import java.util.*;
import java.lang.*;
import java.io.*;

class Islands
{
    //No of rows and columns
    static final int ROW = 5, COL = 5;

    // A function to check if a given cell (row, col) can
    // be included in DFS
    boolean isSafe(int M[][], int row, int col,
                  boolean visited[][])
    {
        // row number is in range, column number is in range
        // and value is 1 and not yet visited
        return (row >= 0) && (row < ROW) &&
            (col >= 0) && (col < COL) &&
            (M[row][col]==1 && !visited[row][col]);
    }

    // A utility function to do DFS for a 2D boolean matrix.
    // It only considers the 8 neighbors as adjacent vertices
    void DFS(int M[][], int row, int col, boolean visited[][])
    {
        // These arrays are used to get row and column numbers
        // of 8 neighbors of a given cell
        int rowNbr[] = new int[] {-1, -1, -1, 0, 0, 1, 1, 1};
        int colNbr[] = new int[] {-1, 0, 1, -1, 1, -1, 0, 1};

        // Mark this cell as visited
        visited[row][col] = true;

        // Recur for all connected neighbours
        for (int k = 0; k < 8; ++k)
            if (isSafe(M, row + rowNbr[k], col + colNbr[k], visited) )
                DFS(M, row + rowNbr[k], col + colNbr[k], visited);
    }

    // The main function that returns count of islands in a given

```

```
// boolean 2D matrix
int countIslands(int M[][])
{
    // Make a bool array to mark visited cells.
    // Initially all cells are unvisited
    boolean visited[][] = new boolean[ROW][COL];

    // Initialize count as 0 and traverse through the all cells
    // of given matrix
    int count = 0;
    for (int i = 0; i < ROW; ++i)
        for (int j = 0; j < COL; ++j)
            if (M[i][j]==1 && !visited[i][j]) // If a cell with
                                                // value 1 is not
                                                // visited yet, then new island found, Visit all
                                                // cells in this island and increment island count
            {
                DFS(M, i, j, visited);
                ++count;
            }

    return count;
}

// Driver method
public static void main (String[] args) throws java.lang.Exception
{
    int M[][]= new int[][] {{1, 1, 0, 0, 0},
                             {0, 1, 0, 0, 1},
                             {1, 0, 0, 1, 1},
                             {0, 0, 0, 0, 0},
                             {1, 0, 1, 0, 1}};

    Islands I = new Islands();
    System.out.println("Number of islands is: "+ I.countIslands(M));
} //Contributed by Aakash Hasija
```

Run on IDE

Python

```
# Program to count islands in boolean 2D matrix
class Graph:

    def __init__(self, row, col, g):
        self.ROW = row
        self.COL = col
        self.graph = g

    # A function to check if a given cell
    # (row, col) can be included in DFS
    def isSafe(self, i, j, visited):
        # row number is in range, column number
        # is in range and value is 1
        # and not yet visited
        return (i >= 0 and i < self.ROW and
                j >= 0 and j < self.COL and
                not visited[i][j] and self.graph[i][j])

    # A utility function to do DFS for a 2D
    # boolean matrix. It only considers
    # the 8 neighbours as adjacent vertices
    def DFS(self, i, j, visited):

        # These arrays are used to get row and
        # column numbers of 8 neighbours
        # of a given cell
        rowNbr = [-1, -1, -1, 0, 0, 1, 1, 1];
        colNbr = [-1, 0, 1, -1, 1, -1, 0, 1];

        # Mark this cell as visited
        visited[i][j] = True

        # Recur for all connected neighbours
```

```

for k in range(8):
    if self.isSafe(i + rowNbr[k], j + colNbr[k], visited):
        self.DFS(i + rowNbr[k], j + colNbr[k], visited)

# The main function that returns
# count of islands in a given boolean
# 2D matrix
def countIslands(self):
    # Make a bool array to mark visited cells.
    # Initially all cells are unvisited
    visited = [[False for j in range(self.COL)] for i in range(self.ROW)]

    # Initialize count as 0 and traverse
    # through the all cells of
    # given matrix
    count = 0
    for i in range(self.ROW):
        for j in range(self.COL):
            # If a cell with value 1 is not visited yet,
            # then new island found
            if visited[i][j] == False and self.graph[i][j] == 1:
                # Visit all cells in this island
                # and increment island count
                self.DFS(i, j, visited)
                count += 1

    return count

graph = [[1, 1, 0, 0, 0],
         [0, 1, 0, 0, 1],
         [1, 0, 0, 1, 1],
         [0, 0, 0, 0, 0],
         [1, 0, 1, 0, 1]]

row = len(graph)
col = len(graph[0])

g = Graph(row, col, graph)

print "Number of islands is :"
print g.countIslands()

#This code is contributed by Neelam Yadav

```

[Run on IDE](#)

Output:

Number of islands is: 5

Time complexity: $O(\text{ROW} \times \text{COL})$

Find the number of Islands | Set 2 (Using Disjoint Set)

Asked in: Amazon, Citrix, DE Shaw, Informatica, Microsoft, Ola, One97, Opera, Paytm, Snapdeal, Streamoid Technology, Visa

Reference:

http://en.wikipedia.org/wiki/Connected_component_%28graph_theory%29

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.



.COM Domain at Just ₹99

Secure The Domain Name You Want Before it's Taken
Buy Now!

An advertisement for New India Assurance Private Car Package Policy. The background is blue with a red car on the right. The text 'PRIVATE CAR PACKAGE POLICY' is at the top in yellow. Below it, 'HIGHLIGHTS' is written in white. A list of features is shown in white text on a blue background: India's Premier Non-life Insurer, Largest Branch Network, Pan India Presence, Quick Claim Settlement, Attractive Premium, Dedicated Customer Portal, Instant and hassle-free renewals, 100% Secure, and Add On Covers. The toll-free number 1800-209 is also displayed. The New India Assurance logo and name are at the bottom.

GATE CS Corner Company Wise Coding Practice

Graph Matrix DFS graph-connectivity

[Login to Improve this Article](#)

Please write to us at contribute@geeksforgeeks.org to report any issue with the above content.

Recommended Posts:

[Find the number of Islands | Set 2 \(Using Disjoint Set\)](#)

[Depth First Traversal or DFS for a Graph](#)

[Find length of the largest region in Boolean Matrix](#)

[Count all possible walks from a source to a destination with exactly k edges](#)

[Count number of islands where every island is row-wise and column-wise separated](#)

[Minimum initial vertices to traverse whole matrix with given conditions](#)

[Shortest path to reach one prime to other by changing single digit at a time](#)

[Traveling Salesman Problem \(TSP\) Implementation](#)

[Degree Centrality \(Centrality Measure\)](#)

[Water Jug problem using BFS](#)



[\(Login to Rate\)](#)**3.2**Average Difficulty : **3.2/5.0**
Based on **147** vote(s)☐

Add to TODO List

☐

Mark as DONE

Basic

Easy

Medium

Hard

Expert

Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.

Load Comments

Share this post!

@geeksforgeeks, Some rights reserved

Contact Us!

About Us!

Careers!

Privacy Policy



