

Optimization on Deep Learning

Santiago VELASCO-FORERO

<http://cmm.ensmp.fr/velasco/>

MINES ParisTech

PSL Research University

Center for Mathematical Morphology



Contents

- 1 Introduction
- 2 Stochastic Gradient Descent
- 3 Optimizers
- 4 Difficulties in Deep Network Optimisation
- 5 How to fight against overfitting
- 6 References

Contents

- 1 Introduction
- 2 Stochastic Gradient Descent
- 3 Optimizers
- 4 Difficulties in Deep Network Optimisation
- 5 How to fight against overfitting
- 6 References

Contents

- 1 Introduction
- 2 Stochastic Gradient Descent**
- 3 Optimizers
- 4 Difficulties in Deep Network Optimisation
- 5 How to fight against overfitting
- 6 References

Stochastic Gradient Descent (SGD) update

- **Require:** Learning rate ϵ (or a learning rate schedule)
- **Initialization:** $k = 1$, θ_1 some random value.
- **while** stopping criterion not met **do**
 - **Sample** a value from the training set $(x^{(0)}, y^{(0)})$
 - **Gradient** $\hat{g}(\theta_i) = \frac{\partial L(f(x^{(0)}, \theta_i), y^{(0)})}{\partial \theta}$
 - **Update** $\theta_{i+1} = \theta_i - \epsilon \hat{g}(\theta_i)$
 - $k = k + 1$

MiniBatch Stochastic Gradient Descent (MSGD) update

- **Require:** Learning rate ϵ (or a learning rate schedule)
- **Initialization:** $k = 1$, θ_1 some random value.
- **while** stopping criterion not met **do**
- **Sample** m examples from the training set
 $\{(x^{(0)}, y^{(0)}), (x^{(1)}, y^{(1)}), \dots, (x^{(m)}, y^{(m)})\}$
- **Gradient** $\hat{g}(\theta_i) = \frac{1}{m} \frac{\partial \sum_{i=0}^m L(f(x^{(i)}, \theta_i), y^{(i)})}{\partial \theta}$
- **Update** $\theta_{i+1} = \theta_i - \epsilon \hat{g}(\theta_i)$
- $k = k + 1$

Of $m = n$ then we get the BSGD.

Learning Rate

INCLUDE FIGURE

Contents

- 1 Introduction
- 2 Stochastic Gradient Descent
- 3 Optimizers**
- 4 Difficulties in Deep Network Optimisation
- 5 How to fight against overfitting
- 6 References

Table: Optimisers

| Method | Update |
|---------------|---|
| SGD | $\theta_{i+1} = \theta_i - \eta \hat{g}(\theta_i)$ |
| Momentum | $\theta_{i+1} = \theta_i + v_i, v_i = \alpha v_{i-1} - \eta \hat{g}(\theta_i)$ |
| Nesterov Mom. | $\theta_{i+1} = \theta_i + v_i, v_i = \alpha v_{i-1} - \eta \hat{g}(\theta_i + \alpha v_{i-1})$ |
| Adagrad | $\theta_{i+1} = \theta_i - \frac{\eta}{\sqrt{G_{ii} + \epsilon}} \hat{g}(\theta_i)$ |

where G_{ii} is the sum of the squares of the gradients of θ_i up to time step i while ϵ is a smoothing term that avoids division by zero.

From Adagrad to Adadelta

In the Adagrad formulation,

$$\theta_{i+1} = \theta_i - \frac{\eta}{\sqrt{G_{ii} + \epsilon}} \hat{g}(\theta_i) \quad (1)$$

Accordingly, RMSprop (G. Hinton) proposes a rule update model's parameter by

$$\theta_{i+1} = \theta_i - \frac{\eta}{\sqrt{\text{RMS}(g)_i + \epsilon}} \hat{g}(\theta_i) \quad (2)$$

However, the unit in the learning rate don't correspondent with denominator. Thus, Adadelta optimiser update by:

$$\theta_{i+1} = \theta_i - \frac{\text{RMS}(\partial\theta)_{i-1}}{\sqrt{\text{RMS}(g)_i + \epsilon}} \hat{g}(\theta_i) \quad (3)$$

Table: Optimisers

| Method | Update |
|---------------|--|
| SGD | $\theta_{i+1} = \theta_i - \eta \hat{g}(\theta_i)$ |
| Momentum | $\theta_{i+1} = \theta_i + v_i, v_i = \alpha v_{i-1} - \eta \hat{g}(\theta_i)$ |
| Nesterov Mom. | $\theta_{i+1} = \theta_i + v_i, v_i = \alpha v_{i-1} - \eta \hat{g}(\theta_i + \alpha v_{i-1})$ |
| Adagrad | $\theta_{i+1} = \theta_i - \frac{\eta}{\sqrt{G_{ii} + \epsilon}} \hat{g}(\theta_i)$ |
| RMSprop | $\theta_{i+1} = \theta_i - \frac{\eta}{\sqrt{\text{RMS}(g)_i + \epsilon}} \hat{g}(\theta_i)$ |
| Adadelta | $\theta_{i+1} = \theta_i - \frac{\text{RMS}(\partial\theta)_{i-1}}{\sqrt{\text{RMS}(g)_i + \epsilon}} \hat{g}(\theta_i)$ |

where G_{ii} is the sum of the squares of the gradients of θ_i up to time step i while ϵ is a smoothing term that avoids division by zero. RMS is the root mean squared error (RMS) of gradient for $\text{RMS}(g)_i$ or of parameter updates for $\text{RMS}(\partial\theta)_i$

TODO ADAM

Contents

- 1 Introduction
- 2 Stochastic Gradient Descent
- 3 Optimizers
- 4 Difficulties in Deep Network Optimisation**
- 5 How to fight against overfitting
- 6 References



Difficulties in Deep Network Optimisation

- A Local minima / Global minima
- B Saddle Point (Plateaus or Flat Regions)
- C Vanishing Gradient
- D Overfitting
- E Initialization issues


Difficulties in Deep Network Optimisation

A Local minima / Global minima

B Saddle Point (Plateaus or Flat Regions)



Big learning rate



Small learning rate






Figure: Loss Function for VGG56

Reference: **Visualizing the Loss Landscape of Neural Net**
[Li et al., 2017]

Difficulties in Deep Network Optimisation

- C Vanishing Gradient: If feedback signal has to be propagated through a deep stack of layers, the signal may become tenuous or even be lost entirely, rendering the network untrainable. During training, it causes the model's parameter to grow so large so that even a very tiny amount change in the input can cause a great update in later layers' output. The value of layer weights sometimes it overflow and the value becomes NaN.

Fighting against Vanishing Gradient

- 1 Initialization of Weights: Don't initialize to values that are too large.
- 2 Gradient clipping: clips parameters gradients during backpropagation by a maximum value or maximum norm

```
from keras import optimizers

# All parameter gradients will be clipped to
# a maximum value of 0.5 and
# a minimum value of -0.5.
sgd = optimizers.SGD(lr=0.01, clipvalue=0.5)


# All parameter gradients will be clipped to
# a maximum norm of 1.
sgd = optimizers.SGD(lr=0.01, clipnorm=1.)
```

On the difficulty of training Recurrent Neural Networks,
[Pascanu et al., 2013]


Fighting against Vanishing Gradient

3 Skip connections or Shortcuts (Residual Networks):

Without shortcut



With shortcut



Visualizing the Loss Landscape of Neural Net, [Li et al., 2017]

Fighting against Vanishing Gradient

4 Avoid "stuck states" induced by activation function:




Figure: Left: Three activation function Right: Derivative of activation function.

Fighting against Vanishing Gradient

- 5 Regularization: L_2 or L_1 norm applies "weight decay" in the cost function of the network. Note that for many activation function, when the activation value is small, that will be almost linear.

```
from keras import regularizers
model.add(Dense(64, input_dim=64,
                kernel_regularizer=regularizers.l2(0.01),
                activity_regularizer=regularizers.l2(0.01)))
```

Batch Normalization

TODO: FORMULA, EXAMPLES

$$\hat{x}_i = \frac{x_i - \mu_B}{\sqrt{\sigma_B^2}}$$

$$BN_{\gamma, \beta}(x_i) := \gamma \hat{x}_i + \beta$$

where μ_B and σ_B^2 are respectively the mini-batch mean and variance. γ scale and β shift.

- In the original paper, BatchNorm is applied before the applying activation.
- Moving values to zero (activation works better!)
- If we use a high learning rate in a traditional neural network, then the gradients could explode or vanish. Large learning rates can scale the parameters which could amplify the gradients, thus leading to an explosion. But if we do batch normalization, small changes in parameter to one layer do not get propagated to other layers. This makes it possible to use higher learning rates for the optimizers, which otherwise would not have been possible. It also makes gradient propagation in

Supervised Learning (Machine Learning)

- **Data:** N observations $(\mathbf{x}_i, y_i) \in \mathcal{X} \times \mathcal{Y}, i = 1, \dots, N$, **i.i.d.**
- **Model:** $\text{Model}(\mathbf{x}) := \boldsymbol{\theta}^T \boldsymbol{\phi}(\mathbf{x})$ of features $\boldsymbol{\phi}(\mathbf{x}) \in \mathbb{R}^P$
Prediction as linear mapping of features
- **Minimization of Regularized Empirical Risk:** We would like to find $\boldsymbol{\theta}^*$ the solution of:

$$\boldsymbol{\theta}^* := \min_{\boldsymbol{\theta} \in \mathbb{R}^P} \frac{1}{N} \sum_{i=1}^N L(y_i, \boldsymbol{\theta}^T \boldsymbol{\phi}(\mathbf{x}_i)) + \alpha \mathcal{R}(\boldsymbol{\theta})$$

Data fitting + regularizer

where $L(\cdot, \cdot)$ is called the *loss function*.

Other loss functions, other models

- ① Support Vector Machine (SVM): "Hinge" Loss

$$L(y, \boldsymbol{\theta}^T \boldsymbol{\phi}(\mathbf{x})) = \max\{1 - y\boldsymbol{\theta}^T \boldsymbol{\phi}(\mathbf{x}), 0\} \quad (4)$$

- ② Logistic Regression:

$$L(y, \boldsymbol{\theta}^T \boldsymbol{\phi}(\mathbf{x})) = \log(1 + \exp(-y\boldsymbol{\theta}^T \boldsymbol{\phi}(\mathbf{x}))) \quad (5)$$

- ③ Mean Squared Regression:

$$L(y, \boldsymbol{\theta}^T \boldsymbol{\phi}(\mathbf{x})) = \frac{1}{2}(y - \boldsymbol{\theta}^T \boldsymbol{\phi}(\mathbf{x}))^2 \quad (6)$$

- ④ Adaboost

$$L(y, \boldsymbol{\theta}^T \boldsymbol{\phi}(\mathbf{x})) = \exp^{-(y - \boldsymbol{\theta}^T \boldsymbol{\phi}(\mathbf{x}))} \quad (7)$$


- ⑤ Others ...

Minimizing Empirical Risk = Problems!

- Empirical Risk: $\hat{f}(\boldsymbol{\theta}) := \frac{1}{N} \sum_{i=1}^N L(y_i, \boldsymbol{\theta}^T \boldsymbol{\phi}(\mathbf{x}_i))$


Minimizing Empirical Risk = Problems!

- Empirical Risk: $\hat{f}(\theta) := \frac{1}{N} \sum_{i=1}^N L(y_i, \theta^T \phi(\mathbf{x}_i))$
Loss in a training set



Minimizing Empirical Risk = Problems!


- Empirical Risk: $\hat{f}(\theta) := \frac{1}{N} \sum_{i=1}^N L(y_i, \theta^T \phi(\mathbf{x}_i))$
Loss in a training set



- Expected Risk : $f(\theta) := \mathbb{E}_{(\mathbf{x}, y)} L(y, \theta^T \phi(\mathbf{x}))$

Minimizing Empirical Risk = Problems!

- Empirical Risk: $\hat{f}(\theta) := \frac{1}{N} \sum_{i=1}^N L(y_i, \theta^T \phi(\mathbf{x}_i))$
Loss in a training set



- Expected Risk : $f(\theta) := \mathbb{E}_{(\mathbf{x}, y)} L(y, \theta^T \phi(\mathbf{x}))$
Loss in a testing set

There are infinity minimizers of the empirical risk, but most of them have a large expected risk (**overfitting**).

Contents

- 1 Introduction
- 2 Stochastic Gradient Descent
- 3 Optimizers
- 4 Difficulties in Deep Network Optimisation
- 5 How to fight against overfitting**
- 6 References

Bias/Variance Tradeoff

Let $\hat{y} := \text{Model}(\mathbf{x})$ the prediction of a deterministic model evaluated at \mathbf{x}

$$\mathbb{E}_{(\mathbf{x}, y)} [(y - \text{Model}(\mathbf{x}))^2] = \\ \text{Var}[y] + \text{Var}[\text{Model}(\mathbf{x})] + (\text{Bias}[\text{Model}(\mathbf{x})])^2$$





Figure: Underfitting / Overfitting

Underfitting : Prediction with less variance but more bias


Overfitting : Prediction with more variance but less bias

How to judge if a deep machine learning model is overfitting or not?



- Training Set / Testing Set
- Cross-Validation
- $\|\theta\|_p$ is large

1. Early Stopping / ReduceLROnPlateau / Learning Rate Scheduler



1. Early Stopping / ReduceLROnPlateau / Learning Rate Scheduler

```
ES=EarlyStopping(monitor='loss', patience=3)
```

```
#Reduce learning rate when a metric has stopped improving.
```

```
reduce_lr = ReduceLROnPlateau(monitor='val_loss', factor=0.2,patience=5, min_lr=0.001)
```

```
#Only Using Early Stopping
```

```
model.fit(x_train, y_train,epochs=100,batch_size=64,shuffle=True,callbacks=[ES])
```

```
#Using Early Stopping and ReduceLRonPLateau
```

```
model.fit(x_train, y_train,epochs=100,batch_size=64,shuffle=True,callbacks=[ES, reduce_lr])
```

Figure: Callbacks in Keras

2. We need more data!

- Additive Gaussian noise.
- Data augmentation.
- Adversarial Training.

Expected Risk (again)

The expected risk

$$\mathbb{E}_{(\mathbf{x},y)}L(y,\text{Model}) = \int L(y,\text{Model}(\mathbf{x}))dP(\mathbf{x},y) := R(\text{Model})$$

Expected Risk (again)

The expected risk

$$\mathbb{E}_{(\mathbf{x},y)}L(y, \text{Model}) = \int L(y, \text{Model}(\mathbf{x}))dP(\mathbf{x}, y) := R(\text{Model})$$

But the distribution P is **unknown** in most practical situations.

Expected Risk (again)

The expected risk

$$\mathbb{E}_{(\mathbf{x}, y)} L(y, \text{Model}) = \int L(y, \text{Model}(\mathbf{x})) dP(\mathbf{x}, y) := R(\text{Model})$$

But the distribution P is **unknown** in most practical situations. We usually have access to a set of training data $T = \{(\mathbf{x}_i, y_i)\}_{i=1}^N$, where $(\mathbf{x}_i, y_i) \sim P$, for all $i = 1, \dots, N$. Thus, we may approximate P by the *empirical distribution*:

$$P_\delta(\mathbf{x}, y) = \frac{1}{N} \sum_{i=1}^N \delta(\mathbf{x} = \mathbf{x}_i, y = y_i)$$

Empirical Risk (again)

Using the empirical distribution P_δ , we can now approximate the expected risk, by the called *empirical risk*

$$R_\delta(\text{Model}) = \int L(y, \text{Model}(\mathbf{x})) dP_\delta(\mathbf{x}, y) = \frac{1}{N} \sum_{i=1}^N L(\text{Model}(\mathbf{x}_i), y_i) \quad (8)$$

Learning the function f by minimizing (8) is known as the Empirical Risk Minimization (ERM) principle [Vapnik, 1999] (Vapnik, 1998). If the number of parameters are comparable to N , one trivial way to minimize (8) is to **memorize** the whole set of training data (overfitting).

Vicinal Risk Minimization (VRM)

P_δ is only one of the possibility to approximate the true distribution P . [Chapelle et al., 2001] proposed to approximate P by:

$$P_v(\mathbf{x}, y) = \frac{1}{N} \sum_{i=1}^N v(\tilde{\mathbf{x}}, \tilde{y}, |\mathbf{x}_i, y_i)$$

where v is *vicinity distribution* that measure the probability for a "virtual" pair $(\tilde{\mathbf{x}}, \tilde{y})$ to be in the *vicinity* of the training pair (\mathbf{x}, y) .

Vicinal Risk Minimization (VRM)

P_δ is only one of the possibility to approximate the true distribution P . [Chapelle et al., 2001] proposed to approximate P by:

$$P_v(\mathbf{x}, y) = \frac{1}{N} \sum_{i=1}^N v(\tilde{\mathbf{x}}, \tilde{y}, |\mathbf{x}_i, y_i)$$

where v is *vicinity distribution* that measure the probability for a "virtual" pair $(\tilde{\mathbf{x}}, \tilde{y})$ to be in the *vicinity* of the training pair (\mathbf{x}, y) .

1 Gaussian vicinities: $v(\tilde{\mathbf{x}}, \tilde{y}, |\mathbf{x}_i, y_i) = \mathcal{N}(\tilde{\mathbf{x}} - \mathbf{x}, \sigma^2 \mathbf{I}) \delta(\tilde{y} = y)$

Vicinal Risk Minimization (VRM)

P_δ is only one of the possibility to approximate the true distribution P . [Chapelle et al., 2001] proposed to approximate P by:

$$P_v(\mathbf{x}, y) = \frac{1}{N} \sum_{i=1}^N v(\tilde{\mathbf{x}}, \tilde{y}, |\mathbf{x}_i, y_i)$$

where v is *vicinity distribution* that measure the probability for a "virtual" pair $(\tilde{\mathbf{x}}, \tilde{y})$ to be in the *vicinity* of the training pair (\mathbf{x}, y) .

1 Gaussian vicinities: $v(\tilde{\mathbf{x}}, \tilde{y}, |\mathbf{x}_i, y_i) = \mathcal{N}(\tilde{\mathbf{x}} - \mathbf{x}, \sigma^2 \mathbf{I}) \delta(\tilde{y} = y)$

which is equivalent to augmenting the training data with additive Gaussian noise

Keras Gaussian Layer

```
import keras
from keras import Input
from keras.layers import GaussianNoise
dim_input=(256,256)
input_img = Input(shape=dim_input)
x =GaussianNoise(.01)(input_img)
...
```

Figure: Gaussian vicinities in Keras

Why Data-augmentation?

2 Data-augmentation based vicinities:

$P_{agg}(\mathbf{x}, y) = \frac{1}{N} \sum_{i=1}^N \delta(\tilde{\mathbf{x}}, y_i)$, where $\tilde{\mathbf{x}}$ is a random transformation applied \mathbf{x}



Figure: Example of a set of image produce by random transformations (translations, rotations, zooming, ...)

```
training_generator = ImageDataGenerator(  
    rotation_range=40,  
    width_shift_range=0.2,  
    height_shift_range=0.2,  
    rescale=1./255,  
    shear_range=0.2,  
    zoom_range=0.2,  
    horizontal_flip=True,  
    fill_mode='nearest')
```

```
training_generator = train_datagen.flow_from_directory(  
    'data/train', # this is the target directory  
    target_size=(224, 224), # all images will be resized to 150x150  
    batch_size=batch_size)
```

```
model.fit_generator(generator=train_gen.flow(x_train, y_train),  
    steps_per_epoch=steps_per_epoch,  
    epochs=epochs,  
    validation_data=valid_gen.flow(x_validation, y_validation),  
    workers=32)
```

Figure: Data Generator in Keras

Regularisation

- ① "Weight Decay": Again?
- ② Early Stopping
- ③ More data! : Data Augmentation
- ④ More data! : Adversarial Examples
- ⑤ Summing-up: Dropout

How can we reduce the variance of ?

- Remember: given N i.i.d. observations $\mathbf{x}_1, \mathbf{x}_2, \dots, \mathbf{x}_N$ each of them with variance equal to σ^2 .
- What is the variance of $\bar{\mathbf{x}} = \frac{1}{N} \sum_{i=1}^N \mathbf{x}_i$?

How can we reduce the variance of ?

- Remember: given N i.i.d. observations $\mathbf{x}_1, \mathbf{x}_2, \dots, \mathbf{x}_N$ each of them with variance equal to σ^2 .
- What is the variance of $\bar{\mathbf{x}} = \frac{1}{N} \sum_{i=1}^N \mathbf{x}_i$? $\frac{\sigma^2}{N}$
- **Hint:** Train model on different training sets, and use the mean of predictions as final model of prediction.

Dropout




Figure: Left: No Dropout Right: Dropout

- Since dropout can be seen as a stochastic regularization technique
- Avoid memorization!
- Dropout forces to learn more robust features that are useful in conjunction with many different random subsets.
- With H hidden units, each of which can be dropped, we have 2^H possible models!

Dropout




Figure: Left: A unit at training time that is present with probability p and is connected to units in the next layer with weights w . Right: At test time, the unit is always present and the weights are multiplied by p . The output at test time is same as the expected output at training time.

Dropout

```
from keras.layers import Dropout
...
x=Dense(50, activation='relu')(x)
x=Dropout(0.5)(x)
...
```

Figure: Dropout in Keras. Layer with a dropout of $p = .5$

Initialization

- ➊ After the success of CNNs in IVSRC 2012 ([Krizhevsky et al., 2012]), initialization with Gaussian noise with mean equal to zero and standard deviation set to 0.01 and adding bias equal to one for some layers become very popular. But, as mentioned before, it is not possible to train very deep network from scratch with it [Simonyan and Zisserman, 2014]). The problem is caused by the activation (and/or) gradient magnitude in final layers ([He et al., 2016]). Values of $k > 1$ lead to extremely large values of output layers, $k < 1$ leads to a diminish
- ➋ [Glorot and Bengio, 2010] proposed a formula for estimating the standard deviation on the basis of the number of input and output channels of the layers under assumption of no non-linearity between layers. Despite invalidity of the assumption, Glorot initialization works well.
- ➌ Orthogonal : Independently, Saxe et al. [Saxe et al., 2014] showed that orthonormal matrix initialization works much better for linear networks than Gaussian noise, which is only

Contents

- 1 Introduction
- 2 Stochastic Gradient Descent
- 3 Optimizers
- 4 Difficulties in Deep Network Optimisation
- 5 How to fight against overfitting
- 6 References

References I

- [Chapelle et al., 2001] Chapelle, O., Weston, J., Bottou, L., and Vapnik, V. (2001). Vicinal risk minimization. In *Advances in neural information processing systems*, pages 416–422.
- [Glorot and Bengio, 2010] Glorot, X. and Bengio, Y. (2010). Understanding the difficulty of training deep feedforward neural networks. In *Proceedings of the thirteenth international conference on artificial intelligence and statistics*, pages 249–256.
- [He et al., 2016] He, K., Zhang, X., Ren, S., and Sun, J. (2016). Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778.
- [Ioffe and Szegedy, 2015] Ioffe, S. and Szegedy, C. (2015). Batch normalization: Accelerating deep network training by reducing internal covariate shift. *arXiv preprint arXiv:1502.03167*.

References II

- [Krizhevsky et al., 2012] Krizhevsky, A., Sutskever, I., and Hinton, G. E. (2012). Imagenet classification with deep convolutional neural networks. In *Advances in neural information processing systems*, pages 1097–1105.
- [Li et al., 2017] Li, H., Xu, Z., Taylor, G., and Goldstein, T. (2017). Visualizing the loss landscape of neural nets. *arXiv preprint arXiv:1712.09913*.
- [Mishkin and Matas, 2016] Mishkin, D. and Matas, J. (2016). All you need is a good init. *ICML*.
- [Pascanu et al., 2013] Pascanu, R., Mikolov, T., and Bengio, Y. (2013). On the difficulty of training recurrent neural networks. In *International Conference on Machine Learning*, pages 1310–1318.

References III

- [Saxe et al., 2014] Saxe, A. M., McClelland, J. L., and Ganguli, S. (2014). Exact solutions to the nonlinear dynamics of learning in deep linear neural networks. *ICLR*.
- [Simonyan and Zisserman, 2014] Simonyan, K. and Zisserman, A. (2014). Very deep convolutional networks for large-scale image recognition. *arXiv preprint arXiv:1409.1556*.
- [Srivastava et al., 2014] Srivastava, N., Hinton, G., Krizhevsky, A., Sutskever, I., and Salakhutdinov, R. (2014). Dropout: a simple way to prevent neural networks from overfitting. *The Journal of Machine Learning Research*, 15(1):1929–1958.
- [Vapnik, 1999] Vapnik, V. N. (1999). An overview of statistical learning theory. *IEEE transactions on neural networks*, 10(5):988–999.