

Software Requirements Specification for Solar Water Heating Systems

Thulasi Jegatheesan

August 12, 2025

Contents

| | | |
|----------|--|----------|
| 1 | Reference Material | 3 |
| 1.1 | Table of Units | 3 |
| 1.2 | Table of Symbols | 3 |
| 1.3 | Abbreviations and Acronyms | 5 |
| 2 | Introduction | 6 |
| 2.1 | Purpose of Document | 6 |
| 2.2 | Scope of Requirements | 7 |
| 2.3 | Characteristics of Intended Reader | 7 |
| 2.4 | Organization of Document | 7 |
| 3 | General System Description | 7 |
| 3.1 | System Context | 7 |
| 3.2 | User Characteristics | 8 |
| 3.3 | System Constraints | 8 |
| 4 | Specific System Description | 8 |
| 4.1 | Problem Description | 8 |
| 4.1.1 | Terminology and Definitions | 9 |
| 4.1.2 | Physical System Description | 9 |
| 4.1.3 | Goal Statements | 11 |
| 4.2 | Solution Characteristics Specification | 11 |
| 4.2.1 | Assumptions | 11 |
| 4.2.2 | Theoretical Models | 12 |
| 4.2.3 | General Definitions | 15 |
| 4.2.4 | Data Definitions | 17 |
| 4.2.5 | Instance Models | 21 |
| 4.2.6 | Data Constraints | 24 |
| 4.2.7 | Properties of a Correct Solution | 25 |

| | | |
|-----------|---|-----------|
| 5 | Requirements | 25 |
| 5.1 | Functional Requirements | 26 |
| 5.2 | Non-Functional Requirements | 27 |
| 6 | Likely Changes | 27 |
| 7 | Unlikely Changes | 27 |
| 8 | Traceability Matrices and Graphs | 28 |
| 9 | Values of Auxiliary Constants | 33 |
| 10 | References | 34 |

1 Reference Material

This section records information for easy reference.

1.1 Table of Units

The unit system used throughout is SI (Système International d'Unités). In addition to the basic units, several derived units are also used. For each unit, the [Table of Units](#) lists the symbol, a description, and the SI name.

Table 1: Table of Units

| Symbol | Description | SI Name |
|--------|-------------|------------|
| °C | temperature | centigrade |
| J | energy | joule |
| kg | mass | kilogram |
| m | length | metre |
| s | time | second |
| W | power | watt |

1.2 Table of Symbols

The symbols used in this document are summarized in the [Table of Symbols](#) along with their units. The choice of symbols was made to be consistent with the heat transfer literature and with existing documentation for solar water heating systems with no phase change material. The symbols are listed in alphabetical order. For vector quantities, the units shown are for each component of the vector.

Table 2: Table of Symbols

| Symbol | Description | Units |
|------------------|---|-------|
| A_C | Heating coil surface area | m^2 |
| A_C^{\max} | Maximum surface area of coil | m^2 |
| A_{in} | Surface area over which heat is transferred in | m^2 |
| A_{out} | Surface area over which heat is transferred out | m^2 |
| A_{tol} | Absolute tolerance | — |
| AR_{\max} | Maximum aspect ratio | — |
| AR_{\min} | Minimum aspect ratio | — |

Continued on next page

Table 2: Table of Symbols (Continued)

| Symbol | Description | Units |
|-----------------------------|---|--|
| C | Specific heat capacity | $\frac{\text{J}}{\text{kg}^\circ\text{C}}$ |
| C^{L} | Specific heat capacity of a liquid | $\frac{\text{J}}{\text{kg}^\circ\text{C}}$ |
| C_{W} | Specific heat capacity of water | $\frac{\text{J}}{\text{kg}^\circ\text{C}}$ |
| $C_{\text{W}}^{\text{max}}$ | Maximum specific heat capacity of water | $\frac{\text{J}}{\text{kg}^\circ\text{C}}$ |
| $C_{\text{W}}^{\text{min}}$ | Minimum specific heat capacity of water | $\frac{\text{J}}{\text{kg}^\circ\text{C}}$ |
| D | Diameter of tank | m |
| E | Sensible heat | J |
| E_{W} | Change in heat energy in the water | J |
| g | Volumetric heat generation per unit volume | $\frac{\text{W}}{\text{m}^3}$ |
| h | Convective heat transfer coefficient | $\frac{\text{W}}{\text{m}^2\text{C}}$ |
| h_{C} | Convective heat transfer coefficient between coil and water | $\frac{\text{W}}{\text{m}^2\text{C}}$ |
| $h_{\text{C}}^{\text{max}}$ | Maximum convective heat transfer coefficient between coil and water | $\frac{\text{W}}{\text{m}^2\text{C}}$ |
| $h_{\text{C}}^{\text{min}}$ | Minimum convective heat transfer coefficient between coil and water | $\frac{\text{W}}{\text{m}^2\text{C}}$ |
| L | Length of tank | m |
| L_{max} | Maximum length of tank | m |
| L_{min} | Minimum length of tank | m |
| m | Mass | kg |
| m_{W} | Mass of water | kg |
| $\hat{\mathbf{n}}$ | Normal vector | — |
| q | Heat flux | $\frac{\text{W}}{\text{m}^2}$ |
| q_{C} | Heat flux into the water from the coil | $\frac{\text{W}}{\text{m}^2}$ |
| q_{in} | Heat flux input | $\frac{\text{W}}{\text{m}^2}$ |
| q_{out} | Heat flux output | $\frac{\text{W}}{\text{m}^2}$ |
| \mathbf{q} | Thermal flux vector | $\frac{\text{W}}{\text{m}^2}$ |
| R_{tol} | Relative tolerance | — |
| S | Surface | m^2 |
| T | Temperature | $^\circ\text{C}$ |
| ΔT | Change in temperature | $^\circ\text{C}$ |
| T_{C} | Temperature of the heating coil | $^\circ\text{C}$ |

Continued on next page

Table 2: Table of Symbols (Continued)

| Symbol | Description | Units |
|---------------------------------|---|--------------------------------|
| T_{env} | Temperature of the environment | $^{\circ}\text{C}$ |
| T_{init} | Initial temperature | $^{\circ}\text{C}$ |
| T_{W} | Temperature of the water | $^{\circ}\text{C}$ |
| t | Time | s |
| t_{final} | Final time | s |
| $t_{\text{final}}^{\text{max}}$ | Maximum final time | s |
| t_{step} | Time step for simulation | s |
| V | Volume | m^3 |
| V_{tank} | Volume of the cylindrical tank | m^3 |
| V_{W} | Volume of water | m^3 |
| π | Ratio of circumference to diameter for any circle | — |
| ρ | Density | $\frac{\text{kg}}{\text{m}^3}$ |
| ρ_{W} | Density of water | $\frac{\text{kg}}{\text{m}^3}$ |
| $\rho_{\text{W}}^{\text{max}}$ | Maximum density of water | $\frac{\text{kg}}{\text{m}^3}$ |
| $\rho_{\text{W}}^{\text{min}}$ | Minimum density of water | $\frac{\text{kg}}{\text{m}^3}$ |
| τ_{W} | ODE parameter for water related to decay time | s |
| ∇ | Gradient | — |

1.3 Abbreviations and Acronyms

Table 3: Abbreviations and Acronyms

| Abbreviation | Full Form |
|--------------|--------------------------------|
| A | Assumption |
| DD | Data Definition |
| GD | General Definition |
| GS | Goal Statement |
| IM | Instance Model |
| LC | Likely Change |
| ODE | Ordinary Differential Equation |

Continued on next page

Table 3: Abbreviations and Acronyms (Continued)

| Abbreviation | Full Form |
|--------------|--|
| PS | Physical System Description |
| R | Requirement |
| RefBy | Referenced by |
| Refname | Reference Name |
| SRS | Software Requirements Specification |
| SWHSNoPCM | Solar Water Heating System With No Phase Change Material |
| TM | Theoretical Model |
| UC | Unlikely Change |
| Uncert. | Typical Uncertainty |

2 Introduction

Due to increasing costs, diminishing availability, and negative environmental impact of fossil fuels, the demand is high for renewable energy sources and energy storage technology. Solar Water Heating System with no Phase Change Material provide a novel way of storing energy.

The following section provides an overview of the Software Requirements Specification (SRS) for solar water heating systems with no phase change material. The developed program will be referred to as Solar Water Heating System With No Phase Change Material (SWHSNoPCM) based on the original, manually created version of [SWHSNoPCM](#). This section explains the purpose of this document, the scope of the requirements, the characteristics of the intended reader, and the organization of the document.

2.1 Purpose of Document

The primary purpose of this document is to record the requirements of SWHSNoPCM. Goals, assumptions, theoretical models, definitions, and other model derivation information are specified, allowing the reader to fully understand and verify the purpose and scientific basis of SWHSNoPCM. With the exception of **system constraints**, this SRS will remain abstract, describing what problem is being solved, but not how to solve it.

This document will be used as a starting point for subsequent development phases, including writing the design specification and the software verification and validation plan. The design document will show how the requirements are to be realized, including decisions on the numerical algorithms and programming environment. The verification and validation plan will show the steps that will be used to increase confidence in the software documentation and the implementation. Although the SRS fits in a series of documents that follow the so-called waterfall model, the actual development process is not constrained in any way.

Even when the waterfall model is not followed, as Parnas and Clements point out [4], the most logical way to present the documentation is still to “fake” a rational design process.

2.2 Scope of Requirements

The scope of the requirements includes thermal analysis of a single solar water heating tank.

2.3 Characteristics of Intended Reader

Reviewers of this documentation should have an understanding of heat transfer theory from level 3 or 4 mechanical engineering and differential equations from level 1 and 2 calculus. The users of SWHSNoPCM can have a lower level of expertise, as explained in [Sec:User Characteristics](#).

2.4 Organization of Document

The organization of this document follows the template for an SRS for scientific computing software proposed by [2], [6], [7], and [5]. The presentation follows the standard pattern of presenting goals, theories, definitions, and assumptions. For readers that would like a more bottom up approach, they can start reading the [instance models](#) and trace back to find any additional information they require.

The [goal statements](#) are refined to the theoretical models and the [theoretical models](#) to the [instance models](#). The instance model to be solved is referred to as [IM:eBalanceOnWtr](#). The instance model provides the Ordinary Differential Equation (ODE) that models the solar water heating system with no phase change material. SWHSNoPCM solves this ODE.

3 General System Description

This section provides general information about the system. It identifies the interfaces between the system and its environment, describes the user characteristics, and lists the system constraints.

3.1 System Context

[Fig:SysCon](#) shows the system context. A circle represents an external entity outside the software, the user in this case. A rectangle represents the software system itself (SWHSNoPCM). Arrows are used to show the data flow between the system and its environment.



Figure 1: System Context

SWHSNoPCM is mostly self-contained. The only external interaction is through the user interface. The responsibilities of the user and the system are as follows:

- User Responsibilities:
 - Provide the input data to the system, ensuring no errors in the data entry
 - Take care that consistent units are used for input variables
- SWHSNoPCM Responsibilities:
 - Detect data type mismatch, such as a string of characters instead of a floating point number
 - Determine if the inputs satisfy the required physical and software constraints
 - Calculate the required outputs

3.2 User Characteristics

The end user of SWHSNoPCM should have an understanding of undergraduate Level 1 Calculus and Physics.

3.3 System Constraints

There are no system constraints.

4 Specific System Description

This section first presents the problem description, which gives a high-level view of the problem to be solved. This is followed by the solution characteristics specification, which presents the assumptions, theories, and definitions that are used.

4.1 Problem Description

A system is needed to investigate the heating of water in a solar water heating tank.

4.1.1 Terminology and Definitions

This subsection provides a list of terms that are used in the subsequent sections and their meaning, with the purpose of reducing ambiguity and making it easier to correctly understand the requirements.

- Heat flux: The rate of thermal energy transfer through a given surface per unit time.
- Specific heat capacity: The amount of energy required to raise the temperature of the unit mass of a given substance by a given amount.
- Thermal conduction: The transfer of heat energy through a substance.
- Transient: Changing with time.

4.1.2 Physical System Description

The physical system of SWHSNoPCM, as shown in **Fig:Tank**, includes the following elements:

PS1: Tank containing water.

PS2: Heating coil at bottom of tank. (q_C represents the heat flux into the water from the coil.)



Figure 2: Solar water heating tank, with heat flux from heating coil of q_C

4.1.3 Goal Statements

Given the temperature of the heating coil, the initial temperature of the water, and the material properties, the goal statements are:

Predict-Water-Temperature: Predict the temperature of the water over time.

Predict-Water-Energy: Predict the change in heat energy in the water over time.

4.2 Solution Characteristics Specification

The instance models that govern SWHSNoPCM are presented in the [Instance Model Section](#). The information to understand the meaning of the instance models and their derivation is also presented, so that the instance models can be verified.

4.2.1 Assumptions

This section simplifies the original problem and helps in developing the theoretical models by filling in the missing information for the physical system. The assumptions refine the scope by providing more detail.

Thermal-Energy-Only: The only form of energy that is relevant for this problem is thermal energy. All other forms of energy, such as mechanical energy, are assumed to be negligible. (RefBy: [TM:consThermE](#).)

Heat-Transfer-Coeffs-Constant: All heat transfer coefficients are constant over time. (RefBy: [TM:nwtnCooling](#).)

Constant-Water-Temp-Across-Tank: The water in the tank is fully mixed, so the temperature of the water is the same throughout the entire tank. (RefBy: [GD:rocTempSimp](#).)

Density-Water-Constant-over-Volume: The density of water has no spatial variation; that is, it is constant over their entire volume. (RefBy: [GD:rocTempSimp](#).)

Specific-Heat-Energy-Constant-over-Volume: The specific heat capacity of water has no spatial variation; that is, it is constant over its entire volume. (RefBy: [GD:rocTempSimp](#).)

Newton-Law-Convective-Cooling-Coil-Water: Newton's law of convective cooling applies between the heating coil and the water. (RefBy: [GD:htFluxWaterFromCoil](#).)

Temp-Heating-Coil-Constant-over-Time: The temperature of the heating coil is constant over time. (RefBy: [GD:htFluxWaterFromCoil](#) and [LC:Temperature-Coil-Variable-Over-Day](#).)

Temp-Heating-Coil-Constant-over-Length: The temperature of the heating coil does not vary along its length. (RefBy: [LC:Temperature-Coil-Variable-Over-Length](#).)

Charging-Tank-No-Temp-Discharge: The model only accounts for charging the tank, not discharging. The temperature of the water can only increase, or remain constant; it cannot decrease. This implies that the initial temperature is less than (or equal to) the temperature of the heating coil. (RefBy: [LC:Discharging-Tank](#).)

Water-Always-Liquid: The operating temperature range of the system is such that the material (water in this case) is always in liquid state. That is, the temperature will not drop below the melting point temperature of water, or rise above its boiling point temperature. (RefBy: [TM:sensHtE](#), [IM:heatEInWtr](#), [IM:eBalanceOnWtr](#), and [UC:Water-Fixed-States](#).)

Perfect-Insulation-Tank: The tank is perfectly insulated so that there is no heat loss from the tank. (RefBy: [IM:eBalanceOnWtr](#) and [LC:Tank-Lose-Heat](#).)

No-Internal-Heat-Generation-By-Water: No internal heat is generated by the water; therefore, the volumetric heat generation per unit volume is zero. (RefBy: [IM:eBalanceOnWtr](#) and [UC:No-Internal-Heat-Generation](#).)

Atmospheric-Pressure-Tank: The pressure in the tank is atmospheric, so the melting point temperature and boiling point temperature of water are 0°C and 100°C, respectively. (RefBy: [IM:heatEInWtr](#).)

Volume-Coil-Negligible: When considering the volume of water in the tank, the volume of the heating coil is assumed to be negligible. (RefBy: [DD:waterVolume_nopcm](#).)

4.2.2 Theoretical Models

This section focuses on the general equations and laws that SWHSNoPCM is based on.

| | |
|-------------|--|
| Refname | TM:consThermE |
| Label | Conservation of thermal energy |
| Equation | $-\nabla \cdot \mathbf{q} + g = \rho C \frac{\partial T}{\partial t}$ |
| Description | <p>∇ is the gradient (Unitless)</p> <p>\mathbf{q} is the thermal flux vector ($\frac{\text{W}}{\text{m}^2}$)</p> <p>$g$ is the volumetric heat generation per unit volume ($\frac{\text{W}}{\text{m}^3}$)</p> <p>$\rho$ is the density ($\frac{\text{kg}}{\text{m}^3}$)</p> <p>$C$ is the specific heat capacity ($\frac{\text{J}}{\text{kg}^\circ\text{C}}$)</p> <p>$t$ is the time (s)</p> <p>T is the temperature ($^\circ\text{C}$)</p> |
| Notes | <p>The above equation gives the law of conservation of energy for transient heat transfer in a given material.</p> <p>For this equation to apply, other forms of energy, such as mechanical energy, are assumed to be negligible in the system</p> <p>(A:Thermal-Energy-Only).</p> |
| Source | Fourier Law of Heat Conduction and Heat Equation |
| RefBy | GD:rocTempSimp |

| | |
|-------------|--|
| Refname | TM:sensHtE |
| Label | Sensible heat energy (no state change) |
| Equation | $E = C^{\text{L}} m \Delta T$ |
| Description | <p>E is the sensible heat (J)</p> <p>C^{L} is the specific heat capacity of a liquid ($\frac{\text{J}}{\text{kg}^{\circ}\text{C}}$)</p> <p>$m$ is the mass (kg)</p> <p>ΔT is the change in temperature ($^{\circ}\text{C}$)</p> |
| Notes | E occurs as long as the material does not reach a temperature where a phase change occurs, as assumed in A:Water-Always-Liquid . |
| Source | Definition of Sensible Heat |
| RefBy | IM:heatEInWtr |

| | |
|-------------|---|
| Refname | TM:nwtnCooling |
| Label | Newton's law of cooling |
| Equation | $q(t) = h \Delta T(t)$ |
| Description | <p>q is the heat flux ($\frac{\text{W}}{\text{m}^2}$)</p> <p>$t$ is the time (s)</p> <p>h is the convective heat transfer coefficient ($\frac{\text{W}}{\text{m}^2\text{C}}$)</p> <p>$\Delta T$ is the change in temperature ($^{\circ}\text{C}$)</p> |
| Notes | <p>Newton's law of cooling describes convective cooling from a surface. The law is stated as: the rate of heat loss from a body is proportional to the difference in temperatures between the body and its surroundings.</p> <p>h is assumed to be independent of T (from A:Heat-Transfer-Coeffs-Constant).</p> <p>$\Delta T(t) = T(t) - T_{\text{env}}(t)$ is the time-dependant thermal gradient between the environment and the object.</p> |
| Source | [1, (pg. 8)] |
| RefBy | GD:htFluxWaterFromCoil |

4.2.3 General Definitions

This section collects the laws and equations that will be used to build the instance models.

| | |
|-------------|--|
| Refname | GD:rocTempSimp |
| Label | Simplified rate of change of temperature |
| Equation | $m C \frac{dT}{dt} = q_{\text{in}} A_{\text{in}} - q_{\text{out}} A_{\text{out}} + g V$ |
| Description | <p> m is the mass (kg) C is the specific heat capacity ($\frac{\text{J}}{\text{kg}^\circ\text{C}}$) t is the time (s) T is the temperature ($^\circ\text{C}$) q_{in} is the heat flux input ($\frac{\text{W}}{\text{m}^2}$) A_{in} is the surface area over which heat is transferred in (m^2) q_{out} is the heat flux output ($\frac{\text{W}}{\text{m}^2}$) A_{out} is the surface area over which heat is transferred out (m^2) g is the volumetric heat generation per unit volume ($\frac{\text{W}}{\text{m}^3}$) V is the volume (m^3) </p> |
| Source | – |
| RefBy | GD:rocTempSimp and IM:eBalanceOnWtr |

Detailed derivation of simplified rate of change of temperature: Integrating **TM:consThermE** over a volume (V), we have:

$$-\int_V \nabla \cdot \mathbf{q} dV + \int_V g dV = \int_V \rho C \frac{\partial T}{\partial t} dV$$

Applying Gauss's Divergence Theorem to the first term over the surface S of the volume, with \mathbf{q} as the thermal flux vector for the surface and $\hat{\mathbf{n}}$ as a unit outward normal vector for a surface:

$$-\int_S \mathbf{q} \cdot \hat{\mathbf{n}} dS + \int_V g dV = \int_V \rho C \frac{\partial T}{\partial t} dV$$

We consider an arbitrary volume. The volumetric heat generation per unit volume is assumed constant. Then Equation (1) can be written as:

$$q_{\text{in}} A_{\text{in}} - q_{\text{out}} A_{\text{out}} + g V = \int_V \rho C \frac{\partial T}{\partial t} dV$$

Where q_{in} , q_{out} , A_{in} , and A_{out} are explained in **GD:rocTempSimp**. Assuming ρ , C , and T are constant over the volume, which is true in our case by **A:Constant-Water-Temp-Across-**

Tank, [A:Density-Water-Constant-over-Volume](#), and [A:Specific-Heat-Energy-Constant-over-Volume](#), we have:

$$\rho C V \frac{dT}{dt} = q_{\text{in}} A_{\text{in}} - q_{\text{out}} A_{\text{out}} + g V$$

Using the fact that $\rho=m/V$, Equation (2) can be written as:

$$m C \frac{dT}{dt} = q_{\text{in}} A_{\text{in}} - q_{\text{out}} A_{\text{out}} + g V$$

| | |
|-------------|---|
| Refname | GD:htFluxWaterFromCoil |
| Label | Heat flux into the water from the coil |
| Units | $\frac{\text{W}}{\text{m}^2}$ |
| Equation | $q_{\text{C}} = h_{\text{C}} (T_{\text{C}} - T_{\text{W}}(t))$ |
| Description | <p>q_{C} is the heat flux into the water from the coil ($\frac{\text{W}}{\text{m}^2}$)</p> <p>$h_{\text{C}}$ is the convective heat transfer coefficient between coil and water ($\frac{\text{W}}{\text{m}^2\text{C}}$)</p> <p>$T_{\text{C}}$ is the temperature of the heating coil ($^{\circ}\text{C}$)</p> <p>T_{W} is the temperature of the water ($^{\circ}\text{C}$)</p> <p>t is the time (s)</p> |
| Notes | <p>q_{C} is found by assuming that Newton's law of cooling applies (A:Newton-Law-Convective-Cooling-Coil-Water). This law (defined in TM:nwtnCooling) is used on the surface of the heating coil.</p> <p>A:Temp-Heating-Coil-Constant-over-Time</p> |
| Source | [2] |
| RefBy | IM:eBalanceOnWtr |

4.2.4 Data Definitions

This section collects and defines all the data needed to build the instance models.

| | |
|-------------|--|
| Refname | DD:waterMass |
| Label | Mass of water |
| Symbol | m_W |
| Units | kg |
| Equation | $m_W = V_W \rho_W$ |
| Description | m_W is the mass of water (kg) V_W is the volume of water (m ³) ρ_W is the density of water ($\frac{\text{kg}}{\text{m}^3}$) |
| Source | – |
| RefBy | FR:Find-Mass |

| | |
|-------------|--|
| Refname | DD:waterVolume.nopcm |
| Label | Volume of water |
| Symbol | V_W |
| Units | m^3 |
| Equation | $V_W = V_{\text{tank}}$ |
| Description | <p>V_W is the volume of water (m^3)</p> <p>V_{tank} is the volume of the cylindrical tank (m^3)</p> |
| Notes | Based on A:Volume-Coil-Negligible . V_{tank} is defined in DD:tankVolume . |
| Source | — |
| RefBy | FR:Find-Mass |

| | |
|-------------|---|
| Refname | DD:tankVolume |
| Label | Volume of the cylindrical tank |
| Symbol | V_{tank} |
| Units | m^3 |
| Equation | $V_{\text{tank}} = \pi \left(\frac{D}{2}\right)^2 L$ |
| Description | <p>V_{tank} is the volume of the cylindrical tank (m^3)</p> <p>π is the ratio of circumference to diameter for any circle (Unitless)</p> <p>D is the diameter of tank (m)</p> <p>L is the length of tank (m)</p> |
| Source | — |
| RefBy | FR:Find-Mass and DD:waterVolume_nopcm |

| | |
|-------------|--|
| Refname | DD:balanceDecayRate |
| Label | ODE parameter for water related to decay time |
| Symbol | τ_W |
| Units | s |
| Equation | $\tau_W = \frac{m_W C_W}{h_C A_C}$ |
| Description | τ_W is the ODE parameter for water related to decay time (s) m_W is the mass of water (kg) C_W is the specific heat capacity of water ($\frac{J}{kg^\circ C}$) h_C is the convective heat transfer coefficient between coil and water $(\frac{W}{m^2^\circ C})$ A_C is the heating coil surface area (m ²) |
| Source | [2] |
| RefBy | IM:eBalanceOnWtr and FR:Output-Input-Derived-Values |

4.2.5 Instance Models

This section transforms the problem defined in the [problem description](#) into one which is expressed in mathematical terms. It uses concrete symbols defined in the [data definitions](#) to replace the abstract symbols in the models identified in [theoretical models](#) and [general definitions](#).

The goal [GS:Predict-Water-Temperature](#) is met by [IM:eBalanceOnWtr](#) and the goal [GS:Predict-Water-Energy](#) is met by [IM:heatEInWtr](#).

| | |
|--------------------|--|
| Refname | IM:eBalanceOnWtr |
| Label | Energy balance on water to find the temperature of the water |
| Input | $T_C, T_{\text{init}}, t_{\text{final}}, A_C, h_C, C_W, m_W$ |
| Output | T_W |
| Input Constraints | $T_C \geq T_{\text{init}}$ |
| Output Constraints | |
| Equation | $\frac{dT_W}{dt} + \frac{1}{\tau_W} T_W = \frac{1}{\tau_W} T_C$ |
| Description | <p>t is the time (s)</p> <p>T_W is the temperature of the water ($^{\circ}\text{C}$)</p> <p>τ_W is the ODE parameter for water related to decay time (s)</p> <p>T_C is the temperature of the heating coil ($^{\circ}\text{C}$)</p> |
| Notes | <p>τ_W is calculated from DD:balanceDecayRate.</p> <p>The above equation applies as long as the water is in liquid form, $0 < T_W < 100$ ($^{\circ}\text{C}$) where 0 ($^{\circ}\text{C}$) and 100 ($^{\circ}\text{C}$) are the melting and boiling point temperatures of water, respectively (A:Water-Always-Liquid).</p> |
| Source | [2, (with PCM removed)] |
| RefBy | UC:No-Internal-Heat-Generation , FR:Output-Values , FR:Find-Mass , and FR:Calculate-Values |

Detailed derivation of the energy balance on water: To find the rate of change of T_W , we look at the energy balance on water. The volume being considered is the volume of water in the tank V_W , which has mass m_W and specific heat capacity, C_W . Heat transfer occurs in the water from the heating coil as q_C (**GD:htFluxWaterFromCoil**), over area A_C . No heat transfer occurs to the outside of the tank, since it has been assumed to be perfectly

insulated ([A:Perfect-Insulation-Tank](#)). Since the assumption is made that no internal heat is generated ([A:No-Internal-Heat-Generation-By-Water](#)), $g = 0$. Therefore, the equation for [GD:rocTempSimp](#) can be written as:

$$m_W C_W \frac{dT_W}{dt} = q_C A_C$$

Using [GD:htFluxWaterFromCoil](#) for q_C , this can be written as:

$$m_W C_W \frac{dT_W}{dt} = h_C A_C (T_C - T_W)$$

Dividing Equation (2) by $m_W C_W$, we obtain:

$$\frac{dT_W}{dt} = \frac{h_C A_C}{m_W C_W} (T_C - T_W)$$

By substituting τ_W (from [DD:balanceDecayRate](#)), this can be written as:

$$\frac{dT_W}{dt} = \frac{1}{\tau_W} (T_C - T_W)$$

| | |
|--------------------|---|
| Refname | IM:heatEInWtr |
| Label | Heat energy in the water |
| Input | $T_{\text{init}}, m_{\text{W}}, C_{\text{W}}, m_{\text{W}}$ |
| Output | E_{W} |
| Input Constraints | |
| Output Constraints | |
| Equation | $E_{\text{W}}(t) = C_{\text{W}} m_{\text{W}} (T_{\text{W}}(t) - T_{\text{init}})$ |
| Description | <p>E_{W} is the change in heat energy in the water (J)</p> <p>t is the time (s)</p> <p>C_{W} is the specific heat capacity of water ($\frac{\text{J}}{\text{kg}^\circ\text{C}}$)</p> <p>$m_{\text{W}}$ is the mass of water (kg)</p> <p>T_{W} is the temperature of the water ($^\circ\text{C}$)</p> <p>T_{init} is the initial temperature ($^\circ\text{C}$)</p> |
| Notes | <p>The above equation is derived using TM:sensHtE.</p> <p>The change in temperature is the difference between the temperature at time t (s), T_{W} and the initial temperature, T_{init} ($^\circ\text{C}$).</p> <p>This equation applies as long as $0 < T_{\text{W}} < 100^\circ\text{C}$ (A:Water-Always-Liquid, A:Atmospheric-Pressure-Tank).</p> |
| Source | [2] |
| RefBy | FR:Output-Values and FR:Calculate-Values |

4.2.6 Data Constraints

The [Data Constraints Table](#) shows the data constraints on the input variables. The column for physical constraints gives the physical limitations on the range of values that can be taken by the variable. The uncertainty column provides an estimate of the confidence with which

the physical quantities can be measured. This information would be part of the input if one were performing an uncertainty quantification exercise. The constraints are conservative to give the user of the model the flexibility to experiment with unusual situations. The column of typical values is intended to provide a feel for a common scenario. The column for software constraints restricts the range of inputs to reasonable values.

Table 4: Input Data Constraints

| Var | Physical Constraints | Software Constraints | Typical Value | Uncert. |
|--------------------|--|--|---|---------|
| A_C | $A_C > 0$ | $A_C \leq A_C^{\max}$ | 0.12 m ² | 10% |
| C_W | $C_W > 0$ | $C_W^{\min} < C_W < C_W^{\max}$ | 4186 $\frac{\text{J}}{\text{kg}^\circ\text{C}}$ | 10% |
| D | $D > 0$ | $AR_{\min} \leq D \leq AR_{\max}$ | 0.412 m | 10% |
| h_C | $h_C > 0$ | $h_C^{\min} \leq h_C \leq h_C^{\max}$ | 1000 $\frac{\text{W}}{\text{m}^2\text{C}}$ | 10% |
| L | $L > 0$ | $L_{\min} \leq L \leq L_{\max}$ | 1.5 m | 10% |
| T_C | $0 < T_C < 100$ | – | 50 °C | 10% |
| T_{init} | $0 < T_{\text{init}} < 100$ | – | 40 °C | 10% |
| t_{final} | $t_{\text{final}} > 0$ | $t_{\text{final}} < t_{\text{final}}^{\max}$ | 50000 s | 10% |
| t_{step} | $0 < t_{\text{step}} < t_{\text{final}}$ | – | 0.01 s | 10% |
| ρ_W | $\rho_W > 0$ | $\rho_W^{\min} < \rho_W \leq \rho_W^{\max}$ | 1000 $\frac{\text{kg}}{\text{m}^3}$ | 10% |

4.2.7 Properties of a Correct Solution

The **Data Constraints Table** shows the data constraints on the output variables. The column for physical constraints gives the physical limitations on the range of values that can be taken by the variable.

Table 5: Output Data Constraints

| Var | Physical Constraints |
|-------|-------------------------------------|
| T_W | $T_{\text{init}} \leq T_W \leq T_C$ |
| E_W | $E_W \geq 0$ |

5 Requirements

This section provides the functional requirements, the tasks and behaviours that the software is expected to complete, and the non-functional requirements, the qualities that the software is expected to exhibit.

5.1 Functional Requirements

This section provides the functional requirements, the tasks and behaviours that the software is expected to complete.

Input-Values: Input the values from **Tab:ReqInputs**, which define the tank parameters, material properties, and initial conditions.

Find-Mass: Use the inputs in **FR:Input-Values** to find the mass needed for **IM:eBalanceOnWtr**, using **DD:waterMass**, **DD:waterVolume_nopcm**, and **DD:tankVolume**.

Check-Input-with-Physical_Constraints: Verify that the inputs satisfy the required **physical constraints**.

Output-Input-Derived-Values: Output the input values and derived values in the following list: the values (from **FR:Input-Values**), the mass (from **FR:Find-Mass**), and τ_W (from **DD:balanceDecayRate**).

Calculate-Values: Calculate the following values: $T_W(t)$ (from **IM:eBalanceOnWtr**) and $E_W(t)$ (from **IM:heatEInWtr**).

Output-Values: Output $T_W(t)$ (from **IM:eBalanceOnWtr**) and $E_W(t)$ (from **IM:heatEInWtr**).

Table 6: Required Inputs

| Symbol | Description | Units |
|-------------|---|-------------------------|
| A_C | Heating coil surface area | m^2 |
| A_{tol} | Absolute tolerance | — |
| C_W | Specific heat capacity of water | $\frac{J}{kg^\circ C}$ |
| D | Diameter of tank | m |
| E_W | Change in heat energy in the water | J |
| h_C | Convective heat transfer coefficient between coil and water | $\frac{W}{m^2^\circ C}$ |
| L | Length of tank | m |
| R_{tol} | Relative tolerance | — |
| T_C | Temperature of the heating coil | $^\circ C$ |
| T_{init} | Initial temperature | $^\circ C$ |
| t_{final} | Final time | s |
| t_{step} | Time step for simulation | s |
| ρ_W | Density of water | $\frac{kg}{m^3}$ |

5.2 Non-Functional Requirements

This section provides the non-functional requirements, the qualities that the software is expected to exhibit.

Correctness: The outputs of the code have the **properties of a correct solution**.

Verifiability: The code is tested with complete verification and validation plan.

Understandability: The code is modularized with complete module guide and module interface specification.

Reusability: The code is modularized.

Maintainability: If a likely change is made to the finished software, it will take at most 10% of the original development time, assuming the same development resources are available.

6 Likely Changes

This section lists the likely changes to be made to the software.

Temperature-Coil-Variable-Over-Day: **A:Temp-Heating-Coil-Constant-over-Time** - The temperature of the heating coil will change over the course of the day, depending on the energy received from the sun.

Temperature-Coil-Variable-Over-Length: **A:Temp-Heating-Coil-Constant-over-Length** - The temperature of the heating coil will actually change along its length as the water within it cools.

Discharging-Tank: **A:Charging-Tank-No-Temp-Discharge** - The model currently only accounts for charging of the tank. That is, increasing the temperature of the water to match the temperature of the coil. A more complete model would also account for discharging of the tank.

Tank-Lose-Heat: **A:Perfect-Insulation-Tank** - Any real tank cannot be perfectly insulated and will lose heat.

7 Unlikely Changes

This section lists the unlikely changes to be made to the software.

Water-Fixed-States: **A:Water-Always-Liquid** - It is unlikely for the change of water from liquid to a solid, or from liquid to gas to be considered.

No-Internal-Heat-Generation: **A:No-Internal-Heat-Generation-By-Water** - Is used for the derivations of **IM:eBalanceOnWtr**.

8 Traceability Matrices and Graphs

The purpose of the traceability matrices is to provide easy references on what has to be additionally modified if a certain component is changed. Every time a component is changed, the items in the column of that component that are marked with an “X” should be modified as well. [Tab:TraceMatAvsA](#) shows the dependencies of the assumptions on each other. [Tab:TraceMatAvsAll](#) shows the dependencies of the data definitions, theoretical models, general definitions, instance models, requirements, likely changes, and unlikely changes on the assumptions. [Tab:TraceMatRefvsRef](#) shows the dependencies of the data definitions, theoretical models, general definitions, and instance models on each other. [Tab:TraceMatAllvsR](#) shows the dependencies of the requirements and goal statements on the data definitions, theoretical models, general definitions, and instance models.

| | A:Thermal-Energy-Only | A:Heat-Transfer-Coeff |
|---|-----------------------|-------------------------|
| A:Thermal-Energy-Only | | |
| A:Heat-Transfer-Coeffs-Constant | | |
| A:Constant-Water-Temp-Across-Tank | | |
| A:Density-Water-Constant-over-Volume | | |
| A:Specific-Heat-Energy-Constant-over-Volume | | |
| A:Newton-Law-Convective-Cooling-Coil-Water | | |
| A:Temp-Heating-Coil-Constant-over-Time | | |
| A:Temp-Heating-Coil-Constant-over-Length | | |
| A:Charging-Tank-No-Temp-Discharge | | |
| A:Water-Always-Liquid | | |
| A:Perfect-Insulation-Tank | | |
| A:No-Internal-Heat-Generation-By-Water | | |
| A:Atmospheric-Pressure-Tank | | |
| A:Volume-Coil-Negligible | | |
| | A:Thermal-Energy-Only | A:Heat-Transfer-Coeffs- |
| DD:waterMass | | |
| DD:waterVolume__nopcm | | |

| | A:Thermal-Energy-Only | A:Heat-Transfer-Coeffs-C |
|--|-----------------------|--------------------------|
| DD:tankVolume | | |
| DD:balanceDecayRate | | |
| TM:consThermE | X | |
| TM:sensHtE | | |
| TM:nwtnCooling | | X |
| GD:rocTempSimp | | |
| GD:htFluxWaterFromCoil | | |
| IM:eBalanceOnWtr | | |
| IM:heatEInWtr | | |
| FR:Input-Values | | |
| FR:Find-Mass | | |
| FR:Check-Input-with-Physical_Constraints | | |
| FR:Output-Input-Derived-Values | | |
| FR:Calculate-Values | | |
| FR:Output-Values | | |
| NFR:Correctness | | |
| NFR:Verifiability | | |
| NFR:Understandability | | |
| NFR:Reusability | | |
| NFR:Maintainability | | |
| LC:Temperature-Coil-Variable-Over-Day | | |
| LC:Temperature-Coil-Variable-Over-Length | | |
| LC:Discharging-Tank | | |
| LC:Tank-Lose-Heat | | |
| UC:Water-Fixed-States | | |
| UC:No-Internal-Heat-Generation | | |

| | DD:waterMass | DD:waterVolume_nopcm | DD:tankVolume | DD: |
|------------------------|--------------|----------------------|---------------|-----|
| DD:waterMass | | | | |
| DD:waterVolume_nopcm | | | X | |
| DD:tankVolume | | | | |
| DD:balanceDecayRate | | | | |
| TM:consThermE | | | | |
| TM:sensHtE | | | | |
| TM:nwtNCooling | | | | |
| GD:rocTempSimp | | | | |
| GD:htFluxWaterFromCoil | | | | |
| IM:eBalanceOnWtr | | | | X |
| IM:heatEInWtr | | | | |

| | DD:waterMass | DD:waterVolume_nopcm | DD:ta |
|--|--------------|----------------------|-------|
| GS:Predict-Water-Temperature | | | |
| GS:Predict-Water-Energy | | | |
| FR:Input-Values | | | |
| FR:Find-Mass | X | X | X |
| FR:Check-Input-with-Physical_Constraints | | | |
| FR:Output-Input-Derived-Values | | | |
| FR:Calculate-Values | | | |
| FR:Output-Values | | | |
| NFR:Correctness | | | |
| NFR:Verifiability | | | |
| NFR:Understandability | | | |
| NFR:Reusability | | | |
| NFR:Maintainability | | | |

The purpose of the traceability graphs is also to provide easy references on what has to be additionally modified if a certain component is changed. The arrows in the graphs

represent dependencies. The component at the tail of an arrow is depended on by the component at the head of that arrow. Therefore, if a component is changed, the components that it points to should also be changed. **Fig:TraceGraphAvsA** shows the dependencies of assumptions on each other. **Fig:TraceGraphAvsAll** shows the dependencies of data definitions, theoretical models, general definitions, instance models, requirements, likely changes, and unlikely changes on the assumptions. **Fig:TraceGraphRefvsRef** shows the dependencies of data definitions, theoretical models, general definitions, and instance models on each other. **Fig:TraceGraphAllvsR** shows the dependencies of requirements and goal statements on the data definitions, theoretical models, general definitions, and instance models. **Fig:TraceGraphAllvsAll** shows the dependencies of dependencies of assumptions, models, definitions, requirements, goals, and changes with each other.



Figure 3: TraceGraphAvsA



Figure 4: TraceGraphAvsAll



Figure 5: TraceGraphRefsvRef



Figure 6: TraceGraphAllvsR



Figure 7: TraceGraphAllvsAll

For convenience, the following graphs can be found at the links below:

- [TraceGraphAvsA](#)
- [TraceGraphAvsAll](#)
- [TraceGraphRefvsRef](#)
- [TraceGraphAllvsR](#)
- [TraceGraphAllvsAll](#)

9 Values of Auxiliary Constants

This section contains the standard values that are used for calculations in SWHSNoPCM.

Table 11: Auxiliary Constants

| Symbol | Description | Value | Unit |
|--------------|------------------------------|--------|----------------|
| A_C^{\max} | maximum surface area of coil | 100000 | m ² |

Continued on next page

Table 11: Auxiliary Constants (Continued)

| Symbol | Description | Value | Unit |
|---------------------------|---|-------|--|
| AR_{\max} | maximum aspect ratio | 100 | – |
| AR_{\min} | minimum aspect ratio | 0.01 | – |
| C_W^{\max} | maximum specific heat capacity of water | 4210 | $\frac{\text{J}}{\text{kg}^\circ\text{C}}$ |
| C_W^{\min} | minimum specific heat capacity of water | 4170 | $\frac{\text{J}}{\text{kg}^\circ\text{C}}$ |
| h_C^{\max} | maximum convective heat transfer coefficient between coil and water | 10000 | $\frac{\text{W}}{\text{m}^2\text{C}}$ |
| h_C^{\min} | minimum convective heat transfer coefficient between coil and water | 10 | $\frac{\text{W}}{\text{m}^2\text{C}}$ |
| L_{\max} | maximum length of tank | 50 | m |
| L_{\min} | minimum length of tank | 0.1 | m |
| t_{final}^{\max} | maximum final time | 86400 | s |
| ρ_W^{\max} | maximum density of water | 1000 | $\frac{\text{kg}}{\text{m}^3}$ |
| ρ_W^{\min} | minimum density of water | 950 | $\frac{\text{kg}}{\text{m}^3}$ |

10 References

- [1] F. P. Incropera et al. *Fundamentals of Heat and Mass Transfer*. 6th ed. Hoboken, New Jersey: John Wiley and Sons, 2007.
- [2] Nirmitha Koothoor. “A Document Driven Approach to Certifying Scientific Computing Software”. MA thesis. Hamilton, ON, Canada: McMaster University, 2013.
- [3] Marilyn Lightstone. *Derivation of tank/pcm model*. From Marilyn Lightstone’s Personal Notes. 2012.
- [4] David L. Parnas and P. C. Clements. “A rational design process: How and why to fake it”. In: *IEEE Transactions on Software Engineering* 12.2 (Feb. 1986), pp. 251–257.
- [5] W. Spencer Smith and Nirmitha Koothoor. “A Document-Driven Method for Certifying Scientific Computing Software for Use in Nuclear Safety Analysis”. In: *Nuclear Engineering and Technology* 48.2 (Apr. 2016), pp. 404–418.
- [6] W. Spencer Smith and Lei Lai. “A new requirements template for scientific computing”. In: *Proceedings of the First International Workshop on Situational Requirements Engineering Processes - Methods, Techniques and Tools to Support Situation-Specific Requirements Engineering Processes, SREP’05*. Ed. by PJ Agerfalk, N. Kraiem, and J. Ralyte. In conjunction with 13th IEEE International Requirements Engineering Conference, Paris, France, 2005, pp. 107–121.

- [7] W. Spencer Smith, Lei Lai, and Ridha Khedri. “Requirements Analysis for Engineering Computation: A Systematic Approach for Improving Software Reliability”. In: *Reliable Computing, Special Issue on Reliable Engineering Computation* 13.1 (Feb. 2007), pp. 83–107.