

A Machine-checked Formal Proof of Birkhoff's Variety Theorem in Martin-Löf Type Theory

William DeMeo ✉ 

<https://williamdemeo.org>

Jacques Carette ✉ 

McMaster University

1 Introduction

The Agda Universal Algebra Library (*agda-algebras*) is a collection of types and programs (theorems and proofs) formalizing the foundations of universal algebra in dependent type theory using the *Agda* programming language and proof assistant. The *agda-algebras* library now includes a substantial collection of definitions, theorems, and proofs from universal algebra and equational logic and as such provides many examples that exhibit the power of inductive and dependent types for representing and reasoning about general algebraic and relational structures.

The first major milestone of the *agda-algebras* project is a new formal proof of *Birkhoff's variety theorem* (also known as the *HSP theorem*), the first version of which was completed in January of 2021. To the best of our knowledge, this was the first time Birkhoff's theorem had been formulated and proved in dependent type theory and verified with a proof assistant.

In this paper, we present a subset of the *agda-algebras* library that culminates in a complete, self-contained, formal proof of the HSP theorem. In the course of our exposition of the proof, we discuss some of the more challenging aspects of formalizing universal algebra in type theory and the issues that arise when attempting to constructively prove some of the basic results in that area. We demonstrate that dependent type theory and Agda, despite the demands they place on the user, are accessible to working mathematicians who have sufficient patience and a strong enough desire to constructively codify their work and formally verify the correctness of their results.

Our presentation may be viewed as a sobering glimpse at the painstaking process of doing mathematics in the languages of dependent types and Agda. Nonetheless we hope to make a compelling case for investing in these languages. Indeed, we are excited to share the gratifying rewards that come with some mastery of type theory and interactive theorem proving technologies.

2 Preliminaries

2.1 Logical foundations

An Agda program typically begins by setting some language options and by importing types from existing Agda libraries. The language options are specified using the *OPTIONS pragma* which affect control the way Agda behaves by controlling the deduction rules that are available to us and the logical axioms that are assumed when the program is type-checked by Agda to verify its correctness. Every Agda program in the *agda-algebras* library begins with the following line.

```
{-# OPTIONS -without-K -exact-split -safe #-}
```

These options control certain foundational assumptions that Agda makes when type-checking the program to verify its correctness.



This work and the *agda-algebras* library by William DeMeo and the *agda-algebras* team is licensed under a [Creative Commons Attribution-ShareAlike 4.0 International License](https://creativecommons.org/licenses/by-sa/4.0/).

- `--without-K` disables Streicher’s *K* axiom ; see also the section on axiom *K* in the Agda Language Reference Manual.
- `--exact-split` makes Agda accept only those definitions that behave like so-called *judgmental* equalities. Martín Escardó explains this by saying it “makes sure that pattern matching corresponds to Martin-Löf eliminators;” see also the Pattern matching and equality section of the Agda Tools documentation.
- `safe` ensures that nothing is postulated outright—every non-MLTT axiom has to be an explicit assumption (e.g., an argument to a function or module); see also this section of the Agda Tools documentation and the Safe Agda section of the Agda Language Reference.

2.2 Agda Modules

The `OPTIONS` pragma is usually followed by the start of a module. Indeed, the `HSP.lagda` program that is subject of this paper begins with the following `import` directives, which import the parts of the Agda Standard Library that we will use in our program.

```
{-# OPTIONS --without-K --exact-split --safe #-}

open import Algebras.Basic using ( ⓪ ; ℳ ; Signature )
module Demos.HSP {S : Signature ⓪ ℳ} where
open import Agda.Primitive using ( _⊔_ ; lsuc ) renaming ( Set to Type )
open import Data.Product using ( Σ-syntax ; _×_ ; _,_ ; Σ ) renaming ( proj₁ to fst ; proj₂ to snd )
open import Function using ( id ; _∘_ ; flip ; Surjection ) renaming ( Func to _→_ )
open import Level using ( Level )
open import Relation.Binary using ( Setoid ; Rel ; IsEquivalence )
open import Relation.Binary.Definitions using ( Reflexive ; Sym ; Trans ; Symmetric ; Transitive )
open import Relation.Unary using ( Pred ; _⊆_ ; _∈_ )
open import Relation.Binary.PropositionalEquality as ≡ using ( _≡_ )
import Function.Definitions as FD
import Relation.Binary.Reasoning.Setoid as SetoidReasoning
open _→_ using ( cong ) renaming ( f to _⟨$⟩_ )
private variable
  α ρa β ρb γ ρc δ ρd ρ χ ℓ : Level
  Γ Δ : Type χ
  f : fst S
```

2.3 Setoids

A *setoid* is a type packaged with an equivalence relation on that type. Setoids are very useful for representing classical (set-theory-based) mathematics in a constructive, type-theoretic setting because most mathematical structures are assumed to come equipped with some (often implicit) notion of equality.

The `agda-algebras` library was first developed without the use of setoids, opting instead for experimenting with specially constructed quotient types. However, this approach resulted in a code base that was hard to comprehend and it became difficult to determine whether the resulting proofs were fully constructive. In particular, our initial proof of the Birkhoff variety theorem required postulating function extensionality, an axiom that is not provable in pure Martin-Löf type theory.[reference needed]

In contrast, our current approach uses setoids and thus makes explicit notions of equality manifest for each type and makes it easier to determine the correctness and constructivity of the proofs. Indeed, using setoids we need no additional axioms beyond Martin-Löf type theory; in particular, no function extensionality axioms are postulated in our current formalization of Birkhoff’s variety theorem.

Since it plays such a central role in the present development and exposition, we reproduce in the appendix the definition of the `Setoid` type of the [Agda Standard Library](#). In addition to `Setoid`, much of our code employs the standard library’s `Func` record type which represents a function from one setoid to another and packages such a function with a proof (called `cong`) that the function respects the underlying setoid equalities. The definition of the `Func` type appears in the appendix. In the list of imports above we rename `Func` to the (more visually appealing) long-arrow symbol \longrightarrow , but we will refer to inhabitants of the `Func` type as “setoid functions” or “funcs” throughout this paper.

A special example of a func is the identity function from a setoid to itself. We define it, along with a composition-of-funcs operation, as follows.

```
id : {A : Setoid α ρa} → A → A
id {A} = record { f = id ; cong = id }

_⟨o⟩_ : {A : Setoid α ρa} {B : Setoid β ρb} {C : Setoid γ ρc}
      → B → C → A → B → A → C

f ⟨o⟩ g = record { f = (λ x. f x) ∘ (λ x. g x)
                  ; cong = (cong f) ∘ (cong g) }
```

2.4 Projection notation

The definition of Σ (and thus, of \times) includes the fields `proj1` and `proj2` representing the first and second projections out of the product. However, we prefer the shorter names `fst` and `snd`. Sometimes we prefer to denote these projections by `|_` and `||_|`, respectively. We define these alternative notations for projections out of pairs as follows.

```
module _ {A : Type α} {B : A → Type β} where

  |_ : Σ[ x ∈ A ] B x → A
  |_ = fst

  ||_| : (z : Σ[ a ∈ A ] B a) → B | z |
  ||_| = snd
```

Here we put the definitions inside an *anonymous module*, which starts with the `module` keyword followed by an underscore (instead of a module name). The purpose is simply to move the postulated typing judgments—the “parameters” of the module (e.g., $A : \text{Type } \alpha$)—out of the way so they don’t obfuscate the definitions inside the module.

2.5 Inverses of functions on setoids

(cf. the `Overture.Func.Inverses` module of the [agda-algebras](#) library.)

We define a data type that represent the semantic concept of the *image* of a function.

```
module _ {A : Setoid α ρa} {B : Setoid β ρb} where
```

```

open Setoid A using () renaming ( Carrier to A )
open Setoid B using ( _≈_ ; sym ) renaming ( Carrier to B )

data Image_⇒_ (F : A → B) : B → Type (α ⊔ β ⊔ ρb) where
  eq : {b : B} → (a : A) → b ≈ (F ⟨$⟩ a) → Image F ⇒ b

open Image_⇒_

```

An inhabitant of $\text{Image } f \ni b$ is a dependent pair (a, p) , where $a : A$ and $p : b \approx f a$ is a proof that f maps a to b . Since the proof that b belongs to the image of f is always accompanied by a witness $a : A$, we can actually *compute* a (pseudo)inverse of f . For convenience, we define this inverse function, which we call Inv , and which takes an arbitrary $b : B$ and a (witness, proof)-pair, $(a, p) : \text{Image } f \ni b$, and returns the witness a .

```

Inv : (F : A → B){b : B} → Image F ⇒ b → A
Inv _ (eq a _) = a

```

In fact, $\text{Inv } f$ is the range-restricted right-inverse of f , which we prove as follows.

```

InvIsInverser : {F : A → B}{b : B}(q : Image F ⇒ b) → (F ⟨$⟩ (Inv F q)) ≈ b
InvIsInverser (eq _ p) = sym p

```

2.6 Injective functions on setoids

(cf. the `Overture.Func.Injective` module of the `agda-algebras` library.)

Naturally, we call a function $f : A \rightarrow B$ from one setoid (A, \approx_0) to another (B, \approx_1) and *injective* function provided $\forall a_0 a_1$, if $f \langle \$ \rangle a_0 \approx_1 f \langle \$ \rangle a_1$, then $a_0 \approx_0 a_1$. The Agda Standard Library defines the type `Injective` to representing injective functions on bare types and we use this to define the type `IsInjective` which represents the property of being an injective function from one setoid to another.

```

module _ {A : Setoid α ρa}{B : Setoid β ρb} where
  open Setoid A using () renaming ( _≈_ to _≈1_ )
  open Setoid B using () renaming ( _≈_ to _≈2_ )
  open FD _≈1_ _≈2_

  IsInjective : (A → B) → Type (α ⊔ ρa ⊔ ρb)
  IsInjective f = Injective ( _⟨$⟩_ f )

```

Proving that the composition of injective functions on setoids is again injective is simply a matter of composing the two assumed witnesses to injectivity.

```

module compose {A : Type α}{B : Type β}{C : Type γ}
  (_≈1_ : Rel A ρa)(_≈2_ : Rel B ρb})(_≈3_ : Rel C ρc) where
  open FD {A = A} {B} _≈1_ _≈2_ using () renaming ( Injective to InjectiveAB )
  open FD {A = B} {C} _≈2_ _≈3_ using () renaming ( Injective to InjectiveBC )
  open FD {A = A} {C} _≈1_ _≈3_ using () renaming ( Injective to InjectiveAC )

  ○-injective-func : {f : A → B}{g : B → C} → InjectiveAB f → InjectiveBC g → InjectiveAC (g ∘ f)
  ○-injective-func finj ginj = finj ∘ ginj

```

2.7 Surjective functions on setoids

(cf. the `Overture.Func.Surjective` module of the `agda-algebras` library.)

A *surjective function* from one setoid $\mathbf{A} = (A, \approx_0)$ to another $\mathbf{B} = (B, \approx_1)$ is a function $f : \mathbf{A} \rightarrow \mathbf{B}$ such that for all $b : B$ there exists $a : A$ such that $(f \langle \$ \rangle a) \approx_1 b$. In other words, the range and codomain of f agree. Here is how we codify this notion in the `agda-algebras` library.

```
module _ {A : Setoid α ρa} {B : Setoid β ρb} where
  open Surjection renaming (f to _⟨$⟩_)
  open Setoid A using () renaming (Carrier to A)
  open Setoid B using () renaming (Carrier to B; _≈_ to _≈2_ )

  IsSurjective : (A → B) → Type (α ⊔ β ⊔ ρb)
  IsSurjective F = ∀ {y} → Image F ∋ y where open Image_∋_
```

With the next definition we represent a *right-inverse* of a surjective function.

```
SurjInv : (f : A → B) → IsSurjective f → B → A
SurjInv f fE b = Inv f (fE {b})
```

Thus, a right-inverse of f is obtained by applying `Inv` to f and a proof of `IsSurjective` f . Next we prove that this does indeed give the right-inverse. Thereafter, we prove that surjectivity is preserved under composition as follows.

```
SurjInvIsInverser : (f : A → B) (fE : IsSurjective f)
  → ∀ {b} → (f ⟨$⟩ ((SurjInv f fE) b)) ≈2 b
SurjInvIsInverser f fE = InvIsInverser fE

module _ {A : Setoid α ρa} {B : Setoid β ρb} {C : Setoid γ ρc}
  {G : A → C} {H : C → B} where
  open Surjection renaming (f to _⟨$⟩_)
  open Setoid B using (trans ; sym)

  o-IsSurjective : IsSurjective G → IsSurjective H → IsSurjective (H ⟨o⟩ G)
  o-IsSurjective gE hE {y} = Goal
  where
    mp : Image H ∋ y → Image H ⟨o⟩ G ∋ y
    mp (eq c p) = η gE
    where
      η : Image G ∋ c → Image H ⟨o⟩ G ∋ y
      η (eq a q) = eq a (trans p (cong H q))

    Goal : Image H ⟨o⟩ G ∋ y
    Goal = mp hE
```

2.8 Kernels

The *kernel* of a function $f : A \rightarrow B$ is defined informally by $\{(x, y) \in A \times A : f x = f y\}$. This can be represented in Agda in a number of ways, but for our purposes it is most convenient to define the kernel as an inhabitant of a (unary) predicate over the square of the function's domain, as follows.

```

module _ {A : Type α} {B : Type β} where

  kernel : Rel B ρ → (A → B) → Pred (A × A) ρ
  kernel _≈_ f (x , y) = f x ≈ f y

```

The kernel of a function $f : A \rightarrow B$ from a setoid A to a setoid B (with carriers A and B , respectively) is defined informally by $\{(x, y) \in A \times A : f \langle \$ \rangle x \approx_2 f \langle \$ \rangle y\}$ and may be defined in Agda as follows.

```

module _ {A : Setoid α ρa} {B : Setoid β ρb} where
  open Setoid A using () renaming (Carrier to A)

  ker : (A → B) → Pred (A × A) ρb
  ker g (x , y) = g ⟨$⟩ x ≈ g ⟨$⟩ y where open Setoid B using ( _≈_ )

```

3 Algebras

3.1 Basic definitions

Here we define algebras over a setoid, instead of a mere type with no equivalence on it.

First we define an operator that translates an ordinary signature into a signature over a setoid domain.

```

open Setoid using (Carrier ; isEquivalence)

EqArgs : {S : Signature ℳ V} {ξ : Setoid α ρa}
  → ∀ {f g} → f ≡ g → (|| S || f → Carrier ξ) → (|| S || g → Carrier ξ) → Type (V ⊔ ρa)

EqArgs {ξ = ξ} ≡ .refl u v = ∀ i → u i ≈ v i
where
  open Setoid ξ using ( _≈_ )

module _ where
  open Setoid using ( _≈_ )
  open IsEquivalence using ( refl ; sym ; trans )

  ⟨_⟩ : Signature ℳ V → Setoid α ρa → Setoid _ _
  Carrier (⟨ S ⟩ ξ) = Σ[ f ∈ | S | ] ((|| S || f) → ξ.Carrier)
  _≈_ (⟨ S ⟩ ξ) (f , u) (g , v) = Σ[ eqv ∈ f ≡ g ] EqArgs {ξ = ξ} eqv u v
  refl (isEquivalence (⟨ S ⟩ ξ)) = ≡.refl , λ _ → Setoid.refl ξ
  sym (isEquivalence (⟨ S ⟩ ξ)) (≡.refl , g) = ≡.refl , λ i → Setoid.sym ξ (g i)
  trans (isEquivalence (⟨ S ⟩ ξ)) (≡.refl , g) (≡.refl , h) = ≡.refl , λ i → Setoid.trans ξ (g i) (h i)

```

We represent an algebra using a record type with two fields: **Domain** is a setoid denoting the underlying *universe* of the algebra (informally, the set of elements of the algebra); **Interp** represents the *interpretation* in the algebra of each operation symbol of the given signature. The record type **Func** from the Agda Standard Library provides what we need for an operation on the domain setoid.

Let us present the definition of the **Algebra** type and then discuss the definition of the **Func** type that provides the interpretation of each operation symbol.

```

record Algebra  $\alpha$   $\rho$  : Type ( $\mathbb{O} \sqcup \mathcal{V} \sqcup \text{Isuc } (\alpha \sqcup \rho)$ ) where
  field
    Domain : Setoid  $\alpha$   $\rho$ 
    Interp : ( $\langle S \rangle$  Domain)  $\rightarrow$  Domain
     $\equiv \rightarrow \approx$  :  $\forall \{x\} \{y\} \rightarrow x \equiv y \rightarrow (\text{Setoid}.\_ \approx \_ \text{Domain}) \times y$ 
     $\equiv \rightarrow \approx \equiv \text{refl} = \text{Setoid.refl Domain}$ 

```

We have thus codified the concept of (universal) algebra as a record type with two fields

1. a function $f : \text{Carrier } (\langle S \rangle \text{Domain}) \rightarrow \text{Carrier Domain}$
2. a proof $\text{cong} : f \text{ Preserves } _ \approx_1 _ \rightarrow _ \approx_2 _$ that f preserves the underlying setoid equalities.

Comparing this with the definition of the `Func` (or `$_ \rightarrow _$`) type shown in the appendix, here \mathbf{A} is `Carrier ($\langle S \rangle$ Domain)` and \mathbf{B} is `Carrier Domain`. Thus `Interp` gives, for each operation symbol in the signature S , a setoid function f —namely, a function where the domain is a power of `Domain` and the codomain is `Domain`—along with a proof that all operations so interpreted respect the underlying setoid equality on `Domain`.

We define the following syntactic sugar: if \mathbf{A} is an algebra, $\mathbb{D}[\mathbf{A}]$ gives the setoid `Domain \mathbf{A}` , while $\mathbb{U}[\mathbf{A}]$ exposes the underlying carrier or “universe” of the algebra \mathbf{A} ; finally, $f^\wedge \mathbf{A}$ denotes the interpretation in the algebra \mathbf{A} of the operation symbol f .

```

open Algebra

 $\mathbb{U}[\_]$  : Algebra  $\alpha$   $\rho^a \rightarrow$  Type  $\alpha$ 
 $\mathbb{U}[\mathbf{A}] = \text{Carrier } (\text{Domain } \mathbf{A})$ 

 $\mathbb{D}[\_]$  : Algebra  $\alpha$   $\rho^a \rightarrow$  Setoid  $\alpha$   $\rho^a$ 
 $\mathbb{D}[\mathbf{A}] = \text{Domain } \mathbf{A}$ 

 $\_^\wedge \_$  : ( $f : |S|$ ) ( $\mathbf{A} : \text{Algebra } \alpha$   $\rho^a$ )  $\rightarrow$  ( $|S| \parallel f \rightarrow \mathbb{U}[\mathbf{A}] \rightarrow \mathbb{U}[\mathbf{A}]$ )

 $f^\wedge \mathbf{A} = \lambda a \rightarrow (\text{Interp } \mathbf{A}) \langle \$ \rangle (f, a)$ 

```

3.2 Universe lifting of algebra types

```

module  $\_$  ( $\mathbf{A} : \text{Algebra } \alpha$   $\rho^a$ ) where
  open Algebra  $\mathbf{A}$  using () renaming ( Domain to  $\mathbf{A}$  ; Interp to InterpA )
  open Setoid  $\mathbf{A}$  using (sym ; trans) renaming ( Carrier to  $|\mathbf{A}|$  ;  $\_ \approx \_$  to  $\_ \approx_1 \_$  ; refl to refl1 )

  open Level

  Lift-Alg $\ell$  : ( $\ell : \text{Level}$ )  $\rightarrow$  Algebra ( $\alpha \sqcup \ell$ )  $\rho^a$ 

  Domain (Lift-Alg $\ell$   $\ell$ ) = record { Carrier = Lift  $\ell$   $|\mathbf{A}|$ 
    ;  $\_ \approx \_$  =  $\lambda x y \rightarrow \text{lower } x \approx_1 \text{lower } y$ 
    ; isEquivalence = record { refl = refl1
    ; sym = sym
    ; trans = trans }}

  Interp (Lift-Alg $\ell$   $\ell$ )  $\langle \$ \rangle$  ( $f, \text{la}$ ) = lift (( $f^\wedge \mathbf{A}$ ) (lower  $\circ$  la))
  cong (Interp (Lift-Alg $\ell$   $\ell$ )) ( $\equiv.\text{refl}$ , la=lb) = cong InterpA (( $\equiv.\text{refl}$ , la=lb))

```

```

Lift-Algr : (ℓ : Level) → Algebra α (ρa ⊔ ℓ)

Domain (Lift-Algr ℓ) =
  record { Carrier = |A|
        ; _≈_ = λ x y → Lift ℓ (x ≈1 y)
        ; isEquivalence = record { refl = lift refl1
                                   ; sym = λ x → lift (sym (lower x))
                                   ; trans = λ x y → lift (trans (lower x) (lower y)) }}

Interp (Lift-Algr ℓ) ($) (f , la) = (f ^ A) la
cong (Interp (Lift-Algr ℓ)) (≡.refl , la≡lb) =
  lift (cong (Interp A) (≡.refl , λ i → lower (la≡lb i)))

Lift-Alg : (A : Algebra α ρa)(ℓ0 ℓ1 : Level) → Algebra (α ⊔ ℓ0) (ρa ⊔ ℓ1)
Lift-Alg A ℓ0 ℓ1 = Lift-Algr (Lift-Algl A ℓ0) ℓ1

```

3.3 Product Algebras

(cf. the `Algebras.Func.Products` module of the `Agda Universal Algebra Library`.)

```

module _ {ℓ : Level} {I : Type ℓ} where

⊔ : (A : I → Algebra α ρa) → Algebra (α ⊔ ℓ) (ρa ⊔ ℓ)

Domain (⊔ A) =
  record { Carrier = ∀ i → ⋃ [ A i ]
        ; _≈_ = λ a b → ∀ i → (Setoid._≈_ D [ A i ]) (a i)(b i)
        ; isEquivalence =
            record { refl = λ i → IsEquivalence.refl (isEquivalence D [ A i ])
                  ; sym = λ x i → IsEquivalence.sym (isEquivalence D [ A i ]) (x i)
                  ; trans = λ x y i → IsEquivalence.trans (isEquivalence D [ A i ]) (x i)(y i) }}

Interp (⊔ A) ($) (f , a) = λ i → (f ^ (A i)) (flip a i)
cong (Interp (⊔ A)) (≡.refl , f=g) = λ i → cong (Interp (A i)) (≡.refl , flip f=g i)

```

4 Homomorphisms

4.1 Basic definitions

Here are some useful definitions and theorems extracted from the `Homomorphisms.Func.Basic` module of the `Agda Universal Algebra Library`.

```

module _ (A : Algebra α ρa)(B : Algebra β ρb) where
  open Algebra A using () renaming (Domain to A)
  open Algebra B using () renaming (Domain to B)
  open Setoid A using () renaming (_≈_ to ≈1)
  open Setoid B using () renaming (_≈_ to ≈2)

compatible-map-op : (A → B) → | S | → Type (ℳ ⊔ α ⊔ ρb)
compatible-map-op h f = ∀ {a} → (h ($) ((f ^ A) a)) ≈2 ((f ^ B) (λ x → (h ($) (a x))))

```



```

compatible-map : (A → B) → Type (ℓ ⊔ ℳ ⊔ α ⊔ ρb)
compatible-map h = ∀ {f} → compatible-map-op h f

– The property of being a homomorphism.
record IsHom (h : A → B) : Type (ℓ ⊔ ℳ ⊔ α ⊔ ρa ⊔ ρb) where
  field compatible : compatible-map h

hom : Type (ℓ ⊔ ℳ ⊔ α ⊔ ρa ⊔ β ⊔ ρb)
hom = Σ (A → B) IsHom

```

4.2 Monomorphisms and epimorphisms

```

record IsMon (h : A → B) : Type (ℓ ⊔ ℳ ⊔ α ⊔ ρa ⊔ β ⊔ ρb) where
  field isHom : IsHom h ; isInjective : IsInjective h

  HomReduct : hom
  HomReduct = h , isHom

mon : Type (ℓ ⊔ ℳ ⊔ α ⊔ ρa ⊔ β ⊔ ρb)
mon = Σ (A → B) IsMon

record IsEpi (h : A → B) : Type (ℓ ⊔ ℳ ⊔ α ⊔ ρa ⊔ β ⊔ ρb) where
  field isHom : IsHom h ; isSurjective : IsSurjective h

  HomReduct : hom
  HomReduct = h , isHom

epi : Type (ℓ ⊔ ℳ ⊔ α ⊔ ρa ⊔ β ⊔ ρb)
epi = Σ (A → B) IsEpi

module _ (A : Algebra α ρa)(B : Algebra β ρb) where
  open IsEpi ; open IsMon

  mon→intohom : mon A B → Σ[ h ∈ hom A B ] IsInjective | h |
  mon→intohom (hh , hhM) = (hh , isHom hhM) , isInjective hhM

  epi→ontohom : epi A B → Σ[ h ∈ hom A B ] IsSurjective | h |
  epi→ontohom (hh , hhE) = (hh , isHom hhE) , isSurjective hhE

```

4.3 Basic properties of homomorphisms

Here are some definitions and theorems extracted from the `Homomorphisms.Func.Properties` module of the `Agda Universal Algebra Library`.

4.3.1 Composition of homomorphisms

```

module _ {A : Algebra α ρa}
  {B : Algebra β ρb}
  {C : Algebra γ ρc} where

  open Algebra A using () renaming (Domain to A)
  open Algebra B using () renaming (Domain to B)

```

```

open Algebra C using () renaming (Domain to C)
open Setoid A using () renaming ( _≈_ to _≈1_ )
open Setoid B using () renaming ( _≈_ to _≈2_ )
open Setoid C using (trans) renaming ( _≈_ to _≈3_ )

open IsHom

-- The composition of homomorphisms is again a homomorphism
o-is-hom : {g : A → B}{h : B → C} → IsHom A B g → IsHom B C h → IsHom A C (h ∘ g)
o-is-hom {g} {h} ghom hhom = record { compatible = c }
  where
    c : compatible-map A C (h ∘ g)
    c {f}{a} = trans lemg lemh
      where
        lemg : (h ($) (g ($) ((f ^ A) a))) ≈3 (h ($) ((f ^ B) (λ x → g ($) (a x))))
        lemg = cong h (compatible ghom)

        lemh : (h ($) ((f ^ B) (λ x → g ($) (a x)))) ≈3 ((f ^ C) (λ x → h ($) (g ($) (a x))))
        lemh = compatible hhom

o-hom : hom A B → hom B C → hom A C
o-hom (h , hhom) (g , ghom) = (g ∘ h) , o-is-hom hhom ghom

-- The composition of epimorphisms is again an epimorphism
open IsEpi

o-is-epi : {g : A → B}{h : B → C} → IsEpi A B g → IsEpi B C h → IsEpi A C (h ∘ g)
o-is-epi gE hE =
  record { isHom = o-is-hom (isHom gE) (isHom hE)
        ; isSurjective = o-IsSurjective (isSurjective gE) (isSurjective hE) }

o-epi : epi A B → epi B C → epi A C
o-epi (h , hepi) (g , gepi) = (g ∘ h) , o-is-epi hepi gepi

```

4.3.2 Universe lifting of homomorphisms

First we define the identity homomorphism for setoid algebras and then we prove that the operations of lifting and lowering of a setoid algebra are homomorphisms.

```

module _ {A : Algebra α ρa} where
  open Algebra A using () renaming (Domain to A)
  open Setoid A using (reflexive) renaming ( _≈_ to _≈1_ ; refl to refl1 )

  id : hom A A
  id = id , record { compatible = reflexive ≡.refl }

module _ {A : Algebra α ρa}{ℓ : Level} where
  open Algebra A using () renaming (Domain to A)
  open Setoid A using (reflexive) renaming ( _≈_ to _≈1_ ; refl to refl1 )

  open Setoid D[ Lift-Algl A ℓ ] using () renaming ( _≈_ to _≈l_ ; refl to refll )
  open Setoid D[ Lift-Algr A ℓ ] using () renaming ( _≈_ to _≈r_ ; refl to reflr )

  open Level
  ToLiftl : hom A (Lift-Algl A ℓ)

```

```

ToLiftl = record { f = lift ; cong = id } , record { compatible = reflexive ≡.refl }

FromLiftl : hom (Lift-Algl A ℓ) A
FromLiftl = record { f = lower ; cong = id } , record { compatible = refll }

ToFromLiftl : ∀ b → (| ToLiftl | ⟨$⟩ (| FromLiftl | ⟨$⟩ b)) ≈l b
ToFromLiftl b = refl1

FromToLiftl : ∀ a → (| FromLiftl | ⟨$⟩ (| ToLiftl | ⟨$⟩ a)) ≈1 a
FromToLiftl a = refl1

ToLiftr : hom A (Lift-Algr A ℓ)
ToLiftr = record { f = id ; cong = lift } , record { compatible = lift (reflexive ≡.refl) }

FromLiftr : hom (Lift-Algr A ℓ) A
FromLiftr = record { f = id ; cong = lower } , record { compatible = refll }

ToFromLiftr : ∀ b → (| ToLiftr | ⟨$⟩ (| FromLiftr | ⟨$⟩ b)) ≈r b
ToFromLiftr b = lift refl1

FromToLiftr : ∀ a → (| FromLiftr | ⟨$⟩ (| ToLiftr | ⟨$⟩ a)) ≈1 a
FromToLiftr a = refl1

module _ {A : Algebra α ρa} {ℓ r : Level} where
  open Level
  open Setoid D[ A ] using (refl)
  open Setoid D[ Lift-Alg A ℓ r ] using ( _≈_ )

  ToLift : hom A (Lift-Alg A ℓ r)
  ToLift = o-hom ToLiftl ToLiftr

  FromLift : hom (Lift-Alg A ℓ r) A
  FromLift = o-hom FromLiftr FromLiftl

  ToFromLift : ∀ b → (| ToLift | ⟨$⟩ (| FromLift | ⟨$⟩ b)) ≈ b
  ToFromLift b = lift refl

  ToLift-epi : epi A (Lift-Alg A ℓ r)
  ToLift-epi = | ToLift | , (record { isHom = || ToLift ||
    ; isSurjective = λ {y} → eq (| FromLift | ⟨$⟩ y) (ToFromLift y) })

```

4.4 Homomorphisms of product algebras

(cf. the [Homomorphisms.Func.Products] module of the [Agda Universal Algebra Library](#).)

Suppose we have an algebra \mathbf{A} , a type $I : \text{Type } \mathcal{I}$, and a family $\mathcal{B} : I \rightarrow \text{Algebra } \beta S$ of algebras. We sometimes refer to the inhabitants of I as *indices*, and call \mathcal{B} an *indexed family of algebras*.

If in addition we have a family $\mathcal{h} : (i : I) \rightarrow \text{hom } \mathbf{A} (\mathcal{B} i)$ of homomorphisms, then we can construct a homomorphism from \mathbf{A} to the product $\prod \mathcal{B}$ in the natural way.

```

module _ {ι : Level} {I : Type ι} {A : Algebra α ρa} {B : I → Algebra β ρb} where
  open Algebra A using () renaming ( Domain to A )
  open Setoid A using ( ) renaming ( refl to refl1 )
  open Algebra (∏ B) using () renaming ( Domain to ∏ B )

```

```

open Setoid using ( refl )
open IsHom

⊔-hom-co : (∀(i : I) → hom A (B i)) → hom A (⊔ B)
⊔-hom-co h = h , hhom
  where
    h : A → ⊔ B
    _⟨$⟩_ h = λ a i → | h i | ⟨$⟩ a
    cong h xy i = cong | h i | xy
    hhom : IsHom A (⊔ B) h
    compatible hhom = λ i → compatible || h i ||

```

4.5 Factorization of homomorphisms

(cf. the `Homomorphisms.Func.Factor` module of the `Agda Universal Algebra Library`.)

If $g : \text{hom } \mathbf{A} \ \mathbf{B}$, $h : \text{hom } \mathbf{A} \ \mathbf{C}$, h is surjective, and $\ker h \subseteq \ker g$, then there exists $\varphi : \text{hom } \mathbf{C} \ \mathbf{B}$ such that $g = \varphi \circ h$ so the following diagram commutes:

$$\begin{array}{ccc}
 \mathbf{A} & \xrightarrow{\quad h \quad} & \mathbf{C} \\
 \searrow & & \downarrow \varphi \\
 & g & \cdot \\
 \searrow & & \downarrow \\
 & & \mathbf{B}
 \end{array}$$

We will prove this in case h is both surjective and injective.

```

module _ {A : Algebra α ρa}{B : Algebra β ρb}{C : Algebra γ ρc}
  (gh : hom A B)(hh : hom A C) where
    open Algebra B using () renaming (Domain to B)
    open Algebra C using (Interp) renaming (Domain to C)
    open Setoid B using () renaming ( _≈_ to _≈2_ ; sym to sym2 )
    open Setoid C using (trans) renaming ( _≈_ to _≈3_ ; sym to sym3 )
    open SetoidReasoning B
    open IsHom
    open Image _⊃_

    private
      gfunc = | gh | ; g = _⟨$⟩_ gfunc
      hfunc = | hh | ; h = _⟨$⟩_ hfunc

    HomFactor : kernel _≈3_ h ⊆ kernel _≈2_ g → IsSurjective hfunc
      → Σ[ φ ∈ hom C B ] ∀ a → (g a) ≈2 | φ | ⟨$⟩ (h a)

    HomFactor Khg hE = (φmap , φhom) , gφh
      where
        kerpres : ∀ a0 a1 → h a0 ≈3 h a1 → g a0 ≈2 g a1
        kerpres a0 a1 hyp = Khg hyp

    h-1 : U[ C ] → U[ A ]

```

```

h-1 = SurjInv hfunc hE

η : ∀ {c} → h (h-1 c) ≈3 c
η = SurjInvIsInverser hfunc hE

ξ : ∀ {a} → h a ≈3 h (h-1 (h a))
ξ = sym3 η

ζ : ∀ {x y} → x ≈3 y → h (h-1 x) ≈3 h (h-1 y)
ζ xy = trans η (trans xy (sym3 η))

φmap : C → B
_($)_ φmap = g ∘ h-1
cong φmap = Khg ∘ ζ

gφh : (a : U[ A ]) → g a ≈2 φmap ($ (h a))
gφh a = Khg ξ

open _→_ φmap using () renaming (cong to φcong)

φcomp : compatible-map C B φmap
φcomp {f}{c} =
  begin
    φmap ($ ((f ^ C) c)) ≈✓ φcong (cong (Interp C) (≡.refl , (λ _ → η)))
    g (h-1 ((f ^ C)(h ∘ (h-1 ∘ c)))) ≈✓ φcong (compatible || hh ||)
    g (h-1 (h ((f ^ A)(h-1 ∘ c)))) ≈✓ gφh ((f ^ A)(h-1 ∘ c))
    g ((f ^ A)(h-1 ∘ c)) ≈✓ compatible || gh ||
    (f ^ B)(g ∘ (h-1 ∘ c)) ■

φhom : IsHom C B φmap
compatible φhom = φcomp

```

4.6 Isomorphisms

(cf. the `Homomorphisms.Func.Isomorphisms` of the Agda Universal Algebra Library.)

Two structures are *isomorphic* provided there are homomorphisms going back and forth between them which compose to the identity map.

```

module _ (A : Algebra α ρa) (B : Algebra β ρb) where
  open Setoid D[ A ] using ( sym ; trans ) renaming ( _≈_ to _≈1_ )
  open Setoid D[ B ] using () renaming ( _≈_ to _≈2_ ; sym to sym2 ; trans to trans2 )

  record ≅ : Type (℔ ℔ ℔ α ℔ β ℔ ρa ℔ ρb) where
    constructor mkiso
    field
      to : hom A B
      from : hom B A
      to~from : ∀ b → (| to | ($ (| from | ($ b))) ≈2 b
      from~to : ∀ a → (| from | ($ (| to | ($ a))) ≈1 a

  toIsSurjective : IsSurjective | to |
  toIsSurjective {y} = eq (| from | ($ y) (sym2 (to~from y))

  toIsInjective : IsInjective | to |

```

```

tolsInjective {x} {y} xy = Goal
  where
    ξ : | from | ⟨$⟩ (| to | ⟨$⟩ x) ≈1 | from | ⟨$⟩ (| to | ⟨$⟩ y)
    ξ = cong | from | xy
    Goal : x ≈1 y
    Goal = trans (sym (from~to x)) (trans ξ (from~to y))

fromIsSurjective : IsSurjective | from |
fromIsSurjective {y} = eq (| to | ⟨$⟩ y) (sym (from~to y))

fromIsInjective : IsInjective | from |
fromIsInjective {x} {y} xy = Goal
  where
    ξ : | to | ⟨$⟩ (| from | ⟨$⟩ x) ≈2 | to | ⟨$⟩ (| from | ⟨$⟩ y)
    ξ = cong | to | xy
    Goal : x ≈2 y
    Goal = trans2 (sym2 (to~from x)) (trans2 ξ (to~from y))

```

4.6.1 Properties of isomorphisms

```

open _≅_

≅-refl : Reflexive (_≅_ {α}{ρa})
≅-refl {α}{ρa}{A} = mkiso id id (λ b → refl) λ a → refl
  where open Setoid D[ A ] using ( refl )

≅-sym : Sym (_≅_ {β}{ρb}) (_≅_ {α}{ρa})
≅-sym φ = mkiso (from φ) (to φ) (from~to φ) (to~from φ)

≅-trans : Trans (_≅_ {α}{ρa})(_≅_ {β}{ρb})(_≅_ {α}{ρa}{γ}{ρc})
≅-trans {ρc = ρc}{A}{B}{C} ab bc = mkiso f g τ ν
  where
    open Setoid D[ A ] using () renaming ( _≅_ to _≈1_ ; trans to trans1 )
    open Setoid D[ C ] using () renaming ( _≅_ to _≈3_ ; trans to trans3 )
    f : hom A C
    f = o-hom (to ab) (to bc)
    g : hom C A
    g = o-hom (from bc) (from ab)
    τ : ∀ b → (| f | ⟨$⟩ (| g | ⟨$⟩ b)) ≈3 b
    τ b = trans3 (cong | to bc | (to~from ab (| from bc | ⟨$⟩ b))) (to~from bc b)
    ν : ∀ a → (| g | ⟨$⟩ (| f | ⟨$⟩ a)) ≈1 a
    ν a = trans1 (cong | from ab | (from~to bc (| to ab | ⟨$⟩ a))) (from~to ab a)

```

Fortunately, the lift operation preserves isomorphism (i.e., it's an *algebraic invariant*). As our focus is universal algebra, this is important and is what makes the lift operation a workable solution to the technical problems that arise from the noncumulativity of Agda's universe hierarchy.

```

module _ {A : Algebra α ρa}{ℓ : Level} where

```

```

Lift-≅l : A ≅ (Lift-Algl A ℓ)
Lift-≅l = mkiso ToLiftl FromLiftl (ToFromLiftl{A = A}) (FromToLiftl{A = A}{ℓ})

Lift-≅r : A ≅ (Lift-Algr A ℓ)
Lift-≅r = mkiso ToLiftr FromLiftr (ToFromLiftr{A = A}) (FromToLiftr{A = A}{ℓ})

Lift-≅ : {A : Algebra α ρa}{ℓ ρ : Level} → A ≅ (Lift-Alg A ℓ ρ)
Lift-≅ = ≅-trans Lift-≅l Lift-≅r

```

4.7 Homomorphic Images

(cf. the `Homomorphisms.Func.HomomorphicImages` module of the `Agda Universal Algebra Library`.)

We begin with what seems, for our purposes, the most useful way to represent the class of *homomorphic images* of an algebra in dependent type theory.

```

ov : Level → Level
ov α = 0 ⊔ ℳ ⊔ Isuc α

_IsHomImageOf_ : (B : Algebra β ρb)(A : Algebra α ρa) → Type (0 ⊔ ℳ ⊔ α ⊔ β ⊔ ρa ⊔ ρb)
B IsHomImageOf A = Σ[ φ ∈ hom A B ] IsSurjective | φ |

HomImages : Algebra α ρa → Type (α ⊔ ρa ⊔ ov (β ⊔ ρb))
HomImages {β = β}{ρb = ρb} A = Σ[ B ∈ Algebra β ρb ] B IsHomImageOf A

```

These types should be self-explanatory, but just to be sure, let's describe the `Sigma` type appearing in the second definition. Given an S -algebra $A : \text{Algebra } \alpha \rho$, the type `HomImages A` denotes the class of algebras $B : \text{Algebra } \beta \rho$ with a map $\varphi : |A| \rightarrow |B|$ such that φ is a surjective homomorphism.

```

module _ {A : Algebra α ρa}{B : Algebra β ρb} where
  open _≅_
  Lift-HomImage-lemma : ∀{γ} → (Lift-Alg A γ γ) IsHomImageOf B → A IsHomImageOf B
  Lift-HomImage-lemma {γ} φ = o-hom | φ | (from Lift-≅) ,
    o-IsSurjective || φ || (fromIsSurjective (Lift-≅{A = A}))

module _ {A A' : Algebra α ρa}{B : Algebra β ρb} where
  open _≅_
  HomImage-≅ : A IsHomImageOf A' → A ≅ B → B IsHomImageOf A'
  HomImage-≅ φ A≅B = o-hom | φ | (to A≅B) , o-IsSurjective || φ || (toIsSurjective A≅B)

```

5 Subalgebras

5.1 Basic definitions

```

_≤_ - (alias for subalgebra relation)
_IsSubalgebraOf_ : Algebra α ρa → Algebra β ρb → Type (0 ⊔ ℳ ⊔ α ⊔ β ⊔ ρa ⊔ β ⊔ ρb)
A IsSubalgebraOf B = Σ[ h ∈ hom A B ] IsInjective | h |

```

– Syntactic sugar for the subalgebra relation.

$A \leq B = A \text{ IsSubalgebraOf } B$

5.2 Basic properties

```

≤-reflexive : {A : Algebra α ρa} → A ≤ A
≤-reflexive {A = A} = id , id

mon→≤ : {A : Algebra α ρa} {B : Algebra β ρb} → mon A B → A ≤ B
mon→≤ {A = A} {B} x = mon→intohom A B x

module _ {A : Algebra α ρa} {B : Algebra β ρb} {C : Algebra γ ρc} where
  open Setoid D[ A ] using () renaming ( _≈_ to _≈1_ ; Carrier to |A| )
  open Setoid D[ B ] using () renaming ( _≈_ to _≈2_ ; Carrier to |B| )
  open Setoid D[ C ] using () renaming ( _≈_ to _≈3_ ; Carrier to |C| )
  open compose {A = |A|} {B = |B|} {C = |C|} _≈1_ _≈2_ _≈3_ using ( o-injective-func )

  ≤-trans : A ≤ B → B ≤ C → A ≤ C
  ≤-trans A≤B B≤C = (o-hom | A≤B | | B≤C | ) , o-injective-func || A≤B || || B≤C ||
  open _≈_ using () renaming ( to to to )

  ≅-trans-≤ : A ≅ B → B ≤ C → A ≤ C
  ≅-trans-≤ A≅B (h , hinj) = (o-hom (to A≅B) h) , (o-injective-func (tolsInjective A≅B) hinj)

```

5.3 Products of subalgebras

```

module _ {ι : Level} {I : Type ι} {A : I → Algebra α ρa} {B : I → Algebra β ρb} where
  open Algebra (⋂ A) using () renaming ( Domain to ⋂A )
  open Algebra (⋂ B) using () renaming ( Domain to ⋂B )
  open Setoid ⋂A using ( refl )
  open IsHom

  ⋂-≤ : (∀ i → B i ≤ A i) → ⋂ B ≤ ⋂ A
  ⋂-≤ B≤A = h , hM
  where
    h : hom (⋂ B) (⋂ A)
    h = hfunc , hhom
    where
      hi : ∀ i → hom (B i) (A i)
      hi i = | B≤A i |

      hfunc : ⋂B → ⋂A
      (hfunc ⟨$⟩ x) i = | hi i | ⟨$⟩ (x i)
      cong hfunc = λ xy i → cong | hi i | (xy i)
      hhom : IsHom (⋂ B) (⋂ A) hfunc
      compatible hhom = λ i → compatible || hi i ||

  hM : IsInjective | h |
  hM = λ xy i → || B≤A i || (xy i)

```


6 Terms

6.1 Basic definitions

Fix a signature S and let X denote an arbitrary nonempty collection of variable symbols. Assume the symbols in X are distinct from the operation symbols of S , that is $X \cap |S| = \emptyset$.

By a *word* in the language of S , we mean a nonempty, finite sequence of members of $X \cup |S|$. We denote the concatenation of such sequences by simple juxtaposition.

Let S_0 denote the set of nullary operation symbols of S . We define by induction on n the sets T_n of *words* over $X \cup |S|$ as follows (cf. Bergman (2012) Def. 4.19):

$$T_0 := X \cup S_0 \text{ and } T_{n+1} := T_n \cup \mathcal{T}_n$$

where \mathcal{T}_n is the collection of all $f \, t$ such that $f : |S|$ and $t : \|S\| f \rightarrow T_n$. (Recall, $\|S\| f$ is the arity of the operation symbol f .)

We define the collection of *terms* in the signature S over X by $\text{Term } X := \bigcup_n T_n$. By an S -*term* we mean a term in the language of S .

The definition of $\text{Term } X$ is recursive, indicating that an inductive type could be used to represent the semantic notion of terms in type theory. Indeed, such a representation is given by the following inductive type.

```
data Term (X : Type χ) : Type (ov χ) where
  g : X → Term X – (g for "generator")
  node : (f : |S|)(t : \|S\| f → Term X) → Term X
open Term
```

This is a very basic inductive type that represents each term as a tree with an operation symbol at each *node* and a variable symbol at each leaf (*generator*).

Notation. As usual, the type X represents an arbitrary collection of variable symbols. Recall, $\text{ov } \chi$ is our shorthand notation for the universe level $\mathcal{O} \sqcup \mathcal{V} \sqcup \text{Isuc } \chi$.

6.2 Equality of terms

We take a different approach here, using Setoids instead of quotient types. That is, we will define the collection of terms in a signature as a setoid with a particular equality-of-terms relation, which we must define. Ultimately we will use this to define the (absolutely free) term algebra as a Algebra whose carrier is the setoid of terms.

```
module _ {X : Type χ} where
  – Equality of terms as an inductive datatype
  data _≐_ : Term X → Term X → Type (ov χ) where
    rfl : {x y : X} → x ≐ y → (g x) ≐ (g y)
    gnl : ∀ {f}{s t : \|S\| f → Term X} → (∀ i → (s i) ≐ (t i)) → (node f s) ≐ (node f t)
  – Equality of terms is an equivalence relation
  open Level
  ≐-isRefl : Reflexive _≐_
  ≐-isRefl {g _} = rfl ≐.refl
  ≐-isRefl {node _ _} = gnl (λ _ → ≐-isRefl)
  ≐-isSym : Symmetric _≐_
  ≐-isSym (rfl x) = rfl (≐.sym x)
  ≐-isSym (gnl x) = gnl (λ i → ≐-isSym (x i))
```

```

 $\dot{=}$ -isTrans : Transitive  $\dot{=}$ 
 $\dot{=}$ -isTrans (rfl x) (rfl y) = rfl ( $\equiv$ .trans x y)
 $\dot{=}$ -isTrans (gnl x) (gnl y) = gnl ( $\lambda$  i  $\rightarrow$   $\dot{=}$ -isTrans (x i) (y i))

 $\dot{=}$ -isEquiv : IsEquivalence  $\dot{=}$ 
 $\dot{=}$ -isEquiv = record { refl =  $\dot{=}$ -isRefl ; sym =  $\dot{=}$ -isSym ; trans =  $\dot{=}$ -isTrans }

```

6.3 The term algebra

For a given signature S , if the type $\text{Term } X$ is nonempty (equivalently, if X or $|S|$ is nonempty), then we can define an algebraic structure, denoted by $\mathbf{T } X$ and called the *term algebra in the signature S over X* . Terms are viewed as acting on other terms, so both the domain and basic operations of the algebra are the terms themselves.

- For each operation symbol $f : |S|$, denote by $f^\wedge(\mathbf{T } X)$ the operation on $\text{Term } X$ that maps a tuple $t : ||S|| f \rightarrow | \mathbf{T } X |$ to the formal term $f t$.
- Define $\mathbf{T } X$ to be the algebra with universe $| \mathbf{T } X | := \text{Term } X$ and operations $f^\wedge(\mathbf{T } X)$, one for each symbol f in $|S|$.

In *Agda* the term algebra can be defined as simply as one might hope.

```

TermSetoid : (X : Type  $\chi$ )  $\rightarrow$  Setoid (ov  $\chi$ ) (ov  $\chi$ )
TermSetoid X = record { Carrier = Term X ;  $\approx$  =  $\dot{=}$  ; isEquivalence =  $\dot{=}$ -isEquiv }

T : (X : Type  $\chi$ )  $\rightarrow$  Algebra (ov  $\chi$ ) (ov  $\chi$ )
Algebra.Domain (T X) = TermSetoid X
Algebra.Interp (T X) ($) (f , ts) = node f ts
cong (Algebra.Interp (T X)) ( $\equiv$ .refl , ss $\dot{=}$ ts) = gnl ss $\dot{=}$ ts

```

6.4 Interpretation of terms

The approach to terms and their interpretation in this module was inspired by [Andreas Abel's formal proof of Birkhoff's completeness theorem](#).

A substitution from X to Y associates a term in X with each variable in Y .

– *Parallel substitutions.*

```

Sub : Type  $\chi$   $\rightarrow$  Type  $\chi$   $\rightarrow$  Type (ov  $\chi$ )
Sub X Y = (y : Y)  $\rightarrow$  Term X

```

– *Application of a substitution.*

```

_[] : {X Y : Type  $\chi$ } {t : Term Y} ( $\sigma$  : Sub X Y)  $\rightarrow$  Term X
(g x) [  $\sigma$  ] =  $\sigma$  x
(node f ts) [  $\sigma$  ] = node f ( $\lambda$  i  $\rightarrow$  ts i [  $\sigma$  ])

```

An environment for Γ maps each variable $x : \Gamma$ to an element of A , and equality of environments is defined pointwise.

```

module Environment (A : Algebra  $\alpha$   $\ell$ ) where
  open Algebra A using ( Interp ) renaming ( Domain to A )
  open Setoid D[ A ] using ( refl ; sym ; trans ) renaming (  $\approx$  to  $\approx_a$  ; Carrier to |A| )

```

```

Env : Type  $\chi \rightarrow$  Setoid  $\_ \_$ 
Env X = record { Carrier = X  $\rightarrow$  |A|
;  $\_ \approx \_$  =  $\lambda \rho \rho' \rightarrow (x : X) \rightarrow \rho x \approx_a \rho' x$ 
; isEquivalence =
    record { refl =  $\lambda \_ \rightarrow$  refl
; sym =  $\lambda h x \rightarrow$  sym (h x)
; trans =  $\lambda g h x \rightarrow$  trans (g x) (h x) }}

[ ] : {X : Type  $\chi$ } (t : Term X)  $\rightarrow$  (Env X)  $\rightarrow$  A
[ g x ] ($)  $\rho = \rho x$ 
[ node f args ] ($)  $\rho =$  (Interp A) ($) (f ,  $\lambda i \rightarrow$  [ args i ] ($)  $\rho$ )
cong [ g x ]  $u \approx v = u \approx v x$ 
cong [ node f args ]  $x \approx y =$  cong (Interp A) ( $\equiv$ .refl ,  $\lambda i \rightarrow$  cong [ args i ]  $x \approx y$ )

```

An equality between two terms holds in a model if the two terms are equal under all valuations of their free variables (cf. Andreas Abel's formal proof of Birkhoff's completeness theorem).

```

Equal :  $\forall \{X : \text{Type } \chi\} (s t : \text{Term } X) \rightarrow \text{Type } \_$ 
Equal {X = X} s t =  $\forall (\rho : \text{Carrier } (\text{Env } X)) \rightarrow [ s ] ($) \rho \approx_a [ t ] ($) \rho$ 

 $\dot{=}$ Equal : {X : Type  $\chi$ } (s t : Term X)  $\rightarrow s \dot{=} t \rightarrow$  Equal s t
 $\dot{=}$ Equal .(g _) .(g _) (rfl  $\equiv$ .refl) =  $\lambda \_ \rightarrow$  refl
 $\dot{=}$ Equal (node _ s) (node _ t) (gnt x) =
   $\lambda \rho \rightarrow$  cong (Interp A) ( $\equiv$ .refl ,  $\lambda i \rightarrow$   $\dot{=}$ Equal (s i) (t i) ( $x i$ )  $\rho$ )

```

Equal is an equivalence relation.

```

EqualsEquiv : { $\Gamma : \text{Type } \chi$ }  $\rightarrow$  IsEquivalence (Equal {X =  $\Gamma$ })
IsEquivalence.refl EqualsEquiv =  $\lambda \_ \rightarrow$  refl
IsEquivalence.sym EqualsEquiv =  $\lambda x=y \rho \rightarrow$  sym (x=y  $\rho$ )
IsEquivalence.trans EqualsEquiv =  $\lambda ij jk \rho \rightarrow$  trans (ij  $\rho$ ) (jk  $\rho$ )

```

Evaluation of a substitution gives an environment (cf. Andreas Abel's formal proof of Birkhoff's completeness theorem)

```

[ ]s : {X Y : Type  $\chi$ }  $\rightarrow$  Sub X Y  $\rightarrow$  Carrier (Env X)  $\rightarrow$  Carrier (Env Y)
[  $\sigma$  ]s  $\rho x =$  [  $\sigma x$  ] ($)  $\rho$ 

```

6.5 Substitution lemma

We prove that $\llbracket t[\sigma] \rrbracket \rho \simeq \llbracket t \rrbracket \llbracket \sigma \rrbracket \rho$ (cf. Andreas Abel's formal proof of Birkhoff's completeness theorem).

```

substitution : {X Y : Type  $\chi$ }  $\rightarrow$  (t : Term Y) ( $\sigma : \text{Sub } X Y$ ) ( $\rho : \text{Carrier } (\text{Env } X)$ )  $\rightarrow$ 
   $\rightarrow [ t [ \sigma ] ] ($) \rho \approx_a [ t ] ($) (\llbracket \sigma \rrbracket s \rho)$ 

substitution (g x)  $\sigma \rho =$  refl
substitution (node f ts)  $\sigma \rho =$  cong (Interp A) ( $\equiv$ .refl ,  $\lambda i \rightarrow$  substitution (ts i)  $\sigma \rho$ )

```

6.6 Compatibility of terms

We now prove two important facts about term operations. The first of these, which is used very often in the sequel, asserts that every term commutes with every homomorphism.

```

module _ {X : Type χ} {A : Algebra α ρa} {B : Algebra β ρb} (hh : hom A B) where
  open Algebra A using () renaming (Domain to A ; Interp to Interp1)
  open Setoid A using () renaming ( _≈_ to _≈1_ ; Carrier to |A| )
  open Algebra B using () renaming (Domain to B ; Interp to Interp2)
  open Setoid B using ( _≈_ ; sym ; refl )
  open SetoidReasoning B
  private hfunc = | hh | ; h = _($)_ hfunc

  open Environment A using () renaming ( [ ] to [ ]1 )
  open Environment B using () renaming ( [ ] to [ ]2 )
  open IsHom

  comm-hom-term : (t : Term X) (a : X → |A|)
    →
      h ([ t ]1 ($ a) ≈ [ t ]2 ($ (h ∘ a))

  comm-hom-term (g x) a = refl
  comm-hom-term (node f t) a = goal
  where
    goal : h ([ node f t ]1 ($ a) ≈ ([ node f t ]2 ($ (h ∘ a)))
    goal =
      begin
        h ([ node f t ]1 ($ a) ≈ (compatible || hh ||) )
        (f ^ B)(λ i → h ([ t i ]1 ($ a)) ≈ (cong Interp2 (≡.refl , λ i → comm-hom-term (t i) a) )
        (f ^ B)(λ i → [ t i ]2 ($ (h ∘ a)) ≈ (refl )
        ([ node f t ]2 ($ (h ∘ a))
  ■

```

6.7 Interpretation of terms in product algebras

```

module _ {X : Type χ} {ι : Level} {I : Type ι} (A : I → Algebra α ρa) where
  open Algebra (Π A) using () renaming ( Domain to Π A ; Interp to Π Interp )
  open Setoid Π A using ( _≈_ ; refl )
  open Environment (Π A) using () renaming ( [ ] to [ ]1 )
  open Environment using ( [ ] ; ≐→Equal )

  interp-prod : (p : Term X) → ∀ ρ → [ p ]1 ($ ρ ≈ (λ i → ([ A i ] p) ($ (λ x → (ρ x) i))
  interp-prod (g x) = λ ρ i → ≐→Equal (A i) (g x) (g x) ≐→isRefl λ x' → (ρ x) i
  interp-prod (node f t) = λ ρ i → cong Π Interp (≡.refl , (λ j k → interp-prod (t j) ρ k)) i

```

7 Model Theory and Equational Logic

(cf. the Varieties.Func.SoundAndComplete module of the Agda Universal Algebra Library)

7.1 Basic definitions

Let S be a signature. By an *identity* or *equation* in S we mean an ordered pair of terms in a given context. For instance, if the context happens to be the type $X : \text{Type } \chi$, then an equation will be a pair of inhabitants of the domain of term algebra $\mathbf{T} X$.

We define an equation in Agda using the following record type with fields denoting the left-hand and right-hand sides of the equation, along with an equation “context” representing the underlying collection of variable symbols (cf. Andreas Abel’s formal proof of Birkhoff’s completeness theorem).

```
record Eq : Type (ov  $\chi$ ) where
  constructor  $\_ \approx \_$ 
  field
    {cxt} : Type  $\chi$ 
    lhs : Term cxt
    rhs : Term cxt

open Eq public
```

We now define a type representing the notion of an equation $p \approx \cdot q$ holding (when p and q are interpreted) in algebra \mathbf{A} .

If \mathbf{A} is an S -algebra we say that \mathbf{A} *satisfies* $p \approx q$ provided for all environments $\rho : X \rightarrow | \mathbf{A} |$ (assigning values in the domain of \mathbf{A} to variable symbols in X) we have $\llbracket p \rrbracket \langle \$ \rangle \rho \approx \llbracket q \rrbracket \langle \$ \rangle \rho$. In this situation, we write $\mathbf{A} \models (p \approx \cdot q)$ and say that \mathbf{A} *models* the identity $p \approx q$.

If \mathcal{K} is a class of algebras, all of the same signature, we write $\mathcal{K} \models (p \approx \cdot q)$ if, for every $\mathbf{A} \in \mathcal{K}$, we have $\mathbf{A} \models (p \approx \cdot q)$.

Because a class of structures has a different type than a single structure, we must use a slightly different syntax to avoid overloading the relations \models and \approx . As a reasonable alternative to what we would normally express informally as $\mathcal{K} \models p \approx q$, we have settled on $\mathcal{K} \models (p \approx \cdot q)$ to denote this relation. To reiterate, if \mathcal{K} is a class of S -algebras, we write $\mathcal{K} \models (p \approx \cdot q)$ provided every $\mathbf{A} \in \mathcal{K}$ satisfies $\mathbf{A} \models (p \approx \cdot q)$.

```
 $\_ \models \_$  : ( $\mathbf{A} : \text{Algebra } \alpha \rho^a$ ) (term-identity :  $\text{Eq}\{\chi\}$ )  $\rightarrow$  Type  $\_$ 
 $\mathbf{A} \models (p \approx \cdot q) = \text{Equal } p \ q \text{ where open Environment } \mathbf{A}$ 

 $\_ \models \_$  : Pred ( $\text{Algebra } \alpha \rho^a$ )  $\ell \rightarrow \text{Eq}\{\chi\} \rightarrow$  Type ( $\ell \sqcup \chi \sqcup \text{ov}(\alpha \sqcup \rho^a)$ )
 $\mathcal{K} \models \text{equ} = \forall \mathbf{A} \rightarrow \mathcal{K} \mathbf{A} \rightarrow \mathbf{A} \models \text{equ}$ 
```

We denote by $\mathbf{A} \models \mathcal{E}$ the assertion that the algebra \mathbf{A} models every equation in a collection \mathcal{E} of equations.

```
 $\_ \models \_$  : ( $\mathbf{A} : \text{Algebra } \alpha \rho^a$ )  $\rightarrow \{ \iota : \text{Level} \} \{ l : \text{Type } \iota \} \rightarrow (l \rightarrow \text{Eq}\{\chi\}) \rightarrow$  Type  $\_$ 
 $\mathbf{A} \models \mathcal{E} = \forall i \rightarrow \text{Equal } (\text{lhs } (\mathcal{E} \ i)) (\text{rhs } (\mathcal{E} \ i)) \text{ where open Environment } \mathbf{A}$ 
```

7.2 Equational theories and models

If \mathcal{K} denotes a class of structures, then $\text{Th } \mathcal{K}$ represents the set of identities modeled by the members of \mathcal{K} .

```
Th :  $\{X : \text{Type } \chi\} \rightarrow \text{Pred } (\text{Algebra } \alpha \rho^a) \ell \rightarrow \text{Pred}(\text{Term } X \times \text{Term } X) \_$ 
Th  $\mathcal{K} = \lambda (p, q) \rightarrow \mathcal{K} \models (p \approx \cdot q)$ 
```

```

Mod : {X : Type χ} → Pred (Term X × Term X) ℓ → Pred (Algebra α ρa) _
Mod ℰ A = ∀ {p q} → (p , q) ∈ ℰ → Equal p q where open Environment A

```

7.3 The entailment relation

Based on Andreas Abel's Agda formalization of Birkhoff's completeness theorem.)

```

module _ {χ ι : Level} where

data _⊢_⊢_≈_ {I : Type ι} {ℰ : I → Eq} : (X : Type χ) (p q : Term X) → Type (ι ⊔ ov χ) where
  hyp : ∀ i → let p ≈ · q = ℰ i in ℰ ⊢ _⊢_ p ≈ q
  app : ∀ {ps qs} → (∀ i → ℰ ⊢ Γ ⊢ ps i ≈ qs i) → ℰ ⊢ Γ ⊢ (node f ps) ≈ (node f qs)
  sub : ∀ {p q} → ℰ ⊢ Δ ⊢ p ≈ q → ∀ (σ : Sub Γ Δ) → ℰ ⊢ Γ ⊢ (p [ σ ]) ≈ (q [ σ ])

  ⊢refl : ∀ {p} → ℰ ⊢ Γ ⊢ p ≈ p
  ⊢sym : ∀ {p q : Term Γ} → ℰ ⊢ Γ ⊢ p ≈ q → ℰ ⊢ Γ ⊢ q ≈ p
  ⊢trans : ∀ {p q r : Term Γ} → ℰ ⊢ Γ ⊢ p ≈ q → ℰ ⊢ Γ ⊢ q ≈ r → ℰ ⊢ Γ ⊢ p ≈ r

⊢≈IsEquiv : {X : Type χ} {I : Type ι} {ℰ : I → Eq} → IsEquivalence (ℰ ⊢ X ⊢_≈_)
⊢≈IsEquiv = record { refl = ⊢refl ; sym = ⊢sym ; trans = ⊢trans }

```

7.4 Soundness

In any model **A** that satisfies the equations \mathcal{E} , derived equality is actual equality (cf. Andreas Abel's Agda formalization of Birkhoff's completeness theorem.)

```

module Soundness {χ α ι : Level} {I : Type ι} {ℰ : I → Eq{χ}}
  (A : Algebra α ρa) – We assume an algebra A
  (V : A ⊢ ℰ) – that models all equations in ℰ.
  where

open Algebra A using () renaming (Domain to A ; Interp to InterpA)
open SetoidReasoning A
open Environment A renaming ( [ ]s to [ ] )
open IsEquivalence using ( refl ; sym ; trans )

sound : ∀ {p q} → ℰ ⊢ Γ ⊢ p ≈ q → A ⊢ (p ≈ · q)
sound (hyp i) = V i
sound (app {f = f} es) ρ = cong InterpA (≡.refl , λ i → sound (es i) ρ)
sound (sub {p = p} {q} Epq σ) ρ =
  begin
    [ p [ σ ] ] ⟨$⟩ ρ ≈ ⟨ substitution p σ ρ ⟩
    [ p ] ⟨$⟩ ⟨ σ ⟩ ρ ≈ ⟨ sound Epq (⟨ σ ⟩ ρ) ⟩
    [ q ] ⟨$⟩ ⟨ σ ⟩ ρ ≈ ⟨ substitution q σ ρ ⟩
    [ q [ σ ] ] ⟨$⟩ ρ ■

sound (⊢refl {p = p}) = refl EqualsEquiv {x = p}
sound (⊢sym {p = p} {q} Epq) = sym EqualsEquiv {x = p} {q} (sound Epq)
sound (⊢trans {p = p} {q} {r} Epq Eqr) = trans EqualsEquiv {i = p} {q} {r} (sound Epq) (sound Eqr)

```

8 The Closure Operators H, S, P and V

Fix a signature S , let \mathcal{K} be a class of S -algebras, and define

- $H \mathcal{K}$ = algebras isomorphic to a homomorphic image of a member of \mathcal{K} ;
- $S \mathcal{K}$ = algebras isomorphic to a subalgebra of a member of \mathcal{K} ;
- $P \mathcal{K}$ = algebras isomorphic to a product of members of \mathcal{K} .

A straight-forward verification confirms that H , S , and P are *closure operators* (expansive, monotone, and idempotent). A class \mathcal{K} of S -algebras is said to be *closed under the taking of homomorphic images* provided $H \mathcal{K} \subseteq \mathcal{K}$. Similarly, \mathcal{K} is *closed under the taking of subalgebras* (resp., *arbitrary products*) provided $S \mathcal{K} \subseteq \mathcal{K}$ (resp., $P \mathcal{K} \subseteq \mathcal{K}$). The operators H , S , and P can be composed with one another repeatedly, forming yet more closure operators.

An algebra is a homomorphic image (resp., subalgebra; resp., product) of every algebra to which it is isomorphic. Thus, the class $H \mathcal{K}$ (resp., $S \mathcal{K}$; resp., $P \mathcal{K}$) is closed under isomorphism.

A *variety* is a class of S -algebras that is closed under the taking of homomorphic images, subalgebras, and arbitrary products. To represent varieties we define types for the closure operators H , S , and P that are composable. Separately, we define a type V which represents closure under all three operators, H , S , and P .

8.1 Basic definitions

We now define the type H to represent classes of algebras that include all homomorphic images of algebras in the class—i.e., classes that are closed under the taking of homomorphic images—the type S to represent classes of algebras that closed under the taking of subalgebras, and the type P to represent classes of algebras closed under the taking of arbitrary products.

```

H : ∀ ℓ → Pred(Algebra α ρa) (α ⊔ ρa ⊔ ov ℓ) → Pred(Algebra β ρb) (β ⊔ ρb ⊔ ov(α ⊔ ρa ⊔ ℓ))
H {α}{ρa} _ ℓ B = Σ[ A ∈ Algebra α ρa ] A ∈ ℓ × B IsHomImageOf A

S : ∀ ℓ → Pred(Algebra α ρa) (α ⊔ ρa ⊔ ov ℓ) → Pred(Algebra β ρb) (β ⊔ ρb ⊔ ov(α ⊔ ρa ⊔ ℓ))
S {α}{ρa} _ ℓ B = Σ[ A ∈ Algebra α ρa ] A ∈ ℓ × B ≤ A

P : ∀ ℓ ι → Pred(Algebra α ρa) (α ⊔ ρa ⊔ ov ℓ) → Pred(Algebra β ρb) (β ⊔ ρb ⊔ ov(α ⊔ ρa ⊔ ℓ ⊔ ι))
P {α}{ρa} _ ι ℓ B = Σ[ I ∈ Type ι ] (Σ[ A ∈ (I → Algebra α ρa) ] (∀ i → A i ∈ ℓ) × (B ≅ ∏ A))

```

A class \mathcal{K} of S -algebras is called a *variety* if it is closed under each of the closure operators H , S , and P defined above. The corresponding closure operator is often denoted \mathbb{V} or \mathcal{V} , but we will denote it by V .

```

module _ {α ρa β ρb γ ρc δ ρd : Level} where
  private a = α ⊔ ρa ; b = β ⊔ ρb ; c = γ ⊔ ρc ; d = δ ⊔ ρd

  V : ∀ ℓ ι → Pred(Algebra α ρa) (a ⊔ ov ℓ) → Pred(Algebra δ ρd) (d ⊔ ov(a ⊔ b ⊔ c ⊔ ℓ ⊔ ι))
  V ℓ ι ℓ = H{γ}{ρc}{δ}{ρd} (a ⊔ b ⊔ ℓ ⊔ ι) (S{β}{ρb} (a ⊔ ℓ ⊔ ι) (P ℓ ι ℓ))

module _ {α ρa ℓ : Level} (ℓ : Pred(Algebra α ρa) (α ⊔ ρa ⊔ ov ℓ))
  (A : Algebra (α ⊔ ρa ⊔ ℓ) (α ⊔ ρa ⊔ ℓ)) where
  private ι = ov(α ⊔ ρa ⊔ ℓ)

  V-≅-lc : Lift-Alg A ι ι ∈ V{β = ι}{ι} ℓ ι ℓ → A ∈ V{γ = ι}{ι} ℓ ι ℓ
  V-≅-lc (A' , spA' , lAimgA') = A' , (spA' , lAimgA')

```

where
 $\text{AimgA}' : \mathbf{A} \text{ IsHomImageOf } \mathbf{A}'$
 $\text{AimgA}' = \text{Lift-HomImage-lemma } \text{IAimgA}'$

8.2 Properties

8.2.1 Idempotence of S

S is a closure operator. The facts that S is monotone and expansive won't be needed, so we omit the proof of these facts. However, we will make use of idempotence of S, so we prove that property as follows.

$\text{S-idem} : \{ \mathcal{K} : \text{Pred } (\text{Algebra } \alpha \rho^a) (\alpha \sqcup \rho^a \sqcup \text{ov } \ell) \}$
 $\rightarrow \text{S} \{ \beta = \gamma \} \{ \rho^c \} (\alpha \sqcup \rho^a \sqcup \ell) (\text{S} \{ \beta = \beta \} \{ \rho^b \} \ell \mathcal{K}) \subseteq \text{S} \{ \beta = \gamma \} \{ \rho^c \} \ell \mathcal{K}$
 $\text{S-idem } (\mathbf{A}, (\mathbf{B}, \text{sB}, \mathbf{A} \leq \mathbf{B}), \mathbf{x} \leq \mathbf{A}) = \mathbf{B}, (\text{sB}, \leq\text{-trans } \mathbf{x} \leq \mathbf{A} \mathbf{A} \leq \mathbf{B})$

8.2.2 Algebraic invariance of \models

The binary relation \models would be practically useless if it were not an *algebraic invariant* (i.e., invariant under isomorphism). Let us now verify that the models relation we defined above has this essential property.

```
module _ {X : Type} {χ} {A : Algebra α ρa} {B : Algebra β ρb} (p q : Term X) where
  open Environment A using () renaming ( [ ] to [ ]1 )
  open Environment B using () renaming ( [ ] to [ ]2 )
  open Setoid D[ A ] using () renaming ( ≈ to ≈1 )
  open Setoid D[ B ] using ( ≈ ; sym )
  open SetoidReasoning D[ B ]

  ⊨-l-invar : A ⊨ (p ≈ · q) → A ≅ B → B ⊨ (p ≈ · q)
  ⊨-l-invar Apq (mkiso fh gh f~g g~f) ρ =
  begin
    [ p ]2 ($) ρ ≈~ ( cong [ p ]2 (λ x → f~g (ρ x)) )
    [ p ]2 ($) (ff ∘ (g ∘ ρ)) ≈~ ( comm-hom-term fh p (g ∘ ρ) )
    ff ([ p ]1 ($) (g ∘ ρ)) ≈ ( cong | fh | (Apq (g ∘ ρ)) )
    ff ([ q ]1 ($) (g ∘ ρ)) ≈ ( comm-hom-term fh q (g ∘ ρ) )
    [ q ]2 ($) (ff ∘ (g ∘ ρ)) ≈ ( cong [ q ]2 (λ x → f~g (ρ x)) )
    [ q ]2 ($) ρ ■
  where private ff = _ ($) _ | fh | ; g = _ ($) _ | gh |
```

8.2.3 Subalgebraic invariance of \models

Identities modeled by an algebra \mathbf{A} are also modeled by every subalgebra of \mathbf{A} , which fact can be formalized as follows.

```
module _ {X : Type} {χ} {A : Algebra α ρa} {B : Algebra β ρb} {p q : Term X} where
  open Environment A using () renaming ( [ ] to [ ]1 )
  open Environment B using () renaming ( [ ] to [ ]2 )
```



```

open Setoid D[ A ] using ( _≈_ )
open Setoid D[ B ] using () renaming ( _≈_ to _≈₂_ )
open SetoidReasoning D[ A ]

|=S-invar : A |= (p ≈ · q) → B ≤ A → B |= (p ≈ · q)
|=S-invar Apq B≤A b = goal
  where
    hh : hom B A
    hh = | B≤A |
    h = _⟨$⟩_ | hh |
    ξ : ∀ b → h (⟦ p ⟧₂ ⟨$⟩ b) ≈ h (⟦ q ⟧₂ ⟨$⟩ b)
    ξ b = begin
      h (⟦ p ⟧₂ ⟨$⟩ b) ≈⟨ comm-hom-term hh p b ⟩
        ⟦ p ⟧₁ ⟨$⟩ (h ○ b) ≈⟨ Apq (h ○ b) ⟩
        ⟦ q ⟧₁ ⟨$⟩ (h ○ b) ≈⟨ comm-hom-term hh q b ⟩
        h (⟦ q ⟧₂ ⟨$⟩ b) ■
    goal : ⟦ p ⟧₂ ⟨$⟩ b ≈₂ ⟦ q ⟧₂ ⟨$⟩ b
    goal = || B≤A || (ξ b)

```

8.2.4 Product invariance of \models

An identity satisfied by all algebras in an indexed collection is also satisfied by the product of algebras in that collection.

```

module _ {X : Type} {χ} {I : Type} {ℓ} {A : I → Algebra α ρa} {p q : Term X} where

|=P-invar : (∀ i → A i |= (p ≈ · q)) → ∏ A |= (p ≈ · q)
|=P-invar A p q a = goal
  where
    open Algebra (∏ A) using () renaming ( Domain to ∏A )
    open Environment (∏ A) using () renaming ( ⟦_⟦ to ⟦_⟦₁ )
    open Environment using ( ⟦_⟦ )
    open Setoid ∏A using ( _≈_ )
    open SetoidReasoning ∏A

    ξ : (λ i → (⟦ A i ⟧ p) ⟨$⟩ (λ x → (a x) i)) ≈ (λ i → (⟦ A i ⟧ q) ⟨$⟩ (λ x → (a x) i))
    ξ = λ i → A p q i (λ x → (a x) i)
    goal : ⟦ p ⟧₁ ⟨$⟩ a ≈ ⟦ q ⟧₁ ⟨$⟩ a
    goal = begin
      ⟦ p ⟧₁ ⟨$⟩ a ≈⟨ interp-prod A p a ⟩
        (λ i → (⟦ A i ⟧ p) ⟨$⟩ (λ x → (a x) i)) ≈⟨ ξ ⟩
        (λ i → (⟦ A i ⟧ q) ⟨$⟩ (λ x → (a x) i)) ≈⟨ interp-prod A q a ⟩
        ⟦ q ⟧₁ ⟨$⟩ a ■

```

8.2.5 $\text{PS} \subseteq \text{SP}$

Another important fact we will need about the operators S and P is that a product of subalgebras of algebras in a class \mathcal{K} is a subalgebra of a product of algebras in \mathcal{K} . We denote this inclusion by $\text{PS} \subseteq \text{SP}$, which we state and prove as follows.

```

module _ { $\mathcal{K} : \text{Pred}(\text{Algebra } \alpha \rho^a) (\alpha \sqcup \rho^a \sqcup \text{ov } \ell)$ } where
private
  a =  $\alpha \sqcup \rho^a$ 
  oal = ov (a  $\sqcup \ell$ )

  PS $\subseteq$ SP : P (a  $\sqcup \ell$ ) oal (S{ $\beta = \alpha$ }{ $\rho^a$ }  $\ell \mathcal{K}$ )  $\subseteq$  S oal (P  $\ell$  oal  $\mathcal{K}$ )
  PS $\subseteq$ SP {B} (I, (A, sA, B $\cong$  $\sqcap$ A)) = Goal
  where
    B : I  $\rightarrow$  Algebra  $\alpha \rho^a$ 
    B i = | sA i |
    kB : (i : I)  $\rightarrow$  B i  $\in \mathcal{K}$ 
    kB i = fst || sA i ||
     $\sqcap$ A $\leq$  $\sqcap$ B :  $\sqcap$  A  $\leq$   $\sqcap$  B
     $\sqcap$ A $\leq$  $\sqcap$ B =  $\sqcap$ - $\leq$   $\lambda$  i  $\rightarrow$  snd || sA i ||
    Goal : B  $\in$  S{ $\beta = \text{oal}$ }{ $\text{oal}$ } oal (P { $\beta = \text{oal}$ }{ $\text{oal}$ }  $\ell$  oal  $\mathcal{K}$ )
    Goal =  $\sqcap$  B, (I, (B, (kB,  $\cong$ -refl))), ( $\cong$ -trans- $\leq$  B $\cong$  $\sqcap$ A  $\sqcap$ A $\leq$  $\sqcap$ B)

```

8.3 Identity preservation

The classes $H \mathcal{K}$, $S \mathcal{K}$, $P \mathcal{K}$, and $V \mathcal{K}$ all satisfy the same set of equations. We will only use a subset of the inclusions used to prove this fact. (For a complete proof, see the Varieties.Func.Preservation module of the Agda Universal Algebra Library.)

8.3.1 H preserves identities

First we prove that the closure operator H is compatible with identities that hold in the given class.

```

module _ {X : Type} { $\mathcal{K} : \text{Pred}(\text{Algebra } \alpha \rho^a) (\alpha \sqcup \rho^a \sqcup \text{ov } \ell)$ } {p q : Term X} where

H-id1 :  $\mathcal{K} \models (p \approx \cdot q) \rightarrow (H \{ \beta = \alpha \} \{ \rho^a \} \ell \mathcal{K}) \models (p \approx \cdot q)$ 
H-id1  $\sigma$  B (A, kA, BimgOfA)  $\rho$  = B $\models$ pq
  where
    IH : A  $\models (p \approx \cdot q)$ 
    IH =  $\sigma$  A kA
    open Environment A using () renaming ( [ ] to [ ]1 )
    open Environment B using ( [ ] )
    open Setoid  $\mathbb{D}[B]$  using (  $\approx$  )
    open SetoidReasoning  $\mathbb{D}[B]$ 

     $\varphi$  : hom A B
     $\varphi$  = | BimgOfA |
     $\varphi$ E : IsSurjective |  $\varphi$  |
     $\varphi$ E = || BimgOfA ||
     $\varphi^{-1}$  :  $\mathbb{U}[B] \rightarrow \mathbb{U}[A]$ 
     $\varphi^{-1}$  = SurjInv |  $\varphi$  |  $\varphi$ E

     $\zeta$  :  $\forall x \rightarrow (| \varphi | \langle \$ \rangle (\varphi^{-1} \circ \rho) x) \approx \rho x$ 
     $\zeta$  =  $\lambda$  _  $\rightarrow$  SurjInvIsInverser |  $\varphi$  |  $\varphi$ E

    B $\models$ pq : ( $\llbracket p \rrbracket \langle \$ \rangle \rho$ )  $\approx$  ( $\llbracket q \rrbracket \langle \$ \rangle \rho$ )

```

```

B⊨pq = begin
  [ p ] $ ρ ≈< cong [ p ] ζ >
  [ p ] $ (λ x → (| φ | $ (φ-1 ∘ ρ) x)) ≈< comm-hom-term φ p (φ-1 ∘ ρ) >
  | φ | $ ([ p ]1 $ (φ-1 ∘ ρ)) ≈< cong | φ | (IH (φ-1 ∘ ρ)) >
  | φ | $ ([ q ]1 $ (φ-1 ∘ ρ)) ≈< comm-hom-term φ q (φ-1 ∘ ρ) >
  [ q ] $ (λ x → (| φ | $ (φ-1 ∘ ρ) x)) ≈< cong [ q ] ζ >
  [ q ] $ ρ
  ■

```

8.3.2 S preserves identities

S-id1 : $\mathcal{K} \models (p \approx \cdot q) \rightarrow (\mathcal{S} \{ \beta = \alpha \} \{ \rho^a \} \ell \mathcal{K}) \models (p \approx \cdot q)$
 S-id1 $\sigma \mathbf{B} (\mathbf{A}, \mathbf{kA}, \mathbf{B} \leq \mathbf{A}) = \models\text{-S-invar} \{ p = p \} \{ q \} (\sigma \mathbf{A} \mathbf{kA}) \mathbf{B} \leq \mathbf{A}$

The obvious converse is barely worth the bits needed to formalize it, but we will use it below, so let's prove it now.

S-id2 : $\mathcal{S} \ell \mathcal{K} \models (p \approx \cdot q) \rightarrow \mathcal{K} \models (p \approx \cdot q)$
 S-id2 $\text{Spq } \mathbf{A} \mathbf{kA} = \text{Spq } \mathbf{A} (\mathbf{A}, (\mathbf{kA}, \leq\text{-reflexive}))$

8.3.3 P preserves identities

P-id1 : $\forall \{ \iota \} \rightarrow \mathcal{K} \models (p \approx \cdot q) \rightarrow \mathbf{P} \{ \beta = \alpha \} \{ \rho^a \} \ell \iota \mathcal{K} \models (p \approx \cdot q)$
 P-id1 $\sigma \mathbf{A} (\mathbf{I}, \mathcal{A}, \mathbf{kA}, \mathbf{A} \cong \sqcap \mathbf{A}) = \models\text{-I-invar } \mathbf{A} \mathbf{p} \mathbf{q} \text{ IH } (\cong\text{-sym } \mathbf{A} \cong \sqcap \mathbf{A})$
 where
 ih : $\forall i \rightarrow \mathcal{A} i \models (p \approx \cdot q)$
 ih i = $\sigma (\mathcal{A} i) (\mathbf{kA} i)$
 IH : $\sqcap \mathcal{A} \models (p \approx \cdot q)$
 IH = $\models\text{-P-invar } \mathcal{A} \{ p \} \{ q \} \text{ ih}$

8.3.4 V preserves identities

Finally, we prove the analogous preservation lemmas for the closure operator V.

```

module _ {X : Type} {χ : {ι : Level}} {K : Pred (Algebra α ρa) (α ⊔ ρa ⊔ ov ℓ)} {p q : Term X} where
  private
    alι = α ⊔ ρa ⊔ ℓ ⊔ ι

  V-id1 : K ⊨ (p ≈ · q) → V ℓ ι K ⊨ (p ≈ · q)
  V-id1 σ B (A, (⊔A, p⊔A, A ≤ ⊔A), BimgA) =
    H-id1 {ℓ = alι} {K = S alι (P {β = α} {ρa} ℓ ι K)} {p = p} {q = q} spK⊨pq B (A, (spA, BimgA))
    where
      spA : A ∈ S alι (P {β = α} {ρa} ℓ ι K)
      spA = ⊔A, (p⊔A, A ≤ ⊔A)
      spK⊨pq : S alι (P ℓ ι K) ⊨ (p ≈ · q)
      spK⊨pq = S-id1 {ℓ = alι} {p = p} {q = q} (P-id1 {ℓ = ℓ} {K = K} {p = p} {q = q} σ)

```

8.3.5 $\text{Th } \mathcal{K} \subseteq \text{Th } (\mathbf{V } \mathcal{K})$

From $\mathbf{V}\text{-id1}$ it follows that if \mathcal{K} is a class of algebras, then the set of identities modeled by the algebras in \mathcal{K} is contained in the set of identities modeled by the algebras in $\mathbf{V } \mathcal{K}$. In other terms, $\text{Th } \mathcal{K} \subseteq \text{Th } (\mathbf{V } \mathcal{K})$. We formalize this observation as follows.

```
classIds-⊆-VIds :  $\mathcal{K} \models (p \approx q) \rightarrow (p, q) \in \text{Th } (\mathbf{V } \ell \iota \mathcal{K})$ 
classIds-⊆-VIds pKq A = V-id1 pKq A
```

9 Free Algebras

9.1 The absolutely free algebra $\mathbf{T } X$

The term algebra $\mathbf{T } X$ is *absolutely free* (or *universal*, or *initial*) for algebras in the signature S . That is, for every S -algebra A , the following hold.

1. Every function from X to $|A|$ lifts to a homomorphism from $\mathbf{T } X$ to A .
2. The homomorphism that exists by item 1 is unique.

We now prove this in Agda, starting with the fact that every map from X to $|A|$ lifts to a map from $|\mathbf{T } X|$ to $|A|$ in a natural way, by induction on the structure of the given term.

```
module _ {X : Type} {A : Algebra α ρa} (h : X → U[ A ]) where
  open Algebra A using () renaming ( Domain to A ; Interp to InterpA )
  open Setoid A using ( _≈_ ; reflexive ; refl ; trans ) renaming ( Carrier to |A| )
  open Algebra (T X) using () renaming ( Domain to TX )
  open Setoid TX using () renaming ( Carrier to |TX| )

  free-lift : U[ T X ] → U[ A ]
  free-lift (g x) = h x
  free-lift (node f t) = (f ^ A) (λ i → free-lift (t i))

  free-lift-func : TX → A
  free-lift-func ($) x = free-lift x
  cong free-lift-func = flcong
  where
    flcong : ∀ {s t} → s ≐ t → free-lift s ≈ free-lift t
    flcong (≐.rfl x) = reflexive (≡.cong h x)
    flcong (≐.gnl x) = cong InterpA (≡.refl , (λ i → flcong (x i)))
```

Naturally, at the base step of the induction, when the term has the form **generator** x , the free lift of h agrees with h . For the inductive step, when the given term has the form **node** $f t$, the free lift is defined as follows: Assuming (the induction hypothesis) that we know the image of each subterm $t i$ under the free lift of h , define the free lift at the full term by applying $f ^ A$ to the images of the subterms.

The free lift so defined is a homomorphism by construction. Indeed, here is the trivial proof.

```
lift-hom : hom (T X) A
lift-hom = free-lift-func , hhom
where
```

```

hfunc : TX → A
hfunc = free-lift-func

hcomp : compatible-map (T X) A free-lift-func
hcomp {f}{a} = cong InterpA (≡.refl , (λ i → (cong free-lift-func){a i} ≐-isRefl))

hhom : IsHom (T X) A hfunc
hhom = record { compatible = λ{f}{a} → hcomp{f}{a} }

module _ {X : Type χ} {A : Algebra α ρa} where
  open Algebra A using () renaming ( Domain to A ; Interp to InterpA )
  open Setoid A using ( _≈_ ; refl ) renaming ( Carrier to |A| )
  open Environment A using ( [ ] )

  free-lift-interp : (η : X → |A|)(p : Term X) → [ p ] ($) η ≈ (free-lift {A = A} η) p

  free-lift-interp η (g x) = refl
  free-lift-interp η (node f t) = cong InterpA (≡.refl , (free-lift-interp η) o t)

```

9.2 The relatively free algebra \mathbb{F}

We now define the algebra $\mathbb{F}[X]$, which plays the role of the relatively free algebra, along with the natural epimorphism $\text{epi}\mathbb{F} : \text{epi}(\mathbf{T} X) \mathbb{F}[X]$ from $\mathbf{T} X$ to $\mathbb{F}[X]$.

```

module FreeAlgebra {χ : Level}{ι : Level}{l : Type ι}{ℳ : l → Eq} where
  open Algebra

  FreeDomain : Type χ → Setoid _ _
  FreeDomain X = record { Carrier = Term X
                        ; _≈_ = ℳ ⊢ X ▷_≈_
                        ; isEquivalence = ▷≈IsEquiv }

```

The interpretation of an operation is simply the operation itself. This works since $\mathcal{E} \vdash X \triangleright_ \approx_$ is a congruence.

```

FreeInterp : ∀ {X} → ⟨ S ⟩ (FreeDomain X) → FreeDomain X
FreeInterp ($) (f , ts) = node f ts
cong FreeInterp (≡.refl , h) = app h

[ ] : Type χ → Algebra (ov χ) (ι ⊔ ov χ)
Domain  $\mathbb{F}[X]$  = FreeDomain X
Interp  $\mathbb{F}[X]$  = FreeInterp

```

9.3 Basic properties of free algebras

In the code below, X will play the role of an arbitrary collection of variables; it would suffice to take X to be the cardinality of the largest algebra in \mathcal{K} , but since we don't know that cardinality, we leave X arbitrary for now.

```

module FreeHom (χ : Level) {ℳ : Pred(Algebra α ρa) (α ⊔ ρa ⊔ ov ℓ)} where
  private ι = ov(χ ⊔ α ⊔ ρa ⊔ ℓ)
  open Eq

```

```

 $\mathcal{J} : \text{Type } \iota$  – indexes the collection of equations modeled by  $\mathcal{K}$ 
 $\mathcal{J} = \Sigma [ \text{eq} \in \text{Eq} \{ \chi \} ] \mathcal{K} \models ((\text{lhs eq}) \approx \cdot (\text{rhs eq}))$ 

 $\mathcal{E} : \mathcal{J} \rightarrow \text{Eq}$ 
 $\mathcal{E} (\text{eqv } , p) = \text{eqv}$ 

 $\mathcal{E} \vdash \_ \triangleright \text{Th} \mathcal{K} : (X : \text{Type } \chi) \rightarrow \forall \{p \ q\} \rightarrow \mathcal{E} \vdash X \triangleright p \approx q \rightarrow \mathcal{K} \models (p \approx \cdot q)$ 
 $\mathcal{E} \vdash [X] \triangleright \text{Th} \mathcal{K} \times \mathbf{A} \text{ kA} = \text{sound } (\lambda i \ \rho \rightarrow \parallel i \parallel \mathbf{A} \text{ kA } \rho) \ x$ 
  where open Soundness  $\mathcal{E} \ \mathbf{A}$ 

open FreeAlgebra  $\{ \iota = \iota \} \{ l = \mathcal{J} \} \mathcal{E}$  using (  $\mathbb{F} [ \_ ]$  )

```

9.3.1 The natural epimorphism from $\mathbf{T} \ X$ to $\mathbb{F} [X]$

Next we define an epimorphism from $\mathbf{T} \ X$ onto the relatively free algebra $\mathbb{F} [X]$. Of course, the kernel of this epimorphism will be the congruence of $\mathbf{T} \ X$ defined by identities modeled by $(S \ \mathcal{K})$, hence \mathcal{K} .

```

epiF [ _ ] : (X : Type  $\chi$ )  $\rightarrow$  epi (  $\mathbf{T} \ X$  )  $\mathbb{F} [ X ]$ 
epiF [ X ] = h , hepi
  where
    open Algebra  $\mathbb{F} [ X ]$  using () renaming ( Domain to F ; Interp to InterpF )
    open Setoid F using () renaming (  $\_ \approx \_$  to  $\_ \approx F \approx \_$  ; refl to reflF )
    open Algebra (  $\mathbf{T} \ X$  ) using () renaming ( Domain to TX )
    open Setoid TX using () renaming (  $\_ \approx \_$  to  $\_ \approx T \approx \_$  ; refl to reflT )
    open  $\_ \dot{=} \_$  ; open IsEpi ; open IsHom

    c :  $\forall \{x \ y\} \rightarrow x \approx T \approx y \rightarrow x \approx F \approx y$ 
    c (rfl {x}{y}  $\equiv$  refl) = reflF
    c (gnl {f}{s}{t} x) = cong InterpF ( $\equiv$ .refl , c  $\circ$  x)

    h : TX  $\rightarrow$  F
    h = record { f = id ; cong = c }

    hepi : IsEpi (  $\mathbf{T} \ X$  )  $\mathbb{F} [ X ]$  h
    compatible (isHom hepi) = cong h reflT
    isSurjective hepi {y} = eq y reflF

    homF [ _ ] : (X : Type  $\chi$ )  $\rightarrow$  hom (  $\mathbf{T} \ X$  )  $\mathbb{F} [ X ]$ 
    homF [ X ] = IsEpi.HomReduct  $\parallel$  epiF [ X ]  $\parallel$ 

    homF [ _ ]-is-epic : (X : Type  $\chi$ )  $\rightarrow$  IsSurjective  $\mid$  homF [ X ]  $\mid$ 
    homF [ X ]-is-epic = IsEpi.isSurjective (snd (epiF [ X ]))

```

9.3.2 The kernel of the natural epimorphism

```

class-models-kernel :  $\forall \{X \ p \ q\} \rightarrow (p , q) \in \text{ker} \mid \text{homF} [ X ] \mid \rightarrow \mathcal{K} \models (p \approx \cdot q)$ 
class-models-kernel {X = X} {p} {q} pKq =  $\mathcal{E} \vdash [ X ] \triangleright \text{Th} \mathcal{K} \ pKq$ 

kernel-in-theory :  $\{X : \text{Type } \chi\} \rightarrow \text{ker} \mid \text{homF} [ X ] \mid \subseteq \text{Th } (\mathbf{V} \ \ell \ \iota \ \mathcal{K})$ 
kernel-in-theory {X = X} {p , q} pKq vkA x = classIds- $\subseteq$ -Vlds {  $\ell = \ell$  } {p = p} {q}
  (class-models-kernel pKq) vkA x

```

```

module _ {X : Type  $\chi$ } {A : Algebra  $\alpha \rho^a$ } {sA : A  $\in$  S { $\beta = \alpha$ } { $\rho^a$ }  $\ell$   $\mathcal{K}$ } where
  open Environment A using ( Equal )
  kerF $\subseteq$ Equal :  $\forall \{p \ q\} \rightarrow (p , q) \in \text{ker} \mid \text{homF}[X] \mid \rightarrow \text{Equal } p \ q$ 
  kerF $\subseteq$ Equal {p = p} {q} x = S-id1 { $\ell = \ell$ } {p = p} {q} (  $\mathcal{E} \vdash X \triangleright \text{Th} \mathcal{K} \ x$  ) A sA

 $\mathcal{K} \models \rightarrow \mathcal{E} \vdash$  : {X : Type  $\chi$ }  $\rightarrow \forall \{p \ q\} \rightarrow \mathcal{K} \models (p \approx \cdot q) \rightarrow \mathcal{E} \vdash X \triangleright p \approx q$ 
 $\mathcal{K} \models \rightarrow \mathcal{E} \vdash$  {p = p} {q} pKq = hyp ((p  $\approx \cdot$  q) , pKq) where open _ $\vdash$  _ $\triangleright$  _ $\approx$  _ using (hyp)

```

9.3.3 The universal property

```

module _ {A : Algebra ( $\alpha \sqcup \rho^a \sqcup \ell$ ) ( $\alpha \sqcup \rho^a \sqcup \ell$ )}
  { $\mathcal{K}$  : Pred(Algebra  $\alpha \rho^a$ ) ( $\alpha \sqcup \rho^a \sqcup \text{ov } \ell$ )} where
  private  $\iota = \text{ov}(\alpha \sqcup \rho^a \sqcup \ell)$ 
  open IsEpi ; open IsHom
  open FreeHom { $\ell = \ell$ } ( $\alpha \sqcup \rho^a \sqcup \ell$ ) { $\mathcal{K}$ }
  open FreeAlgebra { $\iota = \iota$ } { $I = \mathcal{F}$ }  $\mathcal{E}$  using (  $\mathbb{F}[\_]$  )
  open Algebra A using() renaming (Domain to A ; Interp to InterpA )
  open Setoid A using ( trans ; sym ; refl ) renaming ( Carrier to |A| )

 $\mathbb{F}\text{-ModTh-epi}$  : A  $\in$  Mod (Th ( $\mathbb{V} \ell \iota \mathcal{K}$ ))
 $\rightarrow \text{epi } \mathbb{F}[|A|] \ A$ 
 $\mathbb{F}\text{-ModTh-epi}$  A  $\in$  ModThK =  $\varphi$  , isEpi
  where
     $\varphi$  :  $\mathbb{D}[\mathbb{F}[|A|]] \rightarrow A$ 
    _ $\langle \$ \rangle$   $\varphi$  = free-lift {A = A} id
    cong  $\varphi$  {p} {q} pq = trans (sym (free-lift-interp {A = A} id p))
      (trans (A  $\in$  ModThK {p = p} {q} (kernel-in-theory pq) id)
        (free-lift-interp {A = A} id q))

    isEpi : IsEpi  $\mathbb{F}[|A|] \ A \ \varphi$ 
    compatible (isHom isEpi) = cong InterpA ( $\equiv$ .refl , ( $\lambda \_ \rightarrow \text{refl}$ ))
    isSurjective isEpi {y} = eq ( $\mathcal{G} \ y$ ) refl

 $\mathbb{F}\text{-ModTh-epi-lift}$  : A  $\in$  Mod (Th ( $\mathbb{V} \ell \iota \mathcal{K}$ ))  $\rightarrow \text{epi } \mathbb{F}[|A|] \ (\text{Lift-Alg } A \ \iota \ \iota)$ 
 $\mathbb{F}\text{-ModTh-epi-lift}$  A  $\in$  ModThK = o-epi ( $\mathbb{F}\text{-ModTh-epi } (\lambda \{p \ q\} \rightarrow A \in \text{ModThK} \{p = p\} \{q\})$ ) ToLift-epi

```

10 Products of classes of algebras

We want to pair each (A, p) (where $p : A \in S \mathcal{K}$) with an environment $\rho : X \rightarrow |A|$ so that we can quantify over all algebras *and* all assignments of values in the domain $|A|$ to variables in X .

```

module _ ( $\mathcal{K}$  : Pred(Algebra  $\alpha \rho^a$ ) ( $\alpha \sqcup \rho^a \sqcup \text{ov } \ell$ )) {X : Type ( $\alpha \sqcup \rho^a \sqcup \ell$ )} where
  private  $\iota = \text{ov}(\alpha \sqcup \rho^a \sqcup \ell)$ 
  open FreeHom { $\ell = \ell$ } ( $\alpha \sqcup \rho^a \sqcup \ell$ ) { $\mathcal{K}$ }
  open FreeAlgebra { $\iota = \iota$ } { $I = \mathcal{F}$ }  $\mathcal{E}$  using (  $\mathbb{F}[\_]$  )
  open Environment using ( Env )

   $\mathcal{I}^+ : \text{Type } \iota$ 

```

```

 $\mathcal{J}^+ = \Sigma[ \mathbf{A} \in (\text{Algebra } \alpha \rho^a) ] (\mathbf{A} \in S \ell \mathcal{K}) \times (\text{Carrier } (\text{Env } \mathbf{A} \mathbf{X}))$ 

 $\mathfrak{A}^+ : \mathcal{J}^+ \rightarrow \text{Algebra } \alpha \rho^a$ 
 $\mathfrak{A}^+ i = | i |$ 

 $\mathfrak{C} : \text{Algebra } \iota \iota$ 
 $\mathfrak{C} = \prod \mathfrak{A}^+$ 

```

Next we define a useful type, `skEqual`, which we use to represent a term identity $p \approx q$ for any given $i = (\mathbf{A}, s\mathbf{A}, \rho)$ (where \mathbf{A} is an algebra, $s\mathbf{A} : \mathbf{A} \in S \mathcal{K}$ is a proof that \mathbf{A} belongs to $S \mathcal{K}$, and ρ is a mapping from \mathbf{X} to the domain of \mathbf{A}). Then we prove `AllEqual \subseteq kerF` which asserts that if the identity $p \approx q$ holds in all $\mathbf{A} \in S \mathcal{K}$ (for all environments), then $p \approx q$ holds in the relatively free algebra $\mathbb{F}[\mathbf{X}]$; equivalently, the pair (p, q) belongs to the kernel of the natural homomorphism from $\mathbf{T} \mathbf{X}$ onto $\mathbb{F}[\mathbf{X}]$. We will use this fact below to prove that there is a monomorphism from $\mathbb{F}[\mathbf{X}]$ into \mathfrak{C} , and thus $\mathbb{F}[\mathbf{X}]$ is a subalgebra of \mathfrak{C} , so belongs to $S(\mathcal{P} \mathcal{K})$.

```

skEqual : (i :  $\mathcal{J}^+$ )  $\rightarrow \forall \{p q\} \rightarrow \text{Type } \rho^a$ 
skEqual i {p}{q} = [| p |] ($) snd || i ||  $\approx$  [| q |] ($) snd || i ||
  where
    open Setoid  $\mathbb{D}[\mathfrak{A}^+ i]$  using (  $\_ \approx \_$  )
    open Environment ( $\mathfrak{A}^+ i$ ) using ( [|_] )

AllEqual $\subseteq$ kerF :  $\forall \{p q\} \rightarrow (\forall i \rightarrow \text{skEqual } i \{p\}\{q\}) \rightarrow (p, q) \in \text{ker} \mid \text{hom } \mathbb{F}[\mathbf{X}] \mid$ 
AllEqual $\subseteq$ kerF {p} {q} x = Goal
  where
    open Algebra  $\mathbb{F}[\mathbf{X}]$  using () renaming ( Domain to F ; Interp to InterpF )
    open Setoid F using () renaming (  $\_ \approx \_$  to  $\_ \approx F \approx \_$  ; refl to reflF )
     $\mathcal{K} \models pq : S\{\beta = \alpha\}\{\rho^a\} \ell \mathcal{K} \models (p \approx \cdot q)$ 
     $\mathcal{K} \models pq \mathbf{A} s\mathbf{A} \rho = x (\mathbf{A}, s\mathbf{A}, \rho)$ 
    Goal :  $p \approx F \approx q$ 
    Goal =  $\mathcal{K} \models \rightarrow \mathcal{E} \vdash (\text{S-id2}\{\ell = \ell\}\{p = p\}\{q\} \mathcal{K} \models pq)$ 

hom $\mathfrak{C} : \text{hom } (\mathbf{T} \mathbf{X}) \mathfrak{C}$ 
hom $\mathfrak{C} = \prod \text{-hom-co } \mathfrak{A}^+ h$ 
  where
    h :  $\forall i \rightarrow \text{hom } (\mathbf{T} \mathbf{X}) (\mathfrak{A}^+ i)$ 
    h i = lift-hom (snd || i ||)

open Algebra  $\mathbb{F}[\mathbf{X}]$  using () renaming ( Domain to F ; Interp to InterpF )
open Setoid F using () renaming ( refl to reflF ;  $\_ \approx \_$  to  $\_ \approx F \approx \_$  ; Carrier to |F| )

kerF $\subseteq$ ker $\mathfrak{C} : \text{ker} \mid \text{hom } \mathbb{F}[\mathbf{X}] \mid \subseteq \text{ker} \mid \text{hom } \mathfrak{C} \mid$ 
kerF $\subseteq$ ker $\mathfrak{C} \{p, q\} \text{pKq } (\mathbf{A}, s\mathbf{A}, \rho) = \text{Goal}$ 
  where
    open Setoid  $\mathbb{D}[\mathbf{A}]$  using (  $\_ \approx \_$  ; sym ; trans )
    open Environment  $\mathbf{A}$  using ( [|_] )
    fl :  $\forall t \rightarrow [| t |] ($) \rho \approx \text{free-lift } \rho t$ 
    fl t = free-lift-interp  $\{\mathbf{A} = \mathbf{A}\} \rho t$ 
    subgoal : [| p |] ($)  $\rho \approx$  [| q |] ($)  $\rho$ 
    subgoal = kerF $\subseteq$ Equal $\{\mathbf{A} = \mathbf{A}\}\{s\mathbf{A}\} \text{pKq } \rho$ 
    Goal : (free-lift $\{\mathbf{A} = \mathbf{A}\} \rho p) \approx$  (free-lift $\{\mathbf{A} = \mathbf{A}\} \rho q)$ 
    Goal = trans (sym (fl p)) (trans subgoal (fl q))

```



```

homF $\mathcal{C}$  : hom  $\mathbb{F}[X]$   $\mathcal{C}$ 
homF $\mathcal{C}$  = | HomFactor  $\mathcal{C}$  hom $\mathcal{C}$  homF $[X]$  kerF $\subseteq$ ker $\mathcal{C}$  homF $[X]$ -is-epic |

open Environment  $\mathcal{C}$ 

ker $\mathcal{C}\subseteq$ kerF :  $\forall\{p\ q\} \rightarrow (p, q) \in \text{ker} \mid \text{hom}\mathcal{C} \mid \rightarrow (p, q) \in \text{ker} \mid \text{homF}[X] \mid$ 
ker $\mathcal{C}\subseteq$ kerF {p}{q} pKq = E $\vdash$ pq
  where
    pqEqual :  $\forall\ i \rightarrow \text{skEqual}\ i\ \{p\}\{q\}$ 
    pqEqual i = goal
      where
        open Environment ( $\mathfrak{A}^+$  i) using () renaming (  $\llbracket \_ \rrbracket$  to  $\llbracket \_ \rrbracket_i$  )
        open Setoid  $\mathbb{D}[\mathfrak{A}^+ i]$  using (  $\_ \approx \_$  ; sym ; trans )
        goal :  $\llbracket p \rrbracket_i \langle \$ \rangle \text{snd} \parallel i \parallel \approx \llbracket q \rrbracket_i \langle \$ \rangle \text{snd} \parallel i \parallel$ 
        goal = trans (free-lift-interp{A = | i |}(snd  $\parallel i \parallel$ ) p)
                  (trans (pKq i)(sym (free-lift-interp{A = | i |}(snd  $\parallel i \parallel$ ) q)))
    E $\vdash$ pq :  $\mathcal{E} \vdash X \triangleright p \approx q$ 
    E $\vdash$ pq = AllEqual $\subseteq$ kerF pqEqual

monF $\mathcal{C}$  : mon  $\mathbb{F}[X]$   $\mathcal{C}$ 
monF $\mathcal{C}$  = | homF $\mathcal{C}$  | , isMon
  where
    open IsMon
    open IsHom
    isMon : IsMon  $\mathbb{F}[X]$   $\mathcal{C}$  | homF $\mathcal{C}$  |
    isHom isMon =  $\parallel \text{homF}\mathcal{C} \parallel$ 
    isInjective isMon {p} {q}  $\varphi$ pq = ker $\mathcal{C}\subseteq$ kerF  $\varphi$ pq

```

Now that we have proved the existence of a monomorphism from $\mathbb{F}[X]$ to \mathcal{C} we are in a position to prove that $\mathbb{F}[X]$ is a subalgebra of \mathcal{C} , so belongs to $S(P\mathcal{K})$. In fact, we will show that $\mathbb{F}[X]$ is a subalgebra of the *lift* of \mathcal{C} , denoted $\ell\mathcal{C}$.

```

 $\mathbb{F}\leq\mathcal{C}$  :  $\mathbb{F}[X] \leq \mathcal{C}$ 
 $\mathbb{F}\leq\mathcal{C}$  = mon $\rightarrow\leq$  monF $\mathcal{C}$ 

SPF :  $\mathbb{F}[X] \in S\ \iota(P\ \ell\ \iota\mathcal{K})$ 
SPF = S-idem SSPF
  where
    PS $\mathcal{C}$  :  $\mathcal{C} \in P(\alpha \sqcup \rho^a \sqcup \ell) \ \iota(S\ \ell\mathcal{K})$ 
    PS $\mathcal{C}$  =  $\mathfrak{I}^+$  , ( $\mathfrak{A}^+$  , (( $\lambda\ i \rightarrow \text{fst} \parallel i \parallel$ ) ,  $\cong\text{-refl}$ ))
    SP $\mathcal{C}$  :  $\mathcal{C} \in S\ \iota(P\ \ell\ \iota\mathcal{K})$ 
    SP $\mathcal{C}$  = PS $\subseteq$ SP { $\ell = \ell$ } PS $\mathcal{C}$ 
    SSPF :  $\mathbb{F}[X] \in S\ \iota(S\ \iota(P\ \ell\ \iota\mathcal{K}))$ 
    SSPF =  $\mathcal{C}$  , (SP $\mathcal{C}$  ,  $\mathbb{F}\leq\mathcal{C}$ )

```

11 The HSP Theorem

Finally, we are in a position to prove Birkhoff's celebrated variety theorem.

```

module  $\_$  { $\mathcal{K}$  : Pred(Algebra  $\alpha\ \rho^a$ ) ( $\alpha \sqcup \rho^a \sqcup \text{ov}\ \ell$ ) } where

```

```

private  $\iota = \text{ov}(\alpha \sqcup \rho^a \sqcup \ell)$ 
open FreeHom  $\{\ell = \ell\}(\alpha \sqcup \rho^a \sqcup \ell)\{\mathcal{K}\}$ 
open FreeAlgebra  $\{\iota = \iota\}\{I = \mathcal{J}\} \mathcal{E}$  using (  $\mathbb{F}[\_]$  )

Birkhoff :  $\forall \mathbf{A} \rightarrow \mathbf{A} \in \text{Mod} (\text{Th} (\mathbf{V} \ell \iota \mathcal{K})) \rightarrow \mathbf{A} \in \mathbf{V} \ell \iota \mathcal{K}$ 
Birkhoff  $\mathbf{A} \text{ ModThA} = \mathbf{V}\text{-}\cong\text{-Ic}\{\alpha\}\{\rho^a\}\{\ell\} \mathcal{K} \mathbf{A} \text{ VIA}$ 
where
open Setoid  $\mathbb{D}[\mathbf{A}]$  using () renaming ( Carrier to  $\mathbf{A}$  )
spFA :  $\mathbb{F}[\mathbf{A}] \in \mathbf{S}\{\iota\} \iota (\mathbf{P} \ell \iota \mathcal{K})$ 
spFA =  $\text{SPF}\{\ell = \ell\} \mathcal{K}$ 
epiFA :  $\text{epi } \mathbb{F}[\mathbf{A}] (\text{Lift-Alg } \mathbf{A} \iota \iota)$ 
epiFA =  $\mathbb{F}\text{-ModTh-epi-lift}\{\ell = \ell\} (\lambda \{p\ q\} \rightarrow \text{ModThA}\{p = p\}\{q\})$ 
IAimgFA :  $\text{Lift-Alg } \mathbf{A} \iota \iota \text{ IsHomImageOf } \mathbb{F}[\mathbf{A}]$ 
IAimgFA =  $\text{epi} \rightarrow \text{ontohom } \mathbb{F}[\mathbf{A}] (\text{Lift-Alg } \mathbf{A} \iota \iota) \text{ epiFA}$ 
VIA :  $\text{Lift-Alg } \mathbf{A} \iota \iota \in \mathbf{V} \ell \iota \mathcal{K}$ 
VIA =  $\mathbb{F}[\mathbf{A}] , \text{spFA} , \text{IAimgFA}$ 

```

The converse inclusion, $\mathbf{V} \mathcal{K} \subseteq \text{Mod} (\text{Th} (\mathbf{V} \mathcal{K}))$, is a simple consequence of the fact that Mod Th is a closure operator. Nonetheless, completeness demands that we formalize this inclusion as well, however trivial the proof.

```

module _ { $\mathbf{A} : \text{Algebra } \alpha \rho^a$ } where
open Setoid  $\mathbb{D}[\mathbf{A}]$  using () renaming ( Carrier to  $\mathbf{A}$  )

Birkhoff-converse :  $\mathbf{A} \in \mathbf{V}\{\alpha\}\{\rho^a\}\{\alpha\}\{\rho^a\}\{\alpha\}\{\rho^a\} \ell \iota \mathcal{K} \rightarrow \mathbf{A} \in \text{Mod}\{X = \mathbf{A}\} (\text{Th} (\mathbf{V} \ell \iota \mathcal{K}))$ 
Birkhoff-converse vA pThq = pThq  $\mathbf{A}$  vA

```

We have thus proved that every variety is an equational class.

Readers familiar with the classical formulation of the Birkhoff HSP theorem as an “if and only if” assertion might worry that the proof is still incomplete. However, recall that in the `Varieties.Func.Preservation` module we proved the following identity preservation lemma:

$\text{V-id1} : \mathcal{K} \models p \approx q \rightarrow \mathbf{V} \mathcal{K} \models p \approx q$

Thus, if \mathcal{K} is an equational class—that is, if \mathcal{K} is the class of algebras satisfying all identities in some set—then $\mathbf{V} \mathcal{K} \subseteq \mathcal{K}$. On the other hand, we proved that \mathbf{V}' is expansive in the `Varieties.Func.Closure` module:

$\text{V-expa} : \mathcal{K} \subseteq \mathbf{V} \mathcal{K}$

so $\mathcal{K} (= \mathbf{V} \mathcal{K} = \text{HSP } \mathcal{K})$ is a variety.

Taken together, `V-id1` and `V-expa` constitute formal proof that every equational class is a variety.

This completes the formal proof of Birkhoff’s variety theorem.

12 Appendix

The `Setoid` type is defined in the `Agda Standard Library` as follows.

```

record Setoid c  $\ell$  : Set (suc (c  $\sqcup$   $\ell$ )) where
  field
    Carrier          : Set c
     $\approx$                : Rel Carrier  $\ell$ 
    isEquivalence    : IsEquivalence  $\approx$ 

```

The `Func` type is defined in the [Agda Standard Library](#) as follows.

```
record Func : Set (a ⊔ b ⊔ ℓ1 ⊔ ℓ2) where
  field
    f      : A → B
    cong   : f Preserves _≈1_ → _≈2_

  isCongruent : IsCongruent f
  isCongruent = record
    { cong          = cong
    ; isEquivalence1 = isEquivalence From
    ; isEquivalence2 = isEquivalence To
    }

  open IsCongruent isCongruent public
    using (module Eq1; module Eq2)
```

Here, A and B are setoids with respective equality relations \approx_1 and \approx_2 .