

A Language Feature to Unbundle Data at Will

MUSA AL-HASSY, JACQUES CARETTE, WOLFRAM KAHL

ACM Reference format:

Musa Al-hassy, Jacques Carette, Wolfram Kahl. YYYY. A Language Feature to Unbundle Data at Will. VV, NNN, Article AA (MM YYYY), 5 pages.

DOI: 10.1145/nnnnnnnn.nnnnnnnn

Abstract

Programming languages with sufficiently expressive type theories provide users with essentially two levels of data ‘bundling’. For example in Agda, Coq, and Idris, one can choose to make certain constituents of a record either parameters or fields —e.g., we can speak of graphs *over* a particular vertex set, or speak of arbitrary graphs wherein the vertex set is a component. These create isomorphic types, but differ with respect to convenience. Traditionally, a library designer would make this choice between parameters and fields; if a user wants a variant, they are forced to build conversion utilities as well as duplicate functionality, for convenience. In our earlier graphs example, if a library only provides a Haskell-like typeclass view of graphs *over* a vertex set, yet a user wishes to work with the category of graphs, they must now package the vertex set as a component in a record along with the graph over that set. We design and implement a language feature that allows both the library designer and the user to make the choice of information exposure only when necessary and otherwise leave the distinguishing line between parameters and fields unspecified.

Our language feature is currently prototypically implemented as a meta-program that is not only easily incorporated into Agda’s Emacs ecosystem, but is also unobtrusive to Agda users.

1 INTRODUCTION —SELECTING THE ‘RIGHT’ PERSPECTIVE

Library designers want to produce software components that are useful to their immediate needs but also useful to the needs of others, such as themselves for a later project. As such, designers aim for a high-level of generality for increased reusability. The dimension we tackle in this paper is how much of a structures constituents are exposed at the type level and how many are left inside, to be projected when needed.

The subtlety of what is a ‘parameter’ —exposed at the type level— and what is a ‘field’ —hidden as a component value— has led to awkward formulations and the duplication of existing types for the sole purpose of different uses. For example, the ever-ubiquitous monoid, a prime model of compositionality, that, say, in traditional Haskell, is only allowed one instance is for a datatype. The Booleans, however, have multiple monoids such as a sequential and a parallel monoids —the former being conjunction with identity *true* and the latter being disjunction with identity *false*— which are tractable demonstrations mirroring sequential and concurrent programming.

The solution, in Haskell, is to have two isomorphic copies *All* and *Any* for which the former is given the sequential monoid and the latter the parallel monoid. An alternative solution would be to parameterise the monoid interface not only by its carrier type —the Booleans in our example— but also by the underlying compositionality scheme —the conjunction and disjunction operators in our scheme.

It seems that there are two contenders for the monoid interface:

YYYY. XXXX-XX/YYYY/MM-ARTAA \$15.00

DOI: 10.1145/nnnnnnnn.nnnnnnnn

```

1  record Monoid1 (Carrier : Set) : Set where
2    field
3      _◊_      : Carrier → Carrier → Carrier
4      Id       : Carrier
5      assoc    : ∀ {x y z} → (x ◊ y) ◊ z ≡ x ◊ (y ◊ z)
6      leftId   : ∀ {x} → Id ◊ x ≡ x
7      rightId  : ∀ {x} → x ◊ Id ≡ x
8
9
10 record Monoid2 (Carrier : Set) (_◊_ : Carrier → Carrier → Carrier) : Set where
11   Id       : Carrier
12   assoc    : ∀ {x y z} → (x ◊ y) ◊ z ≡ x ◊ (y ◊ z)
13   leftId   : ∀ {x} → Id ◊ x ≡ x
14   rightId  : ∀ {x} → x ◊ Id ≡ x

```

Of-course there are also the alternative formulations of where we bundle up the Carrier rather than have it exposed —e.g., when we wish to speak of *a* monoid rather than *a monoid on a given type*— or where we are interested in the identity element rather than in the compositionality scheme —e.g., discrepancy ‘’ and indistinguishability ‘≡’ have the same identities as conjunction and disjunction, respectively. Moreover, there are other combinations of what is to be exposed and hidden, for cases that we might never conceive of.

Rather code with *interface formulations we think people will likely use*, it is far more general to *commit to no particular formulation* and allow the user to select the form most convenient for their use-cases. This desire for reusability motives a new language feature: The PackageFormer.

Moreover, what if the user wanted the syntax to form monoid terms as in metaprogramming. That would necessitate yet another nearly identical data-structure —having constructors rather than field projections. We show how all these different presentations can be derived from a *single* PackageFormer declaration. It is this massive reduction in duplicated efforts and maintenance that we view as the main contribution of our work.

2 PACKAGEFORMERS —BEING NON-COMMITTAL AS MUCH AS POSSIBLE

It is notoriously difficult to reconstruct the possible inputs to a function that yielded a certain output. That is, unless you are using Prolog of-course, where the distinctions between input and output are an illusion that is otherwise made real only by how Prolog users treat arguments to a relation. Dependently-typed programming at its core is the adamant hygienic blurring of concepts and so the previous presentations of monoids are unified in the following single declaration which does not distinguish between parameters and fields.

```

37 PackageFormer MonoidP : Set where
38   _◊_      : MonoidP → MonoidP → MonoidP
39   Id       : MonoidP
40   assoc    : ∀ {x y z} → (x ◊ y) ◊ z ≡ x ◊ (y ◊ z)
41   leftId   : ∀ {x} → Id ◊ x ≡ x
42   rightId  : ∀ {x} → x ◊ Id ≡ x

```

Superficially, the parameters and fields have been flattened into a single location and the name Carrier has been dispensed with in-favour of MonoidP, which also happens to be name of this new declared entity. We commend the astute reader who has noticed a hint of predicativity here, but it is an issue we shall not address in the current work.

One uses a PacakagFormer by instantiating he particular presentation that is desired./

We conceive of an extensible type `Variations` which includes `datatype` and `record` as two keywords. Moreover, this type is equipped with a number of combinators, one of which is unbundled : `Variation → ℕ → Variation` which modifies a particular presentation by also lifting the first n constituents from the field level to the parameter level. In particular, `typeclass = record unbundled 1`. We also allow the named version of this combinator, namely `exposed : Variation → List Name → Variation`. Let's demonstrate these concepts.

```
PackageFormer MonoidP : Set where
  _%_      : MonoidP → MonoidP → MonoidP
  Id       : MonoidP
  assoc    : ∀ {x y z} → (x % y) % z ≡ x % (y % z)
  leftId   : ∀ {x} → Id % x ≡ x
  rightId  : ∀ {x} → x % Id ≡ x

{- These both yield the previous formulation of Monoid1 -}
Monoid1 = MonoidP typeclass
Monoid1 = MonoidP record exposing Carrier

{- These both yield the previous formulation of Monoid2 -}
Monoid2 = MonoidP record unbundled 2
Monoid2 = MonoidP record exposing (Carrier; _%_)

{- This allows us to speak of “a monoid over an arbitrary carrier”. -}
Monoid3 = MonoidP record
{-
  It behaves as if it were declared thusly:

  record Monoid3 : Set1 where
    field
      Carrier : Set
      _%_      : Carrier → Carrier → Carrier
      Id       : Carrier
      ...
-}

The name Carrier is a default and could be renamed; likewise for Vars below.

{- Finally, we mentioned metaprogramming's need to work with terms. -}
Monoid = MonoidP datatype
{-
  It behaves as if it were declared thusly:

  data Monoid : Set where
    _%_ : Monoid → Monoid → Monoid
    Id  : Monoid

  Note that only “functional” symbols have been exposed; no proof-matter. -}

{- Of course we may want to have terms “over” a particular variable set. -}
Monoid = MonoidP datatype exposing (Vars)
```

```
1  {-
2    It behaves as if it were declared thusly:
```

```
3
4    data Monoid (Vars : Set) : Set where
5      inj : Vars → Monoid Vars
6      _%_ : Monoid Vars → Monoid Vars → Monoid Vars
7      Id  : Monoid Vars
```

```
8
9    Note that only “functional” symbols have been exposed; no proof-matter. -}
```

There are of-course a number of variation on how a package is to be presented, we have only mentioned a two for brevity. The thesis proposal mentions more and provides examples as well.

The PackageFormer language feature unifies disparate representations of the same concept under a single banner. How does one actually *do* anything with these entities? Are we forced to code along particular instantiations? No; unless we desire to do so.

3 A NOVEL POLYMORPHISM

Suppose we want to produce the function `concat`, which composes the elements of a list according to a compositionality scheme —examples of this include summing over a list, multiplication over a list, checking all items in a list are true, or at least one item in the list is true. Depending on the interface presentation selected, the typing of this function could be elegant or awkward, as follows.

```
concat1 : {C : Set} {M : Monoid2 C} → List C → C
```

```
concat3 : {M : Monoid3} → let C = Monoid3.Carrier M in List C → C
```

```
concat : List Monoid → Monoid
```

An immediate attempt to unify these declarations requires pinpointing exactly *which type is referred to semantically by the phrase MonoidP*. For the datatype variation, it could only refer to the resulting algebraic data-type; whereas for the record variation, it could refer to the result record type *or* to the Carrier projection of such record types. Consequently, we use monad-like notation $\text{do} \leftarrow \text{MonoidP}$; \dots whenever we wish to refer to *values* of the underlying carrier of a particular instantiation, rather than referring to the type *of* such values. In particular:

```
do ← MonoidP record; B ≈ λ { : MonoidP record } → B (MonoidP.Carrier )
do ← MonoidP datatype; B ≈ B (MonoidP datatype)
```

With this understanding in-hand, we may write “variation polymorphic” programs:

```
concatP : {v : Variation} → do ← MonoidP v; List →
concatP [] = MonoidP.Id
concatP (x :: xs) = x % concatP xs where _%_ = MonoidP._%_
```

It is important at this juncture to observe that the type of `concatP` depends crucially on the variation v that is supplied, or inferred. This is a prime reason for using a dependently-typed language as the setting for the PackageFormer feature.

4 NEXT STEPS

We have outlined a new unifying language feature that is intended to massively reduce duplicated efforts involving different perspectives of datatypes. Moreover, to make this tractable we have also provided a novel form of polymorphism and demonstrated it with minimal examples.

We have implemented a meta-program that realises these elaborations in an unobtrusive fashion: An Agda programmer simply declares them in special comments. The resulting ‘editor tactic’ demonstrates that this language feature is promising.

Thus far we have relied on the reader’s understanding of functional programming and algebraic data types to provide an informal and indirect semantics by means of elaborations into existing notions. An immediate next step would be to provide explicit semantics for PackageFormer’s within a minimal type theory. Moreover there are a number of auxiliary goals, including:

- (1) How do users extend the built-in Variations type along with the intended elaboration scheme.

One possible route is for a user to ‘install’ a new variation by specifying where the separation line between parameters and fields happens; e.g., by providing a function such as `List Constituent → Pair (List Constituent)`, which may introduce new names, such as the aforementioned `Carrier` and `Vars`.

- (2) Explain how generative modules are supported by this scheme, and they indeed are.
- (3) Demonstrate how tedious boilerplate code for renamings, hidings, extensions, and the flattening of hierarchical structures can be formed.
- (4) How do multiple default, or optional, clauses for a constituent fit into this language feature. This may necessitate a form of limited subtyping.
- (5) Discuss inheritance, coercion, and transport along canonical isomorphisms.
- (6) Flexible polymorphic definitions: One should be able to construct a program according to the most convenient presentation, but be able to have it *automatically* applicable to other instantiations.

For example, the `concat` function was purely syntactic and the easiet formulation uses the algebraic data-type rendition, whence one would write `concat : List MonoidP datatype → MonoidP datatype` and the variation is found then systematically generalised to obtain `concatP : {v : Variation} → do ← MonoidP v; List → .` When there are multiple variations mentioned, the problem becomes less clear cut and the simplest solution may be to simply indicate which variation or occurrences thereof is intended to be generalised.

There are many routes to progress on this fruitful endeavour.

We look forward to this feature reducing the length of our code and alleviating us of tedious boilerplate constructions.