

# Notebook 3 Quiz

**Due** Nov 18 at 5pm **Points** 5 **Questions** 5

**Available** Oct 5 at 5pm - Nov 18 at 5pm about 1 month

**Time Limit** 60 Minutes

**Allowed Attempts** 2

## Instructions

This quiz will review the topics presented in the exercises from the third notebook on feature keypoints, descriptors, and applications. The quiz is open book/notes/resources. You will have 60 minutes to complete the quiz.

**Read the questions carefully.** There are multiple variants of each question, and they may change slightly between each attempt.

[Take the Quiz Again](#)

## Attempt History

	Attempt	Time	Score
LATEST	<a href="#">Attempt 1</a>	60 minutes	3 out of 5

❗ Correct answers are hidden.

Score for this attempt: **3** out of 5

Submitted Nov 14 at 6:49pm

This attempt took 60 minutes.

Incorrect

### Question 1

0 / 1 pts

Use the arrays  $I_x$  and  $I_y$  shown below to calculate the value of  $R$  for the center pixel. Assume that the  $3 \times 3$  weighting matrix  $w(x, y) = 1$  for all  $x$  and  $y$ , and  $\alpha = 0.05$ . Recall:

$$M = \sum_x \sum_y w(x, y) \begin{bmatrix} I_x^2 & I_x I_y \\ I_x I_y & I_y^2 \end{bmatrix}$$

$$R = \det(M) - \alpha \text{trace}^2(M)$$

```
Ix = [[0 1 1]
      [1 0 1]
      [0 1 0]]
```

```
Iy = [[0 1 0]
      [1 0 1]
      [1 1 0]]
```

Enter your answer to one decimal place accuracy, e.g., for a value of 3.14159 enter 3.1; for a value of 2 enter 2.0.

Incorrect

## Question 2

0 / 1 pts

Given the 2x2 magnitude array and a 2x2 angle array (values in degrees) for a cell shown below, use 4 **unsigned** angle bins [0-45), [45-90), [90-135), and [135-180) as shown in the notebook to calculate the cell histogram.

Magnitudes:

```
[[ 9  2]
 [ 1  6]]
```

Angles:

```
[[ 11 353]
 [131 271]]
```

What is the magnitude of the histogram for the [90-135) angle bin?

## Question 3

1 / 1 pts

According to the HoG paper by Dalal & Triggs, which derivative masks work **best** for human recognition with HoG?

- ☐ uncentered (i.e., mask = [-1, 1])
- ☒ centered (i.e., mask = [-1, 0, 1])
- ☐ Sobel
- ☐ diagonal (i.e., mask = [[-1, 0], [0, 1]])

**Question 4****1 / 1 pts**

Given a 128x64 image window, calculate the size of the HoG feature vector that will be computed with 9 angle bins using a 3x3 block shape and 8x8 cell shape.

**Question 5****1 / 1 pts**

What is the default feature detector & descriptor used by OpenSfM?

- ☐ SIFT
- ☐ SURF
- ☐ ORB
- ☐ HoG
- ☒ HAHoG

**Quiz Score: 3 out of 5**

