AI 360: Deep Learning
Group Project Proposal

Test-Time Adaptation for Welding Anomaly Detection

Group: Grad Student Descent

[Please describe your project in ≤4 pages excluding references. This template is for guidance, and you can decide the exact details to include, but we do require you to complete each of the tables and we strongly suggest keeping each section that we have provided in the template.]

---

1 Group Composition

Team Member	Student ID
Jaden Majid	94916335
Hieu Lexuan	76067321
Chris Tardy	33171422
Irene Berezin	43769694

2 Introduction and Problem Definition

[Describe the problem that your project aims to address in 1 paragraph and explain why it is interesting or important. Your introduction should address the following questions:] [What problem are you trying to solve?] We address the detection of weld defects from the acoustic signature of the welding arc, using only good welds for training, and keeping it reliable when deployment conditions change.

[What is the motivation and potential significance of this problem?] Large fabrication projects (e.g. shipbuilding) involve thousands of welds, typically checked by post-weld inspection of a sampled subset. Detecting defects during welding would allow immediate rework and more targeted inspection. However, a deployed detector meets unseen stations, microphones and noise, and labelled data from each new site is rarely available. The project is sponsored by Sonibel Instruments who are building commercial solutions to this problem, and from whom we intend to receive proprietary data for test-time adaptation, under an NDA governing its handling and release.

[What makes the problem suitable for a deep learning approach?] Welding audio is high-dimensional and defects are diverse and rare. Self-supervised audio encoders can model normal welds without defect labels, and test-time adaptation (TTA) [5, 6, 7, 11] can correct for distribution shift using only unlabelled test data. An academic-use welding dataset with a baseline method is available from Intel [1], and competitions such as DCASE [2] publish state-of-the-art methods, including the one proposed for this project [3].

[What is the specific research question or hypothesis you intend to investigate?] Our research question is whether the DCASE 2026 winning method (MERL [3]) outperforms the Intel autoencoder baseline for acoustic weld-defect detection. Furthermore, can TTA recover its performance on shifted welding audio without labels?

[Clearly define the scope of the project. State what you aim to demonstrate or achieve by the end.] The core deliverable is a MERL-style detector that exceeds the published audio-only AUC of 0.846 on the Intel welding benchmark [1]. Extensions are (i) TTA on constructed shifts and Sonibel data, (ii) real-time (online) detection, and (iii) audio–video fusion.

3 Related Work and Background

[Briefly discuss relevant prior work, existing methods, and approaches. Identify the most relevant paper(s).] **Proof of Concept and Baseline.** The Intel welding benchmark [1] is a dataset of both the audio and video streams of welding jobs, classified as correct or as one of 11 real anomalies. Its audio model is a 1D CNN autoencoder on FFT frames of 192 kHz audio. Test AUC (how well anomaly scores rank defective welds above good ones) is 0.846 for audio, 0.898 for video, and 0.918 fused. Audio is weakest on burnthrough (0.70), warping (0.76), excessive penetration and spatter (both 0.78). It should be noted that the published Intel dataset only supports audio up to 16 kHz, so we would re-implement Intel's method on their public data to determine fair baselines.

[How your proposed project relates to existing work.] **The Gap.** DCASE Task 2 [2] is an annual challenge on detecting faulty machines from sound with only normal training data. Recent top systems use pretrained audio encoders (BEATs, EAT, CLAP), fine-tune them on auxiliary labels, and score by k-NN distance to normal embeddings. These consistently beat autoencoder baselines but have not been tested on welding. The 2026 winner, MERL [3], scored 66.2% against 57.7% for the autoencoder baseline. *[Which methods or ideas you intend to build upon.]* Our objective is to take the Intel dataset and beat its baseline with MERL's method.

4 Datasets

[Describe the datasets you plan to use for training, validation, and testing. Specify:] [Dataset name and source (include a URL or citation).] [Approximate dataset size and relevant characteristics.] We use the Intel Robotic Welding Multimodal Dataset [1]: 4,040 robotic arc welds from an automotive production floor, with audio, video, sensor time series and post-weld images. *[Task and type of data (e.g., images, video, text, or multimodal).]* We focus on audio. Defects span 11 categories, including porosity, burnthrough, spatter and lack of fusion. *[Intended training, validation, and test splits.]* We reuse Intel's splits so results are directly comparable (Table 1); training uses good welds only. *[Any preprocessing or data augmentation required.]* Audio is resampled to each encoder's input rate and converted to its expected log-mel input; the baseline uses FFT frames, following [1]. *[Access restrictions, licensing, or computational considerations.]* Access has been approved and we have the dataset; labels denote the intended defect, so some label noise is expected. Sonibel's proprietary data for TTA will be handled under an NDA. *[Explain why the selected datasets are appropriate for the problem.]* The Intel dataset is the only public welding dataset with audio and a published anomaly detection baseline; Sonibel's data provides a realistic shift for TTA.

5 Available Hardware and Computational Resources

[Describe the computational resources available to your group. Include relevant details such as GPUs or other accelerators available (model and memory, if known) beyond colab if any.] Lab

Split	Good welds	Defective welds
Train	576	0
Validation	122	1,610
Test	121	1,611

Table 1: Intel dataset splits.

GPUs, including an RTX 2080 Ti and an A5000, are available for embedding extraction and model experiments, and Chris, a graduate student in the PLAI group at UBC, has access to its GPU cluster. Jaden also has a home PC with an RTX 5070 Ti that he can donate for runs that would exceed Colab runtime limits. Since we start from frozen pretrained encoders with light fine-tuning, these resources are sufficient.

6 Proposed Model and Methodology

[Describe your initial technical approach (this need not be a full definition of the model) and explain how you intend to develop and evaluate your deep learning solution.]

Model and Starting Point. *[Specify the model or architecture (e.g., CNN, RNN, GNN, etc.) you intend to use and justify your choice. Clarify the starting point of your project:]* We use three transformer audio encoders (BEATs, EAT and EAT-large), self-supervised on AudioSet, chosen because public checkpoints are available and the leading DCASE systems use them. As a baseline, we re-implement Intel's 1D CNN autoencoder [1]; its code is not public, but the paper lists the full architecture and training settings. *[Will you use an existing pre-trained model?]* All three encoders are used pretrained, first frozen. *[Will you fine-tune an existing model on your task?]* We then fine-tune them on good welds with an auxiliary task: classifying each weld's process settings (weld type, current, voltage). *[Will you train a model from scratch?]* Only the Intel autoencoder, which we retrain on the released 16 kHz audio (the paper used 192 kHz) to obtain a new, directly comparable baseline. *[Will you adapt or combine existing architectures?]* We pair the encoders with MERL's scoring method [3] and average anomaly scores across encoders.

Proposed Approach. *[Outline the main steps of your proposed method (As much as possible at this stage), including:] [Input representation and preprocessing.]* Inputs are mono 16 kHz weld recordings, converted to the log-mel spectrogram each encoder expects, and to FFT frames for the Intel baseline. *[Model architecture and key components.]* The method has five steps:

1. We reproduce the Intel baseline at 16 kHz, scoring each weld recording by its reconstruction error and measuring test AUC.
2. Each frozen encoder maps a weld to embeddings; its anomaly score is the distance to its nearest neighbours among the 576 good training welds, so a weld unlike any good weld scores high. We measure AUC for an ensemble of 3 encoders $\times$ 3 seeds.
3. We fine-tune the encoders on the auxiliary settings-classification task, so their embeddings separate welding-relevant differences. The classifier head is then discarded.
4. We repeat k-NN detection with MERL's scoring. Rather than comparing whole welds, we compare each frequency band separately and average, so an unfamiliar mix of normal sounds is not flagged; we emphasise moments that differ most from the rest of the weld, so a brief defect is not averaged away; and we adjust scores for how tightly good welds cluster. Hyperparameters

are swept on the validation set if necessary.

5. As an extension, we apply test-time adaptation (TTA) to adapt the encoders to Sonibel data, a distribution shift from the Intel recordings. If Sonibel data is unavailable, we will instead construct corrupted test sets in the spirit of ImageNet-C and CIFAR-10-C [10], using common audio corruptions (e.g. background noise, reverberation, gain changes, clipping). TTA methods will be chosen after a literature review; candidates include EATA [8], FOA [9], SAR [7], ActMAD [6], NOTE [11] and BN adaptation [5].

[Training objective or loss function, if applicable.] The Intel autoencoder baseline minimises reconstruction error; fine-tuning uses a cosine-similarity classification loss on the auxiliary labels, as in MERL. The k-NN scorer requires no training. *[Optimization strategy and important hyperparameters.]* Fine-tuning uses low-rank adapters (LoRA) with AdamW; key hyperparameters are k, the pooling weight and the number of class centres. *[Inference procedure and expected outputs.]* Each weld receives an anomaly score, averaged across the ensemble; online, an alarm is raised when the running score exceeds a threshold set on good validation welds.

[We want you to provide enough detail to establish that the approach is technically plausible, while recognizing that the implementation and design may evolve.]

Baselines and Evaluation. *[Describe how you will determine whether your approach is successful. Specify:] [Baseline methods or reference models.]* Baselines are the reproduced Intel 1D CNN autoencoder (reported 0.846 audio AUC) and log-mel features with the same k-NN scorer. *[Evaluation metrics appropriate to the task.]* Following [1], we report clip-level ROC-AUC overall and per defect category; for online detection, time-to-detection and false-alarm rate. *[Experimental comparisons or ablation studies.]* Ablations isolate the encoder, fine-tuning and each scoring component. For TTA, we compare AUC before and after adaptation (BN adaptation [5], ActMAD [6], SAR [7]) on constructed shifts (e.g. added noise, held-out weld types) and Sonibel data. *[Expected results and how they will be interpreted.]* Success is exceeding 0.846 audio-only AUC; a strong result would approach the 0.918 audio–video figure with audio alone.

7 Timeline and Deliverables

[Provide a realistic timeline for the project, identifying milestones, deliverables, and dependencies.]

Time Period	Milestone / Activities	Expected Deliverable
Nov 6–11	Reproduce Intel baseline	Reproduced baseline AUC
Nov 12–18	Frozen encoders + k-NN (MERL scoring)	Frozen-encoder AUC
Nov 19–25	Fine-tune encoders; hyperparameter sweeps	Fine-tuned AUC beats baseline
Nov 26–Dec 2	TTA on shifted data	AUC before and after TTA
Dec 3–7	Final analysis and report	Final report and slides

We intend to work in parallel where each team member has a primary responsibility, but we contribute across tasks. We intend to merge the best parts of each team member's contributions at the end of each milestone.

[Adapt the timeline to the actual course schedule. Identify at least one intermediate milestone that can be used to assess feasibility and revise the approach if necessary.] **Checkpoint (Nov 25):** compare the reproduced Intel baseline, frozen and fine-tuned encoders on Intel's splits; revise scope if the baseline cannot be exceeded.

8 Division of Work

[Describe the planned responsibilities of each team member. Explain how team members will coordinate and integrate their work. Ensure that the distribution of work is clear and reasonably balanced.] The project is undertaken by a team of four. Individual responsibilities and coordination arrangements will be confirmed by the team. Work to allocate includes the data pipeline and Intel baseline, encoder embedding extraction and fine-tuning, k-NN and MERL-style scoring, evaluation and stretch goals, and the final presentation and report.

Team Member	**Primary Responsibilities**	**Expected Contributions**
Jaden Majid	Fine-tuning Encoders	Fine-tuned encoder checkpoints beating frozen on prediction loss
Hieu Le	Reproduce Baseline	Intel method implementation and new AUC baseline
Chris Tardy	Lit Review + TTA	Novel TTA methods, implementation and results vs. baseline
Irene Berezin	KNN + AUC (Evals)	Frozen-encoder results, k-NN implementation, hyperparameter sweeps, AUC

References

[1] G. Stemmer, J. A. Lopez, J. A. Del Hoyo Ontiveros, A. Raju, T. Thimmanaik, S. Biswas. Unsupervised welding defect detection using audio and video. arXiv:2409.02290, 2024.

[2] DCASE. Task 2: First-shot unsupervised anomalous sound detection for machine condition monitoring. 2026.

[3] MERL. DCASE 2026 Task 2 technical report, TR2026-100. 2026.

[4] Multimodal supervised defect-type classification. Research Square preprint rs-10675288, v1.

[5] Schneider et al. Improving robustness against common corruptions by covariate shift adaptation. NeurIPS, 2020. arXiv:2006.16971.

[6] Mirza et al. ActMAD: Activation matching to align distributions for test-time training. CVPR, 2023. arXiv:2211.12870.

[7] Niu et al. Towards stable test-time adaptation in dynamic wild world. ICLR, 2023. arXiv:2302.12400.

[8] Niu et al. Efficient test-time model adaptation without forgetting. ICML, 2022. arXiv:2204.02610.

[9] Niu et al. Test-time model adaptation with only forward passes. ICML, 2024. arXiv:2404.01650.

[10] Hendrycks and Dietterich. Benchmarking neural network robustness to common corruptions and perturbations. ICLR, 2019. arXiv:1903.12261.

[11] Gong et al. NOTE: Robust continual test-time adaptation against temporal correlation. NeurIPS, 2022. arXiv:2208.05117.