

Prettify (Guangzhou) Prefabricated Building Technology Co., Ltd.

Address:No. 122, No. 38 Shayong Hougang Industrial Road, Dalong Street, Panyu District, Guangzhou, Guangdong,China
WhatsAPP & Wechat +86-18127929407; Web:https://www.meihua-tents.com; Date: 20260810



Aluminum Alloy Integrated Module House - Quotation | 侧房三角屋—报价表

Serial No. 序号	Product Name 产品名称	Product Specification 产品规格	Reference Image	Tentative Quantity 暂定工程量	Product Item 产品列项	Process Description 工艺说明		Response Parameters, Material, Brand 响应参数、材质、品牌	Remarks 备注
						Part 部位	Material Requirement 材质要求		
						Foundation 地基	300*300*500MM, Ground Anchor Cement Pier Embedded (Drawings Provided to Customer) 300*300*500MM, 地锚水泥墩预埋 (出图给客户)	Typhoon Resistant Design and Embedding 抗台风设计及预埋	Owner Customer Responsible 业主客户负责
						Main Steel Frame of Platform 地台主钢架	Hot-dip Galvanized Square Tube 60*60*2MM, 20CM Above Ground Connected to Cement Pier 热镀锌方管60*60*2MM, 离地20CM与水泥墩连接	Typhoon Resistant Structure 抗台风结构	Owner Responsible 业主负责
						Indoor Floor 室内地板	WPC Floor 100*25MM + 5.5MM SPC Floor 塑木地板 100*25MM+5.5MMSPC石塑地板	/	
						Structural Frame 结构框架	Main Structure (80*80mm Galvanized Steel Pipe) Secondary Structure (3mm Thick Galvanized Steel Pipe) 主结构 (80*80mm镀锌钢管) 次结构 (3mm厚镀锌钢管)	Prefabricated Structure 装配式结构	



Perimeter |
外围

Self-locking Polyurethane Insulation Aluminum-plated Tile + Bottom Sealing Plate 自锁聚氨酯隔热镀铝瓦+底部封板	Thickness (20mm) 厚度 (20mm)	/	
Exterior Wall of Side Room is Wood Grain Color Metal Hanging Panel 侧房外墙为木纹色金属挂板	16MM Thick (Including Tin Foil + Polyurethane) 16MM厚 (含锡纸+聚胺脂)	/	
Waterproofing 防水	Self-adhesive Waterproof Membrane 自粘防水卷材	/	
OSB Board 欧松板	9MM OSB Board Used 采用9MM欧松板	/	
Interior Wall Integrated Wall Panel 内墙集成墙板	Wood Grain Color Integrated Wall Panel 8MM or Sauna Board 木纹色集成墙板8MM或桑拿板	/	
XPS Board 挤塑板	5CM XPS Board, Fire Resistant and Flame Retardant 5CM挤塑板, 防火阻燃	/	
Calcium Silicate Board 硅酸钙板	6MM Thick, Fire Resistant and Flame Retardant 6MM厚, 防火阻燃		
1 Unit of Hollow Tempered Glass Entry Door 中空钢化玻璃入户门1个	(Integrated Window Screen, Thickness 5+6A+5), Hollow Tempered Coated Glass + Frame Aluminum Alloy Profile + Surface Treatment, Thickness Over 50, Waterproof, Sound Insulation. (窗纱一体, 厚度5+6A+5), 中空钢化镀膜玻璃+边框铝合金型材+表面处理, 厚度50以上, 防水, 隔音。	/	

1	Triangle House 三角屋	5*7*5.6M + 4*4*3.5M 5*7*5.6M+4*4*3.5M米	1	<table><tr><td>3 Units of Aluminum Alloy Windows, 1 Unit of Aluminum Alloy Entry Door on the Second Floor 铝合金窗户3个，二楼入户铝合金门1个</td><td>Opening Method (Side Opening), Glass (5+6A+5 Tempered Glass), Profile Thickness (1.4). Noise Reduction and Heat Insulation 开启方式（平开），玻璃（5+6A+5 钢化玻璃），型材厚度（1.4）。降燥隔热</td><td>/</td><td></td></tr><tr><td>Smart Lock for Entry Door 入户门智能锁</td><td>Entry Method (Card Swipe) + Key 入户方式（刷卡）+ 钥匙</td><td>/</td><td></td></tr><tr><td>Glass Curtain Wall 玻璃幕墙</td><td>Insulated tempered glass (5mm+9mm air cavity+5mm), aluminum thermal break structure, double-sided metal panels with fluorocarbon baking finish. Structural adhesive sealing is applied at all joints connecting to the main frame. 中空钢化玻璃（5+9+5），铝合金断桥结构，双面金属板氟碳烤漆，与主体连接处采用结构胶密封处理；</td><td>/</td><td></td></tr><tr><td>Viewing Platform + Glass Fence 观景台+玻璃围栏</td><td>1.4m * 8m 1.4米*8米</td><td>/</td><td></td></tr><tr><td>五金配件列表</td><td>Door (Handle, Hinge, Ordinary Lock, Door Stopper), Window (Handle, Hinge), Handle Style to be Submitted for Confirmation 门（拉手，合页，普通锁，门吸），窗（执手、铰链），拉手样式提交确认</td><td>/</td><td></td></tr><tr><td rowspan="2">1 Unit of Bathroom 卫生间1个</td><td>Second Floor Ceiling 顶面二层楼</td><td>Adopt Two-layer Load-bearing Roof, Integrated Board + OSB Board + Steel Frame + WPC Floor 采用二层承重顶，集成板+欧松板+钢架+塑木地板</td><td>/</td></tr><tr><td>Floor Material 地面材料</td><td>SPC Floor + Waterproof Material 石塑地板+防水材料</td><td>/</td></tr></table>	3 Units of Aluminum Alloy Windows, 1 Unit of Aluminum Alloy Entry Door on the Second Floor 铝合金窗户3个，二楼入户铝合金门1个	Opening Method (Side Opening), Glass (5+6A+5 Tempered Glass), Profile Thickness (1.4). Noise Reduction and Heat Insulation 开启方式（平开），玻璃（5+6A+5 钢化玻璃），型材厚度（1.4）。降燥隔热	/		Smart Lock for Entry Door 入户门智能锁	Entry Method (Card Swipe) + Key 入户方式（刷卡）+ 钥匙	/		Glass Curtain Wall 玻璃幕墙	Insulated tempered glass (5mm+9mm air cavity+5mm), aluminum thermal break structure, double-sided metal panels with fluorocarbon baking finish. Structural adhesive sealing is applied at all joints connecting to the main frame. 中空钢化玻璃（5+9+5），铝合金断桥结构，双面金属板氟碳烤漆，与主体连接处采用结构胶密封处理；	/		Viewing Platform + Glass Fence 观景台+玻璃围栏	1.4m * 8m 1.4米*8米	/		五金配件列表	Door (Handle, Hinge, Ordinary Lock, Door Stopper), Window (Handle, Hinge), Handle Style to be Submitted for Confirmation 门（拉手，合页，普通锁，门吸），窗（执手、铰链），拉手样式提交确认	/		1 Unit of Bathroom 卫生间1个	Second Floor Ceiling 顶面二层楼	Adopt Two-layer Load-bearing Roof, Integrated Board + OSB Board + Steel Frame + WPC Floor 采用二层承重顶，集成板+欧松板+钢架+塑木地板	/	Floor Material 地面材料	SPC Floor + Waterproof Material 石塑地板+防水材料	/
3 Units of Aluminum Alloy Windows, 1 Unit of Aluminum Alloy Entry Door on the Second Floor 铝合金窗户3个，二楼入户铝合金门1个	Opening Method (Side Opening), Glass (5+6A+5 Tempered Glass), Profile Thickness (1.4). Noise Reduction and Heat Insulation 开启方式（平开），玻璃（5+6A+5 钢化玻璃），型材厚度（1.4）。降燥隔热	/																													
Smart Lock for Entry Door 入户门智能锁	Entry Method (Card Swipe) + Key 入户方式（刷卡）+ 钥匙	/																													
Glass Curtain Wall 玻璃幕墙	Insulated tempered glass (5mm+9mm air cavity+5mm), aluminum thermal break structure, double-sided metal panels with fluorocarbon baking finish. Structural adhesive sealing is applied at all joints connecting to the main frame. 中空钢化玻璃（5+9+5），铝合金断桥结构，双面金属板氟碳烤漆，与主体连接处采用结构胶密封处理；	/																													
Viewing Platform + Glass Fence 观景台+玻璃围栏	1.4m * 8m 1.4米*8米	/																													
五金配件列表	Door (Handle, Hinge, Ordinary Lock, Door Stopper), Window (Handle, Hinge), Handle Style to be Submitted for Confirmation 门（拉手，合页，普通锁，门吸），窗（执手、铰链），拉手样式提交确认	/																													
1 Unit of Bathroom 卫生间1个	Second Floor Ceiling 顶面二层楼	Adopt Two-layer Load-bearing Roof, Integrated Board + OSB Board + Steel Frame + WPC Floor 采用二层承重顶，集成板+欧松板+钢架+塑木地板	/																												
	Floor Material 地面材料	SPC Floor + Waterproof Material 石塑地板+防水材料	/																												

	Exhaust Fan 排风扇	(Ordinary) （普通）	/	
	Lamp 灯具	Basic Lighting 基础照明	/	
Indoor 室内	Ceiling 天花	Integrated Wood Grain Wall Panel 8MM Thick 集成木纹墙板8MM厚	/	
	Partition Wall 隔墙	Integrated Wall Panel or 8mm Thick Solid Wood Sauna Board + Steel Keel + Calcium Silicate Board + Integrated Wall Panel + Waterproof Membrane (Same as Bathroom Partition Wall) 集成墙板或8mm厚实木桑拿板+钢龙骨+硅酸钙板+集成墙板+防水卷材（同卫生间隔墙）	/	
	Including Indoor Floor 含室内地板	5.5MM Thick SPC Floor 5.5MM厚SPC石塑地板	/	
	Stairs to the Second Floor Indoors 室内上二楼的楼梯	Steel Frame + Solid Wood Stairs 钢架+实木楼梯	/	
	Outdoor Stairs 室外楼梯	Hot-dip Galvanized Steel Frame + Anti-slip Hot-dip Galvanized Steel Plate Steps 热镀锌钢架+防滑热镀锌钢板踏步		
Electrical 电气	Curtain 窗帘	Manual Curtain 手动窗帘	/	
	Cable 线缆	Core Material (Copper), (Panyu Cable National Standard) 线芯材质（铜），（番禺电缆国标）	/	
	Control Switch in Distribution Box 配电箱内控制开关	(Equal Quality) （同等品质）	/	
	Switch Panel 开关面板	Minimalist Style, with Fluorescent Light (with 2 Sockets) 极简款，带荧光（带2个插座）	/	

						Water Pipe 水管	Lesso 联塑	/	
					Water and Electricity 水电	Control System 控制系统	Main Control Switch + 总控制开关+	/	
			EXW USD Price/set			US\$26,500			

The above quotation includes:
+ bathroom partition + doors and windows, glass curtain wall + stairs (inside and outside) + water and electricity pre-embedding (including sockets) + conventional packaging. Items not reflected in the configuration table are not configured (additional quotation required if needed);
2. the quotation does not include ground foundation and main steel frame of platform, soft decoration, home appliances, furniture (), bathroom, wooden box, etc.
Additional quotation required if needed).

1.main materials + attic + side room

2.付款方式:订金预付50%，发货装柜前付清尾款。

2. Payment terms: 50% deposit paid in advance, the remaining balance must be paid in full before delivery and container loading.

3.报价有效期:自报价日起15天内有效，逾期价格需重新确认

3. Quotation validity period: Valid for 15 days from the quotation date. The price shall be reconfirmed after the expiration date.

4.安装派师傅指导安装(1000元/人民币天，客户负责免费提供吃住及报销往返差旅费及计算往返时间工资)，客户免费提供工具及找3人有安装基础的人协助组装。(安装师傅保险300万1人)。.Installation: We will send technicians to guide the installation (RMB 1000 per person per day). The customer shall provide freeaccommodation and meals, reimburse the round-trip travel expenses, and pay the salary for the round -trip travel time. The customer shallprovide tools for free and arrange 3 people with basic installation experience to assist with the assembly. (Each instalation techniclan iscovered by an insurance of RMB 3 million).

| 以上报价：含主体材料+阁楼+侧房+卫生间隔断+门窗、玻璃幕墙+楼梯（内外）+水电预埋（含插座）+含常规包装，配置表内无体现的为未配置（需要增加的另行报价）；报价不含地面基础及地台主钢架框架、不含软装，不含家电、家具，不含卫浴，不含木箱等，如需增加需另行报价），产品材料款签定合同后付50%，发货前付清，指导安装师傅1名为1000RMB/天（计算往返时间工资，客户免费提供食宿，报销往返所有差旅费，购买意外保险300万，客户免费提供现场安装所需工具）。