

Ratings encoding

In the table below, each row represents a user’s ratings of movies: ✓ (check) indicates the person liked the movie, ✕ (x) that they didn’t, and • (dot) that they didn’t rate it one way or another (neutral rating or didn’t watch).

Person	Fyre	Frozen II	Picard	Ratings written as a 3-tuple
P_1	✕	•	✓	
P_2	✓	✓	✕	
P_3	✓	✓	✓	
P_4	•	✕	✓	

Defining sets

To define a set using **roster method**, explicitly list its elements. That is, start with $\{$ then list elements of the set separated by commas and close with $\}$.

To define a set using **set builder definition**, either form “The set of all x from the universe U such that x is ...” by writing

$$\{x \in U \mid \dots x \dots\}$$

or form “the collection of all outputs of some operation when the input ranges over the universe U ” by writing

$$\{\dots x \dots \mid x \in U\}$$

We use the symbol \in as “is an element of” to indicate membership in a set.

Example sets: For each of the following, identify whether it’s defined using the roster method or set builder notation and give an example element.

$$\{-1, 1\}$$

$$\{0, 0\}$$

$$\{-1, 0, 1\}$$

$$\{(x, x, x) \mid x \in \{-1, 0, 1\}\}$$

$$\{\}$$

$$\{x \in \mathbb{Z} \mid x \geq 0\}$$

$$\{x \in \mathbb{Z} \mid x > 0\}$$

$$\{\mathbf{A}, \mathbf{C}, \mathbf{U}, \mathbf{G}\}$$

$$\{\mathbf{AUG}, \mathbf{UAG}, \mathbf{UGA}, \mathbf{UAA}\}$$